

★ ORBITER

(6 m × 4 m × 3 m)

✱ SATELLITE UNIT — ORBITER

ID:

obs-sat-orbiter

Role: Low-Orbit Recon / Signal Relay

Tier: Satellite

Status: Active

● PHYSICAL & TECHNICAL

Length: 6 m

Width: 4 m

Height: 3 m

Mass: 4,200 kg

Power Source: Solar array + micro-reactor backup

Energy Capacity: 18,000 Wh

Fuel Capacity: 40 L (orbital correction thrusters)

Endurance: 3–5 years

Payload Capacity: Internal systems only

Modules:

Low-orbit recon optics

Signal relay dish

Stabilization gyros

Micro-thruster array

Navigation System: Orbital AI + star tracker

Structural Integrity: 1,200 HP

Armor Rating: 0.40

Heat Signature: Very Low

Noise Signature: None

Top Speed: Orbital velocity

Stability Rating: Maximum

● AUTONOMY & AI BEHAVIOR

Behavior Profile: Recon / relay / orbital stabilization

Aggression: 0.0

Caution: 1.0

Persistence: 1.0

Retreat Threshold: N/A

Target Priority: None (non-combat)

Formation Discipline: Maximum

Risk Tolerance: Very Low

Sensors

Optical Range: Global

Thermal Range: High

Radar Range: Medium

Signal Detection Range: Very High

Communication

Mesh Range: Global

Relay Capacity: 4

Command Link Type: Satellite Mesh

Network Priority: High

● COMBAT & THREAT MODEL

Firepower Rating: None

Weapon Mounts: None

Tracking Strength: High (optical + thermal)

Disruption Strength: Medium

Countermeasure Rating: Medium

Threat Modeling

Threat Level: 4

Preferred Terrain: Low orbit

Vulnerability Profile: Debris / EMP / solar storms

● SQUAD & COMMAND INTEGRATION

Squad Role: Recon & Relay

Squad Size Contribution: 2

Formation Behavior: Orbital spacing

Intent Interpretation Rules: Maintain recon coverage

Retreat Behavior: None

Reinforcement Behavior: Supports all grids

Command Hierarchy

Parent Command Unit: Worldmap / Insight

Subordinate Units: None

Relay Nodes: 4

Network Dependencies: Satellite Mesh

● VR OPERATOR MODE

Operator Seat Type: Orbital Recon Console

Operator HUD: Satellite Recon Overlay

Camera Feeds: Optical + thermal

Tactical Overlay: Global recon grid

Operator Controls

Recon optics

Thermal view

Signal relay

Orbital diagnostics

Operator Abilities

Global Recon Sweep

Thermal Scan

Relay Boost

Stabilization Pulse

● ECONOMY & LOGISTICS

Build Cost: 1,200 Metal / 700 Electronics

Build Time: 180 sec

Factory Type: Satellite Bay

Tech Requirements: Satellite Systems I

Maintenance Cost: Low

Repair Time: 40 sec

Supply Consumption: Very Low

Operational Cost: Very Low

Deployment Requirements: Launch pad

Transport Compatibility: Satellite carrier

Launch Method: Orbital insertion



BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

60× **Satellite Alloy Plates**

30× **Reinforced Satellite Rods**

6× **Hydraulic Actuators**

1× **Optics Housing**

Electronics

28× **Circuit Bundles**

20× **Signal Processors**

6× **Satellite Control Chips**

3× **Recon AI Chips**

Power

1× **Solar Array Assembly**

1× **Micro-Reactor Core**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **Orbital Stabilization Module**

Optional Upgrades

Enhanced Optics

Thermal Boost

Anti-Jamming Shielding