



(8 m × 5 m × 3 m)

SATELLITE UNIT — SKYLINK

ID:

obs-sat-skylink

Role: Mid-Orbit Communications / High-Bandwidth Relay

Tier: Satellite

Status: Active

PHYSICAL & TECHNICAL

Length: 8 m

Width: 5 m

Height: 3 m

Mass: 5,600 kg

Power Source: Solar array + micro-reactor backup

Energy Capacity: 24,000 Wh

Fuel Capacity: 60 L (orbital correction thrusters)

Endurance: 4–7 years

Payload Capacity: Internal systems only

Modules:

- High-bandwidth relay dish
- Mid-orbit stabilization gyros
- Multi-node mesh router
- Micro-thruster array

Navigation System: Orbital AI + star tracker

Structural Integrity: 1,400 HP

Armor Rating: 0.45

Heat Signature: Very Low

Noise Signature: None

Top Speed: Orbital velocity

Stability Rating: Maximum

● AUTONOMY & AI BEHAVIOR

Behavior Profile: Communications relay / mesh routing

Aggression: 0.0

Caution: 1.0

Persistence: 1.0

Retreat Threshold: N/A

Target Priority: None (non-combat)

Formation Discipline: Maximum

Risk Tolerance: Very Low

Sensors

Optical Range: Global

Thermal Range: Medium

Radar Range: Medium

Signal Detection Range: Extremely High

Communication

Mesh Range: Global

Relay Capacity: 6

Command Link Type: Satellite Mesh

Network Priority: Maximum

● COMBAT & THREAT MODEL

Firepower Rating: None

Weapon Mounts: None

Tracking Strength: Medium

Disruption Strength: High

Countermeasure Rating: Medium

Threat Modeling

Threat Level: 5

Preferred Terrain: Mid orbit

Vulnerability Profile: Debris / EMP / solar storms

● SQUAD & COMMAND INTEGRATION

Squad Role: High-Bandwidth Relay

Squad Size Contribution: 3

Formation Behavior: Orbital spacing

Intent Interpretation Rules: Maintain communications coverage

Retreat Behavior: None

Reinforcement Behavior: Supports all grids

Command Hierarchy

Parent Command Unit: Fusion / Insight

Subordinate Units: None

Relay Nodes: 6

Network Dependencies: Satellite Mesh

● VR OPERATOR MODE

Operator Seat Type: Communications Console

Operator HUD: Relay Network Overlay

Camera Feeds: Optical + thermal

Tactical Overlay: Mesh routes / signal load / relay health

Operator Controls

Relay routing

Signal balancing

Thermal view

Orbital diagnostics

Operator Abilities

Relay Boost

Mesh Stabilization

Signal Sync

Thermal Sweep

● ECONOMY & LOGISTICS

Build Cost: 1,400 Metal / 900 Electronics

Build Time: 200 sec

Factory Type: Satellite Bay

Tech Requirements: Satellite Systems I

Maintenance Cost: Low

Repair Time: 45 sec

Supply Consumption: Very Low

Operational Cost: Very Low

Deployment Requirements: Launch pad

Transport Compatibility: Satellite carrier

Launch Method: Orbital insertion



BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

70× **Satellite Alloy Plates**

34× **Reinforced Satellite Rods**

6× **Hydraulic Actuators**

1× **Relay Dish Assembly**

Electronics

32× **Circuit Bundles**

22× **Signal Processors**

6× **Satellite Control Chips**

3× **Relay AI Chips**

Power

1× **Solar Array Assembly**

1× **Micro-Reactor Core**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **High-Bandwidth Relay Module**

Optional Upgrades

Enhanced Relay Dish

Thermal Boost

Anti-Jamming Shielding