

★ STARCAST

(10 m × 6 m × 4 m)

✱ SATELLITE UNIT — STARCAST

ID:

obs-sat-starcast

Role: High-Orbit Broadcast / Strategic Signal Distribution

Tier: Satellite

Status: Active

● PHYSICAL & TECHNICAL

Length: 10 m

Width: 6 m

Height: 4 m

Mass: 7,200 kg

Power Source: Expanded solar array + micro-reactor backup

Energy Capacity: 32,000 Wh

Fuel Capacity: 80 L (orbital correction thrusters)

Endurance: 6–10 years

Payload Capacity: Internal systems only

Modules:

- High-orbit broadcast dish
- Wide-band signal amplifier
- Stabilization gyros
- Micro-thruster array

Navigation System: Orbital AI + star tracker

Structural Integrity: 1,600 HP

Armor Rating: 0.50

Heat Signature: Very Low

Noise Signature: None

Top Speed: Orbital velocity

Stability Rating: Maximum

● AUTONOMY & AI BEHAVIOR

Behavior Profile: Broadcast / long-range relay / orbital stabilization

Aggression: 0.0

Caution: 1.0

Persistence: 1.0

Retreat Threshold: N/A

Target Priority: None (non-combat)

Formation Discipline: Maximum

Risk Tolerance: Very Low

Sensors

Optical Range: Global

Thermal Range: Medium

Radar Range: Medium

Signal Detection Range: Extremely High

Communication

Mesh Range: Global

Relay Capacity: 8

Command Link Type: Satellite Mesh

Network Priority: Maximum

● COMBAT & THREAT MODEL

Firepower Rating: None

Weapon Mounts: None

Tracking Strength: Medium

Disruption Strength: High

Countermeasure Rating: Medium

Threat Modeling

Threat Level: 6

Preferred Terrain: High orbit

Vulnerability Profile: Debris / EMP / solar storms

● SQUAD & COMMAND INTEGRATION

Squad Role: Strategic Broadcast

Squad Size Contribution: 4

Formation Behavior: Orbital spacing

Intent Interpretation Rules: Maintain broadcast coverage

Retreat Behavior: None

Reinforcement Behavior: Supports all grids

Command Hierarchy

Parent Command Unit: Fusion / Nexus

Subordinate Units: None

Relay Nodes: 8

Network Dependencies: Satellite Mesh

● **VR OPERATOR MODE**

Operator Seat Type: Broadcast Console

Operator HUD: High-Orbit Signal Overlay

Camera Feeds: Optical + thermal

Tactical Overlay: Broadcast routes / signal load / mesh health

Operator Controls

Broadcast routing

Signal amplification

Thermal view

Orbital diagnostics

Operator Abilities

Broadcast Boost

Mesh Stabilization

Signal Sync

Thermal Sweep

● **ECONOMY & LOGISTICS**

Build Cost: 1,600 Metal / 1,000 Electronics

Build Time: 220 sec

Factory Type: Satellite Bay

Tech Requirements: Satellite Systems II

Maintenance Cost: Low

Repair Time: 50 sec

Supply Consumption: Very Low

Operational Cost: Very Low

Deployment Requirements: Launch pad

Transport Compatibility: Satellite carrier

Launch Method: Orbital insertion



BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

80× **Satellite Alloy Plates**

40× **Reinforced Satellite Rods**

8× **Hydraulic Actuators**

1× **Broadcast Dish Assembly**

Electronics

36× **Circuit Bundles**

26× **Signal Processors**

8× **Satellite Control Chips**

3× **Broadcast AI Chips**

Power

1× **Expanded Solar Array Assembly**

1× **Micro-Reactor Core**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **Wide-Band Broadcast Module**

Optional Upgrades

Enhanced Broadcast Dish

Thermal Boost

Anti-Jamming Shielding