

★ RESCUE

GROUND UNIT — RESCUE

ID:

obs-ground-rescue

Role: Emergency Extraction / Battlefield Recovery

Tier: Support

Status: Active

● PHYSICAL & TECHNICAL

Length: 4.3 m

Width: 2.2 m

Height: 1.8 m

Mass: 1,250 kg

Power Source: Diesel-electric hybrid

Energy Capacity: 4800 Wh

Fuel Capacity: 65 L

Endurance: 5–9 hours

Payload Capacity: 2 personnel or 300 kg equipment

Modules: Medical bay + extraction winch + stabilization cradle

Navigation System: GPS + Rescue AI

Structural Integrity: 800 HP

Armor Rating: 0.38

Heat Signature: Medium

Noise Signature: Medium

Top Speed: 18 m/s

Acceleration: Medium

Turning Radius: Tight

Stability Rating: Very High

● AUTONOMY & AI BEHAVIOR

Behavior Profile: Emergency Response / Extraction

Aggression: 0.0

Caution: 0.95

Persistence: 1.0

Flanking Likelihood: 0.0

Retreat Threshold: 0.9

Target Priority: Downed units / critical injuries

Formation Discipline: High

Risk Tolerance: Low

Sensors

Visual Range: 1500 m

Thermal Range: 800 m

Acoustic Range: Medium

Radar Range: None

LiDAR Range: Short

Signal Detection Range: Short

Communication

Mesh Range: 6 km

Relay Capacity: 1

Command Link Type: Support Grid

Network Priority: High

COMBAT & THREAT MODEL

Firepower Rating: None

Weapon Mounts: None

Weapon Types: None

Suppression Value: 0

Tracking Strength: None

Disruption Strength: Low

Breach Capability: None

Countermeasure Rating: Medium

Threat Modeling

Threat Level: 3

Engagement Distance: N/A

Preferred Terrain: Safe lanes / extraction corridors

Preferred Targets: Downed allies

Vulnerability Profile: Ballistic / explosives

● SQUAD & COMMAND INTEGRATION

Squad Role: Emergency Extraction

Squad Size Contribution: 2

Formation Behavior: Rear-line support spacing

Intent Interpretation Rules: Recover and stabilize allies

Retreat Behavior: Early

Breach Behavior: None

Flanking Behavior: None

Reinforcement Behavior: Supports all squads

Command Hierarchy

Parent Command Unit: Command Core / Fusion

Subordinate Units: Scout, Mule

Relay Nodes: 1

Network Dependencies: Support Grid

● VR OPERATOR MODE

Operator Seat Type: Rescue Cockpit

Operator HUD: Medical & Extraction Overlay

Camera Feeds: Optical + winch cam

Thermal View: Yes

LiDAR View: Yes

Tactical Overlay: Downed-unit markers / safe routes

Operator Controls

Movement Controls: Full vehicle drive

Extraction Controls: Winch / cradle / lift

Sensor Controls: Thermal / LiDAR / zoom

Ability Controls: Stabilize, Extract, Mark Safe Zone

Operator Abilities

Emergency Extraction

Stabilization Pulse

Rapid Recovery

Support Relay

● ECONOMY & LOGISTICS

Build Cost: 450 Metal / 260 Electronics

Build Time: 90 sec

Factory Type: Vehicle Bay

Tech Requirements: Support Systems I

Maintenance Cost: Low

Repair Time: 22 sec

Supply Consumption: Low

Operational Cost: Low

Deployment Requirements: Vehicle pad

Transport Compatibility: Light racks

Launch Method: Drive-out



BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

32× Light Alloy Plates

16× Reinforced Frame Rods

5× Hydraulic Actuators

2× Armor Panels

1× Extraction Cradle Assembly

Electronics

16× Circuit Bundles

12× Signal Processors

4× Vehicle Control Chips

2× Support AI Chips

Power

1× Hybrid Engine Core

2× Power Regulation Nodes

Rare / Tradeable

1× Medical Stabilization Module

Optional Upgrades

Reinforced Cradle

Silent Drive Kit

Extended Fuel Tank

Anti-Jamming Shielding