

★ COMMAND CORE

(14 m × 10 m × 7 m)

⦿ COMMAND UNIT — COMMAND CORE

ID:

obs-command-core

Role: Primary Strategic Command / Global Coordination Hub

Tier: Command (Top-Tier)

Status: Active

● PHYSICAL & TECHNICAL

Length: 14 m

Width: 10 m

Height: 7 m

Mass: 30,000 kg

Power Source: Dual high-capacity command reactors

Energy Capacity: 200,000 Wh

Fuel Capacity: N/A (reactor-based)

Endurance: Continuous

Payload Capacity: Internal systems only

Modules:

Strategic command chamber

Multi-layer encryption lattice

Global mesh router

Redundant cooling towers

Command-grade stabilizers

Navigation System: Stationary (anchored command node)

Structural Integrity: 5,000 HP

Armor Rating: 1.40

Heat Signature: Medium

Noise Signature: Low

Top Speed: N/A

Stability Rating: Maximum

● AUTONOMY & AI BEHAVIOR

Behavior Profile: Global command / coordination / strategic routing

Aggression: 0.0

Caution: 1.0

Persistence: 1.0

Retreat Threshold: N/A

Target Priority: None (non-combat)

Formation Discipline: Maximum

Risk Tolerance: Very Low

Sensors

Visual Range: Short

Thermal Range: Short

Acoustic Range: Short

Radar Range: Medium

Signal Detection Range: Very High

Communication

Mesh Range: Global

Relay Capacity: 12

Command Link Type: Strategic Command Mesh

Network Priority: Maximum

● COMBAT & THREAT MODEL

Firepower Rating: None

Weapon Mounts: None

Tracking Strength: Very High (command-grade signal intelligence)

Disruption Strength: Very High

Countermeasure Rating: Extremely High

Threat Modeling

Threat Level: 8 (highest strategic value)

Preferred Terrain: Secure command zones

Vulnerability Profile: EMP / sabotage / coordinated strikes

● SQUAD & COMMAND INTEGRATION

Squad Role: Primary Command Node

Squad Size Contribution: 10

Formation Behavior: Central anchor

Intent Interpretation Rules: Coordinate all global units

Retreat Behavior: None

Reinforcement Behavior: Supports all units

Command Hierarchy

Parent Command Unit: None (top of hierarchy)

Subordinate Units: Archive, Worldmap, Fusion, Nexus

Relay Nodes: 12

Network Dependencies: Strategic Command Mesh

● **VR OPERATOR MODE**

Operator Seat Type: High Command Console

Operator HUD: Global Command Overlay

Camera Feeds: Internal systems only

Thermal View: Yes

Tactical Overlay: Global unit positions / mesh health / strategic routes

Operator Controls

Global routing

Command mesh management

Encryption lattice control

System diagnostics

Strategic directives

Operator Abilities

Global Command Sync

Mesh Stabilization Pulse

Strategic Directive Broadcast

Encryption Surge

● **ECONOMY & LOGISTICS**

Build Cost: 3,000 Metal / 1,800 Electronics

Build Time: 300 sec

Factory Type: Command Foundry

Tech Requirements: Command Systems II

Maintenance Cost: Very High

Repair Time: 90 sec

Supply Consumption: High

Operational Cost: High

Deployment Requirements: Command zone

Transport Compatibility: Heavy command carriers

Launch Method: Anchor-install

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

180× **Command Alloy Plates**

90× **Reinforced Command Rods**

14× **Hydraulic Actuators**

6× **Armor Panels**

1× **Command Chamber Assembly**

Electronics

60× **Circuit Bundles**

40× **Signal Processors**

14× **Command Control Chips**

6× **Command AI Chips**

Power

1× **High-Capacity Command Reactor Core**

4× **Power Regulation Nodes**

Rare / Tradeable

1× **Strategic Encryption Lattice**

Optional Upgrades

Quantum Encryption

Reinforced Hull

Anti-Jamming Shielding