

★ IRONWALKER

🚶 GROUND UNIT — IRONWALKER

ID:

obs-ground-ironwalker

Role: Heavy Walker / Mobile Fortification

Tier: Heavy Assault

Status: Active

● PHYSICAL & TECHNICAL

Length: 3.8 m

Width: 2.6 m

Height: 3.4 m

Mass: 2,200 kg

Power Source: Dual industrial battery + hydraulic drive

Energy Capacity: 8200 Wh

Fuel Capacity: N/A (fully electric-hydraulic)

Endurance: 3–5 hours

Payload Capacity: 250 kg

Modules: Reinforced walker legs + shock-dampened chassis

Navigation System: GPS + Walker-Stability AI

Structural Integrity: 1,600 HP

Armor Rating: 0.85

Heat Signature: Medium

Noise Signature: High

Top Speed: 8 m/s

Acceleration: Very Low

Turning Radius: Precise pivot

Stability Rating: Maximum

● AUTONOMY & AI BEHAVIOR

Behavior Profile: Heavy Assault / Mobile Cover

Aggression: 0.7

Caution: 0.5

Persistence: 1.0

Flanking Likelihood: 0.0

Retreat Threshold: 0.3

Target Priority: Hardened targets / fortified positions

Formation Discipline: High

Risk Tolerance: High

Sensors

Visual Range: 1600 m

Thermal Range: 700 m

Acoustic Range: Medium

Radar Range: Short

LiDAR Range: Medium

Signal Detection Range: Short

Communication

Mesh Range: 4 km

Relay Capacity: 1

Command Link Type: Assault Grid

Network Priority: High

COMBAT & THREAT MODEL

Firepower Rating: Medium

Weapon Mounts: 2

Weapon Types: Heavy machine gun / suppression cannon

Accuracy: Medium

Suppression Value: High

Tracking Strength: Low

Disruption Strength: Medium

Breach Capability: Medium

Countermeasure Rating: High

Threat Modeling

Threat Level: 7

Engagement Distance: 200–600 m

Preferred Terrain: Urban / fortified zones

Preferred Targets: Heavy infantry / light vehicles

Vulnerability Profile: EMP / concentrated fire

● SQUAD & COMMAND INTEGRATION

Squad Role: Heavy Assault / Mobile Cover

Squad Size Contribution: 4

Formation Behavior: Front-line anchor

Intent Interpretation Rules: Push forward and absorb fire

Retreat Behavior: Late

Breach Behavior: Secondary

Flanking Behavior: None

Reinforcement Behavior: Supports assault squads

Command Hierarchy

Parent Command Unit: Command Core / Fusion

Subordinate Units: Hammer, Crusher

Relay Nodes: 1

Network Dependencies: Assault Grid

● VR OPERATOR MODE

Operator Seat Type: Walker Cockpit

Operator HUD: Assault Overlay

Camera Feeds: Optical + weapon cams

Thermal View: Yes

LiDAR View: Yes

Tactical Overlay: Cover zones / threat arcs

Operator Controls

Movement Controls: Walker stride + pivot

Weapon Controls: Dual mounts

Sensor Controls: Thermal / LiDAR / zoom

Ability Controls: Brace, Suppress, Stabilize

Operator Abilities

Heavy Suppression

Brace Mode

Mobile Cover Deployment

Threat Marking

● ECONOMY & LOGISTICS

Build Cost: 1,200 Metal / 600 Electronics

Build Time: 180 sec

Factory Type: Heavy Vehicle Bay

Tech Requirements: Assault Systems I

Maintenance Cost: High

Repair Time: 45 sec

Supply Consumption: High

Operational Cost: High

Deployment Requirements: Heavy walker pad

Transport Compatibility: Walker racks

Launch Method: Walk-out

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

70× Heavy Alloy Plates

36× Reinforced Frame Rods

12× Hydraulic Actuators

8× Armor Panels

1× Walker Leg Assembly

Electronics

32× Circuit Bundles

20× Signal Processors

7× Vehicle Control Chips

4× Assault AI Chips

Power

1× Dual Industrial Battery Core

3× Power Regulation Nodes

Rare / Tradeable

1× Shock-Dampened Chassis Core

Optional Upgrades

Reinforced Armor

Stabilized Weapon Mounts

Extended Battery Pack

Anti-Jamming Shielding