



SEA UNIT — RESCUE

ID:

obs-sea-rescue

Role: Marine Emergency Response / Extraction

Tier: Support

Status: Active

● PHYSICAL & TECHNICAL

Length: 7.0 m

Width: 3.2 m

Height: 2.5 m

Mass: 2,800 kg

Power Source: Marine diesel-electric hybrid

Energy Capacity: 10,000 Wh

Fuel Capacity: 160 L

Endurance: 6–12 hours

Payload Capacity: 2 personnel or 250 kg medical equipment

Modules: Medical bay, extraction cradle, stabilization winch

Navigation System: Marine GPS + Rescue AI

Structural Integrity: 950 HP

Armor Rating: 0.40

Heat Signature: Low

Noise Signature: Low

Top Speed: 10 m/s

Acceleration: Medium

Turning Radius: Tight marine turn

Stability Rating: Very High

● AUTONOMY & AI BEHAVIOR

Behavior Profile: Emergency Response / Extraction

Aggression: 0.0

Caution: 0.95

Persistence: 1.0

Retreat Threshold: 0.9

Target Priority: Downed units / distress signals

Formation Discipline: High

Risk Tolerance: Low

Sensors

Visual Range: 2000 m

Thermal Range: 900 m

Acoustic Range: High

Sonar Range: Short

Radar Range: Short

Signal Detection Range: Medium

Communication

Mesh Range: 6 km

Relay Capacity: 1

Command Link Type: Marine Support Grid

Network Priority: High

● **COMBAT & THREAT MODEL**

Firepower Rating: None

Weapon Mounts: None

Tracking Strength: Low

Disruption Strength: Low

Countermeasure Rating: Medium

Threat Modeling

Threat Level: 3

Preferred Terrain: Surface waters / rescue corridors

Vulnerability Profile: Ballistic / collision / waves

● **SQUAD & COMMAND INTEGRATION**

Squad Role: Marine Rescue / Extraction

Squad Size Contribution: 2

Formation Behavior: Rear-line support spacing

Intent Interpretation Rules: Recover and stabilize allies

Retreat Behavior: Early

Reinforcement Behavior: Supports all marine squads

Command Hierarchy

Parent Command Unit: Worldmap / Insight

Subordinate Units: None

Relay Nodes: 1

Network Dependencies: Marine Support Grid

● VR OPERATOR MODE

Operator Seat Type: Marine Rescue Console

Operator HUD: Medical & Extraction Overlay

Camera Feeds: Optical + winch cam

Thermal View: Yes

Sonar View: Basic

Tactical Overlay: Distress markers / safe routes

Operator Controls

Movement Controls: Marine drive

Extraction Controls: Winch / cradle / lift

Sensor Controls: Thermal / sonar / zoom

Ability Controls: Stabilize, Extract, Mark Safe Zone

Operator Abilities

Emergency Extraction

Stabilization Pulse

Rapid Recovery

Support Relay

● ECONOMY & LOGISTICS

Build Cost: 480 Metal / 260 Electronics

Build Time: 100 sec

Factory Type: Marine Bay

Tech Requirements: Marine Systems I

Maintenance Cost: Low

Repair Time: 26 sec

Supply Consumption: Low

Operational Cost: Low

Deployment Requirements: Water launch pad

Transport Compatibility: Marine racks

Launch Method: Water drop

BUILD REQUIREMENTS (PLAYER COLLECTION SYSTEM)

Common Components

34× **Marine Alloy Plates**

18× **Reinforced Marine Rods**

5× **Hydraulic Actuators**

1× **Extraction Cradle Assembly**

Electronics

18× **Circuit Bundles**

12× **Signal Processors**

3× **Marine Control Chips**

2× **Support AI Chips**

Power

1× **Marine Hybrid Engine Core**

2× **Power Regulation Nodes**

Rare / Tradeable

1× **Medical Stabilization Module**

Optional Upgrades

Reinforced Cradle

Silent Propulsion

Extended Fuel Tank

Anti-Jamming Shielding