

AIM

To understand the concept of classes and objects in Kotlin by creating a class with properties and methods, and accessing them using an object in an Android application.

Procedure

- 1 Open Android Studio and your project.
 - . Open activity_main.xml and add a **TextView** and **Button**.
- 2 Create a new Kotlin class named Student.
 - . Define properties and a method inside the class.
- 3 Open MainActivity.kt.
 - . Create an object of the class inside onCreate().
- 4 Call the class method using the object.
 - . Display the result in the TextView.
- 5 Run the app and observe output.

Code

```
6
Student.kt
package com.example.kotlinbasics
7
class Student(val name: String, val rollNo: Int) {
    .
    fun displayDetails(): String {
        return "Name: $name\nRoll No: $rollNo"
    }
    .
}
9
```

activity_main.xml

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"

    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:gravity="center"
    android:orientation="vertical">

    <Button
        android:id="@+id/btnShow"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Show Details"/>

    <TextView
```

```
        android:id="@+id/txtOutput"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:textSize="18sp"/>
</LinearLayout>
```

MainActivity.kt

```
package com.example.kotlinbasics
```

```
import android.os.Bundle
import android.widget.Button
import android.widget.TextView
import androidx.appcompat.app.AppCompatActivity
```

```
class MainActivity : AppCompatActivity() {

    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        setContentView(R.layout.activity_main)

        val btn = findViewById<Button>(R.id.btnShow)
        val txt = findViewById<TextView>(R.id.txtOutput)

        btn.setOnClickListener {

            // Creating object
            val student = Student("Ravi", 101)

            // Display output
            txt.text = student.displayDetails()
        }
    }
}
```

Result

The application successfully demonstrates classes and objects by displaying:

