

B.Comp. Dissertation

Benchmarking and Improving OCR Systems for Southeast Asian Languages

By

Qiu Jiasheng, Jason

Department of Computer Science

School of Computing

National University of Singapore

2024/2025

B.Comp. Dissertation

Benchmarking and Improving OCR Systems for Southeast Asian Languages

By

Qiu Jiasheng, Jason

Department of Computer Science

School of Computing

National University of Singapore

2024/2025

Project ID: H0792230

Supervisor: A/P Min-Yen Kan

Advisor: Tongyao Zhu

Deliverables:

Report: 1 Volume

Abstract

While Optical Character Recognition (OCR) has been widely studied for high-resource languages such as English and Chinese, the efficacy and limitations of OCR models on Southeast Asian (SEA) languages remain largely unexplored. This study aims to bridge this gap by evaluating OCR technologies for SEA languages and exploring script-specific challenges. We propose a pipeline to collect textual data from Wikipedia and benchmark open-source OCR tools. Additionally, we demonstrate the potential of fine-tuning existing models on SEA languages, aiming to expand OCR capabilities for these languages.

Subject Descriptors:

H.3.3 Information Search and Retrieval

I.2.7 Natural Language Processing

I.2.10 Vision and Scene Understanding

Keywords:

Optical Character Recognition, Southeast Asian Languages

Implementation Software and Hardware:

Python, Tesseract, EasyOCR

Acknowledgements

I would like to thank my supervisor, A/P Kan Min-Yen, and my advisor, Tongyao Zhu, for their invaluable guidance and mentorship. Their encouragement and constructive guidance have been a significant source of inspiration throughout the project.

List of Figures

3.1 Pipeline for data collection from Wikipedia	6
---	---

List of Tables

4.1	Average OCR Runtime Per Page (Seconds)	8
4.2	Error Classification by Character Type for English Articles	9
4.3	Error Classification by Character Type for Indonesian Articles	9
4.4	Error Classification by Character Type for Vietnamese Articles	9
4.5	Error Classification by Character Type for Thai Articles	10
A.1	Dataset of 98 Wikipedia articles	15

Table of Contents

Title	i
Abstract	ii
Acknowledgements	iii
List of Figures	iii
List of Tables	iv
Table of Contents	v
1 Introduction	1
2 Related Work	3
3 Methodology	4
3.1 Experiment Setup	4
3.1.1 Languages	4
3.1.2 Data Source	4
3.1.3 OCR Systems	5
3.1.4 Evaluation Metrics	5
3.2 Experiment 1: Benchmarking on Real Data	6
3.2.1 Data Collection	6
3.3 Experiment 2: Benchmarking on Synthetic Data	7
3.3.1 Synthetic Data Generation	7

3.4	Experiment 3: Fine-tuning for Vietnamese and Thai	7
4	Results and Analysis	8
4.1	RQ1: How do popular OCR tools perform on SEA scripts?	8
4.1.1	OCR Accuracy	8
4.1.2	Runtime	8
4.2	RQ2: What script-related challenges affect OCR accuracy on SEA languages?	10
4.3	RQ3: What techniques and recommendations can enhance OCR accuracy on SEA languages?	10
5	Discussion	11
6	Conclusion	12
	References	13
A	Wikipedia Article Dataset	15

Chapter 1

Introduction

Current research in Natural Language Processing (NLP) is heavily concentrated on only 20 of the 7,000 languages in the world (Magueresse et al., 2020). In particular, Southeast Asia (SEA) is home to over 1,000 languages but remains a relatively under-researched region in NLP (Aji et al., 2023). A similar trend can be observed in Optical Character Recognition (OCR) research, where the focus is predominantly on high-resource languages (Salehudin et al., 2023; Smith, 2007), leaving many SEA languages underserved.

OCR, the process of converting textual images into machine-readable formats, offers significant potential for languages with limited datasets. While many scanned documents and books in these low-resource languages are available online, the text within them often remains inaccessible due to formats like images and PDFs. By extracting the text from these documents, OCR can generate valuable datasets for low-resource languages, which can then be used for downstream NLP tasks, such as machine translation and named-entity recognition (Agarwal & Anastasopoulos, 2024; Ignat et al., 2022). Therefore, studying OCR performance on SEA languages is crucial to accelerating NLP research and technology development in the region.

While OCR has been widely studied for high-resource languages such as English and Chinese, the efficacy and limitations of OCR models on SEA languages remain largely unexplored. To address this gap, this study presents a pipeline to collect textual data from Wikipedia and benchmark several open-source OCR tools on the collected data.

Additionally, we explore the potential of fine-tuning existing models to improve OCR performance on SEA languages. The primary objective is to evaluate and enhance the performance of OCR technologies on SEA languages, thereby advancing NLP applications in this linguistically diverse region.

Specifically, this project seeks to answer the following research questions (RQs):

- **RQ1:** How do popular OCR tools perform on SEA scripts?
- **RQ2:** What script-related challenges affect OCR accuracy on SEA languages?
- **RQ3:** What techniques and recommendations can enhance OCR accuracy on SEA languages?

Chapter 2

Related Work

Chapter 3

Methodology

To answer the research questions, this study conducts three experiments to benchmark and improve OCR performance on SEA languages.

3.1 Experiment Setup

3.1.1 Languages

We selected English, Indonesian, Vietnamese, and Thai text. English serves as a baseline for sanity checks and bug fixing. The remaining SEA languages were chosen to capture diverse script characteristics. Indonesian represents Latin-based scripts, Vietnamese represents Latin scripts with diacritics, and Thai represents non-Latin scripts.

3.1.2 Data Source

This study collects textual data from Wikipedia for several reasons. Firstly, Wikipedia articles can be easily converted into images via screenshots, making them suitable for OCR applications. The platform also offers a convenient source of ground truth through its APIs that provide plain text for most articles. Secondly, Wikipedia hosts a large corpus in several popular SEA languages, including Thai, Vietnamese, Indonesian, Tamil, and Burmese, supporting our language needs (“List of Wikipedias”, 2024).

3.1.3 OCR Systems

In our selection of OCR systems for benchmarking, we prioritize open-source solutions that support a diverse range of SEA languages, promoting accessibility and reusability for the proposed evaluation pipeline. Additionally, we aim to include models with different underlying architectures, enabling a more comprehensive assessment of their performance across different languages. Consequently, we selected EasyOCR, Tesseract, and GOT, each representing distinct modeling approaches to OCR.

EasyOCR¹ is a modern OCR framework that integrates a text detection model based on the Character Region Awareness for Text (CRAFT) algorithm with a recognition model utilizing a Convolutional Recurrent Neural Network (CRNN).

Tesseract² is an established OCR engine, recognized as one of the top performers in the 1995 UNLV Test (Rice et al., 1995). It utilizes an underlying Long Short-Term Memory (LSTM) model.

Both EasyOCR and Tesseract provide robust support for English, Indonesian, Vietnamese, and Thai, making them suitable candidates for our benchmarking study.

3.1.4 Evaluation Metrics

$$CER = \frac{I + D + S}{N} \quad (3.1)$$

Similar to most OCR benchmark studies, we utilize Character Error Rate (CER) and Word Error Rate (WER) as our evaluation metrics (Hegghammer, 2022; Ignat et al., 2022). CER measures the accuracy of character recognition and is calculated using the

¹<https://github.com/JaidedAI/EasyOCR>

²<https://github.com/tesseract-ocr/tesseract>

Levenshtein or edit distance, which represents the minimum number of single-character insertions (I), deletions (D), and substitutions (S) required to transform one word into another. As shown in Equation 3.1, CER is defined as the edit distance between the OCR-predicted text and ground truth text, divided by the total number of characters in the ground truth text (N). A lower CER value indicates higher accuracy, with 0 representing perfect recognition. Notably, CER can exceed 1, particularly when there are a significant number of insertions. WER serves as the word-based counterpart to CER.

3.2 Experiment 1: Benchmarking on Real Data

3.2.1 Data Collection




Figure 3.1: Pipeline for data collection from Wikipedia

From the dataset of 100 Wikipedia articles, we collected article images and ground truth article text in our selected languages using Python, Selenium³, and the MediaWiki Action API⁴. Figure 3.1 illustrates the overall pipeline for data collection. The detailed steps are as follows:

³Selenium is a framework for automating web browsers, commonly used for web scraping by programmatically interacting with websites.

⁴The MediaWiki Action API allows access to wiki page operation features such as search and retrieval.

1. Manually compile the dataset’s article names and URLs in English.
2. Fetch the article names and URLs in Thai, Vietnamese, and Indonesian from the MediaWiki Action API.
3. Download the article PDFs in all languages using Selenium.
4. Convert the article PDFs into PNG images, where each image represents one page in the PDF.
5. Download the ground truth article text into TXT files from the MediaWiki Action API.

3.3 Experiment 2: Benchmarking on Synthetic Data

3.3.1 Synthetic Data Generation

3.4 Experiment 3: Fine-tuning for Vietnamese and Thai

Chapter 4

Results and Analysis

In this chapter, we analyze and evaluate the results of the experiments to provide answers to the research questions.

4.1 RQ1: How do popular OCR tools perform on SEA scripts?

4.1.1 OCR Accuracy

4.1.2 Runtime

Table 4.1: Average OCR Runtime Per Page (Seconds)

	EasyOCR	Tesseract	GOT
English	3.23	11.68	24.35
Indonesian	2.92	13.19	31.44
Vietnamese	3.91	11.80	-
Thai	2.32	16.76	-

Table 4.2: Error Classification by Character Type for English Articles

	Count	EasyOCR % Missed	Tesseract % Missed	GOT % Missed
Arabic digit	38,324	0.7%	1.9%	0.3%
Latin letter	1,546,964	1.3%	1.8%	0.4%
Latin letter w/ diacritic	424	100.0%	53.1%	14.6%
Punctuation	53,403	28.4%	2.3%	3.4%
Whitespace	317,587	4.9%	4.3%	3.6%
Other	3,298	82.8%	68.5%	76.9%

Table 4.3: Error Classification by Character Type for Indonesian Articles

	Count	EasyOCR % Missed	Tesseract % Missed	GOT % Missed
Arabic digit	24,947	0.4%	1.8%	0.2%
Latin letter	1,208,707	0.5%	1.8%	0.4%
Latin letter w/ diacritic	262	5.3%	100.0%	15.3%
Punctuation	37,788	22.1%	3.1%	0.8%
Whitespace	207,556	4.8%	5.1%	4.1%
Other	2,468	72.2%	80.5%	43.2%

Table 4.4: Error Classification by Character Type for Vietnamese Articles

	Count	EasyOCR % Missed	Tesseract % Missed
Arabic digit	31,473	1.1%	2.2%
Latin letter	916,667	8.5%	1.8%
Latin letter w/ diacritic	292,686	14.8%	1.8%
Punctuation	40,420	24.6%	2.2%
Whitespace	367,936	10.9%	5.3%
Other	35,767	12.5%	7.7%

Table 4.5: Error Classification by Character Type for Thai Articles

	Count	EasyOCR % Missed	Tesseract % Missed
Arabic digit	22,580	0.9%	6.7%
Latin letter	36,174	100.0%	100.0%
Latin letter w/ diacritic	96	100.0%	100.0%
Thai letter	617,699	0.4%	3.1%
Thai diacritic	90,620	3.7%	3.6%
Punctuation	13,669	6.4%	8.4%
Thai punctuation	901	78.8%	3.9%
Whitespace	58,164	37.5%	37.2%
Other	306,647	2.2%	7.1%

4.2 RQ2: What script-related challenges affect OCR accuracy on SEA languages?

4.3 RQ3: What techniques and recommendations can enhance OCR accuracy on SEA languages?

Chapter 5

Discussion

Chapter 6

Conclusion

References

- Agarwal, M., & Anastasopoulos, A. (2024). A concise survey of OCR for low-resource languages. In M. Mager, A. Ebrahimi, S. Rijhwani, A. Oncevay, L. Chiruzzo, R. Pugh, & K. von der Wense (Eds.), *Proceedings of the 4th workshop on natural language processing for indigenous languages of the americas (americasnlp 2024)* (pp. 88–102). Association for Computational Linguistics. <https://doi.org/10.18653/v1/2024.americasnlp-1.10>
- Aji, A. F., Forde, J. Z., Loo, A. M., Sutawika, L., Wang, S., Winata, G. I., Yong, Z.-X., Zhang, R., Doğruöz, A. S., Tan, Y. L., & Cruz, J. C. B. (2023). Current status of NLP in South East Asia with insights from multilingualism and language diversity. *Proceedings of the 13th International Joint Conference on Natural Language Processing and the 3rd Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics*, 8–13. <https://aclanthology.org/2023.ijcnlp-tutorials.2>
- Hegghammer, T. (2022). OCR with Tesseract, Amazon Textract, and Google Document AI: A benchmarking experiment. *Journal of Computational Social Science*, 5, 861–882. <https://doi.org/https://doi.org/10.1007/s42001-021-00149-1>
- Ignat, O., Maillard, J., Chaudhary, V., & Guzmán, F. (2022). OCR improves machine translation for low-resource languages. In S. Muresan, P. Nakov, & A. Villavicencio (Eds.), *Findings of the association for computational linguistics: Acl 2022* (pp. 1164–1174). Association for Computational Linguistics. <https://doi.org/10.18653/v1/2022.findings-acl.92>
- List of wikipedias. (2024). https://en.wikipedia.org/wiki/List_of_Wikipedias

- Magueresse, A., Carles, V., & Heetderks, E. (2020). Low-resource languages: A review of past work and future challenges. *CoRR*, *abs/2006.07264*. <https://arxiv.org/abs/2006.07264>
- Rice, S., Jenkins, F., & Nartker, T. (1995). *The fourth annual test of OCR accuracy* (tech. rep.). Information Science Research Institute.
- Salehudin, M., Basah, S., Yazid, H., Basaruddin, K., Safar, M., Som, M. M., & Sidek, K. (2023). Analysis of optical character recognition using easyocr under image degradation. *Journal of Physics: Conference Series*, *2641*(1), 012001. <https://doi.org/10.1088/1742-6596/2641/1/012001>
- Smith, R. (2007). An overview of the tesseract ocr engine. *Ninth International Conference on Document Analysis and Recognition (ICDAR 2007)*, *2*, 629–633. <https://doi.org/10.1109/ICDAR.2007.4376991>

Appendix A

Wikipedia Article Dataset

Category	Articles
People	Elizabeth II, Barack Obama, Michael Jackson, Elon Musk, Lady Gaga, Adolf Hitler, Eminem, Lionel Messi, Justin Bieber, Freddie Mercury, Kim Kardashian, Johnny Depp, Steve Jobs, Dwayne Johnson, Michael Jordan, Taylor Swift, Stephen Hawking, Kanye West, Donald Trump
Present countries	United States, India, United Kingdom, Canada, Australia, China, Russia, Japan, Germany, France, Singapore, Israel, Pakistan, Philippines, Brazil, Italy, Netherlands, New Zealand, Ukraine, Spain
Cities	New York City, London, Hong Kong, Los Angeles, Dubai, Washington, D.C., Paris, Chicago, Mumbai, San Francisco, Rome, Monaco, Toronto, Tokyo, Philadelphia, Machu Picchu, Jerusalem, Amsterdam, Boston
Life	Cat, Dog, Animal, Lion, Coronavirus, Tiger, Human, Dinosaur, Elephant, Virus, Horse, Photosynthesis, Evolution, Apple, Bird, Mammal, Potato, Polar bear, Shark, Snake
Buildings and structures	Taj Mahal, Burj Khalifa, Statue of Liberty, Great Wall of China, Eiffel Tower, Berlin Wall, Stonehenge, Mount Rushmore, Colosseum, Auschwitz concentration camp, Great Pyramid of Giza, One World Trade Center, Empire State Building, White House, Petra, Large Hadron Collider, Hagia Sophia, Golden Gate Bridge, Panama Canal, Angkor Wat

Table A.1: Dataset of 98 Wikipedia articles