CompTIA Network+ Exam N10-008



Explaining Network Applications

Objectives

- Explain the use of web, file/print, and database services
- Explain the use of email and voice services




Topic 11A


Explain the Use of Web, File/Print, and Database Services

Hypertext Transfer Protocol

- Port TCP/80
- Uniform Resource Locator (URL)
- Headers and payload
- HyperText Markup Language (HTML)
- Web server implementation
 - Hosting type
 - Server software




Secure Sockets Layer/Transport Layer Security




- Encryption service independent of application protocol
 - OSI session layer
 - Typically used with TCP
 - DTLS used with UDP
- HTTP Secure (HTTPS) over TCP/443
 - Install key pair and digital certificate on web server
 - Issuing certificate authority (CA) trusted by both server and client
 - Clients use public key in certificate to encrypt
 - Server uses private key to decrypt


File Transfer Protocol

- File Transfer Protocol (FTP)
 - Download, upload, and directory management
- Active/passive transfer modes
 - Ports TCP/21 + TCP/20
 - Port TCP/21 + Ephemeral
- Trivial File Transfer Protocol (TFTP)
 - Download (GET) and upload (PUT) only
 - Port UDP/69





Secure File Transfer Protocol



- Secure FTP (SFTP)
 - Using FTP over Secure Shell (SSH) on port TCP/22
- FTP over SSL (FTPS)
 - Explicit TLS (FTPES)
 - Use the AUTH TLS command to upgrade an unsecure connection established over port TCP/21
 - Implicit TLS (FTPS)
 - Negotiate an SSL/TLS tunnel before the exchange of any FTP commands
 - Uses the secure port TCP/990 for the control connection

File and Print Services

- Server Message Block (SMB)
 - Underpins Windows File/Printer sharing
 - Supported on UNIX and Linux by the Samba package
 - Runs over port TCP/445 or NetBIOS ports (137 139) on legacy hosts
- Remote Print Protocols
 - Communicate with print monitor over network
 - Port 9100
 - Internet Printing Protocol (IPP)
 - Web Services for Devices (WSD)/AirPrint
 - Printer sharing

Database Services

- Relational databases
 - Structured in linked tables defined by column (field)/row structure
 - Structured Query Language (SQL)
- Relational Database Management System (RDBMS)
 - Oracle SQL*Net over TCP/1521
 - Microsoft SQL Server over TCP/1433
 - MySQL over TCP/3306
 - PostgreSQL over TCP/5432
- NoSQL databases

Review Activity: Web, File/Print, and Database Services


- Hypertext Transfer Protocol
- Secure Sockets Layer/Transport Layer Security
- File Transfer Protocol
- Secure File Transfer Protocol
- File and Print Services
- Database Services



Topic 11B

Explain the Use of Email and Voice Services

Simple Mail Transfer Protocol (Slide 1 of 2)



Simple Mail Transfer Protocol (Slide 2 of 2)


- Server-to-server mail delivery
 - MX records
 - Non-delivery report (NDR)
 - Connection security methods
 - STARTTLS versus SMTPS
- SMTP ports
 - Port TCP/25 for message relay between SMTP servers or Message Transfer Agents (MTAs)
 - Port TCP/587 for Message Submission Agents (MSAs) to submit messages for delivery by an SMTP server
 - Port TCP/465 alternative port for message submission over implicit TLS (SMTPS)

Mailbox Access Protocols

- Post Office Protocol (POP/POP3)
 - Allows client to retrieve messages from mailbox server
 - TCP/110 unsecure or TCP/995 secure
- Internet Message Access Protocol (IMAP)
 - Allows client to manage mail folders in mailbox
 - TCP/143 unsecure or TCP/993 secure

```
GNU nano 2.2.2
                        File: /etc/dovecot/dovecot.comf
                                                                      Mod if ied
protocols = imap imaps
#protocols = none
 A space separated list of IP or host addresses where to listen in for
 connections. "*" listens in all IPv4 interfaces. "[::]" listens in all IPv6
 interfaces. Use "*, [::]" for listening both IPv4 and IPv6.
 If you want to specify ports for each service, you will need to configure
  these settings inside the protocol imap/pop3/managesieve { ... } section,
 so you can specify different ports for IMAP/POP3/MANAGESIEVE. For example:
  protocol imap {
    listen = *:143
    ssl listen = *:943
   protocol pop3 {
     listen = *:10100
   protocol managesieve {
     listen = *:12000
#listen = *
 Disable LOGIN command and all other plaintext authentications unless
                              [ Read 1280 lines ]
🏿 Get Help 🔭 WriteOut 🔭 Read File 📉 Prev Page 🛣 Cut Text 🔭 Cur Pos
```

Voice and Video Services



- Private Branch Exchange (PBX)
 - Legacy PBX terminates lines from telecom provider to provision extensions and call features
 - Supplied as vendor-specific hardware
- VoIP-enabled PBX
 - Voice over IP transfers voice traffic as packetized data
 - VoIP PBX can be hardware or software solutions
 - Normally placed at the network's edge and protected by a firewall

VoIP Protocols

- Session control, data transport, and Quality of Service (QoS) functions
- Session Initiation Protocol (SIP)
 - Session control
 - User agents and user discovery (SIP URI)
 - Ports TCP | UDP/5060 and 5061
- Real-time Transport Protocol (RTP)
 - Delivery of media packets
- RTP Control Protocol (RTCP)
 - Monitor session and provide information to QoS

Voice Gateways

- Means of translating between the VoIP network and external voice networks, such as public switched telephone network (PSTN) lines
- Different VoIP gateways for different functions
 - Connect internal VoIP with external PSTN lines (Foreign Exchange Office (FXO) gateway)
 - Route voice calls to external VoIP service
 - Connect legacy phones/fax to VoIP PBX (Foreign Exchange Subscriber (FXS) gateway)

Review Activity: Use of Email and Voice Services

- Simple Mail Transfer Protocol
- Mailbox Access Protocols
- Voice and Video Services
- VolP Protocols
- VoIP Phones
- Voice Gateways



Assisted Lab: Analyze Application Security Configurations

- Lab types
 - Assisted labs guide you step-by-step through tasks
 - Applied labs set goals with limited guidance
- Complete lab
 - Submit all items for grading and check each progress box
 - Select "Grade Lab" from final page
- Save lab
 - Select the hamburger menu and select "Save"
 - Save up to two labs in progress for up to 7 days
- Cancel lab without grading
 - Select the hamburger menu and select "End"

CompTIA Network+ Exam N10-008

Lesson 11

Summary

となっているというというというないできますが、またい、あっまった、からいかののであるからいか