


Managing Processes and Priorities

Objectives

After completing this lesson, you should be able to:

- Implement process execution in an appropriate scheduling class
- Manage process scheduling priority
- Manage the scheduling class of zones
- Configure the fair share scheduler
- Monitor the fair share scheduler

Job Workflow



Agenda


- Implementing process execution in an appropriate scheduling class
- Managing process scheduling priority
- Configuring the fair share scheduler
- Managing the scheduling class of zones

Importance of Process Execution in an Appropriate Scheduling Class

The process execution in an appropriate scheduling class plan ensures that:

- System resources are used appropriately
- Processes are prioritized in accordance with business needs and requirements
- Process workload distribution is controlled
- Processes are assigned to the appropriate scheduling class

Process Scheduler



Process Priority

- Global priority:
 - It is based on scheduling class.
- Designated priority:
 - Designating a priority affects global priority assignment and position in a priority queue.
 - Both scheduling class and user priority can be designated.
 - User priority is based on the assigned priority range of the scheduling class.

Process Scheduling Classes

Scheduling Class	Description
Time sharing (TS)	Default class for processes and their associated kernel threads. Priorities in this class are dynamically adjusted in an attempt to allocate processor resources evenly.
Interactive (IA)	Enhanced version of the TS class that applies to the in-focus window in the GUI. Its intent is to give extra resources to processes associated with that specific window.
Fair share scheduler (FSS)	This class is share based rather than priority based. Threads managed by FSS are scheduled based on their associated shares and the processor's utilization.
Fixed priority (FX)	Priorities for threads associated with this class are fixed. That is, they do not vary dynamically over the lifetime of the thread.
System (SYS)	Used to schedule kernel threads. Threads in this class are “bound” threads, which means that they run until they block or complete.
System Duty-Cycle Class (SDC)	This class is a variant of the SYS class. SDC adjusts its threads' priority to give them a specified percentage of the processor. It also gives them a scheduling quantum, which gives other threads at the same priority on the same CPU a chance to run.
Real-Time (RT)	Threads in the RT class are fixed priority, with a fixed-time duration called quantum.

Priority Ranges for Scheduling Classes

Scheduling Class	Priority Range
Real-time (RT)	100 through 159
System (SYS)	60 through 99
Fair share scheduler (FSS)	0 through 59
Fixed priority (FX)	0 through 59
Interactive (IA)	0 through 59
Time sharing (TS)	0 through 59

Combining FSS with Other Scheduling Classes

- Ensure that the FSS, TS, IA, and FX scheduling classes do not share the same processor set (pset).
- All processes that run on a processor set must be in the same scheduling class so that they do not compete for the same CPUs.
- To avoid starving applications in the FSS class, use processor sets for FSS class and FX class applications.
- The following classes can be in the same processor sets:
 - TS and IA classes
 - FSS and RT classes

Note: FSS has no control over the RT class processes.

Using CPU Shares with the FSS

- The FSS uses CPU shares to control the allocation of available CPU resources among workloads.
- Assigning a greater number of CPU shares to a project gives that project more CPU resources from the FSS.
- CPU share allocation and CPU resource usage are not the same.
 - CPU shares define the relative importance of workloads in relation to other workloads.
 - Resource utilization is the percentage of CPU capacity being used.
- When allocating CPU shares, you should know:
 - How many shares the project has in comparison with other projects
 - How many of the other projects are competing for CPU resources

Scheduling Class on a System with Zones Installed

- Nonglobal zones use the system's default scheduling class.
- For a new default scheduling class setting, nonglobal zones obtain the new setting when booted or rebooted.
- To ensure that all zones get a fair share of the system CPU resources, set the FSS as the system default scheduling class.

Implementing the Process Execution in an Appropriate Scheduling Class

You will next learn how to:

- Determine the scheduling priorities and classes for the process running on the system
- Modify scheduling priorities
- Set the FSS as the default scheduler
- Configure CPU shares for zones



Quiz



For the operating system to prioritize processes, all processes must have the same scheduling class.

- a. True
- b. False

Quiz



Which scheduling class has the highest range of user priority designations?

- a. Fair share scheduler (FSS)
- b. Real-time (RT)
- c. System (SYS)
- d. Time sharing (TS)

Quiz



What is the purpose of CPU shares?

- a. To control the allocation of available CPU resources among workloads
- b. To increase CPU capacity
- c. To change the global priority of a project in the priority queue
- d. To cap the CPU resource usage of a process

Quiz



Nonglobal zones use the default system scheduling class for the system.

- a. True
- b. False

Agenda

- Implementing process execution in an appropriate scheduling class
- Managing process scheduling priority
- Configuring the fair share scheduler
- Managing the scheduling class of zones

Managing Process Scheduling Priority

This section covers the following topics:

- Displaying processes by using the `top` command
- Displaying process class information
- Determining the global priority of a process
- Designating a process priority
- Modifying a process priority

Displaying Processes by Using the `top` Command

To display the top 10 processes that are using the most CPU resources, use `top 10 -s 10`.

```
# top 10 -s 10
```

```
last pid: 1121; load avg: 0.20, 0.14, 0.12; up 0+01:50:30 14:10:30
```

```
87 processes: 83 sleeping, 3 running, 1 on cpu
```

```
CPU states: 81.8% idle, 5.1% user, 13.1% kernel, 0.0% iowait, 0.0% swap
```

```
Kernel: 609 ctxsw, 9 trap, 327 intr, 1935 syscall, 4 flt
```

```
Memory: 1024M phys mem, 84M free mem, 977M total swap, 977M free swap
```

PID	USERNAME	NLWP	PRI	NICE	SIZE	RES	STATE	TIME	CPU	COMMAND
991	oracle	2	59	0	87M	19M	sleep	0:11	4.03%	gnome-terminal
733	oracle	3	59	0	65M	53M	run	0:23	3.82%	Xorg
929	oracle	20	59	0	160M	140M	run	2:01	1.75%	java
934	oracle	1	56	0	12M	5552K	run	0:06	1.46%	xscreensaver
1120	root	1	59	0	4296K	2480K	cpu	0:00	0.25%	top
917	oracle	1	49	0	107M	36M	sleep	0:01	0.22%	nautilus
913	oracle	1	59	0	27M	15M	sleep	0:01	0.08%	metacity
11	root	18	59	0	12M	11M	sleep	0:41	0.06%	svc.configd

Displaying Process Class Information

To display information about process classes, use `priocntl -l`.

```
# priocntl -l
CONFIGURED CLASSES
=====
SYS (System Class)

TS (Time Sharing)
Configured TS User Priority Range: -60 through 60

SDC (System Duty-Cycle Class)

FSS (Fair Share)
    Configured FSS User Priority Range: -60 through 60

FX (Fixed priority)
Configured FX User Priority Range: 0 through 60
IA (Interactive)
Configured IA User Priority Range: -60 through 60
```

Determining the Global Priority of a Process

To determine the global priority of a process, use `ps -ecl`.

```
$ ps -ecl
```

F	S	UID	PID	PPID	CLS	PRI	ADDR	SZ	WCHAN	TTY	TIME	CMD
19	T	0	0	0	SYS	96	f00d05a8	0		?	0:03	sched
8	S	0	1	0	TS	50	ff0f4678	185	ff0f4848	?	36:51	init
19	S	0	2	0	SYS	98	ff0f4018	0	f00c645c	?	0:01	pageout
19	S	0	3	0	SYS	60	ff0f5998	0	f00d0c68	?	241:01	fsflush
8	S	0	269	1	TS	58	ff0f5338	303	ff49837e	?	0:07	sac
8	S	0	204	1	TS	43	ff2f6008	50	ff2f606e	console	0:02	sh

Designating a Process Priority

1. Start a process with a designated priority by using `prionctl -e -c class -m user-limit -p user-priority command-name`.
2. Verify the process status by using `ps -ecl | grep command-name`.

```
# prionctl -e -c TS -m 60 -p 60 find . -name core -print
# ps -ecl | grep find
0 S      0 2959 2771 TS 60      ?    1865      ? pts/1      0:01 gfind
ps -ecl | grep find
0 S      0 2959 2771 TS 60      ?    1961      ? pts/1      0:01 gfind
ps -ecl | grep find
0 R      0 2959 2771 TS 59      ?    1985      pts/1      0:02 gfind
```

Modifying a Process Priority

1. Change the priority of the process by using `prctl -s -p user-priority pid`.
2. Verify the process status by using `ps -ecl | grep command-name`.

```
# prctl -s -p 30 3093
# ps -ecf | grep myprog
  root   3093   2909   RT  130 09:09:34 pts/3    0:00 /bin/bash /root/myprog
  root   3124   2771   IA   32 09:15:25 pts/1    0:00 grep myprog
```


Agenda

- Implementing process execution in an appropriate scheduling class
- Managing process scheduling priority
- **Configuring the fair share scheduler**
- Managing the scheduling class of zones

Configuring the Fair Share Scheduler (FSS)

This section covers the following topics:

- Making the FSS the default scheduling class
- Manually moving processes from other classes into the FSS class
- Manually moving a project's processes into the FSS class
- Tuning scheduler parameters

Making FSS the Default Scheduling Class

To set the default scheduler for the system to be FSS,
use `dispadmin -d FSS`.

```
# dispadmin -d FSS
# dispadmin -d
FSS      (Fair Share)
```

```
# dispadmin -l
CONFIGURED CLASSES
=====

SYS      (System Class)
TS       (Time Sharing)
SDC      (System Duty-Cycle Class)
FSS      (Fair share)
FX       (Fixed Priority)
IA       (Interactive)
FSS      (Fair Share)
```

Manually Moving the `init` Process into the FSS Class

To move the `init` process into the FSS class, use `priocntl -s -c FSS -i pid 1`.

```
# ps -ecf | grep init
  root      1      0   TS   59 07:42:52 ?           0:00 /usr/sbin/init
  root  4564  1262   FSS    1 10:01:48 pts/1       0:00 grep init
# priocntl -s -c FSS -i pid 1
# ps -ef -o class,zone,fname | grep init
FSS    global init
```

Manually Moving Processes from Other Classes into the FSS Class

To move all processes into the FSS class, use `prionctl -s -c FSS -i all`.

```
# prionctl -s -c FSS -i all
```

```
# ps -ef -o class,zone,fname | grep -v CLS | sort -k2 | more
FSS    global asr-noti
FSS    global auditd
FSS    global automoun
FSS    global automoun
FSS    global bash
FSS    global bash
FSS    global bonobo-a
FSS    global clock-ap
FSS    global console-
FSS    global cron
FSS    global dbus-dae
```

Manually Moving a Project's Processes into the FSS Class

To move the processes that run in a project to the FSS scheduling class, use `priocntl -s -c FSS -i projid projectID_number`.

```
# ps -o user,pid,uid,projid,project,class
  USER   PID   UID PROJID  PROJECT  CLS
  root   2771     0      1 user.root  TS
  root   3000     0      1 user.root  TS
# priocntl -s -c FSS -i projid 1
# ps -o user,pid,uid,projid,project,class
  USER   PID   UID PROJID  PROJECT  CLS
  root   2771     0      1 user.root  FSS
  root   3015     0      1 user.root  FSS
```

Changing Scheduler Parameters

To change the scheduler parameters, use `dispadmin -c scheduler -g [-r resolution]`.

```
$ dispadmin -c FSS -g
#
# Fair Share Scheduler Configuration
#
RES=1000
#
# Time Quantum
#
```

```
QUANTUM=110
```

```
$ dispadmin -c FSS -g -r 100
#
# Fair Share Scheduler Configuration
#
RES=100
#
# Time Quantum
#
```

```
QUANTUM=11
```

Practice 9-1 Overview:

Modifying Process Scheduling Priority

This practice covers the following topics:

- Managing scheduling class and process priorities
- Configuring the fair share scheduler

Agenda

- Implementing process execution in an appropriate scheduling class
- Managing process scheduling priority
- Configuring the fair share scheduler
- Managing the scheduling class of zones

Managing the Scheduling Class of Zones

This section covers the following topics:

- Assigning CPU shares to the global zone
- Configuring CPU shares configuration in a nonglobal zone
- Measuring CPU performance in the zones
- Removing the CPU shares configuration from a zone

Assigning CPU Shares to the Global Zone

To assign CPU shares to the global zones, use `prctl -n zone.cpu-shares -v number_of_shares -r -i zone global`.

```
# prctl -n zone.cpu-shares -v 60 -r -i zone global
```

Configuring CPU Shares Configuration in a Nonglobal Zone

1. Add the CPU shares to the zone by using `zonecfg -z zone`.
2. Set the number of shares for the global zone by using `set cpu-shares=number`.
3. Exit `zonecfg`.
4. Verify the configuration change by using `zonecfg -z zone info`.

Configuring CPU Shares in a Nonglobal Zone: Example

```
# zonecfg -z hrzone
zonecfg:hrzone> set cpu-shares=80
zonecfg:hrzone> verify
zonecfg:hrzone> commit
zonecfg:hrzone> exit
# zonecfg -z hrzone info
zonename: hrzone
zonepath: /zones/hrzone
brand: solaris
autoboot: true
bootargs:
pool:
limitpriv:
scheduling-class:
ip-type: exclusive
hostid:
fs-allowed:
[cpu-shares: 80]
net:
address not specified
allowed-address not specified
physical: vnic1
defrouter not specified
rctl:
name: zone.cpu-shares
value: (priv=privileged,limit=80,action=none)
(output omitted)
```

Measuring CPU Performance in the Zones

To measure CPU performance in the zones, use `prstat -Z`.

```
# prstat -Z
```

```
...
```

```
...
```

```
...
```

ZONEID	NPROC	SWAP	RSS	MEMORY	TIME	CPU	ZONE
0	98	348M	451M	44%	0:00:50	0.3%	global
1	27	34M	43M	4.2%	0:20:09	8.3%	hrzone
2	27	34M	43M	4.2%	0:16:15	2.4%	itzone

Removing the CPU Shares Configuration from a Zone

1. Remove the CPU shares configuration from a zone by using `zonecfg -z zone clear cpu-shares`.
2. Verify the configuration change by using `zonecfg -z zone info`.
3. Reboot the zone to make the configuration effective.

Removing the CPU Shares Configuration from a Zone: Example

```
# zonecfg -z hrzone clear cpu-shares
# zonecfg -z hrzone info
zonename: hrzone
zonepath: /zones/hrzone
brand: solaris
autoboot: true
bootargs:
pool:
limitpriv:
scheduling-class:
ip-type: exclusive
hostid:
fs-allowed:
net:
    address not specified
    allowed-address not specified
    configure-allowed-address: true
    physical: vnic1
    defrouter not specified
...
...
```


Practice 9-2 Overview: Configuring the FSS in an Oracle Solaris Zone

This practice covers the following topics:

- Configuring CPU shares
- Monitoring FSS in two zones
- Removing the CPU shares configuration

Summary

In this lesson, you should have learned how to:

- Implement process execution in an appropriate scheduling class
- Manage process scheduling priority
- Manage the scheduling class of a zone
- Configure the fair share scheduler
- Monitor the fair share scheduler