

EXPERIMENT – 1

1.

```
mysql> use meher;
Database changed
mysql> create table student(regno int(3),name char(15),gender char(1),dob in
t(10),mobilen no int(10),city char(10));
Query OK, 0 rows affected, 3 warnings (0.03 sec)

mysql> desc student;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| regno | int | YES | | NULL | |
| name | char(15) | YES | | NULL | |
| gender | char(1) | YES | | NULL | |
| dob | int | YES | | NULL | |
| mobilen o | int | YES | | NULL | |
| city | char(10) | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.01 sec)
```

2.

```
mysql> create table faculty(facno int(10),facname varchar(15), gender char(1),dob int(10),mobilen o int(10));
Query OK, 0 rows affected, 3 warnings (0.08 sec)

mysql> describe faculty;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| facno | int | YES | | NULL | |
| facname | varchar(15) | YES | | NULL | |
| gender | char(1) | YES | | NULL | |
| dob | int | YES | | NULL | |
| mobilen o | int | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

3.

```
mysql> create table course(coursecode int(5),coursename char(15),facname char(10),semno int(10),halltcktno int(10));
Query OK, 0 rows affected, 3 warnings (0.03 sec)

mysql> describe course;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| coursecode | int | YES | | NULL | |
| coursename | char(15) | YES | | NULL | |
| facname | char(10) | YES | | NULL | |
| semno | int | YES | | NULL | |
| halltcktno | int | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

4.

```
mysql> describe department;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| deptno     | int       | YES  |     | NULL    |       |
| deptname   | char(10)  | YES  |     | NULL    |       |
| depthead   | int       | YES  |     | NULL    |       |
| facn0      | int       | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

5.

```
mysql> alter table faculty add dept char(10);
Query OK, 0 rows affected (0.06 sec)
Records: 0 Duplicates: 0 Warnings: 0

mysql> describe faculty;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| facno      | int       | YES  |     | NULL    |       |
| facname    | varchar(15) | YES  |     | NULL    |       |
| gender     | char(1)    | YES  |     | NULL    |       |
| dob        | int       | YES  |     | NULL    |       |
| mobileno   | int       | YES  |     | NULL    |       |
| dept       | char(10)   | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```