Ex.No: 1	Implementation and Time analysis of sorting algorithms. Bubble sort, Selection sort, Insertion sort, Merge sort and Quicksort

1. Bubble Sort

Objective

- To implement the Bubble Sort algorithm.
- To sort elements in ascending order by repeatedly swapping adjacent elements.
- To analyze its time complexity and performance.

code

```
#include <stdio.h>

void bubbleSort(int arr[], int n) {
    int i, j, temp;

    for(i = 0; i < n - 1; i++) {
        for(j = 0; j < n - i - 1; j++) {
            if(arr[j] > arr[j + 1]) {
                temp = arr[j];
                arr[j] = arr[j + 1];
                arr[j + 1] = temp;
            }
        }
    }
```

```
}

void printArray(int arr[], int n) {
    int i;
    for(i = 0; i < n; i++)
        printf("%d ", arr[i]);
}

int main() {
    int arr[] = {64, 34, 25, 12, 22, 11, 90};
    int n = sizeof(arr) / sizeof(arr[0]);

    bubbleSort(arr, n);

    printf("Sorted array: ");
    printArray(arr, n);

    return 0;
}
```

Output

```
Sorted array: 11 12 22 25 34 64 90

=== Code Execution Successful ===
```

Analysis

- Bubble Sort compares adjacent elements and swaps them if they are in the wrong order.

- After each pass, the largest element moves to its correct position.
- It is simple to implement but inefficient for large datasets.
- Best suited for small or nearly sorted arrays.

Conclusion

Bubble Sort is easy to understand and implement. However, due to its **$O(n^2)$** complexity, it is not suitable for large datasets. It is mainly used for educational purposes.

2. Selection Sort

Objective

- To implement the Selection Sort algorithm.
- To sort elements by selecting the minimum element in each pass.
- To analyze its performance.

Code (C)

```
#include <stdio.h>


int main() {
    int n, i, j, min, temp;
    printf("Enter number of elements: ");
    scanf("%d", &n);

    int a[n];

    printf("Enter elements:\n");
    for(i = 0; i < n; i++)
        scanf("%d", &a[i]);

    for(i = 0; i < n - 1; i++) {
        min = i;
        for(j = i + 1; j < n; j++) {
            if(a[j] < a[min])
                min = j;
        }
```

```
        temp = a[i];
        a[i] = a[min];
        a[min] = temp;
    }

    printf("Sorted array:\n");
    for(i = 0; i < n; i++)
        printf("%d ", a[i]);

    return 0;
}
```

Out put: Enter number of elements: 5

Enter elements:

64

34

25

12

22

Sorted array:

12 22 25 34 64

Analysis

- Finds the minimum element in the unsorted portion.
- Swaps it with the first unsorted element.

Conclusion

Selection Sort is easy to implement and performs fewer swaps, but it is inefficient for large datasets.

4. Merge Sort

Objective

- To implement the Merge Sort algorithm.
- To sort elements using the Divide and Conquer technique.

- To analyze its performance.

Code (C)

```
#include <stdio.h>


void merge(int a[], int l, int m, int r) {
    int i, j, k;
    int n1 = m - l + 1;
    int n2 = r - m;


    int L[n1], R[n2];


    for(i = 0; i < n1; i++)
        L[i] = a[l + i];


    for(j = 0; j < n2; j++)
        R[j] = a[m + 1 + j];


    i = j = 0;
    k = l;


    while(i < n1 && j < n2) {
        if(L[i] <= R[j])
            a[k++] = L[i++];
```

```
        else
            a[k++] = R[j++];
    }

    while(i < n1)
        a[k++] = L[i++];

    while(j < n2)
        a[k++] = R[j++];
}

void mergeSort(int a[], int l, int r) {
    if(l < r) {
        int m = (l + r) / 2;
        mergeSort(a, l, m);
        mergeSort(a, m + 1, r);
        merge(a, l, m, r);
    }
}

int main() {
    int n, i;

    printf("Enter number of elements: ");
```

```
    scanf("%d", &n);

    int a[n];

    printf("Enter elements:\n");
    for(i = 0; i < n; i++)
        scanf("%d", &a[i]);

    mergeSort(a, 0, n - 1);

    printf("Sorted array:\n");
    for(i = 0; i < n; i++)
        printf("%d ", a[i]);

    return 0;
}
```

Output

Enter number of elements: 5

Enter elements:

64

34

25

12

22

Sorted array:

12 22 25 34 64

Analysis

- Merge Sort divides the array into smaller subarrays and merges them after sorting.
- It guarantees O(n log n) performance in all cases.

Conclusion

Merge Sort is highly efficient for large datasets but requires extra memory during merging.

5. Quick Sort

Objective

- To implement the Quick Sort algorithm.
- To sort elements using partitioning.
- To analyze its efficiency.

Code (C)

```
#include <stdio.h>

int partition(int a[], int low, int high) {
    int pivot = a[high];
    int i = low - 1, temp;

    for(int j = low; j < high; j++) {
        if(a[j] < pivot) {
            i++;
            temp = a[i];
            a[i] = a[j];
            a[j] = temp;
        }
    }

    temp = a[i + 1];
    a[i + 1] = a[high];
    a[high] = temp;

    return i + 1;
}

void quickSort(int a[], int low, int high) {
    if(low < high) {
```

```
        int pi = partition(a, low, high);
        quickSort(a, low, pi - 1);
        quickSort(a, pi + 1, high);
    }
}

int main() {
    int n, i;

    printf("Enter number of elements: ");
    scanf("%d", &n);

    int a[n];

    printf("Enter elements:\n");
    for(i = 0; i < n; i++)
        scanf("%d", &a[i]);

    quickSort(a, 0, n - 1);

    printf("Sorted array:\n");
    for(i = 0; i < n; i++)
        printf("%d ", a[i]);
```

```
    return 0;
}
```

Output

Enter number of elements: 5

Enter elements:

64

34

25

12

22

Sorted array:

12 22 25 34 64

Analysis

- Quick Sort partitions the array around a pivot element.
- It is one of the fastest sorting algorithms in practice.

Time Complexity

- Best Case: O(n log n)
- Average Case: O(n log n)
- Worst Case: $O(n^2)$

Conclusion

Quick Sort provides excellent average-case performance and is widely used for sorting large datasets. Its worst case occurs only when poor pivot selection leads to highly unbalanced partitions.