

# Rajalakshmi Engineering College

Name: Jathin Chowdary CH  
Email: 240701209@rajalakshmi.edu.in  
Roll no: 240701209  
Phone: 8939767767  
Branch: REC  
Department: CSE - Section 10  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 9\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

#### Section 1 : Coding

##### 1. Problem Statement

Aarav is developing a music playlist application where users can manage their favorite songs. He wants to implement a feature that allows users to reorder the playlist by moving a song from one position to another.

You need to implement a function that performs the following operations using a LinkedList:

Add songs to the playlist in the given order. Move a song from a specified position to another position in the playlist. Print the final playlist after all operations.

##### ***Input Format***

The first line of the input consists of an integer  $n$  representing the number of songs.

The next n lines, each containing a string representing a song name.

After the songs are given the next line contains an integer m, the number of move operations.

The next m lines, each containing two integers x and y representing the move operation where the song at position x (0-based index) should be moved to position y.

### ***Output Format***

The output prints the final playlist, each song on a new line.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

SongA

SongB

SongC

SongD

SongE

2

2 4

0 3

Output: SongB

SongD

SongE

SongA

SongC

### ***Answer***

```
import java.util.*;
public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = sc.nextInt();
        sc.nextLine();
        LinkedList<String> playlist = new LinkedList<>();
```

```

    for (int i = 0; i < n; i++) playlist.add(sc.nextLine());
    int m = sc.nextInt();
    for (int i = 0; i < m; i++) {
        int x = sc.nextInt();
        int y = sc.nextInt();
        String song = playlist.remove(x);
        playlist.add(y, song);
    }
    for (String song : playlist) System.out.println(song);
}
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Sarah, a warehouse manager, is managing a list of product names in her store's inventory system. She needs to perform basic operations like adding (inserting) new products, removing products that are sold out or discontinued, displaying all the products in stock, and searching for a specific product in the inventory list.

Sarah's goal is to manage the inventory using a list of product names (strings). The system allows her to perform the following operations using ArrayList:

**Insert a Product:** Sarah adds a new product to the inventory. **Delete a Product:** Sarah removes a product from the inventory when it's sold or discontinued. **Display the Inventory:** Sarah checks all the products currently available in the inventory. **Search for a Product:** Sarah searches for a specific product in the inventory to check if it's available.

### **Input Format**

The input consists of multiple space-separated values representing different operations on a product list. Each operation follows a specific format:

- 1 <product\_name> - Adds <product\_name> to the product list.
- 2 <product\_name> - Removes <product\_name> from the product list if it exists.

3 - Print all products currently on the list.

4 <product\_name> - Checks if <product\_name> exists in the list.

### **Output Format**

The output displays,

For (choice 1) prints, " <item> has been added to the list."

For (choice 2) prints, " <item> has been removed from the list."

For (choice 3) prints, "Items in the list:" followed by each item in the list on a new line, or "The list is empty." if the list is empty.

For (choice 4) prints, " <item> is found in the list." or " <item> not found in the list."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1 apple 1 banana 2 apple 3 4 apple

Output: apple has been added to the list.

banana has been added to the list.

apple has been removed from the list.

Items in the list:

banana

apple not found in the list.

### **Answer**

```
import java.util.ArrayList;  
import java.util.Scanner;
```

```
class StringListOperations {  
    public static void insertItem(ArrayList<String> list, String item) {  
        list.add(item);  
        System.out.println(item + " has been added to the list.");  
    }  
}
```

```

public static void deleteItem(ArrayList<String> list, String item) {
    if (list.contains(item)) {
        list.remove(item);
        System.out.println(item + " has been removed from the list.");
    } else {
        System.out.println(item + " not found in the list.");
    }
}

```

```

public static void displayList(ArrayList<String> list) {
    if (list.isEmpty()) {
        System.out.println("The list is empty.");
    } else {
        System.out.println("Items in the list:");
        for (String item : list) {
            System.out.println(item);
        }
    }
}

```

```

public static void searchItem(ArrayList<String> list, String item) {
    if (list.contains(item)) {
        System.out.println(item + " is found in the list.");
    } else {
        System.out.println(item + " not found in the list.");
    }
}
}

```

```

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        ArrayList<String> list = new ArrayList<>();

        String input = sc.nextLine();
        String[] commands = input.split(" ");
        int i = 0;
        while (i < commands.length) {
            int choice = Integer.parseInt(commands[i]);
            switch (choice) {

```

```

case 1:
    if (i + 1 < commands.length) {
        StringListOperations.insertItem(list, commands[i + 1]);
        i += 2;
    } else {
        System.out.println("No string provided for insertion.");
        i++;
    }
    break;
case 2:
    if (i + 1 < commands.length) {
        StringListOperations.deleteItem(list, commands[i + 1]);
        i += 2;
    } else {
        System.out.println("No string provided for deletion.");
        i++;
    }
    break;
case 3:
    StringListOperations.displayList(list);
    i += 1;
    break;
case 4:
    if (i + 1 < commands.length) {
        StringListOperations.searchItem(list, commands[i + 1]);
        i += 2;
    } else {
        System.out.println("No string provided for searching.");
        i++;
    }
    break;
}
}
}
}
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Sanjay is working on a program to merge two sorted linked lists into a

single sorted list using Java's LinkedList class from the Collections framework. Given two sorted linked lists, he wants to merge them while maintaining the sorted order.

Write a Java program that:

Reads two sorted linked lists. Merges them into a single sorted linked list. Prints the merged list in ascending order.

***Input Format***

The first line contains an integer m (the size of the first linked list).

The second line contains m space-separated integers (sorted).

The third line contains an integer n (the size of the second linked list).

The fourth line contains n space-separated integers (sorted).

***Output Format***

The output prints the merged linked list as space-separated integers.

Refer to the sample output for formatting specifications.

***Sample Test Case***

Input: 2

5 10

3

1 3 8

Output: 1 3 5 8 10

***Answer***

```
import java.util.*;
class MergeSortedLinkedLists {

    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int m = sc.nextInt();
```

```

LinkedList<Integer> list1 = new LinkedList<>();
for (int i = 0; i < m; i++) {
    list1.add(sc.nextInt());
}

int n = sc.nextInt();
LinkedList<Integer> list2 = new LinkedList<>();
for (int i = 0; i < n; i++) {
    list2.add(sc.nextInt());
}

list1.addAll(list2); // Merge the two lists
Collections.sort(list1); // Sort the combined list

for (int num : list1) {
    System.out.print(num + " ");
}

sc.close();
}
}

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

A teacher is filtering a list of words provided by students. Some words contain too many vowels, making them difficult for a spelling competition. The teacher decides to remove all words that contain more than two vowels.

Help the teacher to implement it using ArrayList.

##### **Input Format**

The first line contains an integer N, representing the number of words in the list.

The next N lines contain a string representing the words (one per line).

##### **Output Format**



The output consists of words that contain two or less than two vowels, printed in the same order they appeared in the input. Each word is printed on a new line.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 1

sri

Output: sri

### **Answer**

```
import java.util.ArrayList;
import java.util.Scanner;

class VowelFilter {
    public static int countVowels(String word) {
        int count = 0;
        for (char c : word.toCharArray()) {
            if ("aeiou".indexOf(c) != -1) {
                count++;
            }
        }
        return count;
    }

    public static void filterWords(int n, Scanner sc) {
        ArrayList<String> validWords = new ArrayList<>();
        for (int i = 0; i < n; i++) {
            String word = sc.nextLine();
            if (countVowels(word) <= 2) {
                validWords.add(word);
            }
        }
        for (String word : validWords) {
            System.out.println(word);
        }
    }
}

public class Main {
```

```
public static void main(String[] args) {  
    Scanner sc = new Scanner(System.in);  
    int n = sc.nextInt();  
    sc.nextLine();  
    VowelFilter.filterWords(n, sc);  
    sc.close();  
}  
}
```

**Status :** Correct

**Marks :** 10/10