INSTAHEALTH: A PRIVACY-PRESERVING ZERO-CLOUD ON-DEVICE SMARTWATCH HEALTH INTELLIGENCE SYSTEM WITH ADAPTIVE MULTI-PROFILE PHYSIOLOGICAL MODELING

A Project Report

Submitted by

A . Jathin Reddy (reg no : 122311520105)

K.Pranay Kumar (reg.no : 122311520133)

in partial fulfillment for the award of the degree

of

Bachelor of Technology


in

Computer Sciences & Engineering

Under the Guidance of

Dr. Thirumalesu.K

Assistant Professor



SCHOOL OF TECHNOLOGY

DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

THE APOLLO UNIVERSITY, CHITTOOR

April, 2026

DECLARATION

We hereby declare that the project entitled “INSTAHEALTH: A PRIVACY-PRESERVING ZERO-CLOUD ON-DEVICE SMARTWATCH HEALTH INTELLIGENCE SYSTEM WITH ADAPTIVE MULTI-PROFILE PHYSIOLOGICAL MODELING” submitted by us, for the award of the degree of Bachelor of Technology in Computer Science & Engineering, School of Technology to The Apollo University is a record of bonafide work carried out by us under the supervision of Dr. Thirumalesu.K, Assistant Professor, Department of Computer Science & Engineering. We further declare that the work reported in this thesis has not been submitted and will not be submitted, either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university.

Signature of the Candidate(s) with names:

1. A . Jathin Reddy (reg no : 122311520105) _____

2. K.Pranay Kumar (reg.no : 122311520133) _____

Place : Chittoor

Date : April, 2026

THE APOLLO UNIVERSITY, CHITTOOR

SCHOOL OF TECHNOLOGY

BONAFIDE CERTIFICATE

This is to certify that the project report entitled “INSTAHEALTH: A PRIVACY-PRESERVING ZERO-CLOUD ON-DEVICE SMARTWATCH HEALTH INTELLIGENCE SYSTEM WITH ADAPTIVE MULTI-PROFILE PHYSIOLOGICAL MODELING” is the bonafide work carried out by A. JATHIN REDDY (Register No: 122311520105) and K. PRANAY KUMAR (Register No: 122311520133), under my supervision and guidance, in partial fulfillment of the requirements for the award of the degree of Bachelor of Technology in Computer Science & Engineering by The Apollo University, Chittoor.

Signature of the Guide

Dr. Thirumalesu.K
Assistant Professor, Dept. of CSE

Program Coordinator
Dept. of CSE
The Apollo University

Dean
School of Technology
The Apollo University

Internal Examiner

External Examiner

ACKNOWLEDGEMENT

We express our sincere gratitude to our project guide Dr. Thirumalesu.K, Assistant Professor, Department of Computer Science & Engineering, School of Technology, The Apollo University, Chittoor, for his continuous guidance, valuable suggestions and constructive feedback throughout the course of this project. His academic rigor and support have been instrumental in the successful completion of this work.

We also thank the Project Coordinator, Department of Computer Science & Engineering, School of Technology, The Apollo University for providing direction, structured milestone reviews, and invaluable technical counsel throughout the progression of this research.

We extend our heartfelt thanks to the Programme Coordinator, Department of Computer Science & Engineering, School of Technology, The Apollo University for providing the necessary academic support, laboratories, and computing infrastructure to carry out this project effectively.

We convey our sincere thanks to Prof. D. Jagadeesan, Dean, School of Technology, for his encouragement, leadership, and administrative support throughout the tenure of our project work.

We express our profound gratitude to the Honourable Chancellor Emeritus Dr. Prathap C. Reddy, Dr. H. Vinod Bhat, Vice-Chancellor, and Prof. M. Potharaju, Registrar of The Apollo University for their visionary leadership, institutional inspiration, and continuous fostering of a vibrant research and innovation culture.

We gratefully acknowledge the support of all faculty members and technical staff of the Department of Computer Science & Engineering for their cooperation, critical reviews, and valuable inputs during the project period.

We also thank our fellow classmates, peers, and friends for their camaraderie, constructive debates, and collaborative assistance during the experimental benchmarking phases.

Finally, we express our deepest gratitude to our parents and family members for their unconditional love, moral support, patient understanding, and perpetual blessings throughout our academic journey.

I would like to thank my friends and classmates for their constant encouragement and support.

Finally, I express my deepest gratitude to my parents and family members for their unwavering support, motivation and blessings.

A . Jathin Reddy (reg no : 122311520105)

K.Pranay Kumar (reg.no : 122311520133)

TABLE OF CONTENTS

Chapter	CONTENTS	Page No.
	ABSTRACT	I
	List of Figures	II
	List of Tables	III
	Abbreviations	IV
1	**INTRODUCTION**	**1**
	1.1 Background of the Study	1
	1.2 Problem Statement	3
2	**LITERATURE REVIEW**	**6**
	2.1 Introduction	6
	2.2 Review of Existing Systems	7
	2.3 Limitations of Existing Systems	11
	2.4 Proposed System Overview	12
3	**OBJECTIVES AND SCOPE OF WORK**	**15**
	3.1 Objectives of the Project	15
	3.2 Scope of the Project	17
4	**SYSTEM ANALYSIS & DESIGN**	**20**
	4.1 System Requirements (Hardware & Software)	20
	4.2 System Architecture	23
	4.3 Data Flow Diagram (DFD)	27
5	**IMPLEMENTATION**	**33**
	5.1 Tools & Technologies Used	33
	5.2 Module Description	35
	5.3 Algorithms / Methods Used	38
	5.4 Code Snippets (optional)	42
6	**RESULTS AND DISCUSSIONS**	**45**
	6.1 Output Screens / Results	45
	6.2 Testing (Test Cases & Results)	48
	6.3 Performance Analysis	51

Chapter	CONTENTS	Page No.
7	**CONCLUSION AND FUTURE SCOPE**	**55**
	7.1 Conclusion	55
	7.2 Future Enhancements	56
	REFERENCES	**58**
	PUBLICATIONS/CONFERENCES	**62**

ABSTRACT

Modern wearable health intelligence predominantly relies on continuous cloud transmission of raw photoplethysmography (PPG) and inertial telemetry, introducing profound privacy vulnerabilities, non-ephemeral data exposure, and high energy overheads. Concurrently, commercial wearables enforce static normative population thresholds that disregard individual circadian rhythms, athletic conditioning, and accumulated recovery deficits. This project introduces InstaHealth, a strictly zero-cloud, privacy-preserving on-device smartwatch health intelligence system featuring adaptive multi-profile physiological modeling. InstaHealth executes entirely within the resource constraints of wearable microcontrollers without network permissions. The architecture integrates a real-time Signal Quality Index (SQI) motion-artifact filter, a 48-hour autonomous calibration state machine transitioning from clinically grounded Tanaka and Gulati demographic priors to personalized baselines, and an on-device TinyML Multi-Layer Perceptron utilizing micro-batch Stochastic Gradient Descent with bounded gradient clipping ($|\Delta W| \leq 0.05$). Sandboxed multi-profile isolation enables concurrent, zero-leakage tracking across disparate athletic personas. Deployed and evaluated on embedded smartwatch runtimes, InstaHealth achieves a 62.4% reduction in target prediction Mean Absolute Error over static population baselines, executes forward inference in 1.18 ms with 18.2 KB RAM utilization, and sustains 52.8 hours continuous operation on a standard 65 mAh battery cell, demonstrating sovereign, clinically rigorous personal health intelligence.

Keywords: *Edge Computing, On-Device TinyML, Zero-Cloud Privacy, Adaptive Physiological Modeling, Smartwatch Health Intelligence*

LIST OF FIGURES

Figure No.	Title	Page No.
Figure 3.1	InstaHealth 12-Week Comprehensive Project Engineering Gantt Schedule	18
Figure 4.1	InstaHealth Multi-Layered Zero-Cloud On-Device Smartwatch Architecture	23
Figure 4.2	Data Flow Diagram (DFD) Level 0: Context Level System Representation	26
Figure 4.3	Data Flow Diagram (DFD) Level 1: Subsystem Level Functional Decomposition	27
Figure 4.4	Data Flow Diagram (DFD) Level 2: Detailed Process Flow for TinyML Micro-SGD Engine	28
Figure 5.1	InstaHealth 48-Hour On-Device Calibration and Lifecycle State Machine Workflow	36
Figure 6.1	InstaHealth Day 1 & Day 2 Calibration UI: Real-Time Telemetry vs Demographic Benchmarks	43
Figure 6.2	InstaHealth Day 3+ Calibrated Prescription UI: Multi-Metric Circular Ring Carousel	44
Figure 6.3	Empirical Ablation Study: Mean Absolute Error (MAE) Across Physiological Models	49
Figure 6.4	Hardware Subsystem Current Draw Profile and 48-Hour Smartwatch Battery Budget	51

LIST OF TABLES

Table No.	Title	Page No.
Table 2.1	Comparative Architectural and Privacy Matrix: InstaHealth vs Commercial Platforms	11
Table 3.1	Project Risk Assessment, Likelihood-Impact Rating, and Architectural Mitigation Matrix	19
Table 4.1	Embedded Microcontroller and Biometric Hardware Sensor Specifications	22
Table 4.2	InstaHealth System Comprehensive Data Dictionary and Flow Specifications	29
Table 4.3	Clinically Stratified Demographic Population Baseline Lookup Table	30
Table 4.4	Karvonen Heart Rate Reserve (HRR) Training Intensity Zones and Metabolic Demands	31
Table 5.1	Embedded Hardware Platform Comparison and Compute Resource Allocation	33
Table 5.2	Software Toolchains, Libraries, Compilers, and Runtime Dependencies	34
Table 5.3	InstaHealth Multi-Profile Avatar Sandboxing and Namespace Partitioning	36
Table 6.1	Comprehensive System Test Cases (TC01 to TC12) and Experimental Validation Results	46
Table 6.2	Signal Quality Index (SQI) Artifact Rejection Performance Across Activity Modalities	48
Table 6.3	Empirical Model Ablation Performance: TinyML MLP vs Linear Regression vs Static Rules	49
Table 6.4	On-Device Execution Latency and Memory Footprint Profile on ARM Cortex-M4F	50
Table 6.5	Subsystem Current Consumption Profile and 65 mAh Battery Life Budget	51

LIST OF ABBREVIATIONS

Abbreviation	Full Terminology
API	Application Programming Interface
BLE	Bluetooth Low Energy
BPM	Beats Per Minute
CDC	Centers for Disease Control and Prevention
CMSIS-NN	Cortex Microcontroller Software Interface Standard - Neural Network
DFD	Data Flow Diagram
DMA	Direct Memory Access
DSP	Digital Signal Processing
ECG	Electrocardiogram
EDA	Electrodermal Activity
EEPROM	Electrically Erasable Programmable Read-Only Memory
EMA	Exponential Moving Average
FFT	Fast Fourier Transform
FPU	Floating Point Unit
GDPR	General Data Protection Regulation
GUI	Graphical User Interface
HIPAA	Health Insurance Portability and Accountability Act
HR	Heart Rate
HRmax	Maximum Heart Rate
HRR	Heart Rate Reserve
HRV	Heart Rate Variability
IMU	Inertial Measurement Unit
INT8	8-Bit Signed Integer Quantization
IoT	Internet of Things
MAE	Mean Absolute Error
MCU	Microcontroller Unit
MLP	Multi-Layer Perceptron
MSE	Mean Squared Error

Abbreviation	Full Terminology
PPG	Photoplethysmography
PWA	Progressive Web Application
RAM	Random Access Memory
ReLU	Rectified Linear Unit
RMSSD	Root Mean Square of Successive Differences
ROM	Read-Only Memory
SaMD	Software as a Medical Device
SGD	Stochastic Gradient Descent
SoC	System on Chip
SQI	Signal Quality Index
SRAM	Static Random Access Memory
TFLM	TensorFlow Lite for Microcontrollers
TinyML	Tiny Machine Learning
UI	User Interface
UX	User Experience
VO2 Max	Maximal Oxygen Consumption Rate
WHO	World Health Organization

CHAPTER 1: INTRODUCTION

1.1 Background of the Study

The past decade has witnessed an unprecedented paradigm shift in consumer health informatics and personal computing, catalyzed by the explosive proliferation of miniaturized, wrist-worn wearable devices. Commercial smartwatches and biometric fitness trackers—manufactured by industry leaders such as Apple, Google, Samsung, Garmin, and Whoop—have transitioned from novelty pedometers into continuous, multi-modal physiological surveillance platforms. Equipped with high-density optical photoplethysmography (PPG) sensor arrays, triaxial micro-electro-mechanical systems (MEMS) accelerometers, continuous skin temperature thermistors, and peripheral capillary oxygen saturation (SpO2) monitors, modern smartwatches record hundreds of millions of discrete physiological telemetry points per user per week.

This continuous biosensing capability represents a profound evolution in modern preventive medicine. Traditionally, clinical medicine has functioned under an episodic diagnostic model: patients present symptoms during scheduled examinations, yielding discrete, cross-sectional snapshots of cardiac activity, blood pressure, and systemic health. Such episodic measurements frequently fail to capture transient arrhythmias, white-coat hypertension, intermittent nocturnal apnea, or cumulative physiological strain. Wrist-worn continuous monitoring bridges this clinical blind spot by providing high-resolution, longitudinal physiological trajectories, enabling the early detection of cardiovascular anomalies, chronic sleep deprivation, and autonomic nervous system fatigue long before acute symptoms manifest.

Concurrently, the computational capabilities of wrist-worn System-on-Chips (SoCs) have expanded dramatically. Microcontroller units (MCUs) featuring ARM Cortex-M33, Cortex-M4F, and dual-core application processors now incorporate hardware floating-point units (FPUs), digital signal processing (DSP) instruction extensions, and dedicated low-power neural processing accelerators. These hardware breakthroughs have fostered the emergence of Tiny Machine Learning (TinyML)—the discipline of deploying and executing optimized machine learning inferences and micro-training routines directly on resource-constrained embedded platforms operating with sub-milliwatt power budgets and kilobytes of Static Random-Access Memory (SRAM).

However, this technological convergence has exposed a critical architectural dichotomy. While the sensing and compute capabilities of wearable hardware have grown exponentially, commercial health platforms continue to adhere to an outdated, cloud-dependent architectural paradigm. In current market ecosystems, smartwatches function primarily as passive telemetry conduits: raw or minimally pre-processed biosignals are continuously streamed via Bluetooth Low Energy (BLE) to a companion smartphone, which subsequently exfiltrates the telemetry across the public Internet to multi-tenant corporate cloud data centers for batch analytics, feature

extraction, and target scoring. This architectural reliance on cloud infrastructure introduces severe privacy vulnerabilities, continuous energy consumption over radio interfaces, and systemic data ownership risks.

1.2 Problem Statement

The dominant cloud-centric paradigm of contemporary wearable health intelligence suffers from two critical, interrelated structural flaws: the Privacy and Security Crisis, and the Clinical Flaw of Static Normative Thresholds.

1. The Privacy and Security Crisis: Continuous biometric telemetry is fundamentally distinct from other categories of digital data. A user's continuous PPG waveform, heart rate variability (HRV) signature, circadian rest-activity cycle, and spatial gait dynamics represent unique, immutable biological identifiers—effectively constituting a continuous physiological fingerprint. When these sensitive telemetry streams are transmitted across public networks and stored in persistent cloud databases, they become susceptible to catastrophic security breaches, unauthorized commercial exploitation, and involuntary surveillance. Secondary data monetization by third-party health insurers, data brokers, and targeted advertising cartels routinely occurs behind opaque terms-of-service agreements, potentially resulting in insurance premium penalties or employment discrimination based on inferred health risks. Furthermore, compliance with international data privacy regulations—including the European Union General Data Protection Regulation (GDPR), the United States Health Insurance Portability and Accountability Act (HIPAA), and the Indian Digital Personal Data Protection (DPDP) Act of 2023—becomes exceptionally difficult to audit or enforce across distributed cloud pipelines. Finally, cloud-dependent wearables exhibit zero offline autonomy; when users enter remote, tactical, aviation, or maritime environments lacking cellular or Wi-Fi connectivity, cloud-dependent health algorithms completely cease functioning, stranding users without actionable health intelligence.

2. The Clinical Flaw of Static Normative Thresholds: Despite collecting rich, individualized physiological time-series data, commercial wearable platforms predominantly evaluate user health against crude, static, one-size-fits-all population averages. The most pervasive example is the ubiquitous daily target of 10,000 steps—a figure that originated not from a peer-reviewed clinical trial, but as a marketing gimmick devised by the Yamasa Clock and Instrument Company in 1965 to promote the 'Manpo-kei' (10,000-steps meter) ahead of the Tokyo Olympics. Enforcing this uniform threshold across diverse populations disregards biological sex, chronological age, biomechanical limitations, and clinical contraindications: for a sedentary geriatric patient recovering from myocardial infarction, 10,000 steps represents dangerous overexertion; for an elite collegiate endurance athlete, it represents a sedentary rest day.

Similarly, commercial sleep tracking platforms enforce an arbitrary, uniform requirement of 8.0 hours of nightly rest, completely ignoring established sleep medicine literature demonstrating

that baseline nocturnal sleep needs vary across healthy human adults from 6.5 to 9.0 hours, regulated by homeostatic sleep pressure (Process S) and endogenous circadian phase (Process C). When a user who naturally thrives on 7.0 hours of deep, consolidated sleep is repeatedly penalized with low 'sleep scores' and ominous red warnings, the system induces orthosomnia—a clinical anxiety disorder driven by the obsessive pursuit of arbitrary wearable sleep metrics. Furthermore, commercial heart rate tracking remains shackled to the archaic Fox and Haskell formula (HRmax = 220 - Age), introduced in 1971 without formal regression validation, which exhibits standard estimation errors exceeding ±12 to ±15 beats per minute and systematically underpredicts maximum heart rate in older adults and females.

Consequently, there exists an urgent, unaddressed imperative for a fully autonomous, on-device health intelligence architecture that eliminates all cloud dependencies while replacing static population heuristics with continuous, adaptive physiological modeling.

1.3 Motivation and Research Questions

The overarching motivation of this project is to restore absolute biological data sovereignty to the individual user while advancing the clinical efficacy of wearable physiological modeling. By executing all digital signal processing, demographic cohort stratification, baseline calibration, and neural adaptation strictly on-device inside an air-gapped embedded sandbox, we can provably guarantee that zero bytes of physiological telemetry ever leave the physical perimeter of the wearable device.

To achieve this objective, this research investigates and resolves four fundamental research questions (RQs):

• Research Question 1 (RQ1 - Autonomous Calibration): How can an embedded smartwatch runtime autonomously transition from cold-start population demographic priors to a mathematically converged, individualized physiological baseline over an initial 48-hour continuous wear cycle without requiring cloud-side batch processing or manual clinical configuration?

• Research Question 2 (RQ2 - Stable On-Device Adaptation): What mathematical formulations, learning rate schedules, and gradient clipping bounds are required to enable continuous, on-device TinyML micro-batch training on live physiological telemetry streams without inducing catastrophic gradient explosion, divergence, or memory exhaustion on an embedded ARM microcontroller?

• Research Question 3 (RQ3 - Multi-Profile Contextual Sandboxing): How can multiple distinct physical activity personas (e.g., endurance running, mindfulness meditation, cycling, swimming) be maintained simultaneously on a single wearable device such that baseline physiological parameters for one activity do not corrupt or contaminate the adaptation parameters of another?

• Research Question 4 (RQ4 - Embedded Resource & Power Budgeting): What hardware-software co-design principles enable real-time biosignal ingestion (25 Hz), signal quality index (SQI) motion artifact filtering, TinyML neural inference (<2 ms), and 60 fps glanceable visualization while maintaining a total active current draw under 1.35 mA to sustain multi-day battery life on a standard 65 mAh lithium-ion cell?

1.4 Overview of Proposed Solution and Key Contributions

To address the identified crises and answer these research questions, this project presents InstaHealth: a privacy-preserving, zero-cloud, on-device smartwatch health intelligence system featuring adaptive multi-profile physiological modeling. InstaHealth executes as a fully autonomous software stack deployed on wearable hardware, enforcing an air-gapped operational model with zero network socket allocation and zero cloud communication.

The key technical and scientific contributions of this research are summarized as follows:

1. Zero-Cloud Sovereign Architecture: We design and implement a strictly localized health intelligence engine that executes continuous biosignal filtering, feature extraction, baseline tracking, and target prescription entirely within the local embedded memory space. InstaHealth requires zero cloud servers, zero external APIs, zero companion smartphone exfiltration, and zero persistent user telemetry logs, establishing absolute mathematical privacy guarantees.

2. Clinically Stratified Demographic Initialization: To resolve the cold-start problem inherent in purely localized systems, InstaHealth integrates a locally stored lookup matrix derived from extensive clinical epidemiological data (spanning five age cohorts: 18-29, 30-39, 40-49, 50-59, and 60+). The system implements sex-specific maximum heart rate modeling using the Tanaka et al. (2001) formula for males ($HRmax = 208 - 0.7 \times Age$) and the Gulati et al. (2010) formula for females ($HRmax = 206 - 0.88 \times Age$), establishing statistically rigorous initial priors without requiring cloud consultation.

3. 48-Hour Autonomous Calibration State Machine: We engineer a deterministic three-phase calibration state machine. During Day 1 (UNCALIBRATED) and Day 2 (CALIBRATING), the system continuously records passive telemetry and presents glanceable comparative visualizations ('You' vs 'Human Average') without enforcing disruptive alarms. At the conclusion of the 48-hour window, the system automatically commits the converged baseline and transitions to Day 3+ (CALIBRATED), unlocking dynamic, personalized daily health prescriptions.

4. On-Device TinyML Micro-SGD Engine: We formulate and deploy a quantized 2-layer Multi-Layer Perceptron (MLP) (5 inputs, 8 hidden neurons with ReLU activation, 3 linear outputs) that performs on-device incremental learning directly from live physiological streams. The engine utilizes micro-batch Stochastic Gradient Descent (Micro-SGD) with hard gradient clipping ($|\Delta W| \leq 0.05$), preventing catastrophic weight drift while achieving a 62.4% reduction in prediction Mean Absolute Error (MAE) compared to static population heuristics.

5. Sandboxed Multi-Profile Context Isolation: We introduce an emoji-keyed namespace isolation architecture that partitions the embedded storage into completely independent silos for distinct athletic personas (Runner, Meditator, Cyclist, Swimmer). Each persona maintains dedicated baseline vectors, weight parameters, and calibration counters, enabling rapid context switching with zero inter-profile data leakage.

6. Dynamic Prescription Synthesis Engine: InstaHealth replaces rigid goals with dynamic daily prescriptions. The system integrates the Karvonen Heart Rate Reserve (HRR) formula for cardiovascular strain tracking, Belenky et al. (2003) sleep debt carryover modeling (with an exponential decay factor $\lambda = 0.5$), and adaptive step targets modulated by real-time autonomic recovery, ensuring clinical safety and high user adherence.

7. High-Performance Glanceable Circular UI: We develop a high-DPI HTML5 Canvas rendering engine optimized for circular smartwatch displays (360x360 to 454x454 pixels). The interface delivers smooth 60 fps anti-aliased circular gauge animations, glanceable color-coded strain arcs, and swipe-driven carousel navigation while consuming less than 48.6 KB of executable storage.

1.5 Organization of the Project Report

The remainder of this project report is systematically structured into six subsequent chapters:

• Chapter 2 (Literature Review) conducts an exhaustive review of commercial wearable ecosystems, cloud vulnerabilities, static vs. dynamic physiological models (Tanaka, Gulati, Karvonen, Belenky), and the emergence of TinyML edge computing. It presents a detailed comparative matrix contrasting InstaHealth against commercial market leaders and formalizes the underlying mathematical frameworks.

• Chapter 3 (Objectives and Scope of Work) articulates the primary research and engineering objectives, establishes clear in-scope capabilities and out-of-scope boundaries, provides a comprehensive 12-week project schedule with an embedded Gantt chart (Figure 3.1), and presents a rigorous risk assessment and mitigation matrix.

• Chapter 4 (System Analysis & Design) details the functional and non-functional requirements, hardware sensor specifications, and the multi-layered on-device system architecture (Figure 4.1). It presents complete Data Flow Diagrams across Context Level 0 (Figure 4.2), Subsystem Level 1 (Figure 4.3), and Detailed Process Level 2 (Figure 4.4), accompanied by a comprehensive data dictionary and mathematical derivations.

• Chapter 5 (Implementation) describes the embedded hardware testbeds, software libraries, and toolchains utilized. It details each of the six architectural modules, presents formal algorithmic workflows with structured pseudo-code (Algorithms 5.1 through 5.4), embeds the 48-hour calibration lifecycle workflow (Figure 5.1), and provides fully annotated production source code listings.

• Chapter 6 (Results and Discussion) showcases the high-resolution user interface output screens across calibration and calibrated operational states (Figures 6.1 and 6.2). It presents the complete test suite execution results across twelve comprehensive test cases (TC01 to TC12), analyzes signal quality index performance under motion corruption, details the empirical model ablation study (Figure 6.3), profiles microcontroller latency and memory footprints, and evaluates system current draw against the 48-hour battery budget (Figure 6.4).

• Chapter 7 (Conclusion and Future Scope) synthesizes the scientific contributions of the project, evaluates its broader implications for digital health sovereignty, and outlines key future enhancements, including multi-modal sensor expansion, federated edge learning, and on-device quantized conversational language models.

The report concludes with a comprehensive References section formatted strictly according to institutional standards, followed by a preprint summary of the draft research publication submitted to IEEE BSN 2026.

CHAPTER 2: LITERATURE REVIEW

2.1 Introduction

Wearable health informatics has emerged as a cornerstone of modern digital medicine, bridging consumer wellness devices and clinical preventive monitoring. The historical trajectory of this field spans three distinct technological epochs. The first epoch (1970s–1990s) was characterized by simple mechanical and electromechanical step counters and episodic clinical electrocardiograms (ECGs). These devices operated under strict analog constraints, lacked internal non-volatile memory, and provided rudimentary cumulative metrics without real-time physiological context.

The second epoch (2000s–2010s) witnessed the commercial maturation of optical photoplethysmography (PPG) and micro-electro-mechanical systems (MEMS) inertial sensors. PPG operates fundamentally on the optical Beer-Lambert law: light emitted from light-emitting diodes (typically green at 525 nm for wrist wearables, or red/infrared at 660/940 nm for pulse oximetry) penetrates cutaneous and subcutaneous vascular tissues. As pulsatile arterial blood flows through microvascular beds with each cardiac contraction, optical absorption fluctuates. Photodetectors capture the backscattered photons, generating a time-series voltage signal proportional to blood volume changes. Concurrent triaxial accelerometry enabled basic actigraphy and sleep-wake estimation. However, this epoch remained inextricably bound to paired smartphone synchronization and centralized web portals for offline processing.

The current third epoch (2020s–present) is defined by the convergence of multi-wavelength optical sensor arrays, high-throughput embedded System-on-Chips (SoCs), and edge artificial intelligence. Modern wearables capture continuous photoplethysmography, heart rate variability (HRV), peripheral oxygen saturation (SpO2), continuous skin temperature, and single-lead electrocardiography. Nevertheless, the software and data architectures governing these sophisticated sensing platforms have largely remained centralized, creating severe privacy vulnerabilities and clinical limitations that this research systematically investigates.

2.2 Review of Existing Systems

A comprehensive analysis of contemporary wearable computing reveals critical architectural choices across commercial platforms and academic research systems. This section reviews existing work across three essential domains: cloud-centric architectures and privacy vulnerabilities, the clinical inadequacy of static normative thresholds, and the state-of-the-art in edge AI and TinyML.

2.2.1 Cloud-Centric Wearables and Privacy Vulnerabilities

Commercial wearable ecosystems—including Apple HealthKit, Google Fit / Fitbit Health Cloud, Garmin Connect, Whoop Analytics, and the Oura Cloud Platform—rely almost exclusively on

client-server cloud architectures. Under this operational model, the physical wrist-worn device functions primarily as an ephemeral sensor gateway. Telemetry packets are serialized and transmitted across a Bluetooth Low Energy (BLE) link to a companion smartphone app, which batches and uploads the raw or compressed time-series data to multi-tenant cloud storage clusters over cellular or Wi-Fi networks.

Extensive cybersecurity and privacy research has demonstrated that this cloud-dependent topology presents profound structural vulnerabilities. In their seminal privacy analysis of wearable health data, Christodoulou and Pezoulas (2021) demonstrated that continuous physiological time-series data—specifically high-resolution resting heart rate, sleep architecture timestamps, and diurnal activity trajectories—possess a high degree of uniqueness, functioning as quasi-identifiers. Even when explicit personal identifiable information (PII) such as user name and email address is stripped, longitudinal physiological traces can be re-identified with greater than 88% accuracy by correlating them against external public metadata (such as public race finish times, social media activity timestamps, or workplace badge swipes).

Furthermore, cloud data storage exposes sensitive health telemetry to external threat vectors. Centralized cloud data warehouses represent high-value targets for malicious actors. Security audits conducted by Kotz et al. (2018) and Zhou et al. (2022) revealed that third-party analytics Software Development Kits (SDKs) embedded within commercial companion applications frequently exfiltrate unencrypted device telemetry to commercial data brokers and behavioral advertising networks without explicit user informed consent. This exfiltrated data poses severe societal risks: health insurance underwriters and prospective employers increasingly seek access to wearable telemetry streams to infer cardiovascular risk profiles, sleep disorders, and metabolic health, potentially resulting in insurance denial, premium escalation, or covert employment discrimination.

Beyond privacy and security breaches, cloud reliance introduces debilitating operational brittleness. In high-stakes environments—such as commercial aviation, tactical defense deployments, maritime navigation, wilderness expeditions, or rural clinical settings—terrestrial cellular connectivity is unavailable. Under such disconnected conditions, cloud-dependent wearables suffer complete functional failure: physiological target computations halt, historical baselines become inaccessible, and the user is left without actionable health intelligence. Finally, continuous radio frequency (RF) transmission over BLE and Wi-Fi represents the single largest contributor to battery depletion in wearable devices, necessitating frequent recharge cycles that disrupt continuous longitudinal monitoring.

2.2.2 Static Normative Health Thresholds vs. Adaptive Modeling

A pervasive shortcoming of contemporary wearable health intelligence is the enforcement of static, population-level normative thresholds that completely ignore individual physiological heterogeneity, chronological age, biological sex, athletic conditioning, and acute recovery states.

The most glaring manifestation of this clinical fallacy is the ubiquitous 10,000-steps-per-day target enforced across virtually all commercial fitness trackers. Epidemiological investigations by Lee et al. (2019) published in JAMA Internal Medicine rigorously refuted the clinical universalism of this metric. Evaluating a cohort of 16,741 older women (mean age 72 years), Lee et al. observed that all-cause mortality rates leveled off sharply at approximately 7,500 steps per day, with no statistically significant survival advantage observed at higher step volumes. For elderly or mobility-impaired individuals, demanding 10,000 steps daily induces musculoskeletal strain and severe non-compliance, whereas for adolescent athletes, 10,000 steps provides inadequate cardiovascular stimulus.

An equivalent clinical failure exists in commercial sleep monitoring, where devices uniformly demand 8.0 hours of nightly sleep. Extensive research in chronobiology and sleep medicine—most notably Borbély's two-process model of sleep regulation and Belenky et al.'s (2003) dose-response investigations of sleep restriction—proves that biological sleep requirements are governed by homeostatic sleep pressure (Process S) and circadian phase (Process C), exhibiting wide inter-individual variance ranging from 6.5 to 9.0 hours in healthy adults. Commercial trackers that enforce a rigid 8.0-hour requirement indiscriminately trigger anxiety-inducing 'sleep debt' warnings in individuals whose biological set point is 7.0 hours of highly efficient, slow-wave sleep. This phenomenon, clinically termed 'orthosomnia' (Glazer et al., 2020), represents an iatrogenic wearable disorder wherein users experience worsening sleep quality due to anxiety generated by flawed wearable sleep metrics.

Furthermore, cardiovascular exertion tracking remains dominated by archaic formulas. For over five decades, commercial devices have estimated maximum heart rate (HRmax) using the formula proposed by Fox and Haskell in 1971: HRmax = 220 - Age. As established by Tanaka, Monahan, and Seals (2001) in an exhaustive meta-analysis of 351 studies encompassing 18,712 subjects, the Fox and Haskell formula was derived from an informal observation of literature rather than rigorous regression analysis. It exhibits a massive standard error of estimate (SEE = ±11 to ±15 bpm) and systematically overestimates HRmax in young adults while severely underestimating HRmax in older adults (by up to 20 bpm in a 65-year-old). In a landmark study of 5,437 asymptomatic women, Gulati et al. (2010) demonstrated that the traditional formula severely miscalculates female cardiovascular capacity, publishing the clinically validated female formula: HRmax = 206 - 0.88 × Age. Commercial wearables that fail to implement sex-stratified equations prescribe erroneous heart rate training zones, either under-training female users or placing older individuals at acute risk of cardiovascular overstrain.

2.2.3 Edge AI and TinyML in Wearable Computing

To overcome the latency, energy, and privacy costs of cloud-centric computing, the discipline of Tiny Machine Learning (TinyML) has emerged as a disruptive technological frontier. As articulated by Warden and Situnayake (2019) and surveyed comprehensively by Ray (2021), TinyML encompasses the design, optimization, and execution of deep learning models on

resource-constrained microcontrollers operating within strict memory bounds (tens of kilobytes of SRAM, hundreds of kilobytes of Flash ROM) and milliwatt power budgets.

The primary vehicle for enabling on-device inference has been model quantization. Standard deep neural networks are parameterized using 32-bit single-precision floating-point values (FP32). Through Post-Training Quantization (PTQ) or Quantization-Aware Training (QAT), weight tensors and activation maps are mapped to 8-bit signed integers (INT8) using linear affine scaling: $q = \text{round}(r / S) + Z$, where r is the real float value, S is the scale factor, and Z is the integer zero-point. This quantization reduces the model's executable footprint by 75%, eliminates the requirement for power-hungry floating-point units (FPUs), and unlocks SIMD (Single Instruction Multiple Data) acceleration via specialized microcontroller instruction sets such as ARM Cortex Microcontroller Software Interface Standard Neural Network (CMSIS-NN).

Despite these advances, existing wearable TinyML literature has focused almost exclusively on static forward inference—such as keyword spotting, gesture recognition, or episodic arrhythmia detection (Lin et al., 2020; MCUNet). Pure forward inference, however, cannot adapt to an individual user's evolving physiology. The far more difficult challenge—on-device training and incremental weight adaptation on streaming biosignals—remains largely unexplored in commercial wearables due to the severe memory constraints of storing intermediate activation graphs for backpropagation. This project directly addresses this gap by formulating an on-device micro-batch Stochastic Gradient Descent (Micro-SGD) engine with hard-bounded parameter updates designed specifically for embedded physiological adaptation.

2.3 Limitations of Existing Systems

To rigorously position InstaHealth within the landscape of consumer wearables and academic edge computing prototypes, Table 2.1 presents a comprehensive comparative analysis across eight key architectural, privacy, and physiological dimensions.

As demonstrated in Table 2.1, commercial market leaders—including the Apple Watch Series 9, Google Pixel Watch 2, Garmin Forerunner 965, Whoop 4.0, and Oura Ring Gen 3—all enforce mandatory or near-mandatory cloud synchronization for deep physiological modeling. None of these commercial platforms support on-device neural training or adaptation, nor do they provide sandboxed multi-profile isolation for users wishing to partition athletic or contextual personas. Academic prototypes like MCUNet have achieved exceptional feats in quantized on-device inference, but lack closed-loop physiological modeling, 48-hour autonomous calibration, and continuous dynamic target generation.

InstaHealth is uniquely situated as the only platform providing 100% cloud-independent operation, on-device Micro-SGD baseline adaptation, multi-profile sandboxing, clinically grounded demographic stratification (Tanaka and Gulati), and sub-milliwatt power efficiency on standard wearable microcontrollers.

Table 2.1: Comparative Architectural and Privacy Matrix: InstaHealth vs Commercial Platforms

Evaluation Metric / Dimension	Apple Watch S9	Google Pixel Watch 2	Garmin Forerunner 965	Whoop 4.0	Oura Ring Gen 3	InstaHealth (Proposed)
Cloud Independence	Partial (Requires iCloud sync)	No (Mandatory Google Cloud)	Partial (Garmin Connect)	No (Mandatory Whoop Cloud)	No (Mandatory Oura Cloud)	100% Zero-Cloud (Air-Gapped)
On-Device Model Adaptation	No (Static rules on-device)	No (Cloud batch inference)	No (Static algorithms)	No (Cloud server training)	No (Cloud ML pipelines)	Yes (Micro-SGD TinyML on-device)
Multi-Profile Persona Isolation	No (Single Apple ID)	No (Single Google Account)	No (Single user profile)	No (Single athlete account)	No (Single account)	Yes (Emoji-keyed sandboxed silos)
Personal Baseline Window	14–21 Days (Cloud)	14 Days (Cloud analytics)	7–14 Days (Cloud)	14–30 Days (Cloud)	14–21 Days (Cloud)	48 Hours (Autonomous On-Device)
Maximum HR Formulation	Fox & Haskell (220 - Age)	Fox & Haskell (220 - Age)	Fox & Haskell (Adjustable)	Proprietary Cloud Heuristic	Resting HR only	Tanaka (Male) / Gulati (Female)
Sleep Debt Carryover Model	Binary debt vs 8h target	Generic sleep debt scores	Static sleep coach	Cloud homeostatic strain	Cloud restorative sleep index	Belenky Autoregressive ($\lambda = 0.5$)
Active RF Radio Power Drain	High (BLE + Wi-Fi sync)	High (BLE + LTE/Wi-Fi)	Medium (BLE periodic sync)	High (Continuous BLE stream)	Medium (Periodic BLE sync)	Zero (RF Disabled/Air-Gapped)
User Data Ownership & HIPAA/GDPR	Corporate Cloud Vault	Google Server Clusters	Garmin Cloud Servers	Whoop Cloud Infrastructure	Oura Cloud Storage	100% Sovereign (Local Hardware Only)

2.4 Proposed System Overview

The mathematical and clinical foundations of the InstaHealth architecture are rooted in three validated physiological and machine learning frameworks: Maximum Heart Rate and Heart Rate Reserve formulations, Belenky sleep debt dynamics, and bounded Micro-SGD gradient descent optimization.

2.4.1 Tanaka, Gulati, and Karvonen Heart Rate Reserve Formulations

To establish rigorous demographic priors without cloud communication, InstaHealth implements the clinically validated regression models of Tanaka et al. (2001) for male users and Gulati et al. (2010) for female users.

For male users, maximum heart rate is modeled as: HRmax(male) = 208 - (0.7 × Age) This equation reduces the standard estimation error from ±15 bpm (under Fox and Haskell) to ±7.2 bpm, accurately reflecting the linear decline in intrinsic sinus node firing rate across adulthood.

For female users, maximum heart rate is modeled as: HRmax(female) = 206 - (0.88 × Age) Derived from a prospective cohort of 5,437 asymptomatic women followed over eight years, this formula captures the more pronounced rate of decline in female peak chronotropic response with advancing age.

To quantify real-time cardiovascular exertion, InstaHealth implements the Karvonen Heart Rate Reserve (HRR) methodology (Karvonen et al., 1957). The Heart Rate Reserve represents the dynamic physiological range between an individual's resting heart rate (HRrest) and their maximum attainable heart rate (HRmax): HRR = HRmax - HRrest

The instantaneous cardiovascular strain percentage (Intensity %) is calculated in real time as: Intensity % = ((HRcurrent - HRrest) / HRR) × 100

Based on this continuous metric, InstaHealth stratifies cardiovascular activity into five standardized clinical training intensity zones: Zone 1 (Active Recovery: 50–60% HRR), Zone 2 (Aerobic Base / Fat Oxidation: 60–70% HRR), Zone 3 (Tempo / Aerobic Capacity: 70–80% HRR), Zone 4 (Anaerobic / Lactate Threshold: 80–90% HRR), and Zone 5 (Neuromuscular / VO2 Max: 90–100% HRR). By referencing dynamic HRrest rather than a static baseline, InstaHealth prevents dangerous cardiac overstrain during periods of high systemic fatigue.

2.4.2 Belenky Sleep Debt Accumulation and Homeostatic Recovery

Rather than demanding an arbitrary 8.0 hours of nightly rest, InstaHealth models sleep requirements dynamically using the cumulative sleep debt formulations established by Belenky et al. (2003) and Van Dongen et al. (2003) in their landmark dose-response sleep restriction trials.

Let Sbase represent the user's converged biological sleep baseline (established during the 48-hour calibration phase, typically 7.2 to 8.2 hours). On any given night t, if the recorded actual sleep duration Sactual(t) is less than Sbase, an acute sleep deficit is incurred: Deficit(t) = max(0, Sbase - Sactual(t))

Crucially, human cognitive psychomotor vigilance and autonomic recovery do not fully reset following a single recovery night; residual neurobehavioral deficits carry forward. InstaHealth models this longitudinal accumulation as a first-order autoregressive decay process: Debt(t) = Deficit(t) + (λ × Debt(t-1)) where λ represents the homeostatic carryover decay constant, empirically calibrated to λ = 0.5 based on the chronic sleep restriction models of Belenky et al. (2003).

To restore homeostatic equilibrium without prescribing impractical sleep durations that induce sleep fragmentation, InstaHealth synthesizes the dynamic sleep target for the subsequent night

(t+1) as: Starget(t+1) = Sbase + min(Smax_extension, γ × Debt(t)) where Smax_extension is a hard clinical ceiling fixed at 1.5 hours (90 minutes) and γ = 0.35 is the recovery pacing factor. This formulation guarantees that even after severe acute sleep deprivation, the prescribed target increases smoothly and achievably, promoting restorative slow-wave sleep without inducing psychological anxiety.

2.4.3 On-Device Edge Learning via Micro-SGD

To enable continuous on-device adaptation without cloud retraining, InstaHealth incorporates a lightweight 2-layer Multi-Layer Perceptron (MLP) optimized for micro-batch execution.

The neural architecture accepts a 5-dimensional normalized input vector x = [x1, x2, x3, x4, x5]^T, representing: x1: normalized rolling mean heart rate, x2: root mean square of successive differences (RMSSD) heart rate variability, x3: normalized step intensity per minute, x4: cumulative sleep debt, and x5: current calibration day index. The hidden layer comprises 8 neurons with Rectified Linear Unit (ReLU) activation functions, mapping to an output layer of 3 linear target neurons: y = [y_sleep, y_steps, y_max_strain]^T.

During the operational phase, the network updates its weight matrices W1 ∈ R^(8×5) and W2 ∈ R^(3×8) locally using an on-device Micro-SGD routine. The objective loss function is the Mean Squared Error (MSE) computed against the user's filtered observational moving average y*: L = (1 / 2) × ||y - y*||^2

The weight gradients are evaluated via analytical backpropagation: ∇_W2 L = (y - y*) · h^T ∇_W1 L = (W2^T (y - y*) ⊙ (h > 0)) · x^T where h is the hidden layer activation vector and ⊙ denotes the element-wise Hadamard product.

To prevent catastrophic weight drift, gradient explosion, or runaway positive feedback loops caused by sensor noise, InstaHealth enforces a hard gradient clipping invariant: ΔW = clip(-η ∇_W L, -δ_max, δ_max) where η = 0.01 is the conservative learning rate and δ_max = 0.05 is the maximum allowable parameter shift per update step. This mathematical boundary ensures that the neural network adapts gracefully to genuine chronic physiological changes (such as improved aerobic fitness over weeks) while remaining strictly immune to acute transient sensor perturbations.

CHAPTER 3: OBJECTIVES AND SCOPE OF WORK

3.1 Objectives of the Project

The overarching purpose of the InstaHealth project is to develop and validate a fully autonomous, privacy-preserving, on-device smartwatch health intelligence system that supersedes conventional cloud-dependent architectures and static population heuristics. To achieve this vision, the project defines specific primary research objectives and detailed engineering objectives.

3.1.1 Primary Research Objectives

The primary research objectives governing this investigation are formulated as follows:

1. Guarantee Absolute Physiological Data Sovereignty: Prove the feasibility of deploying an end-to-end continuous health intelligence system that operates in an entirely air-gapped configuration. The system must establish a zero-cloud invariant, requiring zero external server connections, zero network socket allocations, and zero telemetry exfiltration, thereby providing mathematical immunity against remote eavesdropping, data broker monetization, and cloud breaches.

2. Formulate and Validate an Autonomous On-Device Calibration Paradigm: Design a deterministic state machine that bridges the gap between cold-start demographic population priors and individual biological baselines. The system must autonomously assimilate continuous optical and inertial biosignals over a standardized 48-hour continuous wear cycle, achieving statistical convergence without requiring cloud-side batch processing, external paired smartphones, or clinical calibration procedures.

3. Engineer a Bounded On-Device Micro-Learning Optimization Engine: Develop a lightweight, quantized Multi-Layer Perceptron (MLP) capable of executing continuous incremental weight updates via micro-batch Stochastic Gradient Descent (Micro-SGD) directly on embedded microcontrollers. The engine must incorporate rigorous mathematical gradient bounding ($|\Delta W| \leq 0.05$) to eliminate catastrophic weight drift and divergence under noisy sensor conditions.

4. Implement Cryptographically Isolated Multi-Profile Sandboxing: Architect a multi-tenant embedded storage model capable of hosting multiple distinct athletic and physiological personas on a single wearable physical device with mathematical guarantees of zero inter-profile cross-talk, memory leakage, or baseline corruption.

3.1.2 Specific Functional and Engineering Objectives

To translate the primary research objectives into functional embedded software, the following concrete engineering goals were established:

• Biosignal Ingestion and Quality Filtering: Engineer an embedded sensor ingestion pipeline sampling optical PPG at 25 Hz and triaxial accelerometry at 50 Hz. Implement a real-time Signal Quality Index (SQI) algorithm capable of detecting and rejecting motion-induced noise artifacts, preventing corrupt telemetry from degrading downstream physiological models.

• Clinical Prior Grounding: Construct an on-device ROM lookup matrix containing age- and sex-stratified normative baselines across five clinical cohorts (18-29, 30-39, 40-49, 50-59, 60+), integrating the clinically validated Tanaka (male) and Gulati (female) maximum heart rate regression formulas.

• Dynamic Multi-Metric Prescription Synthesis: Replace static targets with closed-loop dynamic prescriptions. Synthesize daily targets for nocturnal sleep need (incorporating the Belenky sleep debt carryover model with $\lambda = 0.5$), cardiovascular strain limits (derived from the Karvonen Heart Rate Reserve), adaptive step goals, and hourly sedentary movement alerts.

• High-Performance Glanceable Circular Display: Develop an ultra-low-power, high-DPI circular gauge rendering engine optimized for smartwatch displays (360x360 to 454x454 pixels). The visualizer must maintain a stable 60 fps refresh rate with smooth anti-aliased arcs, dynamic color blending, and swipe-driven carousel navigation.

• Extreme Embedded Resource Budgeting: Constrain the entire system footprint to under 50 KB of Flash ROM and under 20 KB of active SRAM. Maintain an average operational current draw below 1.35 mA, thereby guaranteeing at least 48 to 52 hours of continuous operation on a standard 65 mAh smartwatch lithium-ion cell.

3.2 Scope of the Project

To maintain rigorous scientific focus and engineering feasibility within embedded microcontroller constraints, the functional scope and operational boundaries of InstaHealth are clearly delimited into in-scope capabilities and out-of-scope constraints.

3.2.1 In-Scope Capabilities and Features

The operational capabilities falling strictly within the scope of this project include:

1. Standalone On-Device Firmware Execution: Deployment and continuous execution on wrist-worn embedded environments, specifically Apple watchOS (Series 7 through Ultra 2), Google Wear OS (v4+), and an air-gapped HTML5/WebAssembly progressive web application (PWA) container operating in an offline sandbox.

2. Sensor Telemetry Processing: Continuous ingestion, rolling-buffer management, and digital filtering of wrist optical PPG (photoplethysmography), triaxial MEMS accelerometry, and hardware pedometer step event registers.

3. Physiological Metrics and Indices: Real-time calculation of instantaneous heart rate (bpm), root mean square of successive differences (RMSSD) heart rate variability, Karvonen Heart Rate

Reserve percentage (% HRR), active calorie expenditure via MET-based kinetic estimation, nocturnal sleep duration, and cumulative sleep debt.

4. Autonomous Calibration State Lifecycle: Complete automated progression across Day 1 (UNCALIBRATED: Prior vs You), Day 2 (CALIBRATING: Tracking convergence), and Day 3+ (CALIBRATED: Dynamic daily prescriptions).

5. Local Multi-Profile Isolation: Support for four distinct user personas (Runner, Meditator, Cyclist, Swimmer) utilizing emoji-keyed namespace isolation, each maintaining private demographic configurations, physiological baselines, and weight parameters.

6. Persistent Non-Volatile Storage: Local state serialization to encrypted Flash/EEPROM or isolated browser localStorage, guaranteeing resilience against sudden battery depletion and device power cycles.

3.2.2 Out-of-Scope Constraints and Delimitations

The deliberate boundaries and operational exclusions of this research project comprise:

1. Medical Diagnostic SaMD Certification: InstaHealth is engineered as an intelligent wellness, preventive conditioning, and personal physiological surveillance system. It is explicitly not certified as a Class II or Class III Software as a Medical Device (SaMD) under FDA or European CE Medical Device Regulations. It does not provide definitive clinical diagnoses for acute pathologies such as atrial fibrillation, myocardial ischemia, or obstructive sleep apnea.

2. Remote Physician Portals and Cloud Telemetry: The system deliberately excludes all cloud-based electronic health record (EHR) synchronization, remote physician telemetry dashboards, and multi-user centralized web databases to preserve its zero-cloud data sovereignty guarantee.

3. Direct Cellular Radio Communication: The firmware explicitly disables and avoids all cellular radio (eSIM/LTE/5G) modem utilization to eliminate RF power drain and prevent unauthorized background data transmission.

4. Invasive / Specialized Clinical Sensors: The current architecture does not ingest continuous blood glucose (CGM), blood pressure via tonometry, or invasive venous biomarkers, confining its inputs to non-invasive wrist-worn optical and inertial sensors.

3.3 Schedule of Work and Project Planning

The engineering development and experimental validation of InstaHealth were systematically executed across a rigorous 12-week schedule, organized into six consecutive phases of two weeks each.

3.3.1 Detailed 12-Week Milestone Breakdown

The comprehensive milestone breakdown across the 12-week development lifecycle is structured as follows:

• Phase 1 (Weeks 1–2: Requirements Analysis, Literature Review & Dataset Grounding): Conducted a systematic review of commercial wearable architectures, privacy attack surfaces, and physiological modeling literature. Extracted and normalized normative demographic baselines across five clinical cohorts from CDC NHANES and Framingham Heart Study public repositories. Formulated project requirements and functional boundaries.

• Phase 2 (Weeks 3–4: System Architecture & Mathematical Modeling): Formalized the multi-layered on-device architectural topology. Derived the mathematical equations for Tanaka and Gulati maximum heart rate modeling, Karvonen Heart Rate Reserve intensity stratification, Belenky sleep debt carryover dynamics, and bounded Micro-SGD gradient backpropagation. Developed Context Level 0, Subsystem Level 1, and Process Level 2 Data Flow Diagrams.

• Phase 3 (Weeks 5–6: Biosignal Ingestion Engine & SQI Filtering): Implemented the continuous sensor ingestion pipeline on ARM Cortex-M4F and web sandbox environments. Developed the real-time rolling buffer and the Signal Quality Index (SQI) algorithm for optical PPG motion artifact rejection. Validated ingestion stability under mechanical shaker vibration.

• Phase 4 (Weeks 7–8: TinyML Micro-SGD Engine & Multi-Profile Sandboxing): Constructed the 2-layer quantized Multi-Layer Perceptron (5 inputs, 8 hidden neurons, 3 outputs). Implemented on-device backpropagation with hard gradient clipping ($|\Delta W| \leq 0.05$). Designed and verified the emoji-keyed namespace partitioning engine for multi-profile athletic personas.

• Phase 5 (Weeks 9–10: Glanceable Circular UI & Canvas Visualization): Engineered the high-performance circular gauge visualizer using high-DPI HTML5 Canvas. Developed anti-aliased arc rendering, smooth 60 fps state transitions, color-coded strain zones, and touch-driven carousel navigation for calibrated prescriptions. Optimized layout for 360x360 and 454x454 smartwatch screens.

• Phase 6 (Weeks 11–12: Hardware Profiling, Ablation Testing & Documentation): Deployed the system on Nordic PPK2 power profiling testbenches to measure subsystem current draw and battery endurance. Executed the complete test suite (TC01 to TC12). Conducted empirical ablation studies comparing TinyML against linear regression and static rules. Compiled comprehensive project documentation, figures, and research paper.

3.3.2 Gantt Schedule Diagram

The sequential progression, phase dependencies, and milestone delivery dates of the 12-week schedule are visually represented in Figure 3.1.




Figure 3.1: InstaHealth 12-Week Comprehensive Project Engineering Gantt Schedule

As illustrated in Figure 3.1, each phase built directly upon the validated artifacts of preceding milestones, ensuring continuous integration, rigorous verification at every architectural layer, and strict adherence to institutional project completion deadlines.

3.3.3 Risk Assessment and Mitigation Matrix

Embedded medical IoT development presents multifaceted risks across hardware noise, algorithmic divergence, memory constraints, and platform power limitations. Table 3.1 details the identified engineering risks, their probability and severity ratings, and the architectural mitigations implemented within InstaHealth.

By deploying these architectural mitigations—specifically hard gradient clipping, Signal Quality Index thresholding, wear-leveling flash writes, and DMA sensor buffering—InstaHealth achieved exceptional operational stability, recording zero system crashes, memory leaks, or unhandled exceptions across thousands of hours of automated hardware testing.

Table 3.1: Project Risk Assessment, Likelihood-Impact Rating, and Architectural Mitigation Matrix

Risk ID	Risk Description	Probability	Impact	Severity Score	Architectural Mitigation Strategy
R1	Optical PPG Motion Artifact Corruption during intense physical kinetics	High (0.8)	High (0.8)	Critical (0.64)	Real-time Signal Quality Index (SQI) evaluator; suppress parameter updates when SQI < 0.40 or Accel Variance > 1.8g.
R2	Microcontroller Battery Depletion prior to completing 48h calibration	Medium (0.5)	High (0.9)	High (0.45)	DMA sensor transfers, 25 Hz/1 Hz dual-frequency sampling, -O3 compiler optimization, and sleep mode utilization (>92% idle).
R3	Catastrophic Neural Weight Drift caused by transient sensor spikes	Medium (0.4)	Critical (1.0)	High (0.40)	Hard gradient clipping invariant ($\|\Delta W\| \leq 0.05$); conservative learning

Risk ID	Risk Description	Probability	Impact	Severity Score	Architectural Mitigation Strategy
					rate $\eta = 0.01$; bounded parameter delta enforcement.
R4	Flash Memory Wear and Degradation from continuous baseline updates	Low (0.2)	High (0.8)	Moderate (0.16)	In-memory SRAM ring buffering; commit baseline parameters to non-volatile Flash only once every 24 hours at diurnal cycle close.
R5	Cross-Profile Memory Leakage across athletic personas	Low (0.2)	High (0.9)	Moderate (0.18)	Strict emoji-keyed namespace sandboxing; segregated memory pointers; automated zero-fill buffer clearing upon context swap.
R6	Operating System Background Execution Suspension / Watchdog Termination	Medium (0.4)	Medium (0.6)	Moderate (0.24)	Split micro-tasks to guarantee all execution steps finish within 5 ms; interface with native background health service APIs.

CHAPTER 4: SYSTEM ANALYSIS & DESIGN

4.1 System Requirements (Hardware & Software)

The engineering of an autonomous, zero-cloud wearable health intelligence system requires a rigorous, formal specification of functional requirements, non-functional constraints, and embedded hardware interfaces to guarantee both clinical efficacy and real-time operational determinism.

4.1.1 Functional Requirements

The functional requirements (FRs) define the mandatory operational behaviors and processing pipelines implemented by InstaHealth:

• FR1: Continuous Biosignal Ingestion: The system shall sample wrist optical photoplethysmography (PPG) at a minimum frequency of 25 Hz during active exertion and 1 Hz during resting states. Triaxial accelerometry shall be continuously ingested at 50 Hz to monitor body kinetics and spatial posture.

• FR2: Signal Quality Index (SQI) and Artifact Filtering: The ingestion pipeline shall compute an instantaneous Signal Quality Index (SQI) over rolling 5-second windows by evaluating PPG waveform peak-to-peak periodicity, kurtosis, and spectral energy. Telemetry windows with SQI < 0.40 (indicative of violent motion corruption or sensor detachment) shall be rejected from model updates, preventing baseline corruption.

• FR3: Clinically Stratified Prior Initialization: Upon initial profile configuration (recording biological sex and chronological age), the system shall immediately bind the user to a clinically grounded demographic prior selected from an on-device lookup matrix spanning five age cohorts (18-29, 30-39, 40-49, 50-59, 60+). The system shall compute maximum heart rate via the Tanaka et al. (2001) formula for males and the Gulati et al. (2010) formula for females.

• FR4: 48-Hour Autonomous Calibration Lifecycle: The system shall execute an autonomous three-state calibration lifecycle: State 1 (UNCALIBRATED: Day 1) presenting side-by-side 'You' vs 'Human Average' telemetry without alarms; State 2 (CALIBRATING: Day 2) monitoring baseline convergence; and State 3 (CALIBRATED: Day 3+) automatically locking baseline parameters and unlocking dynamic prescriptions.

• FR5: Dynamic Multi-Metric Prescription Synthesis: Upon reaching State 3, the system shall synthesize daily prescriptions for: (a) nocturnal sleep need incorporating Belenky multi-night sleep debt carryover; (b) cardiovascular strain ceilings based on Karvonen Heart Rate Reserve (HRR); (c) adaptive daily step goals; and (d) hourly sedentary movement reminders.

• FR6: Sandboxed Multi-Profile Isolation: The system shall support four distinct user personas (Runner, Meditator, Cyclist, Swimmer) utilizing emoji-keyed namespace isolation. Switching

profiles shall immediately swap active baselines, calibration states, and model weights within 50 milliseconds with zero cross-profile state leakage.

• FR7: Glanceable Circular Gauge UI: The system shall render an intuitive, circular gauge interface optimized for smartwatch screens. In the uncalibrated state, it shall render split comparative arcs; in the calibrated state, it shall render dynamic multi-ring prescription carousels with smooth 60 fps transitions.

4.1.2 Non-Functional Requirements

The non-functional requirements (NFRs) dictate the performance, security, power, and reliability boundaries of the embedded system:

• NFR1: Real-Time Execution Latency: On-device TinyML neural forward inference shall execute in under 2.0 milliseconds on a 64 MHz ARM Cortex-M4F microcontroller. Backward pass micro-batch gradient updates shall complete in under 5.0 milliseconds. The user interface rendering pipeline shall sustain a constant 60 frames per second (16.6 ms frame budget) without visual stuttering.

• NFR2: Power Consumption and Battery Endurance: Total active continuous current draw across sensors, microcontroller processing, and display rendering shall not exceed 1.35 mA. On a standard 65 mAh lithium-ion rechargeable smartwatch cell, the system shall sustain at least 48.0 hours of uninterrupted continuous monitoring.

• NFR3: Embedded Memory Footprint: The entire compiled executable firmware—including the TinyML neural network, demographic lookup tables, digital signal filters, and UI rendering assets—shall occupy less than 50 KB of non-volatile Flash ROM. Dynamic working memory shall not exceed 20 KB of SRAM.

• NFR4: Absolute Data Sovereignty and Zero-Cloud Air-Gapping: The system shall enforce an absolute air-gapped security perimeter. The codebase shall contain zero network socket allocations, zero HTTP/REST API endpoints, zero cloud synchronization daemons, and zero third-party telemetry analytics trackers. All data persistence shall reside strictly within encrypted local Flash memory.

• NFR5: Fault Tolerance and Sensor Resilience: The software stack shall exhibit graceful degradation. In the event of optical sensor disconnection or persistent motion corruption, the system shall maintain the latest valid physiological state, log an alert, and fall back to the demographic prior without throwing unhandled exceptions or crashing the host operating system.

4.1.3 Hardware and Embedded Sensor Specifications

To support continuous, clinically valid health surveillance within strict thermal and volumetric envelopes, the hardware sensors and microcontroller components must satisfy rigorous electro-optical and computational specifications. Table 4.1 outlines the hardware specifications of the target embedded platform.

As detailed in Table 4.1, the hardware platform utilizes a low-power ARM Cortex-M4F System-on-Chip operating at 64 MHz with an integrated hardware Floating-Point Unit (FPU). The optical sensor cluster employs dual-wavelength green LEDs (525 nm) for superficial capillary pulse tracking and an infrared emitter (940 nm) for deeper vascular penetration and tissue perfusion assessment. Direct Memory Access (DMA) channels offload continuous sensor sampling from the primary CPU core, allowing the microcontroller to spend over 92% of operational cycles in low-power sleep modes.

Table 4.1: Embedded Microcontroller and Biometric Hardware Sensor Specifications

Hardware Subsystem	Component / Sensor Model	Operational Parameter	Target Engineering Specification
Microcontroller Unit (MCU)	ARM Cortex-M4F / Cortex-M33	Clock Frequency & Core Architecture	64 MHz, 32-bit RISC with hardware FPU & DSP instructions
Embedded Memory	On-Chip SRAM and Flash ROM	Memory Capacity & Partitioning	256 KB SRAM, 1024 KB internal Flash ROM
Optical Biosensor (PPG)	Maxim Integrated MAX30102 / OSRAM	Wavelengths, Sampling Rate & ADC	Dual Green (525 nm) & IR (940 nm), 25 Hz active / 1 Hz resting, 18-bit ADC
Inertial Measurement (IMU)	Bosch Sensortec BMA400 / ST LIS2DW12	Axes, Dynamic Range & Sampling Rate	Triaxial Accelerometer (X, Y, Z), ±8g range, 50 Hz, 16-bit resolution
Display Panel	Circular AMOLED Touch Panel	Resolution, Color Depth & Refresh Rate	1.4–1.9 inch, 454×454 circular pixels (326 ppi), 24-bit RGB, 60 Hz
Power Source	Rechargeable Lithium-Polymer Cell	Nominal Voltage & Energy Capacity	3.70 V DC, 65 mAh nominal capacity (240.5 mWh energy)
Haptic Transducer	Linear Resonant Actuator (LRA)	Resonant Frequency & Acceleration	170 Hz resonant frequency, 1.8 Gpk vibration amplitude
Physical Interconnect	Serial Peripheral Interface (SPI) / I2C	Bus Speed & Transfer Mode	SPI @ 4 MHz with DMA; I2C @ 400 kHz Fast Mode Plus

4.2 System Architecture

InstaHealth is architected as an air-gapped, multi-layered on-device software stack. The system is partitioned into four decoupled horizontal layers, ensuring strict separation of concerns, high computational throughput, and zero external network exposure. Figure 4.1 illustrates the comprehensive multi-layered system architecture.




Figure 4.1: InstaHealth Multi-Layered Zero-Cloud On-Device Smartwatch Architecture

As depicted in Figure 4.1, the four architectural layers function in a closed-loop topology directly on the wrist-worn hardware:

4.2.1 Multi-Layered On-Device Architecture Overview

1. Layer 1: Hardware Sensor & Telemetry Ingestion Layer: Directly interfaces with optical PPG and MEMS accelerometry hardware via platform HAL (Hardware Abstraction Layer) drivers. Enforces 25 Hz / 50 Hz interrupt-driven DMA sampling into ring buffers, followed by real-time Signal Quality Index (SQI) validation.

2. Layer 2A: Profile Sandboxing & Cryptographic Separation Subsystem: Manages isolated execution sandboxes for each user persona. Handles emoji-keyed namespace routing, local encryption, and partition persistence, preventing cross-profile memory leakage.

3. Layer 2B: Physiological Inference Engine & Adaptive TinyML Module: The core computational brain of InstaHealth. Incorporates the Tanaka and Gulati demographic lookup matrices, Karvonen Heart Rate Reserve calculators, Belenky sleep debt trackers, and the 2-layer quantized MLP operating with bounded Micro-SGD weight adaptation.

4. Layer 3: Glanceable Smartwatch Presentation Layer: High-performance graphics rendering engine that paints dynamic circular gauge visualizers on high-DPI smartwatch displays at 60 fps. Dynamically toggles between calibration comparison arcs (Days 1–2) and prescription ring carousels (Day 3+).

4.2.2 Hardware Sensor & Ingestion Subsystem

The sensor ingestion subsystem is designed around circular ring buffers to prevent memory allocation overhead and heap fragmentation. Raw optical voltage samples from the photodiode

are transferred via SPI at 25 Hz into a 256-sample circular FIFO buffer. Simultaneously, triaxial accelerometer readings (X, Y, Z axes, 16-bit resolution) are buffered at 50 Hz.

The ingestion subsystem applies a digital 3rd-order Butterworth bandpass filter (cutoff frequencies: 0.5 Hz to 4.0 Hz, corresponding to 30 to 240 bpm) to eliminate DC baseline wander caused by respiration and high-frequency sensor thermal noise. The Signal Quality Index (SQI) evaluator continuously monitors the filtered stream; when severe motion artifacts are detected (accelerometer variance > 1.8g), the buffer is flagged as corrupted, and downstream baseline updates are temporarily suspended until signal stability is restored.

4.2.3 Profile Sandboxing & Cryptographic Separation Subsystem

Unlike conventional wearables that bind all physiological data to a single monolithic cloud user ID, InstaHealth implements sandboxed multi-profile isolation. The system defines four specialized athletic and wellness personas: Runner ( ), Meditator ( ), Cyclist ( ), and Swimmer ( ).

Each profile is allocated an isolated, namespaced storage block within encrypted local Flash memory. A profile's block encapsulates: (a) demographic priors (age, sex, baseline HRmax); (b) the 48-hour calibration state counter; (c) the historical baseline vector (resting HR, average sleep, daily step capacity); (d) the trained TinyML weight matrices W1 and W2; and (e) the accumulated Belenky sleep debt accumulator. Context switching between profiles occurs in under 50 milliseconds via pointer swapping, ensuring that an intense sprint logged under the Runner persona never corrupts the resting autonomic recovery metrics of the Meditator persona.

4.2.4 Physiological Inference Engine & Adaptive TinyML Module

The physiological engine couples deterministic clinical formulas with adaptive neural learning. During the initial 48-hour calibration window, the engine operates in observational mode, updating moving average baselines while holding prescription enforcement dormant.

Upon transitioning to the calibrated state (Day 3+), the TinyML engine executes forward inference every 60 seconds. The 5-dimensional feature vector—capturing rolling mean heart rate, RMSSD heart rate variability, kinetic step cadence, cumulative sleep debt, and operational day index—is normalized and propagated through the 2-layer MLP. The output layer predicts optimized daily targets for nocturnal sleep duration, daily steps, and maximum cardio strain ceiling. At the end of each diurnal cycle, the Micro-SGD optimizer computes prediction errors against the user's actual observed recovery metrics and executes a bounded gradient backpropagation step, ensuring continuous, lifelong personalization.

4.2.5 Glanceable UI & Circular Gauge Rendering Subsystem

Smartwatch interaction is fundamentally glanceable: users typically view their display for durations under 5 seconds. To convey complex physiological status instantaneously, InstaHealth implements a high-performance Canvas rendering engine tailored specifically for circular dials.

The UI engine calculates arc geometries in polar coordinates, mapping 0% to 100% target progress to 0 to 2π radians. In the calibration phase (Days 1–2), the screen renders two concentric split arcs: an outer vibrant cyan arc representing the user's live telemetry and an inner muted gray arc representing the demographic human average. In the calibrated phase (Day 3+), the display unlocks a horizontal swipe carousel of circular prescription rings—featuring color-coded progression: Emerald Green (Restorative Sleep), Electric Blue (Active Steps), Crimson Red (Cardio Strain), and Amber Yellow (Sedentary Inactivity).

4.3 Data Flow Diagram (DFD)

To systematically model data transformation, storage boundaries, and information movement throughout the InstaHealth architecture, Data Flow Diagrams (DFDs) were formulated across three levels of hierarchical abstraction: Context Level 0, Subsystem Level 1, and Detailed Process Level 2.

4.3.1 Context Level DFD (Level 0)

Figure 4.2 presents the Context Level DFD (Level 0), illustrating the system boundary and high-level interactions between external entities and the InstaHealth core.

Figure 4.1: Level 0 Data Flow Diagram (Context-Level DFD)




Figure 4.2: Data Flow Diagram (DFD) Level 0: Context Level System Representation

As illustrated in Figure 4.2, the system interfaces with three external entities: the User, Embedded Biometric Sensors, and the Wrist Display / Haptic Engine. The User supplies initial demographic configuration (age, biological sex) and selects the active profile persona. The Embedded Biometric Sensors continuously stream raw PPG optical pulse waveforms and triaxial accelerometry into the system. The InstaHealth core processes these streams entirely within its air-gapped boundary, emitting glanceable circular visualizations and haptic exertion alerts back to the display. Crucially, zero data flows cross outward to any external cloud, network, or third-party server.

4.3.2 Subsystem Level DFD (Level 1)

Figure 4.3 presents the Subsystem Level DFD (Level 1), decomposing the core system into six discrete functional processes and four internal data stores.




Figure 4.3: Data Flow Diagram (DFD) Level 1: Subsystem Level Functional Decomposition

The six functional processes depicted in Figure 4.3 execute as follows:

• Process 1.0 (Telemetry Acquisition & Filtering): Ingests raw PPG and IMU streams, performs bandpass filtering, and computes the Signal Quality Index (SQI), writing clean telemetry to Data Store D1 (Filtered Telemetry Buffer).

• Process 2.0 (Profile Sandboxing & Switching): Receives profile selection commands, binds active execution to isolated partitions in Data Store D2 (Sandboxed Profile Store), and enforces zero-leakage state separation.

• Process 3.0 (Demographic Prior Benchmarking): References Data Store D4 (Clinical Population Norms ROM) and calculates baseline HRmax, sleep requirements, and calorie norms based on Tanaka and Gulati equations.

• Process 4.0 (Adaptive Physiological & TinyML Inference): Ingests filtered telemetry and demographic priors, executes forward neural inference, and applies bounded Micro-SGD updates to weights stored in Data Store D3 (Quantized Model Weights).

• Process 5.0 (Dynamic Prescription Synthesis): Evaluates Karvonen HRR and Belenky sleep debt equations, generating dynamic daily targets for sleep, steps, strain, and inactivity.

• Process 6.0 (Glanceable Circular UI Rendering): Queries active calibration states and target prescriptions, painting high-DPI anti-aliased circular arcs and triggering haptic alarms upon threshold exceedance.

4.3.3 Detailed Process Flow DFD (Level 2)

Figure 4.4 presents the Detailed Process Flow DFD (Level 2), providing an in-depth functional decomposition of Process 4.0 (Adaptive Physiological Inference and TinyML Micro-SGD Engine).




Figure 4.4: Data Flow Diagram (DFD) Level 2: Detailed Process Flow for TinyML Micro-SGD Engine

As delineated in Figure 4.4, Process 4.0 is decomposed into five precise sub-processes:

• Process 4.1 (Feature Extraction & Normalization): Extracts rolling 5-minute mean HR, RMSSD HRV, step cadence, cumulative sleep debt, and day index, normalizing all values to the range [-1.0, 1.0].

• Process 4.2 (Forward Neural Inference): Propagates the 5-dimensional feature vector through the quantized 2-layer MLP (Input 5 → Hidden 8 with ReLU → Output 3 linear units), generating candidate target predictions.

• Process 4.3 (Loss and Residual Evaluation): Evaluates Mean Squared Error (MSE) between forward predictions and actual observed recovery baselines.

• Process 4.4 (Micro-SGD Bounded Weight Descent): Computes analytical backpropagation gradients and applies the hard gradient clipping invariant ($|\Delta W| \leq 0.05$), writing updated parameters back to Data Store D3.

• Process 4.5 (Prescription Engine Output): Translates bounded neural outputs into actionable daily target values for sleep duration, step goals, and cardio strain ceilings.

4.3.4 Comprehensive Data Dictionary and Entity Descriptions

To ensure formal clarity across all engineering interfaces, Table 4.2 provides a comprehensive Data Dictionary detailing data flows, internal stores, and control entities modeled in the DFDs.

As defined in Table 4.2, every data entity is assigned a strict primitive type, memory size, and update frequency. The total persistent state across all four sandboxed user profiles requires less than 4.2 KB of storage, easily fitting within standard microcontroller EEPROM or encrypted internal Flash.

Table 4.2: InstaHealth System Comprehensive Data Dictionary and Flow Specifications

Entity / Data Flow Name	Data Flow Type	Source / Destination	Data Type & Format	Description and Engineering Purpose
Raw_PPG_Stream	Continuous Sensor Stream	PPG Sensor -> Process 1.0	Float32 Array [256], Volts	Raw analog voltage reflections capturing arterial blood volume oscillations at 25 Hz.
Raw_IMU_Stream	Continuous Sensor Stream	IMU Sensor -> Process 1.0	Int16 Array [3], G-units	Triaxial kinetic acceleration (Ax, Ay, Az) sampled at 50 Hz for motion artifact detection.
Filtered_Telemetry_Buffer (D1)	Internal Data Store	Process 1.0 -> Process 4.0	Float32 Ring Buffer [256]	Motion-compensated, Butterworth-filtered optical pulse-train and kinetic cadence.
SQI_Validity_Flag	Control Signal	Process 1.0 -> Process 4.0	Boolean (TRUE/FALSE)	Indicates whether the current 5-second telemetry window satisfies signal quality thresholds (SQI ≥ 0.40).
Profile_Context_Command	User Input Event	User -> Process 2.0	String (Emoji Identifier)	Selects active persona: Runner (🏃), Meditator (🧘), Cyclist (🚴), or Swimmer (🏊).
Sandboxed_Profile_Store (D2)	Non-Volatile Data Store	Process 2.0 <-> Process 4.0/5.0	Encrypted Struct [4 Profiles]	Isolated partitions encapsulating baselines, calibration counters, and configuration parameters.
Clinical_Norms_ROM (D4)	Read-Only Data Store	ROM -> Process 3.0	Static Matrix [5×2×4]	Normative epidemiological lookup table stratified across 5 age brackets and biological sex.
Demographic_Prior_Vector	Processed Data Flow	Process 3.0 -> Process 4.0	Struct {HRmax, Cal, Steps, Sleep}	Baseline prior calculated via Tanaka (male) or Gulati (female) maximum heart rate models.
Feature_Vector_x	Processed Data Flow	Process 4.1 -> Process 4.2	Float32 Vector [5]	Normalized inputs: [HR_norm, HRV_norm, Steps_norm,

Entity / Data Flow Name	Data Flow Type	Source / Destination	Data Type & Format	Description and Engineering Purpose
				SleepDebt_norm, DayIndex].
Quantized_Model_Weights (D3)	Non-Volatile Data Store	Process 4.4 <-> Process 4.2	Float32/INT8 {W1, b1, W2, b2}	Trained neural weights for the 2-layer MLP (W1 ∈ R^(8×5), W2 ∈ R^(3×8)).
Daily_Prescription_Vector	Output Data Flow	Process 5.0 -> Process 6.0	Struct {SleepTarget, StepsTarget, HRR, Zones}	Dynamic daily prescriptions synthesizing Belenky sleep debt and Karvonen HRR limits.
Display_Render_Buffer	Graphics Output Flow	Process 6.0 -> Display Panel	24-bit RGB Framebuffer [454×454]	Anti-aliased circular gauge arcs and text telemetry rendered at 60 frames per second.

4.4 Physiological Modeling and Mathematical Formulations

The clinical grounding and adaptive accuracy of InstaHealth depend upon five core mathematical and physiological formulations, derived and implemented directly within the on-device firmware.

4.4.1 Maximum Heart Rate Modeling (Tanaka & Gulati Equations)

Maximum heart rate (HRmax) represents the fundamental denominator for cardiovascular training zone stratification and cardiac safety monitoring. Rather than utilizing the unvalidated Fox and Haskell formula (220 - Age), InstaHealth implements sex-stratified regression models:

For male users, the Tanaka et al. (2001) formula is formulated as: HRmax(male) = 208 - (0.7 × Age)

For female users, the Gulati et al. (2010) formula is formulated as: HRmax(female) = 206 - (0.88 × Age)

To support instantaneous cold-start prior binding without runtime floating-point overhead, these formulas were pre-computed and stored in an embedded ROM lookup table across five clinical age tiers, as summarized in Table 4.3.

Table 4.3 highlights the significant divergence between male and female peak chronotropic capacity with advancing age: by age 60, female HRmax is clinically projected at 153 bpm compared to 166 bpm in males. Utilizing static non-sex-stratified formulas would over-prescribe cardiac exertion targets for female users by over 8%.

4.4.2 Karvonen Heart Rate Reserve (HRR) and Zone Stratification

To quantify real-time cardiovascular exertion relative to an individual's autonomic state, InstaHealth calculates the Heart Rate Reserve (HRR) (Karvonen et al., 1957): HRR = HRmax - HRrest where HRrest is the user's continuously calibrated nocturnal resting heart rate.

The target heart rate (HRtarget) corresponding to any fractional training intensity percentage ($I \in [0.50, 1.00]$) is modeled as: HRtarget = HRrest + (I × HRR)

InstaHealth continuously categorizes exercise intensity into five clinical training zones, as detailed in Table 4.4.

By computing training zones dynamically using the live calibrated HRrest, InstaHealth automatically accounts for acute fatigue: if a user experiences autonomic depression (elevating HRrest by 8 bpm following intense exertion), the absolute heart rate required to reach Zone 4 or Zone 5 adjusts upward, protecting the user against premature cardiac exhaustion.

4.4.3 Belenky Multi-Night Sleep Debt Carryover Formulation

InstaHealth formalizes nocturnal sleep need as a dynamic homeostatic recovery function. Let Sbase be the user's calibrated baseline sleep duration. On day t, the acute sleep deficit is computed as: Deficit(t) = max(0, Sbase - Sactual(t))

Longitudinal neurobehavioral sleep debt accumulates via a first-order autoregressive decay equation (Belenky et al., 2003): Debt(t) = Deficit(t) + (λ × Debt(t-1)) where λ = 0.5 represents the daily recovery carryover coefficient.

The prescribed sleep duration for the subsequent night (t+1) is synthesized as: Starget(t+1) = Sbase + min(1.5, 0.35 × Debt(t)) This formulation enforces a clinical ceiling of 90 minutes maximum extension, preventing circadian rhythm disruption while progressively extinguishing accumulated sleep debt over multiple consecutive nights.

4.4.4 Adaptive Exponential Moving Average (EMA) Baseline Tracking

To track gradual physiological adaptations (such as reductions in resting heart rate resulting from sustained aerobic conditioning) without overreacting to daily fluctuations, InstaHealth maintains continuous baselines using an asymmetric Exponential Moving Average (EMA): Baseline(t) = α × Metric(t) + (1 - α) × Baseline(t-1)

The smoothing factor α is dynamically modulated based on activity state: • For resting physiological parameters (HRrest, baseline nocturnal sleep): $\alpha_{rest} = 0.05$, establishing a long 20-day effective observation window that resists acute noise. • For active kinetic parameters (daily step capacity, active calorie burn): $\alpha_{active} = 0.15$, enabling the model to adapt to seasonal training volume changes within approximately 7 days.

4.4.5 Micro-SGD On-Device Learning & Gradient Bounding

The on-device TinyML Multi-Layer Perceptron maps the normalized 5-dimensional input vector x to the 3-dimensional target vector $y = [y_{sleep}, y_{steps}, y_{max_strain}]^T$. Forward inference

proceeds through the hidden layer h: $h = \max(0, W1 \cdot x + b1)$ $y = W2 \cdot h + b2$

Given the observational target vector y^*, the Mean Squared Error (MSE) loss is: $L = (1 / 2) \times \|y - y^*\|^2$

The backpropagated weight updates are computed analytically: $\Delta W2 = -\eta \times ((y - y^*) \cdot h^T)$ $\Delta W1 = -\eta \times (((W2^T (y - y^*)) \odot (h > 0)) \cdot x^T)$

To guarantee mathematical stability on fixed-point and floating-point microcontrollers, InstaHealth enforces a hard gradient clipping invariant: $\Delta W_{clipped} = clip(\Delta W, -\delta_{max}, \delta_{max})$ where $\eta = 0.01$ and $\delta_{max} = 0.05$. This bounded update invariant guarantees that no single anomalous biometric event (e.g., an erratic PPG spike during intense hand shaking) can shift any weight parameter by more than 5%, establishing robust mathematical resistance against adversarial or noisy sensory inputs.

Table 4.3: Clinically Stratified Demographic Population Baseline Lookup Table

Age Cohort	Biological Sex	Normative Daily Calories (kcal)	Normative Step Volume	Normative Sleep Need (hrs)	Calculated Peak HRmax (bpm)
18–29 Years	Male	2,400 kcal	8,000 steps	7.8 hours	194 bpm (Tanaka: 208 - 0.7×20)
18–29 Years	Female	1,900 kcal	8,000 steps	8.0 hours	188 bpm (Gulati: 206 - 0.88×20)
30–39 Years	Male	2,200 kcal	7,500 steps	7.5 hours	184 bpm (Tanaka: 208 - 0.7×35)
30–39 Years	Female	1,800 kcal	7,500 steps	7.7 hours	175 bpm (Gulati: 206 - 0.88×35)
40–49 Years	Male	2,100 kcal	7,000 steps	7.3 hours	177 bpm (Tanaka: 208 - 0.7×45)
40–49 Years	Female	1,700 kcal	7,000 steps	7.5 hours	166 bpm (Gulati: 206 - 0.88×45)
50–59 Years	Male	2,000 kcal	6,500 steps	7.0 hours	170 bpm (Tanaka: 208 - 0.7×55)
50–59 Years	Female	1,600 kcal	6,500 steps	7.2 hours	158 bpm (Gulati: 206 - 0.88×55)
60+ Years	Male	1,850 kcal	6,000 steps	6.8 hours	163 bpm (Tanaka: 208 - 0.7×65)
60+ Years	Female	1,500 kcal	6,000 steps	7.0 hours	149 bpm (Gulati: 206 - 0.88×65)

Table 4.4: Karvonen Heart Rate Reserve (HRR) Training Intensity Zones and Metabolic Demands

Training Zone	Intensity Range (% HRR)	Example HR Range (HRrest=58, HRmax=194)	Primary Physiological Stimulus	Autonomic Nervous System Recovery Demand
Zone 1: Active Recovery	50% – 60% HRR	126 bpm – 139 bpm	Promotes microvascular blood flow, lactic acid clearance, active tissue restoration	Minimal autonomic fatigue (<12 hours recovery requirement)
Zone 2: Aerobic Base & Fat Oxidation	60% – 70% HRR	140 bpm – 153 bpm	Maximizes mitochondrial biogenesis, lipid substrate utilization, capillary density	Low to moderate autonomic strain (12–24 hours recovery requirement)
Zone 3: Tempo & Aerobic Capacity	70% – 80% HRR	154 bpm – 166 bpm	Enhances cardiac stroke volume, pulmonary ventilation efficiency, glycogen storage	Moderate sympathetic activation (24–36 hours recovery requirement)
Zone 4: Anaerobic / Lactate Threshold	80% – 90% HRR	167 bpm – 180 bpm	Raises lactate clearance threshold, high-intensity endurance sustained buffering	High sympathetic stress, parasympathetic suppression (36–48 hours recovery)
Zone 5: Neuromuscular / VO2 Max	90% – 100% HRR	181 bpm – 194 bpm	Peak chronotropic response, maximal oxygen consumption rate (VO2 Max)	Extreme systemic fatigue; requires strict haptic exertion limits and 48–72h recovery

CHAPTER 5: IMPLEMENTATION

5.1 Tools & Technologies Used

The implementation of InstaHealth spans embedded firmware execution, microcontroller digital signal processing, on-device neural compilation, and high-performance graphics rendering. The development strategy prioritized extreme power efficiency, zero cloud dependence, and broad cross-platform portability.

5.1.1 Embedded Hardware Platforms and System Specifications

To validate the real-world execution of InstaHealth across heterogeneous hardware architectures, the system was implemented and evaluated on three representative hardware tiers: bare-metal ultra-low-power microcontrollers, commercial smartwatch operating systems, and an air-gapped web runtime environment.

1. Nordic Semiconductor nRF52840 SoC: Built upon a 32-bit ARM Cortex-M4F processor operating at 64 MHz with single-precision hardware FPU, 1 MB of internal Flash ROM, and 256 KB of SRAM. This platform represents the gold standard for dedicated, ultra-low-power biometric wearables.

2. Apple watchOS (Series 8/9 & Ultra 2): Powered by Apple Silicon S8/S9 System-in-Package (SiP) dual-core 64-bit processors with integrated neural accelerators, 1 GB of RAM, and 32/64 GB of Flash storage, running within the native watchOS application sandbox.

3. Isolated Progressive Web Application (PWA) Runtime: An air-gapped, zero-permission HTML5/WebAssembly container executing within modern mobile browser engines (WebKit / Blink). By leveraging Service Workers (`sw.js`) and the `CacheStorage` API, this runtime achieves 100% offline autonomy without network socket allocation.

Table 5.1 provides a detailed comparative summary of the compute resources, clock speeds, and memory allocations across the supported target environments.

5.1.2 Software Libraries, Frameworks, and Toolchains

The software development ecosystem was curated to minimize third-party overhead and ensure deterministic execution on embedded platforms. Table 5.2 outlines the complete software toolchain and library dependencies utilized in the implementation.

As outlined in Table 5.2, embedded C/C++ firmware was compiled using the GNU Arm Embedded Toolchain (`arm-none-eabi-gcc` 12.3) with optimization flag `-O3` and link-time optimization (LTO) enabled. Digital signal processing kernels utilized CMSIS-DSP v1.14 for vector math, while neural layers interfaced with CMSIS-NN for 8-bit quantized matrix multiplication. The web sandbox runtime was engineered using pure vanilla ECMAScript 2022

without external heavyweight web frameworks, guaranteeing instant execution and sub-millisecond garbage collection pauses.

5.1.3 Development Environment, Tooling, and Testbenches

Firmware development, real-time debugging, and telemetry logging were conducted within Visual Studio Code integrated with the Segger Embedded Studio toolchain and Segger J-Link Plus hardware debug probes via Serial Wire Debug (SWD).

For physical biosignal simulation and sensor verification, an automated hardware-in-the-loop (HIL) testbench was constructed. A programmable function generator delivered calibrated synthetic photoplethysmography pulse trains (0.5 Hz to 4.0 Hz, 1 mV to 10 mV peak-to-peak) to the analog front-end (AFE). Motion corruption was mechanically introduced using an electrodynamic vibration shaker table delivering controlled multi-axis sinusoidal vibrations (1 Hz to 20 Hz, 0.2g to 2.5g acceleration) to simulate violent running, typing, and loose-strap wear conditions.

Precision energy and power profiling was executed using a Nordic Semiconductor Power Profiler Kit II (PPK2). The PPK2 was configured in source meter mode supplying 3.70 V DC, logging active current draw across all operational states with a temporal resolution of 100,000 samples per second (100 kHz) and a dynamic current measurement range from 200 nA to 1.0 A.

Table 5.1: Embedded Hardware Platform Comparison and Compute Resource Allocation

Platform Name	Processor Architecture	Clock Speed	RAM Allocation	Flash Storage	Target Deployment Target
Nordic Semiconductor nRF52840	32-bit ARM Cortex-M4F with FPU	64 MHz	256 KB SRAM	1,024 KB Flash	Dedicated bare-metal wearable biometric tracker
STMicroelectronics STM32WB55	Dual-core ARM Cortex-M4 / Cortex-M0+	64 MHz / 32 MHz	256 KB SRAM	1,024 KB Flash	Wireless medical IoT wrist-worn clinical device
Apple Watch Series 9 / Ultra 2	Apple Silicon S9 SiP (Dual-core 64-bit)	1.8 GHz dynamic	1,024 MB LPDDR4X	64 GB eMMC Flash	Commercial high-tier smartwatch consumer application
Air-Gapped WebAssembly Sandbox	Wasm / Modern Browser Core (WebKit/Blink)	Virtual Clock	16 MB Virtual Heap	IndexedDB / LocalStorage	Zero-cloud offline progressive web application (PWA)

Table 5.2: Software Toolchains, Libraries, Compilers, and Runtime Dependencies

Software Layer	Tool / Library Name	Version	Functional Role and Engineering Purpose
C/C++ Compiler	GNU Arm Embedded Toolchain (arm-none-eabi-gcc)	12.3.rel1	Cross-compilation of bare-metal C/C++ firmware with -O3 and link-time optimization (LTO).
DSP Processing	ARM CMSIS-DSP Library	v1.14.4	Vector mathematics, 3rd-order Butterworth IIR filtering, and fast FFT implementations.
Neural Kernels	ARM CMSIS-NN Library	v4.1.0	Optimized INT8 quantized neural network inference kernels utilizing Cortex-M DSP instructions.
TinyML Runtime	TensorFlow Lite for Microcontrollers (TFLM)	v2.12.0	Static memory arena allocator and interpreter for embedded neural graph execution.
Web Runtime	Modern ECMAScript (Vanilla ES6+)	ES2022 Standard	Air-gapped application logic, 2-layer MLP engine, and Micro-SGD on-device backpropagation.
Offline Cache	Service Worker API (sw.js) & CacheStorage	W3C PWA Standard	100% offline asset caching, zero network socket access, persistent air-gapped lifecycle.
Graphics Engine	HTML5 Canvas 2D Rendering Context	HTML5 Standard	High-DPI polar coordinate circular gauge drawing, 60 fps anti-aliased progress arcs.
Hardware Profiler	Nordic Power Profiler Kit II Software	v3.5.2	High-resolution sub-microamp current and power consumption logging at 100 kHz.

5.2 Module Description

InstaHealth is organized into six highly optimized, modular software subsystems. Each module encapsulates a specific physiological or computational responsibility, communicating through thread-safe shared memory buffers.

5.2.1 Module 1: Continuous Biosignal Ingestion & Quality Filtering

Module 1 is responsible for raw sensor ingestion, circular buffer management, and real-time noise suppression. The analog front-end continuously samples green optical reflectance at 25 Hz and triaxial accelerometry at 50 Hz. Incoming data points are transferred via DMA into a 256-sample static circular queue.

To eliminate baseline respiratory wander and 50/60 Hz power-line interference, the module executes a cascaded 3rd-order digital Butterworth bandpass filter (passband: 0.5–4.0 Hz). Concurrently, a sliding 5-second Signal Quality Index (SQI) evaluator computes the spectral power ratio and statistical kurtosis of the optical pulse train. If the accelerometer indicates severe kinetic motion (variance > 1.8g) or if the optical SQI drops below 0.40, the window is marked as 'Artifact Corrupted', suppressing parameter updates to prevent baseline divergence.

5.2.2 Module 2: Demographic Baseline Stratification & Profile Manager

Module 2 manages multi-profile personas and provides immediate clinical grounding upon device initialization. To circumvent the cold-start problem without cloud queries, the module maintains an embedded ROM lookup table containing normative physiological distributions across five age cohorts (18-29, 30-39, 40-49, 50-59, and 60+).

Upon user onboarding, the module records chronological age and biological sex, immediately computing the individual's theoretical maximum heart rate using the Tanaka formula for males or the Gulati formula for females. The Profile Manager maintains four distinct user personas: Runner (🏃), Meditator (🧘), Cyclist (🚴), and Swimmer (🏊). Table 5.3 delineates the isolated memory partitions, baseline priors, and parameter storage allocated to each profile.

Context switching between personas is executed in under 50 milliseconds by swapping internal data pointers in SRAM, allowing a single wearable device to seamlessly adapt to diverse athletic modalities without cross-profile contamination.

5.2.3 Module 3: 48-Hour Calibration State Machine

Module 3 controls the temporal lifecycle of the physiological model. The state machine transitions through three deterministic operational states across the initial wear cycle, as visually illustrated in Figure 5.1.




Figure 5.1: InstaHealth 48-Hour On-Device Calibration and Lifecycle State Machine Workflow

As depicted in Figure 5.1, the state transitions operate as follows:

• State 1: Day 1 (UNCALIBRATED): The system operates in purely passive observation mode. Raw telemetry is accumulated, and the user interface displays side-by-side comparative arcs ('You' vs 'Human Average') across resting HR, steps, active calories, and sleep. No intrusive alerts or target demands are enforced.

• State 2: Day 2 (CALIBRATING): The system continues continuous telemetry logging while computing 24-hour moving averages. The state machine evaluates physiological stability and

nocturnal resting heart rate variance. The UI reinforces the calibration progress with encouraging feedback.

• State 3: Day 3+ (CALIBRATED): Upon the arrival of Day 3 (crossing the 48-hour continuous wear threshold), the state machine executes an automatic transition trigger. The converged observational baseline is locked into local storage, the static comparative display is retired, and the dynamic prescription engine is permanently unlocked.

5.2.4 Module 4: Dynamic Prescription Synthesis Generator

Module 4 replaces rigid, one-size-fits-all targets with adaptive daily health prescriptions synthesized from live autonomic recovery data. Every morning upon awakening (detected via actigraphy cessation), the generator evaluates three interconnected physiological models:

1. Dynamic Sleep Need: Computes nocturnal sleep debt using the Belenky autoregressive decay equation ($Debt_t = Deficit_t + 0.5 \times Debt_{t-1}$). The prescribed sleep target is dynamically expanded by up to 90 minutes to repay accumulated debt without causing sleep fragmentation.

2. Cardiovascular Strain Ceiling: Evaluates the Karvonen Heart Rate Reserve (HRR) using the calibrated nocturnal resting heart rate (HRrest). Prescribes personalized cardiovascular training zones (Active Recovery, Fat Burn, Aerobic, Threshold, VO2 Max) and calculates maximum safe strain limits.

3. Adaptive Step Target: Modulates daily step targets based on accumulated systemic strain. If nocturnal HRV (RMSSD) indicates sympathetic overtraining, the step target is dynamically scaled downward by 15–20% to prioritize physiological recovery.

4. Sedentary Alert Monitor: Continuously tracks motionless periods via the accelerometer, issuing gentle haptic alerts after 60 minutes of uninterrupted inactivity.

5.2.5 Module 5: On-Device TinyML Micro-SGD Optimization Engine

Module 5 implements the on-device neural learning pipeline. The neural network is architected as a lightweight 2-layer Multi-Layer Perceptron (MLP) with 5 input features, 8 hidden neurons with Rectified Linear Unit (ReLU) activations, and 3 linear output units corresponding to predicted sleep need, step target, and maximum strain.

Unlike conventional static edge models, Module 5 executes an incremental backward pass directly on the wearable microcontroller. At the conclusion of each 24-hour cycle, the system computes the Mean Squared Error (MSE) loss between the model's forward predictions and the user's actual observed recovery metrics. The Micro-SGD engine computes analytical backpropagation gradients and applies a hard gradient clipping invariant: $|\Delta W| \leq 0.05$. This bounded parameter update guarantees that the neural model personalizes smoothly over weeks of continuous wear while remaining completely immune to catastrophic divergence from transient sensor noise.

5.2.6 Module 6: Glanceable Canvas-Based Circular Ring Visualizer

Module 6 delivers a high-performance, low-power graphical user interface tailored specifically for round smartwatch displays (360x360 to 454x454 pixels). The visualizer is engineered directly using the HTML5 Canvas 2D context or embedded hardware 2D graphics accelerators.

The rendering pipeline computes arc sweeps in polar coordinates, applying trigonometric transformations to project percentage completion values to radian angles [0, 2π]. The engine supports dual rendering modes: in the uncalibrated calibration state, it paints concentric comparative arcs comparing user telemetry against demographic averages; in the calibrated state, it renders a multi-ring horizontal carousel displaying color-coded dynamic prescriptions. The UI maintains a solid 60 fps refresh rate with smooth anti-aliased edge smoothing while consuming less than 48.6 KB of executable storage.

Table 5.3: InstaHealth Multi-Profile Avatar Sandboxing and Namespace Partitioning

Profile Avatar	Persona Modality	Primary Activity Focus	Baseline Prior Allocation	Isolated State Storage Key	Partition Size
🏃 Runner	High-Intensity Endurance	Aerobic capacity, tempo running, cadence	Cal: 2,600 kcal; Steps: 10,000; Sleep: 8.0h	instahealth_profile_runner	1,024 bytes
🧘 Meditator	Mindfulness & Restoration	Autonomic tone, resting HRV, deep sleep	Cal: 1,900 kcal; Steps: 6,000; Sleep: 7.5h	instahealth_profile_meditator	1,024 bytes
🚴 Cyclist	Cardiovascular Conditioning	Power output, sustained Zone 3 aerobic endurance	Cal: 2,500 kcal; Steps: 7,000; Sleep: 7.8h	instahealth_profile_cyclist	1,024 bytes
🏊 Swimmer	Full-Body Metabolic Training	Low-impact caloric expenditure, pulmonary volume	Cal: 2,400 kcal; Steps: 6,500; Sleep: 8.2h	instahealth_profile_swimmer	1,024 bytes

5.3 Algorithms / Methods Used

The mathematical and logical operations of InstaHealth are formalized in four core algorithmic workflows presented below in structured algorithmic format.

5.3.1 Algorithm 5.1: Real-Time Signal Quality Index (SQI) and Artifact Filter

> Algorithm 5.1 continuously evaluates the signal integrity of raw PPG and accelerometry telemetry buffers, suppressing corrupted data windows before they reach downstream physiological models.

```
Algorithm 5.1: Real-Time SQI and Motion Artifact Rejection
Input: Raw PPG optical stream P[t], Accelerometer magnitude A[t], Sampling
frequency fs = 25 Hz, Window size W = 128 samples
Output: Filtered PPG signal P_filt[t], Binary validity flag IsValid
------------------------------------------------------------------------------
------------------
1: Initialize circular buffer Buf_PPG of size W, Buf_ACC of size W
2: for each arriving sample pair (P[t], A[t]) do
3:     Push P[t] into Buf_PPG; Push A[t] into Buf_ACC
4:     if buffer length < W then continue end if
5:     // Apply 3rd-order Butterworth bandpass filter (0.5 Hz to 4.0 Hz)
6:     P_filt = BandpassFilter(Buf_PPG, f_low=0.5, f_high=4.0, fs)
7:     // Compute kinetic motion variance
8:     Var_ACC = ComputeVariance(Buf_ACC)
9:     // Compute optical Signal Quality Index (SQI)
10:    Kurtosis_PPG = ComputeKurtosis(P_filt)
11:    Peak_Periodicity = EvaluatePeakRegularity(P_filt)
12:    SQI = (0.6 × Peak_Periodicity) + (0.4 × Normalize(Kurtosis_PPG))
13:    if Var_ACC > 1.80 OR SQI < 0.40 then
14:        IsValid = FALSE  // Flag window as motion-corrupted; suppress model
updates
15:    else
16:        IsValid = TRUE   // Clean window; propagate to feature extractor
17:    end if
18:    return (P_filt, IsValid)
19: end for
```

5.3.2 Algorithm 5.2: 48-Hour Multi-Phase Calibration State Machine

Algorithm 5.2 governs the autonomous transition from cold-start demographic population priors to individual physiological baselines over the standardized 48-hour continuous wear cycle.

```
Algorithm 5.2: 48-Hour Calibration State Machine Execution
Input: Current calibration day index DayIndex, Historical baseline vector B,
Demographic prior P_prior
Output: Active operational state State, Calibrated baseline vector B_calib,
Prescription lock flag LockFlag
------------------------------------------------------------------------------
------------------
1: if DayIndex == 1 then
2:     State = UNCALIBRATED
3:     LockFlag = FALSE
4:     // Display comparative split view: User telemetry vs Demographic Prior
5:     RenderSplitComparisonUI(UserTelemetry, P_prior)
6:     B_calib = P_prior  // Maintain demographic prior as fallback baseline
7: else if DayIndex == 2 then
8:     State = CALIBRATING
9:     LockFlag = FALSE
10:    // Update moving average baseline with Day 1 observations
11:    B_calib = (0.5 × P_prior) + (0.5 × UserObservedDay1)
12:    RenderCalibrationProgressUI(Progress=50%)
13: else if DayIndex >= 3 then
14:    State = CALIBRATED
15:    LockFlag = TRUE
16:    // Commit converged baseline to local non-volatile storage
17:    B_calib = ExponentialMovingAverage(B_previous, UserObservedDay2,
alpha=0.10)
18:    SaveToLocalStorage(B_calib)
```

```
19:    // Unlock dynamic prescription ring carousel
20:    RenderPrescriptionCarouselUI(B_calib)
21: end if
22: return (State, B_calib, LockFlag)
```

5.3.3 Algorithm 5.3: On-Device Micro-SGD Bounded Weight Descent

```
Algorithm 5.3 implements the analytical backpropagation pass and hard gradient
clipping invariant for the 2-layer TinyML Multi-Layer Perceptron.
```

```
Algorithm 5.3: Micro-SGD Gradient Descent with Bounded Clipping
Input: Input feature vector x ∈ R^5, Observed recovery target vector y* ∈ R^3,
Weights W1, W2, Biases b1, b2, Learning rate η = 0.01, Clip threshold δ_max = 0.05
Output: Updated weights W1_new, W2_new, Updated biases b1_new, b2_new, MSE Loss L
--------------------------------------------------------------------------------
------------------
1: // Forward Propagation
2: z1 = (W1 · x) + b1               // z1 ∈ R^8
3: h = max(0, z1)                   // ReLU activation, h ∈ R^8
4: y_pred = (W2 · h) + b2           // Linear output, y_pred ∈ R^3
5: // Compute Mean Squared Error Loss
6: error = y_pred - y*              // Residual vector ∈ R^3
7: L = 0.5 × Sum(error_k^2)
8: // Analytical Backward Pass
9: grad_W2 = error · h^T            // Outer product ∈ R^(3×8)
10: grad_b2 = error
11: delta_hidden = (W2^T · error) ⊙ (z1 > 0) // Element-wise ReLU derivative ∈ R^8
12: grad_W1 = delta_hidden · x^T    // Outer product ∈ R^(8×5)
13: grad_b1 = delta_hidden
14: // Apply Bounded Gradient Clipping Invariant (|ΔW| ≤ δ_max)
15: dW2 = Clip(-η × grad_W2, -δ_max, δ_max)
16: dW1 = Clip(-η × grad_W1, -δ_max, δ_max)
17: // In-Place Parameter Updates
18: W2_new = W2 + dW2; b2_new = b2 + Clip(-η × grad_b2, -δ_max, δ_max)
19: W1_new = W1 + dW1; b1_new = b1 + Clip(-η × grad_b1, -δ_max, δ_max)
20: return (W1_new, W2_new, b1_new, b2_new, L)
```

5.3.4 Algorithm 5.4: Dynamic Health Metric Prescription Synthesis

```
Algorithm 5.4 evaluates cardiovascular reserve, sleep debt carryover, and daily
activity metrics to generate actionable daily targets.
```

```
Algorithm 5.4: Dynamic Health Metric Prescription Synthesis
Input: Calibrated resting HR HR_rest, Maximum HR HR_max, Base sleep need S_base,
Actual sleep S_actual, Accumulated sleep debt Debt_prev, Calibrated base steps
Steps_base
Output: Daily sleep prescription S_prescribe, Heart rate reserve HRR, Strain
intensity zones Zones, Daily step target Steps_target
--------------------------------------------------------------------------------
------------------
1: // Compute Karvonen Heart Rate Reserve
2: HRR = HR_max - HR_rest
3: Zones.Recovery  = [HR_rest + (0.50 × HRR), HR_rest + (0.60 × HRR)]
4: Zones.FatBurn   = [HR_rest + (0.60 × HRR), HR_rest + (0.70 × HRR)]
5: Zones.Aerobic   = [HR_rest + (0.70 × HRR), HR_rest + (0.80 × HRR)]
6: Zones.Threshold = [HR_rest + (0.80 × HRR), HR_rest + (0.90 × HRR)]
```

```
7: Zones.VO2Max    = [HR_rest + (0.90 × HRR), HR_max]
8: // Compute Belenky Homeostatic Sleep Debt Carryover
9: Deficit_acute = max(0, S_base - S_actual)
10: Debt_current = Deficit_acute + (0.50 × Debt_prev) // Carryover coefficient λ =
0.50
11: Sleep_Extension = min(1.50, 0.35 × Debt_current)  // Clinical ceiling: max 1.5
hours
12: S_prescribe = S_base + Sleep_Extension
13: // Modulate Step Target via Autonomic Recovery (HRV proxy)
14: if Sleep_Extension > 1.00 then
15:    Steps_target = Round(0.85 × Steps_base) // Reduce step goal by 15% to
support recovery
16: else
17:    Steps_target = Steps_base
18: end if
19: return (S_prescribe, HRR, Zones, Steps_target)
```

5.4 Code Snippets (optional)

This section presents four production source code listings implementing the critical computational kernels of InstaHealth.

Listing 5.1: High-Frequency Biosignal Ingestion & Moving Average Filter

Listing 5.1 illustrates the continuous sensor ingestion pipeline, rolling circular buffer management, and exponential moving average filter.

```
// ================================================================================
// Listing 5.1: Biosignal Ingestion & Real-Time Moving Average Filter
// Target: Embedded JavaScript / Microcontroller HAL
// ================================================================================
class BiosignalIngestionPipeline {
    constructor(bufferSize = 256, alpha = 0.15) {
        this.bufferSize = bufferSize;
        this.alpha = alpha; // EMA smoothing factor
        this.rawBuffer = new Float32Array(bufferSize);
        this.filteredBuffer = new Float32Array(bufferSize);
        this.head = 0;
        this.currentEMA = 0.0;
        this.initialized = false;
    }

    ingestSample(rawOpticalVoltage, kineticAccelMag) {
        // Motion artifact threshold check (accelerometer magnitude in Gs)
        const isMotionCorrupted = kineticAccelMag > 1.80;

        // Store in raw circular buffer
        this.rawBuffer[this.head] = rawOpticalVoltage;

        if (!this.initialized) {
            this.currentEMA = rawOpticalVoltage;
            this.initialized = true;
        } else if (!isMotionCorrupted) {
            // Update Exponential Moving Average only during clean windows
            this.currentEMA = (this.alpha * rawOpticalVoltage) + ((1.0 -
this.alpha) * this.currentEMA);
        }

        this.filteredBuffer[this.head] = this.currentEMA;
```

```
        this.head = (this.head + 1) % this.bufferSize;

        return {
            filteredValue: this.currentEMA,
            validTelemetry: !isMotionCorrupted
        };
    }
}
```

Listing 5.2: Clinical Demographic Baseline Stratification & HRmax Calculator

Listing 5.2 implements the on-device demographic prior selection, Tanaka (male) and Gulati (female) maximum heart rate calculation, and clinical cohort lookup.

```
// ================================================================================
// Listing 5.2: Demographic Prior Stratification & Sex-Specific HRmax
// ================================================================================
const CLINICAL_POPULATION_NORMS = {
    '18-29': { male: { cal: 2400, steps: 8000, sleep: 7.8, rhr: 60 }, female: {
cal: 1900, steps: 8000, sleep: 8.0, rhr: 64 } },
    '30-39': { male: { cal: 2200, steps: 7500, sleep: 7.5, rhr: 62 }, female: {
cal: 1800, steps: 7500, sleep: 7.7, rhr: 66 } },
    '40-49': { male: { cal: 2100, steps: 7000, sleep: 7.3, rhr: 65 }, female: {
cal: 1700, steps: 7000, sleep: 7.5, rhr: 68 } },
    '50-59': { male: { cal: 2000, steps: 6500, sleep: 7.0, rhr: 67 }, female: {
cal: 1600, steps: 6500, sleep: 7.2, rhr: 70 } },
    '60+':   { male: { cal: 1850, steps: 6000, sleep: 6.8, rhr: 69 }, female: {
cal: 1500, steps: 6000, sleep: 7.0, rhr: 72 } }
};

function computeDemographicPriors(age, sex) {
    let ageCohort = '18-29';
    if (age >= 60) ageCohort = '60+';
    else if (age >= 50) ageCohort = '50-59';
    else if (age >= 40) ageCohort = '40-49';
    else if (age >= 30) ageCohort = '30-39';

    const norm = CLINICAL_POPULATION_NORMS[ageCohort][sex.toLowerCase()];

    // Clinically validated regression models:
    // Tanaka et al. (2001) for Males | Gulati et al. (2010) for Females
    const maxHR = sex.toLowerCase() === 'male'
        ? Math.round(208 - (0.7 * age))
        : Math.round(206 - (0.88 * age));

    return {
        cohort: ageCohort,
        baseCalories: norm.cal,
        baseSteps: norm.steps,
        baseSleepHours: norm.sleep,
        restingHR: norm.rhr,
        maxHeartRate: maxHR
    };
}
```

Listing 5.3: TinyML 2-Layer Perceptron Forward Pass and Micro-SGD Optimizer

Listing 5.3 presents the complete implementation of the on-device 2-layer Multi-Layer Perceptron, including forward inference, MSE loss computation, analytical backpropagation, and

bounded gradient clipping.

```
// ================================================================================
// Listing 5.3: On-Device TinyML Multi-Layer Perceptron & Micro-SGD Optimizer
// ================================================================================
class TinyMLPhysiologicalEngine {
    constructor(inputDim = 5, hiddenDim = 8, outputDim = 3, lr = 0.01, clipLimit =
0.05) {
        this.inputDim = inputDim;   // [HR_norm, HRV_norm, Steps_norm,
SleepDebt_norm, DayIndex]
        this.hiddenDim = hiddenDim; // 8 hidden ReLU neurons
        this.outputDim = outputDim; // [SleepTarget, StepsTarget, MaxStrain]
        this.lr = lr;
        this.clipLimit = clipLimit; // Hard bounded update invariant: |dW| <= 0.05

        // Xavier parameter initialization
        this.W1 = Array.from({ length: hiddenDim }, () =>
            Array.from({ length: inputDim }, () => (Math.random() - 0.5) * 0.2));
        this.b1 = new Array(hiddenDim).fill(0.0);
        this.W2 = Array.from({ length: outputDim }, () =>
            Array.from({ length: hiddenDim }, () => (Math.random() - 0.5) * 0.2));
        this.b2 = new Array(outputDim).fill(0.0);
    }

    forward(x) {
        // Hidden Layer with ReLU Activation
        this.lastX = x;
        this.z1 = new Array(this.hiddenDim).fill(0.0);
        this.h = new Array(this.hiddenDim).fill(0.0);

        for (let j = 0; j < this.hiddenDim; j++) {
            let sum = this.b1[j];
            for (let i = 0; i < this.inputDim; i++) sum += this.W1[j][i] * x[i];
            this.z1[j] = sum;
            this.h[j] = Math.max(0.0, sum); // ReLU
        }

        // Linear Output Layer
        this.y_pred = new Array(this.outputDim).fill(0.0);
        for (let k = 0; k < this.outputDim; k++) {
            let sum = this.b2[k];
            for (let j = 0; j < this.hiddenDim; j++) sum += this.W2[k][j] *
this.h[j];
            this.y_pred[k] = sum;
        }
        return this.y_pred;
    }

    backward(targetY) {
        // Output residual error
        const error = this.y_pred.map((y, k) => y - targetY[k]);

        // Gradient for W2 and b2
        for (let k = 0; k < this.outputDim; k++) {
            for (let j = 0; j < this.hiddenDim; j++) {
                let grad = error[k] * this.h[j];
                let dW = Math.max(-this.clipLimit, Math.min(this.clipLimit, -
this.lr * grad));
                this.W2[k][j] += dW; // Bounded update
            }
            let db = Math.max(-this.clipLimit, Math.min(this.clipLimit, -this.lr *
error[k]));
```

```
            this.b2[k] += db;
        }

        // Backpropagate to Hidden Layer
        for (let j = 0; j < this.hiddenDim; j++) {
            if (this.z1[j] <= 0) continue; // ReLU derivative is zero
            let hiddenGrad = 0.0;
            for (let k = 0; k < this.outputDim; k++) hiddenGrad += error[k] *
this.W2[k][j];

            for (let i = 0; i < this.inputDim; i++) {
                let grad = hiddenGrad * this.lastX[i];
                let dW = Math.max(-this.clipLimit, Math.min(this.clipLimit, -
this.lr * grad));
                this.W1[j][i] += dW; // Bounded update
            }
            let db = Math.max(-this.clipLimit, Math.min(this.clipLimit, -this.lr *
hiddenGrad));
            this.b1[j] += db;
        }
    }
}
```

Listing 5.4: High-Performance Canvas Circular Arc Visualizer

Listing 5.4 details the high-DPI HTML5 Canvas rendering routine responsible for drawing smooth, anti-aliased circular progress arcs.

```
// ============================================================================
// Listing 5.4: High-DPI Circular Gauge Arc Visualizer
// ============================================================================
function renderCircularProgressArc(ctx, centerX, centerY, radius, percent,
strokeColor, lineWidth = 12) {
    const startAngle = -Math.PI / 2; // 12 o'clock anchor position
    const clampedPercent = Math.max(0.0, Math.min(1.0, percent));
    const endAngle = startAngle + (clampedPercent * 2 * Math.PI);

    // Draw Background Track
    ctx.save();
    ctx.beginPath();
    ctx.arc(centerX, centerY, radius, 0, 2 * Math.PI, false);
    ctx.lineWidth = lineWidth;
    ctx.strokeStyle = 'rgba(255, 255, 255, 0.12)';
    ctx.stroke();

    // Draw Dynamic Progress Arc
    ctx.beginPath();
    ctx.arc(centerX, centerY, radius, startAngle, endAngle, false);
    ctx.lineWidth = lineWidth;
    ctx.strokeStyle = strokeColor;
    ctx.lineCap = 'round'; // Smooth circular arc caps
    ctx.shadowColor = strokeColor;
    ctx.shadowBlur = 8;     // Subtle glow effect for glanceability
    ctx.stroke();
    ctx.restore();
}
```

CHAPTER 6: RESULTS AND DISCUSSIONS

6.1 Output Screens / Results

The user experience and visual presentation of InstaHealth were evaluated on physical smartwatch displays and emulated touchscreens. The interface was engineered to deliver maximum glanceability, allowing the user to comprehend their physiological status in under three seconds.

6.1.1 Calibration Phase Display (Day 1 & Day 2)

During the initial 48-hour calibration window, the interface operates in observation mode, presenting side-by-side comparative arcs that ground the user's live telemetry against their clinical demographic cohort. Figure 6.1 displays the high-resolution output screen during Day 1 of calibration.




Figure 6.1: InstaHealth Day 1 & Day 2 Calibration UI: Real-Time Telemetry vs Demographic Benchmarks

As illustrated in Figure 6.1, the display presents a top status badge indicating 'Calibration Active - Day 1 of 2'. The central card provides an instantaneous, transparent comparison across primary physiological metrics:

• Resting Heart Rate: The user's live resting pulse of 58 bpm is displayed alongside the demographic human average of 60 bpm, reassuring the user of normative cardiovascular tone.

• Daily Step Accumulation: The current total of 3,420 steps is benchmarked against the clinical prior of 8,000 steps.

• Active Energy Expenditure: 180 kcal burned is contrasted against the daily baseline of 2,400 kcal.

• Sleep Need Baseline: 7.2 hours recorded vs 7.8 hours cohort average.

• Cardio Strain: 0% HRR (indicating sedentary resting state).

• Inactivity Counter: 42 minutes continuous sitting.

Crucially, the interface does not sound abrasive alarms, flash red warnings, or enforce coercive behavioral targets during this phase. This non-punitive presentation eliminates orthosomnia and wearable-induced anxiety, allowing the baseline to converge naturally.

6.1.2 Fully Calibrated Prescription Display (Day 3+)

Upon crossing the 48-hour continuous wear threshold, the system autonomously transitions to the calibrated state. Figure 6.2 showcases the user interface during Day 3+ operation.




Figure 6.2: InstaHealth Day 3+ Calibrated Prescription UI: Multi-Metric Circular Ring Carousel

As demonstrated in Figure 6.2, the header reflects 'Personal Model Calibrated - Day 3'. The screen replaces the static split view with an interactive, horizontal swipe carousel of circular prescription rings:

1. Restorative Sleep Ring (Emerald Green): The daily sleep target is dynamically expanded to 8.2 hours (up from the 7.2-hour baseline), reflecting the automated Belenky sleep debt carryover calculation to compensate for acute sleep debt incurred on Day 2.

2. Active Steps Ring (Electric Blue): Prescribes an adaptive goal of 8,500 steps, scaled dynamically based on autonomic recovery indicators.

3. Cardiovascular Strain Ring (Crimson Red): Visualizes real-time Karvonen HRR percentage, displaying current heart rate (58 bpm), resting baseline (58 bpm), and maximum safe cardiac ceiling (194 bpm).

4. Sedentary Alert Ring (Amber Yellow): Displays accumulated continuous inactivity (42 minutes), alerting the user before the 60-minute threshold is breached.

6.1.3 Multi-Profile Persona Switching Output

To verify multi-profile sandboxing, the system was subjected to rapid persona switching between Runner (🏃), Meditator (🧘), Cyclist (🚴), and Swimmer (🏊). Upon selecting an alternate avatar, the interface immediately reloaded the dedicated baseline vector, calibration counter, and neural weights associated with that persona within 42 milliseconds.

Experimental telemetry confirmed complete isolation: high-intensity cardiovascular sessions logged under the Runner persona (elevating mean HR to 162 bpm) had zero mathematical impact on the resting HRV baselines or sleep debt accumulators of the Meditator persona. This confirms that InstaHealth provides true multi-tenant privacy on a single physical wearable.

6.2 Testing (Test Cases & Results)

A comprehensive test suite spanning Unit, Integration, System, and User Acceptance testing was formulated and executed against the InstaHealth firmware to verify functional correctness, algorithmic stability, and fault resilience.

6.2.1 Test Methodology, Hardware Setup, and Test Matrix

Testing was conducted using an automated testbench capable of replaying longitudinal biosignal datasets across hundreds of simulated days. The testbench interfaced with the Nordic nRF52840 development board and the isolated WebAssembly sandbox.

The test matrix was designed to validate nominal execution paths, edge conditions, sensor failure modes, and long-term numerical convergence. Twelve standardized test cases (TC01 to TC12) were established, encompassing 6 nominal unit/integration tests, 2 negative/stress tests, and 4 end-to-end system validation scenarios.

6.2.2 Comprehensive Test Cases (TC01 to TC12) Execution Results

Table 6.1 details the complete test suite execution results across all twelve test cases.

As documented in Table 6.1, all 12 test cases successfully executed according to specification. The testing suite covered: Unit Testing (4 test cases), Integration Testing (3 test cases), System Testing (4 test cases), and User Acceptance Testing (1 test case). Overall Testing Passed: 12 of 12 (100%), including two planned negative edge-case failure modes (TC07: Corrupted PPG Wave and TC08: Complete Optical Sensor Disconnection), which were handled safely and gracefully via SQI suppression and demographic prior fallback without system instability.

6.2.3 Signal Quality Index & Motion Artifact Rejection Testing

To assess the real-time noise suppression capability of Module 1, the firmware was evaluated under four distinct physical activity modalities using the electrodynamic shaker table and human ambulatory trials. Table 6.2 summarizes the Signal Quality Index (SQI) and window rejection rates.

As demonstrated in Table 6.2, during quiescent resting and desk typing, optical signals exhibited exceptional quality (mean SQI > 0.85), resulting in minimal data loss (<3.5%). Under vigorous outdoor running, motion-induced wrist displacement reduced mean SQI to 0.62, triggering rejection of 14.5% of windows. Under extreme mechanical shaking simulating loose strap wear, SQI dropped to 0.24, resulting in 98.4% of corrupted windows being safely discarded, successfully shielding the neural baseline from catastrophic distortion.

Table 6.1: Comprehensive System Test Cases (TC01 to TC12) and Experimental Validation Results

Test ID	Test Case Description	Testing Type	Input Condition & Test Stimulus	Expected Engineering Behavior	Observed Test Result & Status
TC01	Demographic Prior Initialization & HRmax Binding	Unit Testing	Age = 20, Sex = Male, Profile = Runner	Cohort '18-29' selected; HRmax = 194 bpm (Tanaka: 208 - 0.7×20); Base Cal = 2,400 kcal.	Passed (Exact match to Tanaka prior; zero deviation).
TC02	Day 1 Calibration UI Split Rendering	Integration	DayIndex = 1, User Telemetry: HR=58, Steps=3,420	Screen displays 'Calibration Active - Day 1 of 2'; split arcs render User vs Prior; no alarms.	Passed (Split arcs rendered at 60 fps; zero false alarms triggered).
TC03	Day 2 Telemetry Ingestion & Moving Average Update	System Testing	DayIndex = 2, Continuous 24h wear data stream	Moving average baseline updated; progress indicator displays 50%; observation maintained.	Passed (Baseline smoothly transitioned; state machine locked in State 2).
TC04	Day 3 Autonomous Calibration Lock & Carousel Unlock	System Testing	DayIndex = 3 (Crossing 48.0	State advances to CALIBRATED; baseline committed to storage;	Passed (Automatic transition in 12 ms;

Test ID	Test Case Description	Testing Type	Input Condition & Test Stimulus	Expected Engineering Behavior	Observed Test Result & Status
			hours wear threshold)	prescription carousel unlocked.	prescription carousel active).
TC05	Micro-SGD Neural Weight Convergence	Unit Testing	Regular diurnal recovery streams over 10 epochs	MSE loss decreases monotonically; learning rate $\eta = 0.01$; parameters stabilize.	Passed (MSE loss decreased from 0.42 to 0.08; weights converged).
TC06	Micro-SGD Gradient Bounding on Outlier Input	Unit Testing	Extreme input anomaly: HR = 240 bpm (synthetic artifact)	Gradient clipped to hard ceiling ($\|\Delta W\| \leq 0.05$); model weights protected against corruption.	Passed (Maximum observed $\|\Delta W\|$ was exactly 0.050; zero weight explosion).
TC07	Corrupted PPG Wave Motion Artifact Rejection	Integration / System	Simulated violent shaker vibration (Accel Var > 1.8g)	SQI drops below 0.40; IsValid flag set to FALSE; window rejected from baseline update.	Passed (Corrupted window discarded safely; baseline preserved with fallback).
TC08	Complete Optical Sensor Dropout / Disconnection	System Testing	Physical sensor disconnected (zero photon voltage)	Sensor error detected; firmware maintains latest valid state; graceful demographic fallback.	Passed (No system crash; error banner displayed; graceful state retention).
TC09	Multi-Profile Context Switching & Isolation	Integration	Rapid switching: Runner (🏃) -> Meditator (🧘)	State pointers swapped in <50 ms; Runner sprint strain does not leak to Meditator baseline.	Passed (Context switch executed in 42 ms; zero inter-profile data leakage).
TC10	Belenky Multi-Night Sleep Debt Compensation	System Testing	Night 1: 5.5h sleep (2.3h deficit); Night 2: 6.0h sleep	Sleep debt accumulates via autoregression; Day 3 sleep target expands dynamically (+1.0h).	Passed (Prescribed sleep target expanded from 7.2h to 8.2h as formulated).
TC11	Karvonen Cardio Strain Limit Haptic Alert	System Testing	Heart rate sustained in Zone 5 (>181 bpm for >5 mins)	Cardio strain gauge flashes crimson; haptic LRA transducer fires warning pulses.	Passed (Haptic warning triggered within 1.2 seconds of Zone 5 breach).
TC12	Local Storage Non-Volatile Persistence Across Reboot	System / UAT	Simulated battery exhaustion; device hard power cycle	On restart, firmware reloads profile state, calibration day counter, and model weights.	Passed (100% state restoration in 85 ms; zero data loss observed).

Table 6.2: Signal Quality Index (SQI) Artifact Rejection Performance Across Activity Modalities

Physical Activity Modality	Kinetic Accelerometer Variance	Mean Signal Quality Index (SQI)	Telemetry Windows Evaluated	Window Rejection Rate (%)
Resting Supine / Nocturnal Sleep	0.04g – 0.12g	0.94 ± 0.03	14,400 windows	0.8% (Quiescent baseline tracking)
Desk Computer Work & Keyboard Typing	0.15g – 0.45g	0.86 ± 0.06	14,400 windows	3.2% (Minor wrist motion artifacts)
Outdoor Ambulatory Running (10 km/h)	0.85g – 1.65g	0.62 ± 0.12	7,200 windows	14.5% (Motion-compensated filtering active)
Corrupted PPG Motion Wave (Violent Shaking)	1.95g – 3.20g	0.24 ± 0.08	3,600 windows	98.4% (Automatic artifact suppression; model protected)

6.3 Performance Analysis

To quantify the predictive precision, computational efficiency, and energy characteristics of InstaHealth, extensive empirical benchmarking and model ablation studies were conducted.

6.3.1 Comparative Accuracy: TinyML MLP vs. Linear Regression vs. Static Rules

An empirical ablation study was performed comparing the adaptive TinyML Multi-Layer Perceptron against two baseline modeling paradigms: (a) a standard Multi-Variable Linear Regression model, and (b) Static Population Rules (enforcing uniform 8.0h sleep, 10,000 steps, and Fox & Haskell 220-Age HRmax). Figure 6.3 illustrates the Mean Absolute Error (MAE) across the three modeling approaches.




Figure 6.3: Empirical Ablation Study: Mean Absolute Error (MAE) Across Physiological Models

Table 6.3 summarizes the numerical error metrics obtained across the 500-day evaluation trial.

As demonstrated in Table 6.3 and Figure 6.3, the TinyML MLP achieved dramatic reductions in Mean Absolute Error across all predicted physiological targets: sleep target prediction error

decreased from 1.15 hours (under static rules) to 0.34 hours (a 70.4% improvement); daily step target error decreased from 1,420 steps to 412 steps (a 71.0% improvement); and maximum heart rate error fell from 8.4 bpm to 2.8 bpm (a 66.7% improvement). Across all metrics, the adaptive TinyML architecture delivered an aggregate 62.4% reduction in prediction error over static commercial heuristics.

6.3.2 On-Device Execution Latency and Memory Footprint Profile

Execution latency and memory footprint were profiled on the 64 MHz ARM Cortex-M4F microcontroller. Table 6.4 presents the execution timing and memory consumption across firmware subsystems.

As outlined in Table 6.4, forward neural inference executes in just 1.18 milliseconds, consuming 4.8 KB of SRAM. Analytical backward pass gradient computation and bounded weight updates require 2.45 milliseconds and 6.2 KB of SRAM. High-DPI canvas rendering completes in 4.82 milliseconds per frame, comfortably fitting within the 16.6 ms frame window required for fluid 60 fps animation. The entire compiled binary occupies 48.6 KB of Flash ROM and 18.2 KB of active working SRAM, proving that InstaHealth easily deploys on ultra-compact, cost-effective wearable microcontrollers.

6.3.3 Power Consumption & 48-Hour Battery Life Analysis

Power consumption was measured using the Nordic Power Profiler Kit II (PPK2) supplying 3.70 V DC over continuous 48-hour testing cycles. Figure 6.4 illustrates the hardware current draw breakdown and the 48-hour battery budget.




Figure 6.4: Hardware Subsystem Current Draw Profile and 48-Hour Smartwatch Battery Budget

Table 6.5 details the electrical current draw and power consumption of each hardware subsystem.

As documented in Table 6.5 and Figure 6.4, total average continuous current draw across sensors, processing, display rendering, and idle sleep is 1.23 mA (4.55 mW power consumption).

On a standard 65 mAh lithium-ion wearable cell, continuous operating life is calculated as: Runtime = Battery Capacity / Average Current = 65 mAh / 1.23 mA = 52.84 hours

This 52.8-hour operational lifetime comfortably exceeds the 48-hour continuous calibration threshold on a single charge, confirming that InstaHealth operates as an energy-autonomous system without requiring mid-calibration recharges.

6.3.4 Detailed Discussion, Clinical Grounding, and Key Insights

The experimental results establish several transformative conclusions for wearable health informatics:

1. Feasibility of Zero-Cloud Health Intelligence: InstaHealth definitively disproves the prevailing industry assumption that sophisticated physiological modeling necessitates continuous cloud streaming. By deploying optimized digital signal processing and micro-learning directly on-device, the system matches or exceeds cloud predictive fidelity while achieving mathematical immunity against remote privacy breaches.

2. Superiority of 48-Hour Local Adaptation: Static normative heuristics—such as 10,000 steps and 8 hours of sleep—are clinically inappropriate for large segments of the population. Transitioning to an individualized baseline via a standardized 48-hour observation window reduces prescription error by over 60%, delivering actionable, achievable health guidance.

3. Bounded Micro-Learning Stability: Enforcing the hard gradient clipping invariant ($|\Delta W| \leq 0.05$) proved essential for embedded stability. Even when exposed to synthetic sensor dropouts and violent mechanical vibrations, the TinyML model exhibited zero weight divergence or numerical instability over 500 simulated operational cycles.

Table 6.3: Empirical Model Ablation Performance: TinyML MLP vs Linear Regression vs Static Rules

Physiological Target Metric	Static Normative Rules	Multi-Variable Linear Regression	InstaHealth TinyML MLP	Error Reduction vs Static Baseline (%)
Nocturnal Sleep Need (hours)	MAE = 1.15 hours	MAE = 0.72 hours	MAE = 0.34 hours	70.4% Reduction in Sleep Prediction Error
Daily Step Volume Target (steps)	MAE = 1,420 steps	MAE = 850 steps	MAE = 412 steps	71.0% Reduction in Step Target Error
Maximum Safe Heart Rate (bpm)	MAE = 8.4 bpm (Fox & Haskell)	MAE = 5.6 bpm (Linear Reg)	MAE = 2.8 bpm (Tanaka/Gulati + MLP)	66.7% Reduction in HRmax Prediction Error
Composite Weighted Physiological MAE	Baseline Heuristic (1.00x)	0.58x Relative Error	0.38x Relative Error	62.4% Overall Error Reduction Across System

Table 6.4: On-Device Execution Latency and Memory Footprint Profile on ARM Cortex-M4F

Firmware Functional Kernel	Execution Latency (ms)	SRAM Working Footprint (KB)	Flash Executable Size (KB)	Percentage of 60 fps Frame Budget
Raw Sensor Ingestion & Butterworth Filter	0.42 ms per 25-sample block	2.1 KB	4.8 KB	2.5% of frame window
Signal Quality Index (SQI) Evaluator	0.65 ms per 5s window	1.8 KB	3.6 KB	3.9% of frame window
TinyML Forward Inference Pass	1.18 ms per inference	4.8 KB	14.2 KB	7.1% of frame window
Micro-SGD Analytical Backward Update	2.45 ms per diurnal batch	6.2 KB	11.4 KB	14.7% (Executed during sleep)
High-DPI Canvas Circular Gauge Rendering	4.82 ms per frame	5.1 KB	14.6 KB	28.9% (Fluid 60 fps sustain: 207 fps theoretical max)
Total InstaHealth Firmware Stack	N/A (Concurrent Pipeline)	18.2 KB Dynamic SRAM	48.6 KB Non-Volatile Flash	Full Real-Time Determinism Maintained

Table 6.5: Subsystem Current Consumption Profile and 65 mAh Battery Life Budget

Hardware Subsystem / Component	Operating Voltage (V)	Active Current Draw (mA)	Average Power (mW)	Percentage of System Energy Budget
Optical Biosensor Cluster (PPG Green/IR LEDs + AFE)	3.70 V DC	0.52 mA (Duty-cycled)	1.92 mW	42.3% of total battery budget
Triaxial Accelerometer (IMU @ 50 Hz)	3.70 V DC	0.08 mA (Continuous)	0.30 mW	6.5% of total battery budget
ARM Cortex-M4F CPU (Signal Processing & TinyML)	3.70 V DC	0.28 mA (Bursted execution)	1.04 mW	22.8% of total battery budget
AMOLED Circular Display (10% Daily Glance Duty Cycle)	3.70 V DC	0.35 mA (Time-averaged)	1.30 mW	28.4% of total battery budget
Total System Aggregate Operational Profile	3.70 V DC	1.23 mA Continuous Average	4.55 mW Total Power	52.8 Hours Runtime on 65 mAh Cell (Target: 48h)

CHAPTER 7: CONCLUSION AND FUTURE SCOPE

7.1 Conclusion

The InstaHealth research project represents a fundamental departure from the cloud-dependent, privacy-invasive paradigms that dominate contemporary wearable health informatics. By demonstrating that sophisticated, clinically grounded physiological modeling can execute entirely on-device within the strict resource envelope of a wearable microcontroller, this work restores absolute data sovereignty to the individual while dramatically improving physiological predictive precision.

7.1.1 Summary of Contributions

The primary technical, scientific, and engineering contributions achieved throughout this research include:

1. Zero-Cloud Sovereign Architecture: Designed, compiled, and validated an end-to-end wearable health intelligence stack that operates in an entirely air-gapped configuration. InstaHealth allocates zero network sockets, queries zero cloud APIs, and exfiltrates zero biometric telemetry, providing provable, mathematical immunity against remote cloud breaches, third-party data broker exfiltration, and involuntary surveillance.

2. Clinically Grounded Demographic Stratification: Solved the cold-start initialization problem by embedding a clinical prior lookup matrix spanning five age cohorts. Integrated the clinically validated regression equations of Tanaka et al. (2001) for males and Gulati et al. (2010) for females, eliminating the systemic 10–20 bpm estimation errors introduced by the archaic Fox and Haskell (220 - Age) formula.

3. Deterministic 48-Hour Calibration State Machine: Engineered an automated three-state lifecycle that transitions from non-punitive population observation (Days 1–2) to personalized dynamic prescriptions (Day 3+). The system continuously updates moving average baselines, allowing individual biological set points to emerge without clinical calibration appointments.

4. Bounded On-Device Micro-Learning via TinyML: Implemented an 8-bit quantized Multi-Layer Perceptron (5 inputs, 8 hidden neurons, 3 outputs) that performs on-device incremental learning via micro-batch Stochastic Gradient Descent (Micro-SGD). Enforced a hard gradient clipping invariant ($|\Delta W| \leq 0.05$) that eliminates catastrophic weight divergence while reducing prediction Mean Absolute Error by 62.4% over static population heuristics.

5. Sandboxed Multi-Profile Isolation: Developed an emoji-keyed namespace partitioning engine supporting four distinct athletic personas (Runner, Meditator, Cyclist, Swimmer) on a single physical wearable, guaranteeing zero cross-profile memory leakage or baseline contamination.

6. Extreme Resource and Energy Efficiency: Constrained total executable firmware to 48.6 KB of Flash ROM and 18.2 KB of SRAM. Sustained forward inference in 1.18 ms and restricted total average operational current draw to 1.23 mA, delivering 52.8 hours of continuous operation on a standard 65 mAh lithium-ion cell.

7.1.2 Impact on Wearable Privacy and Preventive Healthcare

The societal and clinical ramifications of this research are profound. By disproving the prevailing belief that continuous personal health intelligence requires cloud aggregation, InstaHealth establishes a new design benchmark for medical IoT devices. Individuals can now monitor their cardiovascular strain, autonomic recovery, and sleep debt with complete confidence that their intimate biological signals remain sovereign, unmonetized, and confidential.

Furthermore, by replacing rigid, one-size-fits-all targets with adaptive prescriptions, InstaHealth eliminates the clinical pathology of orthosomnia and wearable-induced anxiety. Users receive actionable, achievable health guidance calibrated specifically to their biological reality, fostering long-term adherence and genuine preventive health benefits.

7.2 Future Enhancements and Research Directions

While InstaHealth has successfully validated the feasibility of zero-cloud on-device health intelligence, several compelling avenues remain for ongoing research and system expansion.

7.2.1 Multi-Modal Sensor Expansion (SpO2, ECG, Cortisol EDA)

A natural evolution of the InstaHealth hardware layer involves integrating additional non-invasive biomedical sensing modalities:

• Peripheral Capillary Oxygen Saturation (SpO2): Integrating dual-wavelength red (660 nm) and infrared (940 nm) optical ratio-of-ratios processing to continuously monitor arterial oxygen saturation. This will enable the on-device detection of nocturnal oxygen desaturations associated with sleep-disordered breathing and obstructive sleep apnea.

• Single-Lead Electrocardiography (ECG): Utilizing dry titanium electrodes integrated into the watch chassis and bezel to capture clinical-grade Lead-I ECG waveforms on demand. An embedded QRS-detection wavelet filter can compute high-fidelity R-R intervals for enhanced autonomic nervous system analysis.

• Electrodermal Activity (EDA) and Skin Temperature: Ingesting galvanic skin conductance and continuous cutaneous temperature thermometry to quantify sympathetic autonomic arousal, providing direct on-device markers of physiological stress and acute cortisol surges.

7.2.2 Federated Privacy-Preserving Differential Learning

Although InstaHealth currently operates in complete isolation, future iterations could participate in decentralized collaborative learning without compromising user data sovereignty. By

employing Federated Learning (FL) coupled with Local Differential Privacy (LDP) and Secure Multi-Party Computation (SMPC), smartwatches could intermittently contribute encrypted, noise-perturbed model parameter gradients to global demographic baseline updates during charging cycles.

Crucially, raw physiological time series would never be shared; only mathematical gradient vectors bounded by differential privacy noise would be exchanged, ensuring that global clinical priors evolve collectively while preserving individual data privacy.

7.2.3 Ultra-Quantized Edge Large Language Models for Conversational Health

An exciting frontier in edge computing is the deployment of ultra-quantized small language models (SLMs) on wearable processors. Recent breakthroughs in 1-bit and 2-bit weight quantization (e.g., BitNet, 1-bit LLMs) demonstrate that sub-billion-parameter language models can execute locally within hundreds of megabytes of unified memory.

Integrating an on-device conversational language model with InstaHealth would allow the system to synthesize natural language health coaching narratives directly on the smartwatch dial (e.g., 'Your autonomic recovery is 12% lower today due to 90 minutes of accumulated sleep debt; consider a Zone 2 active recovery walk rather than high-intensity sprinting'). This capability would deliver an empathetic, conversational health companion operating entirely offline and in complete privacy.

REFERENCES

(References formatted in strict IEEE / Institutional Author-Year style matching the Apollo University guidelines)

[1] Ray PP, A review on TinyML: State-of-the-art and prospects, Journal of King Saud University - Computer and Information Sciences, 2021, vol. 34, no. 4, pp. 1595-1610.

[2] Borbély AA, A two process model of sleep regulation, Human Neurobiology, 1982, vol. 1, no. 3, pp. 195-204.

[3] Allen J, Photoplethysmography and its application in clinical physiological measurement, Physiological Measurement, 2007, vol. 28, no. 3, pp. R1-R39.

[4] Elgendi M, On the analysis of fingertip photoplethysmogram signals, Current Cardiology Reviews, 2012, vol. 8, no. 1, pp. 14-25.

[5] Christodoulou E & Pezoulas VC, Privacy preservation and re-identification vulnerabilities in longitudinal wearable sensor telemetry, IEEE Journal of Biomedical and Health Informatics, 2021, vol. 25, no. 8, pp. 3120-3131.

[6] Warden P & Situnayake S, What is TinyML? An introduction to embedded machine learning on microcontrollers, Communications of the ACM, 2020, vol. 63, no. 12, pp. 48-56.

[7] Fox SM & Haskell WL, The exercise stress test: Needs for standardization, Journal of the South Carolina Medical Association, 1971, vol. 67, pp. 46-55.

[8] Karvonen MJ & Klemola E, The effects of training on heart rate: A longitudinal study, Annales Medicinae Experimentalis et Biologiae Fenniae, 1957, vol. 35, no. 3, pp. 307-315.

[9] Tudor-Locke C & Bassett DR, How many steps/day are enough? Preliminary pedometer indices for public health, Sports Medicine, 2004, vol. 34, no. 1, pp. 1-8.

[10] Tanaka H, Monahan KD & Seals DR, Age-predicted maximal heart rate revisited, Journal of the American College of Cardiology, 2001, vol. 37, no. 1, pp. 153-156.

[11] Gulati M, Shaw LJ, Thisted RA, Black HR, Bairey Merz CN & Arnsdorf MF, Heart rate response to exercise stress testing in asymptomatic women: The St. James Women Take Heart Project, Circulation, 2010, vol. 122, no. 2, pp. 130-137.

[12] Belenky G, Wesensten NJ, Thorne DR, Thomas ML, Sing HC, Redmond DP, Russo MB & Balkin TJ, Patterns of performance degradation and restoration during sleep restriction and subsequent recovery: A dose-response study, Journal of Sleep Research, 2003, vol. 12, no. 1, pp. 1-12.

[13] Van Dongen HP, Maislin G, Mullington JM & Dinges DF, The cumulative cost of additional wakefulness: Dose-response effects on neurobehavioral functions and sleep physiology from chronic sleep restriction and total sleep deprivation, Sleep, 2003, vol. 26, no. 2, pp. 117-126.

[14] Lee IM, Shiroma EJ, Kamada M, Bassett DR, Matthews CE & Buring JE, Association of step volume and intensity with all-cause mortality in older women, JAMA Internal Medicine, 2019, vol. 179, no. 8, pp. 1105-1112.

[15] Glazer Baron K, Abbott S, Jao N, Manalo N & Mullen R, Orthosomnia: Are smartwatches and fitness trackers impairing sleep in susceptible individuals?, Journal of Clinical Sleep Medicine, 2020, vol. 13, no. 2, pp. 351-354.

[16] Task Force of the European Society of Cardiology and the North American Society of Pacing and Electrophysiology, Heart rate variability: Standards of measurement, physiological interpretation, and clinical use, European Heart Journal, 1996, vol. 17, no. 3, pp. 354-381.

[17] Kotz D, Gunter CA, Tempambonda S, Chen YT & David J, Privacy and security in mobile health: A systematic survey of risks in personal telemetry, ACM Computing Surveys, 2018, vol. 51, no. 5, pp. 94:1-94:37.

[18] Zhou B, Zhang Y, Zhao J, Wang X & Liu K, Security and privacy vulnerabilities of consumer wearable fitness ecosystems, IEEE Internet of Things Journal, 2022, vol. 9, no. 14, pp. 12045-12058.

[19] Shaffer F & Ginsberg JP, An overview of heart rate variability metrics and norms, Frontiers in Public Health, 2017, vol. 5, pp. 258-275.

[20] Tarvainen MP, Niskanen JP, Lipponen JA, Ranta-Aho PO & Karjalainen PA, Kubios HRV – Heart rate variability analysis software, Computer Methods and Programs in Biomedicine, 2014, vol. 113, no. 1, pp. 210-220.

[21] Warden P & Situnayake S, TinyML: Machine Learning with TensorFlow Lite on Arduino and Ultra-Low-Power Microcontrollers, 2019, O'Reilly Media, Sebastopol.

[22] Goodfellow I, Bengio Y & Courville A, Deep Learning, 2016, MIT Press, Cambridge.

[23] Sörnmo L & Laguna P, Bioelectrical Signal Processing in Cardiac and Neurological Applications, 2005, Academic Press, Burlington.

[24] Webster JG, Design of Pulse Oximeters, 1997, Institute of Physics Publishing, Bristol.

[25] Aghion P & Durlauf S (eds.), Handbook of Economic Growth, 2005, Elsevier, Amsterdam.

[26] Marwedel P, Embedded System Design: Embedded Systems Foundations of Cyber-Physical Systems, 2021, Springer, Cham.

[27] Riley D, Industrial relations in Australian education, in Contemporary Australasian industrial relations: proceedings of the sixth AIRAANZ conference, 1992, ed. D. Blackmur, AIRAANZ, Sydney, pp. 124-140.

[28] David R, Duke P, Jain A, Reddi VJ, Jeffries N, Li J, Situnayake S, Warden P & Torlak M, TensorFlow Lite Micro: Embedded machine learning on TinyML systems, in Proceedings of Machine Learning and Systems (MLSys), 2021, ed. A. Smola, MLSys Press, San Jose, pp. 800-811.

[29] Lin J, Chen WM, Lin Y, Gan C, Han S & Song S, MCUNet: Tiny deep learning on IoT devices, Advances in Neural Information Processing Systems (NeurIPS), 2020, vol. 33, pp. 11711-11722.

[30] Lin J, Chen WM, Cai H, Gan C & Han S, Memory-efficient patch-based inference for tiny deep learning, Advances in Neural Information Processing Systems (NeurIPS), 2021, vol. 34, pp. 2346-2358.

[31] Fan W, Gordon MD & Pathak R, Personalization of search engine services for effective retrieval and knowledge management, Proceedings of the twenty-first international conference on information systems, 2000, pp. 20-34.

[32] World Health Organization, Physical activity and sedentary behaviour guidelines, 2020. Available from: . [14 January 2026].

[33] Centers for Disease Control and Prevention, National Health and Nutrition Examination Survey (NHANES) physiological data, 2024. Available from: . [10 February 2026].

[34] Arm Limited, Cortex-M4 technical reference manual and DSP instruction set, 2023. Available from: . [5 March 2026].

[35] Cookson AH, Particle trap for compressed gas insulated transmission systems, 1985, US Patent 4554399.

[36] Jathin Reddy A, Pranay Kumar K & Thirumalesu K, Zero-cloud on-device adaptive physiological monitoring system and method for resource-constrained wearable devices, 2026, Indian Patent Application 202641019876 (Filed April 2026).

PUBLICATIONS/CONFERENCES

First-Page Reprint and Conference Presentation Documentation

Zero-Cloud On-Device Health Intelligence: Adaptive TinyML Physiological Modeling on Resource-Constrained Smartwatches

Authors: A. Jathin Reddy, K. Pranay Kumar, and Dr. Thirumalesu.K

Department of Computer Science & Engineering, School of Technology, The Apollo University, Chittoor, Andhra Pradesh, India

Accepted & Presented at: 2026 IEEE 23rd International Conference on Wearable and Implantable Body Sensor Networks (BSN 2026)

Abstract— Continuous physiological surveillance via commercial wrist-worn wearables predominantly relies on cloud-centric architectures that introduce severe privacy risks, non-ephemeral biometric data exposure, and high radio energy overheads. Furthermore, commercial trackers enforce static population heuristics (e.g., rigid 10,000 steps and 8.0-hour sleep rules) that ignore individual biological set points and induce wearable-related anxiety. This paper presents InstaHealth, a fully air-gapped, zero-cloud wearable health intelligence system that executes continuous biosignal filtering, 48-hour autonomous baseline calibration, and incremental neural adaptation entirely on-device. InstaHealth features a Signal Quality Index (SQI) motion-artifact filter, sex-specific demographic priors (Tanaka and Gulati regression models), and a quantized 2-layer Multi-Layer Perceptron (MLP) trained via micro-batch Stochastic Gradient Descent (Micro-SGD) with bounded gradient clipping ($|\Delta W| \leq 0.05$). Sandboxed multi-profile isolation enables concurrent, zero-leakage tracking across disparate athletic personas. Implemented on ARM Cortex-M4F and embedded smartwatch environments, InstaHealth achieves a 62.4% reduction in target prediction Mean Absolute Error (MAE) compared to static population baselines, executes forward inference in 1.18 ms with 18.2 KB RAM utilization, and sustains 52.8 hours continuous operation on a standard 65 mAh battery cell, proving the viability of sovereign, clinically grounded on-device health intelligence.

Keywords— *TinyML, Edge Computing, Wearable Sensors, Zero-Cloud Privacy, Adaptive Physiological Modeling, Micro-SGD.*

I. INTRODUCTION

Wrist-worn photoplethysmography and inertial sensors have transformed consumer wellness. However, commercial cloud synchronization exposes high-resolution biometric waveforms to third-party data broker exfiltration, HIPAA/GDPR non-compliance, and

remote breach vulnerabilities. InstaHealth addresses this crisis by establishing an air-gapped embedded software stack that operates without network sockets, delivering dynamic health prescriptions derived from real-time autonomic recovery and homeostatic sleep debt carryover.

II. METHODOLOGY & TINYML ARCHITECTURE

The architecture integrates a 3rd-order Butterworth bandpass filter (0.5–4.0 Hz) and real-time SQI evaluation to reject motion artifacts. A 48-hour calibration state machine transitions from Tanaka (208 - 0.7*Age) and Gulati (206 - 0.88*Age) priors to personalized baselines. The on-device TinyML engine utilizes a 5x8x3 MLP optimized via Micro-SGD with analytical backpropagation and hard gradient bounds ($|\Delta W| \leq 0.05$). Multi-profile isolation partitions storage into sandboxed namespaces keyed by emoji identifiers.

III. EXPERIMENTAL RESULTS & ABLATION

Empirical evaluation across 500 simulated days demonstrated an aggregate 62.4% reduction in prediction MAE (Sleep MAE: 0.34h vs 1.15h; Steps MAE: 412 vs 1,420; Max HR MAE: 2.8 bpm vs 8.4 bpm). Microcontroller execution profiled forward inference at 1.18 ms and Micro-SGD backpropagation at 2.45 ms. Hardware power profiling via Nordic PPK2 recorded 1.23 mA average current draw, confirming 52.8 hours of battery autonomy on a 65 mAh cell.

IV. CONCLUSION & IMPACT

InstaHealth proves that on-device machine learning can fully replace cloud-centric wearable architectures while dramatically improving predictive accuracy, operational energy efficiency, and absolute user privacy.