

BDA LAB - 3

1. Create a key space by name Employee

```
cqlsh> create keyspace Employee2 with replication = {'class':'SimpleStrategy','replication_factor':1};
cqlsh> describe Employee2;

CREATE KEYSPACE employee2 WITH replication = {'class': 'SimpleStrategy', 'replication_factor': '1'} AND durable_writes = true;
```

2. Create a column family by name Employee-Info with attributes Emp_Id Primary Key, Emp_Name, Designation, Date_of_Joining, Salary, Dept_Name

```
cqlsh> create table Employee2.Employee_Info(Emp_ID int Primary key,Emp_Name text,Designation text, Date_of_Joining timestamp,Salary double,Dept_Name text);
cqlsh> select * from Employee2.Employee_Info;

emp_id | date_of_joining | dept_name | designation | emp_name | salary
-----+-----+-----+-----+-----+-----
(0 rows)
cqlsh>
```

3. Insert the values into the table in batch

```
cqlsh> begin batch insert into Employee2.Employee_Info(emp_id,date_of_joining,dept_name,designation,emp_name,salary)values(2,'2020-03-07','Development','Manager','Tarun',1500000.0);insert into Employee2.E
mployee_Info(emp_id,date_of_joining,dept_name,designation,emp_name,salary)values(3,'2021-03-29','R&D','Web developer','Nithish',750000.0); apply batch;
cqlsh> select * from Employee2.Employee_Info;

emp_id | date_of_joining | dept_name | designation | emp_name | salary
-----+-----+-----+-----+-----+-----
1 | 2022-04-26 18:30:00.000000+0000 | Deployment | Team Lead | Prem Sai | 1e+06
2 | 2020-03-06 18:30:00.000000+0000 | Development | Manager | Tarun | 1.5e+06
3 | 2021-03-28 18:30:00.000000+0000 | R&D | Web developer | Nithish | 7.5e+05
(3 rows)
```

4. Update Employee name and Department of Emp-Id 121

```
cqlsh> update Employee2.Employee_Info set emp_name = 'Harsha',dept_name='Testing' where emp_id = 3;
cqlsh> select * from Employee2.Employee_Info;

emp_id | date_of_joining | dept_name | designation | emp_name | salary
-----+-----+-----+-----+-----+-----
1 | 2022-04-26 18:30:00.000000+0000 | Deployment | Team Lead | Prem Sai | 1e+06
2 | 2020-03-06 18:30:00.000000+0000 | Development | Manager | Tarun | 1.5e+06
3 | 2021-03-28 18:30:00.000000+0000 | Testing | Web developer | Harsha | 7.5e+05
```

5. Sort the details of Employee records based on salary

```
cqlsh> create table Employee2.emp(Emp_Id int ,Salary double,primary key(Emp_Id,Salary));
cqlsh> begin batch
... insert into Employee2.emp(emp_Id,salary) values(1,1000000);
... insert into Employee2.emp(emp_Id,salary) values(2,1500000);
... insert into Employee2.emp(emp_Id,salary) values(3,700000);
... apply batch;
cqlsh> select * from Employee2.emp;
```

emp_id	salary
1	1e+06
2	1.5e+06
3	7e+05

(3 rows)

```
cqlsh> paging off;
```

Disabled Query paging.

```
cqlsh> select * from Employee2.emp where emp_id in(1,2,3) order by salary;
```

emp_id	salary
3	7e+05
1	1e+06
2	1.5e+06

(3 rows)

6. Alter the schema of the table Employee_Info to add a column Projects which stores a set of Projects done by the corresponding Employee.

```
cqlsh> alter table Employee2.Employee_Info add Projects set<text>;
scqlsh> select * from Employee2.Employee_Info ;
```

emp_id	date_of_joining	dept_name	designation	emp_name	projects	salary
1	2022-04-26 18:30:00.000000+0000	Deployment	Team lead	Prem Sai	null	1e+06
2	2020-03-06 18:30:00.000000+0000	Development	Manager	Tarun	null	1.5e+06
3	2021-03-28 18:30:00.000000+0000	Testing	Web developer	Harsha	null	7.5e+05

7. Update the altered table to add project names.

```
cqlsh> update Employee2.Employee_Info set projects= projects+{'abc','xyz'} where emp_id=1;
cqlsh> select * from Employee2.Employee_Info ;
```

emp_id	date_of_joining	dept_name	designation	emp_name	projects	salary
1	2022-04-26 18:30:00.000000+0000	Deployment	Team lead	Prem Sai	{'abc', 'xyz'}	1e+06
2	2020-03-06 18:30:00.000000+0000	Development	Manager	Tarun	null	1.5e+06
3	2021-03-28 18:30:00.000000+0000	Testing	Web developer	Harsha	null	7.5e+05

(3 rows)

```
cqlsh> update Employee2.Employee_Info set projects= projects+{'def','pqr'} where emp_id=2;
```

```
cqlsh> update Employee2.Employee_Info set projects= projects+{'gjd','ads'} where emp_id=3;
```

```
cqlsh> select * from Employee2.Employee_Info ;
```

emp_id	date_of_joining	dept_name	designation	emp_name	projects	salary
1	2022-04-26 18:30:00.000000+0000	Deployment	Team lead	Prem Sai	{'abc', 'xyz'}	1e+06
2	2020-03-06 18:30:00.000000+0000	Development	Manager	Tarun	{'def', 'pqr'}	1.5e+06
3	2021-03-28 18:30:00.000000+0000	Testing	Web developer	Harsha	{'ads', 'gjd'}	7.5e+05

8 Create a TTL of 15 seconds to display the values of Employees.

```
cqlsh> insert into Employee2.Employee_Info(emp_id,date_of_joining,dept_name,designation,emp_name,salary)values(10,'2020-02-27','Development','Intern','XYZ',150000.0) using TTL 15;
cqlsh> select * from Employee2.Employee_Info ;
```

emp_id	date_of_joining	dept_name	designation	emp_name	projects	salary
10	2020-02-26 18:30:00.000000+0000	Development	Intern	XYZ	null	1.5e+05
1	2022-04-26 18:30:00.000000+0000	Deployment	Team lead	Prem Sai	{'abc', 'xyz'}	1e+06
2	2020-03-06 18:30:00.000000+0000	Development	Manager	Tarun	{'def', 'pqr'}	1.5e+06
3	2021-03-28 18:30:00.000000+0000	Testing	Web developer	Harsha	{'ads', 'gjd'}	7.5e+05

```
cqlsh> select * from Employee2.Employee_Info ;
```

emp_id	date_of_joining	dept_name	designation	emp_name	projects	salary
1	2022-04-26 18:30:00.000000+0000	Deployment	Team lead	Prem Sai	{'abc', 'xyz'}	1e+06
2	2020-03-06 18:30:00.000000+0000	Development	Manager	Tarun	{'def', 'pqr'}	1.5e+06
3	2021-03-28 18:30:00.000000+0000	Testing	Web developer	Harsha	{'ads', 'gjd'}	7.5e+05

```
(3 rows)
```