

Week-2 Module-2

Q-1 Linear search

logic → Take the no of IDs

→ Array banega

→ ~~Linear search kar ke output dega~~

→ Suspicious ID Enter

Mila toh
show case kar dega

→ nhi toh
ID is not found

↓
Search kar ga

↓
Print the result

Dry Run: — Enter Input no of ID

↓
Array

Input suspicious ID

bool found = false;

for (int i=0; i<n; i++)

{

if (arr[i] == suspicious ID)

{

found = true;

break;

}

```

}
if (!found)

```

```

    cout << "ID is not found";

```

```

}

```

```

else

```

```

{

```

```

}

```

Q-2 Binary Search

Logic → Input ID;

↓

Store the ID

↓

Enter ID to search

↓

Initialize variable

↓

Binary search

→

ID = found

↓

!found = ID

Day Run $\rightarrow$ Input

Array

ID to search

int low = 0;

int high = ServerIDs - 1;

bool found = false;

while (low <= high)

Binary search

Q-3 Bubble Sort

Logic $\rightarrow$ Input no of empl

$\downarrow$
store

$\downarrow$
sort

Day Run $\rightarrow$ Input

$\downarrow$

arr

$\downarrow$

for (int i = 0; i < n - 1; i++)
{

for (int j = 0; j < n - i - 1; j++)

{ if (arr[j] > arr[j + 1])

return