

GroAurum

B2B Domain Migration Plan

B2B dry-fruit wholesale ordering and distribution platform
Launch market: Gurugram, India | Ops base: Fatehpur Beri
Generated: July 15, 2026
Git checkpoint: 18ee50a

This document summarizes the migration from the current Blinkit-style consumer quick-commerce MVP to the target GroAurum B2B architecture. No migration implementation has started yet.

1. Domain Correction Summary

The current repository is a functional consumer quick-commerce MVP. The business domain is incorrect for GroAurum. The target product is a B2B dry-fruit wholesale ordering and distribution platform serving verified retailers and shops in Gurugram.

Incorrect assumptions to remove:

- Nearest dark store and service radius
- Store-scoped hard-coded catalog
- Guest checkout
- Simulated OTP, payment, and rider progress
- Auto-advancing order status
- Consumer grocery pricing and fees

Target architecture pillars:

- Service areas (Gurugram clusters), not dark stores
- Fully dynamic admin-managed catalogue (empty catalog must work)
- Verified shop accounts with lifecycle and salesman assignment
- Salesman-assisted orders with customer-only confirmation OTP
- Zero credit: Pay Online Now or Pay on Delivery only
- Separate order status and payment status state machines
- Route-based B2B delivery, not fake rider GPS
- Four interfaces on one Supabase/PostgreSQL backend

2. Module Classification (KEEP / ADAPT / REPLACE / REMOVE)

Module	Disposition	Notes
Expo Router shell	KEEP	Adapt routes later for TradeFlow UX
React Query + AppProviders	KEEP	Swap mock queryFns for Supabase
Zustand pattern	KEEP/ADAPT	Shop session + draft order stores
Design tokens (theme.ts)	KEEP	Brand foundation
ProductCard, QtyButton, CartBar	ADAPT	B2B trade price, MOQ, units
EmptyState, LoadingBlock, BrandLogo	KEEP	Domain-agnostic
StatusTimeline	ADAPT	Real order states, no rider copy
Search, PDP, cart, orders screens	ADAPT	Keep shells, rebind data
Location flow + location store	REPLACE	Shop address + service area
Dark store / geo radius	REMOVE	Pin-code service areas instead
Mock catalogue + data.ts seed	REPLACE	Admin-managed dynamic catalog
types/index.ts	REPLACE	New B2B domain types
Cart store	ADAPT	Shop-scoped draft order lines
Session store (guest)	REPLACE	Verified shop + auth session
Checkout + mock OTP/payment	REPLACE	Real confirmation + payment
Order service + simulator	REPLACE	Server-driven state machine
Rider progress UI	REMOVE	Route-based delivery
Consumer delivery fees	REMOVE	B2B trade pricing rules
Expo template leftovers	REMOVE	Cleanup phase

3. Target Repository Structure

```
groaurum/
  apps/customer/      Expo RN app (current MVP moved here)
  apps/sales-pwa/     Salesman mobile-first PWA
  apps/delivery-pwa/  Delivery user PWA
  apps/admin-web/     Desktop-first admin panel
  packages/shared-types/  Domain enums + DTOs
  packages/db/        Migrations, empty-catalog default seed
  packages/api-client/ Typed Supabase + Edge clients
  supabase/migrations/ PostgreSQL + RLS
  supabase/functions/ Privileged workflows
```

Defaults: npnm monorepo; current Expo app becomes apps/customer via git mv.

4. Target Domain Model (Core Entities)

Territory

- ServiceArea (Gurugram clusters, pin codes)
- Warehouse/OpsBase (Fatehpur Beri)

Catalog

- Category, Product, Sku, SkuPrice (history)
- InventoryBalance
- Product types: PACKED, BULK
- Selling units: CARTON, KG (extensible)

Shops

- Shop, ShopInvitation, ShopAuthLink
- Profile roles: CUSTOMER, SALESMAN, DELIVERY, ADMIN
- Lifecycle: LEAD -> INVITED -> ACTIVATED -> FIRST_ORDER -> REPEAT_CUSTOMER

Orders

- Order, OrderLine, OrderEvent
- OrderConfirmationChallenge (customer OTP only)

Payments

- Payment, PaymentEvent (separate from order status)

Fulfillment

- StockReservation, DeliveryRoute, RouteStop, DeliveryAttempt

Audit

- AuditLog (append-only)

5. Authentication and Authorization

Auth: Supabase Auth with phone OTP. Shop identity is separate from auth user.

- Salesman creates shop + invitation before customer installs app
- Customer authenticates with registered mobile -> link to existing shop
- No duplicate shops; lifecycle INVITED -> ACTIVATED on link
- No guest checkout
- Privileged ops via Edge Functions (service role server-side only)
- RLS: customers see own shop/orders; salesmen assigned shops only
- Salesmen cannot confirm OTP, grant credit, or force DELIVERED
- Delivery users cannot grant credit

6. Assisted-Order Confirmation Flow

```
salesman prepares DRAFT_ASSISTED
-> AWAITING_CUSTOMER_CONFIRMATION
-> customer reviews items, units, prices, total, delivery
-> customer chooses PAY_ONLINE_NOW or PAY_ON_DELIVERY
```

- > customer confirms on own device + OTP
- > CONFIRMED

Outcomes: customer confirmed | requested changes | rejected
Salesman cannot enter or bypass customer confirmation OTP.

7. Order State Machine

DRAFT_ASSISTED

- > AWAITING_CUSTOMER_CONFIRMATION
- > CONFIRMED
- > STOCK_RESERVED
- > PROCESSING
- > READY_FOR_DISPATCH
- > ASSIGNED_TO_ROUTE
- > OUT_FOR_DELIVERY
- > DELIVERED (only if payment PAID)
- > DELIVERY_FAILED | CANCELLED

No automatic timer-based status progression.

8. Payment State Machine (Separate Field)

UNPAID -> PAYMENT_PENDING -> PAID | FAILED | REFUNDED

Launch methods: Pay Online Now | Pay on Delivery (cash or confirmed UPI)
Zero credit at launch. DELIVERED requires PAID (DB + Edge Function enforced).

9. Service Area Model

- Admin manages Gurugram clusters with pin-code membership
- Shop delivery address maps to active ServiceArea to order
- Territory expansion cluster by cluster
- Fatehpur Beri is ops base metadata, not a consumer store picker

10. Route-Based Delivery

confirmed -> stock reserved -> processing -> ready for dispatch
 -> grouped into DeliveryRoute -> assigned delivery user
 -> route stops -> payment collected/confirmed at stop
 -> goods handed over -> DELIVERED

Failure reasons: customer_unavailable, shop_closed, payment_not_available, customer_requested_credit, customer_refused_order, address_location_issue, damaged_order_issue, other (+ note)

11. Four Target Interfaces

Interface	Stack	Focus
Customer app	Expo + RN + TS	Retailer ordering, assisted review
Sales PWA	Mobile-first PWA	Shop creation, draft orders
Delivery PWA	Mobile-first PWA	Routes, POD, delivery outcomes
Admin web	Desktop responsive	Catalog, areas, inventory, users

12. Migration Phases

Phase 0 (done)

Git checkpoint 18ee50a - preserve consumer MVP

Phase 1

B2B domain types + service adapter boundary; no UI redesign

Phase 2

Monorepo scaffold + Supabase migrations, RLS stubs, DB types

Phase 3

Replace services/mock with Supabase; empty catalog; service-area gate

Phase 4

Phone OTP auth + shop invitation/activation linking

Phase 5

Order/payment state machines; assisted OTP; remove simulator

Phase 6

Inventory reservation + admin catalog/service-area CRUD

Phase 7

Sales PWA + Delivery PWA

Phase 8

Customer TradeFlow UX redesign (HOME/CATALOGUE/RESTOCK/ORDERS/ACCOUNT)

13. Preserve from Existing MVP

- Expo 57 + Expo Router + TypeScript shell
- TanStack Query provider pattern
- Zustand client state pattern
- ProductCard, QtyButton, CartBar, EmptyState, LoadingBlock, BrandLogo
- Search, PDP, cart, orders list, order detail screen foundations

- Theme tokens as starting visual language

14. Remove Before UI Redesign

- Dark stores, nearest-store, service radius, preset consumer addresses
- Hard-coded catalog seed in app source
- Guest checkout and mock OTP 1234
- Simulated payment and auto status simulator
- Rider progress and consumer delivery fee logic
- Store-scoped cart lock and Q-commerce copy

15. Explicit Non-Goals (Current Step)

- No UI redesign / TradeFlow visual overhaul yet
- No deleting project or rebuilding Expo from zero
- No hard-coding Kaju/Badam/W320 etc. as permanent catalog
- No implementing all four apps in one PR
- No migration implementation until plan approval

16. Immediate Next Step After Approval

Start Phase 1 only: introduce B2B domain types and a service adapter boundary without breaking the runnable MVP until a deliberate cutover in Phase 3. Stop again for approval before monorepo move and Supabase provisioning.