

GroAurum

Phase 3 Completion Summary

Customer data adapters: auth session, linked shop, serviceability, catalogue

Generated: July 16, 2026

Phase 3 commit: af9e616

Phase 3 proves authenticated customer -> linked shop -> serviceability -> dynamic catalogue against local Supabase, while preserving the legacy mock adapter behind an explicit development flag. Phase 4 not started.

1. Phase 3 Goal

Connect the existing customer Expo architecture to real Supabase-backed read/auth/shop/serviceability/catalogue adapters. Database remains source of truth. Customer UI may remain visually legacy. No invitation SMS, assisted-order OTP, payment gateway, Sales/Delivery/Admin features, or production catalogue seeds.

2. Adapter Selection

Mode	Behavior
mock (default)	Legacy MVP: dark-store location + in-memory catalogue
supabase	Real anon client + RLS; empty catalogue stays empty

EXPO_PUBLIC_CUSTOMER_DATA_ADAPTER=mock | supabase

Invalid values fail validation. Mode is logged in development only - never shown as a technical label to production customers.

3. Public Supabase Client Boundary

- createGroAurumSupabaseClient in @groaurum/api-client - typed Database access
- Expo may use EXPO_PUBLIC_SUPABASE_URL + EXPO_PUBLIC_SUPABASE_ANON_KEY only
- Rejects postgresql:// URLs and service-role / secret keys
- Anon key is public by design; RLS enforces row access
- Local API URL in this repo: http://127.0.0.1:54421 (ports remapped for Windows)

4. Auth Session Foundation

- Restore session on startup (getSession) and subscribe via onAuthStateChange
- Expose loading / authenticated / unauthenticated states; provide sign-out
- Local/dev path: signInWithEmailPassword against local Auth users
- Phone OTP request/verify throw clear not-configured errors (no fake SMS)
- Assisted-order confirmation OTP is a separate concept - not implemented
- Sign-out clears customer-specific React Query caches

5. Linked Shop Resolution

resolveCustomerSession() never auto-creates shops or auth links. Invitation activation remains a later trusted workflow.

Phase	Meaning
AUTH_LOADING	Session loading
UNAUTHENTICATED	No session
AUTHENTICATED_NO_SHOP_LINK	Auth OK, no shop_auth_links row
LINKED_SHOP_LOADING	Resolving link
LINKED_SHOP_READY	Shop + contacts loaded
LINKED_SHOP_INACTIVE_OR_BLOCKED	Inactive or blocked shop
ERROR	Load failure

6. Serviceability Adapter

Pure evaluator `evaluateServiceabilityRules` supports `PIN_CODE` and `ADMIN_AREA`. `ADMIN_AREA` matches `shop.deliveryCity`. Multiple matches: lowest `displayOrder`, then name. No polygon matching. No dark-store / nearest-hub radius logic in supabase mode.

Status	When
SERVICEABLE	Active area + active matching rule
NOT_SERVICEABLE	No match / inactive area or rule
INSUFFICIENT_ADDRESS_DATA	No PIN / admin area
UNSUPPORTED_RULE_TYPE	Only POLYGON rules present
ERROR	Unexpected failure

7. Dynamic Catalogue Adapter

- Reads categories -> products -> skus -> sku_prices
- Only active categories/products/SKUs; category `display_order` respected
- Current price: `effective_from` <= now and (`effective_to` null or > now)
- Among matches: newest `effective_from`, then newest `created_at`
- SKU without current price is not orderable / not exposed
- Empty DB returns empty result - no demo product injection in supabase mode
- Malformed SKU rows skipped when safe; backend errors remain errors

8. Customer Query Integration and Flow Gate

- Screens use `@/services/customer-catalogue` (not direct mock imports for catalogue)
- Query keys include customer scope: store id (mock) or shop id (supabase)
- `CustomerFlowGate`: mock uses location; supabase uses auth -> shop -> serviceability
- Minimal panels: sign-in, awaiting activation, shop unavailable, not serviceable, error
- Empty catalogue shown as empty state; backend error as error state
- Checkout blocked in supabase mode (order placement deferred)

9. Legacy Dark-Store Isolation

- `findNearestStore` / store radius do not gate catalogue in supabase mode
- `/location` redirects away when adapter is supabase
- Location store skips geo matching outside mock mode
- Dark-store code retained under `services/mock/geo.ts` for mock-only development

10. Test Fixtures

`supabase/fixtures/phase3_dev_fixtures.sql` is test/development only. Not wired as `seed.sql`. Not presented as GroAurum launch catalogue. Live integration tests also insert ephemeral fixtures via db-tests helpers.

11. Tests Added

- api-client unit: adapter mode validation, effective price selection, serviceability rules
- db-tests live: unauthenticated, no shop link, own shop only, inactive shop
- db-tests live: PIN match serviceable; inactive area/rule not serviceable; insufficient data
- db-tests live: unpriced SKU not exposed; priced SKU visible; inactive category hides products
- Preserved all prior Phase 2.5 invariant and RLS tests

12. Validation Results

Command	Result
pnpm typecheck	Pass (all workspaces)
pnpm lint	Pass
pnpm test	Pass - 14 shared-types + 15 api-client + 9 validation
pnpm test:db	Pass - 44/44 (incl. 10 Phase 3 adapter tests)
pnpm --filter @groaurum/customer build	Pass - Expo web export
Mock mode	Default adapter; location -> catalogue path preserved
Supabase mode	Live adapters under RLS; empty catalogue stays empty

13. Local Ports (Windows)

Default Supabase ports 54321-54341 overlapped a Windows Hyper-V reserved range on this host. Local stack remapped in supabase/config.toml:

```
API    http://127.0.0.1:54421
DB     postgresql://...@127.0.0.1:54422/postgres
Studio http://127.0.0.1:54423
Analytics disabled locally (not required for Phase 3)
```

14. What Phase 3 Did NOT Do

- No invitation activation / SMS provider integration
- No assisted-order confirmation OTP
- No payment gateway
- No Supabase order placement
- No customer UI redesign / TradeFlow / Restock
- No Sales PWA, Delivery PWA, or full Admin UI
- No production Gurugram or launch catalogue seeds
- Phase 4 not started

15. Git History

```
18ee50a checkpoint: preserve original customer MVP
eb05c74 feat: add GroAurum B2B domain and service boundaries
fbcddb7 feat: scaffold monorepo and Supabase B2B schema
726e175 test: prove Supabase schema invariants and RLS
ca2967b test: complete live Supabase database proof
af9e616 feat: connect customer data adapters to Supabase
```

16. Documentation

Primary architecture doc: docs/architecture/phase-3-customer-adapters.md. Env template: apps/customer/.env.example.

17. Next Step (Phase 4 - not started)

Phase 4 is out of scope for this commit. Likely later work includes invitation activation, order placement against Supabase, and product-facing UI redesign - none of which were implemented in Phase 3.