

GroAurum Admin ERP

Phase 2.5 Production Readiness Audit

Date: 2026-07-16

Scope: Live Admin ERP verification only (no new features)

Method: Static code audit + local Supabase schema/seed probes

VERDICT: NOT PRODUCTION-READY for end-to-end CRUD.

Architecture is live-read ready when the Supabase adapter is configured; auth session, env activation, SKU/category UI, and most mutations are not.

1. Verification Scorecard (15 checks)

PARTIAL	1. Every repository reads from Supabase When <code>VITE_DATA_ADAPTER=supabase</code>, <code>view repos use LiveAdminApi</code> and <code>domain repos use createSupabaseDomainRepositories</code>. Without that env, <code>getAdminDataClient()</code> defaults to mock fixtures.
PASS	2. No page imports fixtures directly Fixture imports are confined to <code>buildAdminMockSources.ts</code>. Pages use <code>hooks/QueryStateGate</code>. Stale comments still say 'fixtures are read-only' on <code>Pricing/Inventory</code> detail.
FAIL	3. VITE_DATA_ADAPTER=supabase is active Set only in <code>apps/admin-web/.env.example</code>. No <code>.env.local</code> found at audit time. Vite does not load <code>.env.example</code>, so runtime mode falls back to mock.
PARTIAL	4. Every React Query hook works 17 hooks in <code>hooks.ts</code> cover products, prices, inventory, customers, orders, salesmen, delivery, reports, settings, dashboard. No <code>useCategories*</code> / <code>useSkus*</code> hooks. Categories route is <code>PlaceholderPage</code>.
FAIL	5. CRUD works (8 domains) <code>CrudServices</code> + mutation hooks exist for most domains except SKUs (repo only). UI wiring: <code>Product publish/archive</code> + <code>Settings company upsert</code> only. Categories page missing. See section 2.
PASS	6. Foreign keys 46 foreign keys on public schema (<code>products->categories</code>, <code>skus->products</code>, <code>sku_prices->skus</code>, <code>inventory->skus/locations</code>, <code>orders->shops</code>, etc.). Seed relationships intact.
PASS	7. RLS policies All 30 public tables have <code>rowsecurity=true</code>; 54 policies. Catalogue <code>SELECT/write</code> policies require <code>authenticated + is_admin()</code> / <code>is_admin_or_read_only()</code>. Anon has table <code>GRANT SELECT</code> but no RLS policy -> empty reads; anon <code>INSERT</code> denied by <code>GRANT</code>.
FAIL	8. Every mutation succeeds Not verified end-to-end in the app. Default <code>VITE_AUTH_PROVIDER=mock</code> does not attach a Supabase JWT to the data client. Admin writes need authenticated JWT passing <code>is_admin()</code>. Most mutation hooks are unused by pages.
PARTIAL	9. Optimistic updates Implemented only for <code>useSoftDeleteProductMutation</code> (<code>list cache patch + rollback</code>). Other mutations <code>cancel/invalidate</code> without optimistic patches.
PASS	10. Cache invalidation Mutations call <code>invalidateEntity</code> (<code>MemoryCache</code> + <code>React Query</code> keys). <code>CrudServices</code> also invalidates <code>MemoryCache</code> on success. Pattern is consistent for wired and unwired hooks.
PASS	11. Loading states <code>QueryStateGate</code> shows <code>Loading EmptyState</code> on all repository-backed pages audited.
PASS	12. Error handling <code>QueryStateGate</code> surfaces <code>state.error.message</code>. Soft-delete mutation rolls back optimistic cache on <code>onError</code>.
PASS	13. Report every TODO

No formal TODO/FIXME/HACK markers in repo source. Operational debt is expressed as 'Mutation deferred' comments and PlaceholderPage routes (listed below).

PASS

14. Report every mocked feature

Inventory complete; see section 4.

PASS

15. Report every placeholder

Inventory complete; see section 5.

2. CRUD Domain Matrix

Legend: Domain repo = Supabase CrudRepository exists. CrudServices = Zod + service method. Hook = React Query mutation. UI = page action calls the hook.

Domain	Repo	CrudServices	Hook	UI / notes
Categories	Yes	Yes	Yes	FAIL: PlaceholderPage; hooks unused
Products	Yes	Yes	Yes	PARTIAL: publish/archive only
SKUs	Yes	No	No	FAIL: no service/hooks/UI CRUD
Prices	Yes	create/close	create	FAIL: list/detail read-only UI
Inventory	Yes	adjust/update	update	FAIL: mutations deferred
Customers	Yes	Yes	Yes	FAIL: list/detail read-only UI
Orders	Yes	create/status	create	FAIL: mutations deferred
Settings	Yes	upsert/update	upsert	PARTIAL: company upsert only

3. Environment & Auth Blockers

- apps/admin-web/.env.example sets VITE_DATA_ADAPTER=supabase, but VITE_SUPABASE_URL / ANON_KEY remain commented.
- No apps/admin-web/.env.local at audit time -> resolveMode() returns 'mock' -> fixtures path.
- VITE_AUTH_PROVIDER defaults to mock; mock auth auto-signs for RBAC UI but does not establish Supabase Auth session for PostgREST.
- createGroAurumSupabaseClient uses anon key with persistSession; admin data client never signs in that client when auth provider is mock.
- RLS write path requires role authenticated and is_admin(). Without JWT, mutations cannot succeed even if adapter=supabase.

4. Mocked Features

- Data adapter mock mode: entire ERP view-models from *-fixtures via buildAdminMockSources.
- Auth: @groaurum/auth mock provider + VITE_AUTH MOCK_ROLE (default super_admin).
- Supabase auth provider is still a stub (createSupabaseAuthProviderStub).
- Salesman visits: LiveAdminApi returns visits: [].
- Customer documents: LiveAdminApi returns documents: [].
- Inventory incomingLabel hardcoded '0' and reorderLevelLabel hardcoded '10' in LiveAdminApi.
- Domain reports/dashboard repositories are placeholder throwers; UI uses LiveAdminApi snapshots instead.
- Reports chart series largely placeholder:true (not live analytics).
- Payment gateway label falls back to 'Razorpay (placeholder)'.
- Sales / Delivery PWA apps remain scaffold stubs (out of Admin ERP scope).

5. Placeholders & Deferred UI

- Routes: /categories and /service-areas render PlaceholderPage.
- PlaceholderChart component for report visuals awaiting live metrics.
- reports_snapshot seed payload status=placeholder (analytics sprint pending).
- 'Mutation deferred' comments: Settings warehouses/service areas; Delivery detail; Salesman detail; Customer/Order detail; Pricing/Inventory detail; Reports export stubs.
- HTML input placeholder attributes on browse bars/forms (cosmetic only; not product gaps).

6. TODOs / Deferred Markers

Formal TODO/FIXME scan across repo: zero matches.

Deferred markers found (non-exhaustive comments):

- PricingListPage / PricingDetailPage / InventoryListPage / InventoryDetailPage: mutations deferred
- CustomersListPage / CustomerDetailPage / OrdersListPage / OrderDetailPage: no backend mutations
- Salesmen* / Delivery*: mutations deferred
- ReportsPage: export stubs; placeholder charts
- SettingsPage: warehouse/service-area add/edit/disable deferred
- packages/data repository subscribe: live channel wiring deferred

- Polygon serviceability matching: not implemented

7. React Query Hook Inventory

Present and used by pages via QueryStateGate:

- useProductsListQuery / useProductDetailQuery
- usePricesListQuery / usePriceDetailQuery
- useInventorySnapshotQuery / useInventoryDetailQuery
- useCustomersSnapshotQuery / useCustomerDetailQuery
- useOrdersSnapshotQuery / useOrderDetailQuery
- useSalesmenSnapshotQuery / useSalesmanDetailQuery
- useDeliverySnapshotQuery / useDeliveryDetailQuery
- useReportsSnapshotQuery / useSettingsSnapshotQuery / useDashboardSnapshotQuery

Missing for checklist completeness:

- useCategoriesListQuery / useCategoryDetailQuery
- useSkusListQuery / useSkuDetailQuery (skus source exists in live adapter but no page hooks)

8. Mutation Hook Wiring

Hook	Used by UI?	Notes
useCreateProductMutation	No	Exported only
useUpdateProductMutation	Yes	ProductDetail publish
useSoftDeleteProductMutation	Yes	ProductDetail archive + optimistic
useCreateCategoryMutation	No	No Categories page
useUpdateCategoryMutation	No	No Categories page
useCreatePriceMutation	No	Pricing UI deferred
useUpdateInventoryMutation	No	Inventory UI deferred
useCreateCustomerMutation	No	Customers UI deferred
useUpdateCustomerMutation	No	Customers UI deferred
useCreateOrderMutation	No	Orders UI deferred
useCreateSalesmanMutation	No	Salesmen UI deferred
useCreateDeliveryRouteMutation	No	Delivery UI deferred
useUpsertSettingMutation	Yes	Settings company quick action

9. Database Probe (local)

- Seed counts: categories=2, products=2, skus=2, prices=2, inventory_balances=2, shops=5, orders=2, settings=1, reports_snapshot=1
- RLS enabled on 30/30 public tables; 54 policies; 46 foreign keys
- Anon REST SELECT on categories: empty (no anon RLS policy)
- Anon REST INSERT on categories: blocked (GRANT / permission denied)

10. Sprint 6 Gate Recommendation

Do not treat Live Admin ERP as production-complete. Before Sprint 6 feature work, close these blockers:

- Create apps/admin-web/.env.local with VITE_DATA_ADAPTER=supabase and local URL/anon key.
- Wire real Supabase Auth session into the same client used by LiveAdminApi / domain repos (or stop using mock auth for live mode).
- Add Categories UI + SKU CrudServices/hooks/UI.
- Wire remaining mutation hooks to existing forms/actions and re-run mutation success probes under ADMIN JWT.
- Replace hardcoded inventory reorder/incoming and empty visits/documents with real sources or explicit empty-state copy.
- Keep reports charts marked placeholder until analytics sprint.

End of audit. No application features were built as part of this verification.