Department of Computer Science and Engineering Indian Institute of Technology Kharagpur

Compilers Laboratory: CS39003

3rd Year CSE: 5th Semester

Assignment - 3: Lexer for tiny Marks: 100
Assign Date: August 12, 2024

1 Preamble – tinyC

This assignment follows the lexical specification of C language from the International Standard ISO/IEC 9899:1999 (E). To keep the assignment within our required scope, we have chosen a subset of the specification as given below. We shall refer to this language as tiny C and subsequently (in a later assignment) specify its grammar from the Phase Structure Grammar given in the C Standard.

The lexical specification quoted here is written using a precise yet compact notation typically used for writing language specifications. We first outline the notation and then present the Lexical Grammar that we shall work with.

2 Notation

In the syntax notation used here, syntactic categories (non-terminals) are indicated by *italic type*, and literal words and character set members (terminals) by **bold type**. A colon (:) following a non-terminal introduces its definition. Alternative definitions are listed on separate lines, except when prefaced by the words "one of". An optional symbol is indicated by the subscript "opt", so that the following indicates an optional expression enclosed in braces.

```
\{expression_{opt}\}
```

3 Lexical Grammar of tinyC

1. Lexical Elements

token:

keyword identifier constant string-literal punctuator

2. Keywords

keyword: one of

a. One or			
auto	enum	$\mathbf{restrict}$	${f unsigned}$
\mathbf{break}	extern	return	\mathbf{void}
case	float	${f short}$	volatile
$_{ m char}$	\mathbf{for}	\mathbf{signed}	while
\mathbf{const}	goto	sizeof	$_{ m Bool}$
continue	if	static	$_{ m extsf{L}}$ Complex
$\mathbf{default}$	inline	\mathbf{struct}	I maginary
do	${f int}$	\mathbf{switch}	
\mathbf{double}	long	$\mathbf{typedef}$	
${f else}$	register	union	

3. Identifiers

identifier:

identifier-nondigit identifier identifier-nondigit identifier digit

```
identifier-nondigit: one of
                                                                                                                                          1
                                   b
                                                                                                                                                   \mathbf{m}
                                                                                               \mathbf{u}
                                   o
                                             \mathbf{p}
                                                       \mathbf{q}
                                                                                                                    \mathbf{w}
                                                                                                                               \mathbf{x}
                                                                                                                                                    {f z}
                                   В
                                             \mathbf{C}
                                                      \mathbf{D}
                                                                 {f E}
                                                                           \mathbf{F}
                                                                                     \mathbf{G}
                                                                                              \mathbf{H}
                                                                                                         Ι
                                                                                                                    J
                                                                                                                              \mathbf{K}
                                                                                                                                                   \mathbf{M}
                        N
                                   O
                                                                {f R}
                                                                                     \mathbf{T}
                                                                                                                                                    {f Z}
digit: one of
                                    \mathbf{2}
                                             3
                        1
                                                      4
                                                              5
                                                                       6
```

4. Constants

integer-constant
floating-constant
enumeration-constant
character-constant
integer-constant:
nonzero-digit
integer-constant digit
nonzero-digit: one of

1 2 3 4 5 6 7 8 9

 $floating\hbox{-}constant:$

 $fractional\text{-}constant\ exponent\text{-}part_{opt}$ $digit\text{-}sequence\ exponent\text{-}part$

 $fractional ext{-}constant:$

 $\textit{digit-sequence}_{opt}$. digit-sequence digit-sequence .

 $exponent ext{-}part:$

e sign_{opt} digit-sequence

 $\mathbf{E} \ sign_{opt} \ digit\text{-}sequence$

sign: one of

+

digit-sequence:

digit

 $digit\text{-}sequence\ digit$

 $enumeration\mbox{-}constant:$

identifier

 $character\hbox{-}constant:$

' c-char-sequence '

c-char-sequence:

c-char

 $c\text{-}char\text{-}sequence\ c\text{-}char$

c-char:

any member of the source character set except

the single-quote $\,$, backslash $\,$, or new-line character

escape-sequence

escape-sequence: one of

5. String literals

 $string ext{-}literal:$

 $"s-char-sequence_{opt}"$

 $s ext{-}char ext{-}sequence:$

s-char

 $s\text{-}char\text{-}sequence\ s\text{-}char$

s-char:

any member of the source character set except

the double-quote $^{\rm II},$ backslash $\backslash,$ or new-line character $escape\mbox{-}sequence$

6. Punctuators

punctuator: one of

```
[ ] ( ) { } . ->
++ -- & * + - ~ !
/ % << >> < > == != ^ | && ||
? : ; ...
= *= /= %= += -= <<= >>= &= ^= |=
, #
```

7. Comments

(a) Multi-line Comment

Except within a character constant, a string literal, or a comment, the characters /* introduce a comment. The contents of such a comment are examined only to identify multibyte characters and to find the characters */ that terminate it. Thus, /* ... */ comments do not nest.

(b) Single-line Comment

Except within a character constant, a string literal, or a comment, the characters // introduce a comment that includes all multibyte characters up to, but not including, the next new-line character. The contents of such a comment are examined only to identify multibyte characters and to find the terminating new-line character.

4 The Assignment

- 1. Write a flex specification for the language of tiny C using the above lexical grammar. Name of your file should be ass3_roll1_roll2.1. The ass3_roll1_roll2.1 should not contain the function main().
- Write your main() (in a separate file ass3_roll1_roll2.c) to test your lexer.
- 3. Prepare a Makefile to compile the specifications and generate the lexer.
- 4. Prepare a test input file **ass3_roll1_roll2_test.c** that will test all the lexical rules that you have coded.
- 5. Prepare a tar-archive with the name <code>ass3_roll1_roll2.tar</code> containing all the above files and upload to Moodle.

5 Credits

1. Flex Specifications: 60

2. Main function and Makefile: **20** [15+5]

3. Test file: **20**