All skip-connections can be expanded indifinetly: An Analysis of Representation Dynamics on Vision Models with Differential Geometry

Jaume Ivars Grimalt [1]

Abstract

The abstract must contain a brief intro of the field you are attacking on, the phenomenon you observed, an explanation and an interpretation. Code is available at https://github.com/jaume2000/dynamics_skip_nn.

1. Introduction

A residual block $x + f(x)$ has the algebraic form of one Euler step of size 1. That observation has been used to read residual networks as discretisations of an ODE, but a trained stack need not be a *smooth* field in depth: Figure 1 shows two ConvNeXt stage-3 transports of the same horizon T=9. Sharing one block yields a single autonomous flow whose speed rises and falls as a bell; independent blocks produce a new field every unit of time, with kinks and speed jumps at every integer. The rest of the paper makes that contrast quantitative—and asks how much of the accuracy of the switched stack is already carried by the shared field.

Skip Connections-NN (SCNN) wanted to solve grad vanishing problem that VGG introduced. By defining $x = f(x) + x$ it induced some properties: Works in the same feature representation. P.e. A given channel will have the same purpose in the next layer.

(Sander et al., 2022; Queiruga et al., 2020) says that resnets just have the algebraic form of Euler ODE solver, that if params are steps they won'r be ODEs. We apport evidence that residual blocks are 1-step ODE solvers and we therefore have a sum of Ode solvers that are constantly changing of domain and we can accomplish the same dynamics by sharing the weights and we augmentate the resolution of the feature dynamics to study with better quality how X moves along the latent-space manifold in time / depth.

Questions we want to solve:

- Can SCNN's blocks be looped indefinitely? → Yes
- Are all this weights necessary? + Shared networks can reach similar performance? → No + Yes
- What are the dynamics of the features in this two types of models? Statement: The over-parametrized networks undo what the previous layer does, that's why SCNNs and weight-tied are equal. Tangential acceleration is crucial for this affirmation. Here we analyze the geometry of trajectories. Take into account the massive activations here.
- How can we improve discrete models given this evidence? -¿ Delta networks?

2. Related Work

3. Method

We study residual vision networks as a three-part map. Stages 1–2 encode the image onto an input manifold; the longest stage transports a point x_0 on that manifold to a point x_T on an output manifold; stage 4 and the prediction head decode x_T into class logits. We focus on that middle transport—stage 3 in ConvNeXt, Swin and ResNet—where most of the residual depth sits. In ConvNeXt-T, stage 3 has n=9 blocks; we take the trained horizon to be T=n=9 and refine discretisations with repetitions R and step Δt=$1/R$ (Section 3.2).

The question is whether this transport requires n independent residual maps, or whether it is (approximately) the integration of one vector field. A natural test is to refine the discretisation and check that it converges, but that test is weaker than it looks. Residual blocks are Lipschitz maps, so refining them at fixed T always converges to a unique continuous limit, whatever the weights: we observe the same first-order convergence for randomly initialised ConvNeXt, ResNet and Swin blocks, and the distance from the native one-step path to that limit is mainly set by how far each block moves the state, with training shifting it in an architecture-dependent direction (Appendix C). Evidence for the ODE reading must therefore come from properties a random network cannot have: that one shared field can replace the nine blocks, that the continuous limit keeps the network's function, and how the trajectory towards x_T is

[1]Mycrospace AI Research, Valencia, Spain. **AUTHORERR: Missing \icmlcorrespondingauthor.**

arXiv preprint.




Figure 1. Stage-3 feature trajectories of a weight-tied ConvNeXt (left) and a standard ConvNeXt-T (right), refined at inference with Δt=0.01 (T=9; massive channel removed). **Top:** PCA of all states, paths coloured by depth t; white dots mark integer t. **Bottom:** residual speed $\|f(x(t))\|$ (class means; shade: spread). One shared block is a single autonomous field $\dot{x} = f(x)$; nine independent blocks switch the field at every integer, $\dot{x} = f_{\lfloor t \rfloor}(x)$. We analyse this contrast throughout the paper.

organised. We organise the section accordingly:

1. Section 3.1 shows that a weight-tied stage 3 nearly matches an untied ConvNeXt-T (80.36% vs. 80.97% top-1), so one shared field already carries most of the accuracy;

2. Section 3.2 loops the residual blocks at inference without fine-tuning, on both weight-tied and standard networks: at fixed T every solver reaches the same limit, which retains almost all the accuracy, whereas breaking T collapses the networks;

3. Section 3.3 compares the geometry of the resulting trajectories, contrasting one block reused throughout the stage (autonomous field) with nine blocks used once each (switched field);

4. Section 3.4 examines how untied blocks redirect and partially undo each other along depth;

5. Section 3.5 asks whether small per-block corrections on top of a shared field can close the remaining gap.

3.1. Do weight-tied stage-3 networks achieve similar results?

We first ask whether the stage-3 transport needs nine independent blocks, or whether one shared block applied nine times is enough. Sun et al. (2025) study a related question in transformers: they replace and loop layers with a middle block to test whether all layers implement the same operation. We observe the same phenomenon in ConvNeXt stage 3—ablations that permute, duplicate or substitute blocks are reported in Appendix D—and go one step further: if the stage can be run with a single repeated function, a network trained to use that shared function should reach a similar accuracy level.

We train a vanilla ConvNeXt-T and a weight-tied stage-3 variant under the same recipe (ImageNet-1k, batch size 1024; configuration in Appendix X). Our baseline reaches 80.97% top-1 (28.59M params), slightly below the original ConvNeXt-T report of 82.1% (Liu et al., 2022)—expected under our hardware constraints—but all comparisons below use models trained by us under matched conditions.

The weight-tied model (18.97M params, 33% fewer) reaches 80.36% top-1 (-0.61 points). Sharing all four stages (8.68M params, 70% fewer) reaches 79.01% (-1.96 points).

A network that implements (approximately) the same residual function at every depth can therefore sit close to the untied baseline. That motivates the next subsection: if stage 3 is approximately the Euler discretisation of one vector field, refining that discretisation at inference—looping with step $\Delta t{=}1/R$ while keeping $T{=}9$—should remain meaningful, without fine-tuning. We test this on both the weight-tied network and standard residual models.

3.2. Indefinite looping without fine-tune

Section 3.1 showed that one shared block nearly matches a standard ConvNeXt stage 3 (independent per-block weights). We now test whether residual blocks behave as one-step Euler updates of a vector field: if so, repeating each update R times with step $\Delta t{=}1/R$—without fine-tuning—should preserve the trained horizon $T{=}n$ and the function the network computes. Convergence of the refinement by itself is not diagnostic, since any residual block with Lipschitz f has a continuous limit (Appendix C); the informative quantities are what the limit retains and how far the native path is from it. We apply this probe to weight-tied and standard networks; the geometry of the resulting trajectories is deferred to Section 3.3.

A residual block computes $x + f(x)$ (He et al., 2016). With step size 1, that is exactly one step of the explicit Euler method for the ODE $\dot{x} = f(x, t)$ (E, 2017; Haber & Ruthotto, 2017; Lu et al., 2018). Write the residual of block i as

$$f_i(x) \;=\; \mathrm{block}_i(x) - x. \tag{1}$$

Then the native network is one Euler step of size 1 per block. Over a stage of n blocks (e.g. $n{=}9$ in ConvNeXt-T stage 3), starting from the output x_0 of the previous stage,

$$x_{i+1} \;=\; x_i + f_i(x_i), \qquad x_n \;=\; x_0 + \sum_{i=0}^{n-1} f_i(x_i). \tag{2}$$

Some argue that this algebraic form is already enough to call the network an Euler solver (E, 2017; Haber & Ruthotto, 2017; Lu et al., 2018), but algebraic form alone is not sufficient evidence: Queiruga et al. (2020) argue that ResNets fail to be meaningful dynamical integrators beyond that syntactic similarity, and Sander et al. (2022) show that a ResNet approaches its associated Neural ODE only when the residual maps vary smoothly in depth (otherwise the discrete stack need not be a consistent discretization of a single continuous flow).

We suggest reading the stage as a *sum of several ODEs*, one per block, where the network is trained to solve each unit interval with a single Euler step. The continuous object behind (2) is therefore

$$x_n \;=\; x_0 + \sum_{i=0}^{n-1} \int_i^{i+1} f_i\big(x(t)\big)\, dt, \tag{3}$$

or, block by block,

$$x_{i+1} \;=\; x_i + \int_i^{i+1} f_i\big(x(t)\big)\, dt. \tag{4}$$

Here the sum is the stack of residual blocks, and each integral is the continuous counterpart of the one-step update in (2): instead of taking one Euler step of size 1, we integrate f_i over the unit interval $[i, i+1]$, keeping the horizon of each block equal to 1. For a stage with n blocks trained at unit step, the stage horizon is therefore

$$T \;=\; n \qquad \text{(ConvNeXt-T stage 3: } n{=}9\text{, so } T{=}9\text{).} \tag{5}$$

Repetitions R. Throughout the paper we use a single refinement parameter R (*repetitions*). For a non-tied stage, $R{=}2$ means each of the n blocks is applied twice, for nR residual updates in total. For a weight-tied stage, $R{=}2$ means the *same* shared block is applied $nR{=}18$ times. In both cases we set the Euler step from the trained horizon,

$$\Delta t \;=\; \frac{1}{R} \qquad \Rightarrow \qquad T \;=\; nR \cdot \Delta t \;=\; n, \tag{6}$$

so refining never changes the integration time—only the resolution.

Plain interpolation keeps the field piecewise constant on each block and discretizes the integral with R Euler substeps of size $\Delta t = 1/R$:

$$\int_i^{i+1} f_i\big(x(t)\big)\, dt \;\approx\; \sum_{r=0}^{R-1} \Delta t\, f_i\big(x_{i+r\Delta t}\big). \tag{7}$$

Equivalently, over the whole stage the refined trajectory is

$$x_T \;=\; x_0 + \sum_{i=0}^{T-1} \sum_{r=0}^{R-1} \Delta t\, f_i\big(x_{i+r\Delta t}\big), \qquad \Delta t = \tfrac{1}{R}. \tag{8}$$

When $R{=}1$, (8) recovers the original network (2). As R grows with $T{=}n$ fixed, the scheme approaches the continuous limit (3); we also compare against Midpoint (RK2) and RK4 on the same horizon.

In a weight-tied stage the residual field is the same at every depth, $f_i \equiv f$ for all i. Then (3) collapses to a single autonomous integral over $[0, T]$ with $T{=}n$:

$$x_T \;=\; x_0 + \int_0^T f\big(x(t)\big)\, dt. \tag{9}$$

Inference uses nR applications of f with $\Delta t{=}1/R$; training uses $R{=}1$ (n steps of size 1), hence $T{=}9$ for our shared ConvNeXt-T.




Figure 2. **Left:** top-1 vs. repetitions R (solid: Euler / RK1; dashed: RK4), with $\Delta t{=}1/R$ so $T{=}n$ is conserved (weight-tied: nR applications of the shared block). **Right:** residual-field norm $\|f(x)\|$ along stage 3 (mean and P5–P95 over 500 images). ConvNeXt is piecewise constant in depth; the weight-tied model is a single smooth autonomous field. See Section 3.2.2.

3.2.1. Ablations

We apply the refinement (8) (plain interpolation, T conserved via $\Delta t{=}1/R$) to our ConvNeXt-T, our weight-tied ConvNeXt-T, Swin-T, ResNet-50 and ResNet-101 (ImageNet-1k validation, top-1). Figure 2 (left) summarises the sweep over R; numbers are in Table 1.

Accuracy decreases monotonically as R grows and plateaus at a continuous limit that matches RK4. Euler (RK1), Midpoint (RK2) and RK4 all converge to the *same* accuracy once the step is fine enough; full Mid/RK4 tables are in Appendix A. (Matched top-1 alone does not prove a shared state x_T; we check endpoint agreement of the solvers later in Appendix B.) The trained network itself (Euler, $R{=}1$) is *not* at that limit; it is the best point of every sweep. Keeping the nine steps of size $\Delta t{=}1$ but swapping Euler for RK4 already lands on the limit, both in accuracy and in the stage-3 state (Appendix B), and costs 0.6–0.9 points on the untied models (0.2 on the weight-tied one): the decoder is tuned to the state produced by a single Euler step of size 1, not to the flow it approximates.

Wrong step size. Repeating blocks without shrinking the step (e.g. $R{=}10$ with $\Delta t{=}1$, so T grows tenfold) collapses every pretrained model to chance ($\approx 0.1\%$–1% top-1). The same holds for the weight-tied network when T leaves the trained horizon (Figures 3 and 4). The Euler step must be $\Delta t{=}1/R$, equivalently $T{=}n$ for an n-block stage ($T{=}9$ when $n{=}9$). The trajectory dynamics behind this collapse are analysed in Section 3.3.5.

Weight-tied fractional $R < 1$. Figure 3 reports the shared network at fixed $T{=}9$ with fewer than nine steps ($R < 1$, i.e. $9R$ applications with $\Delta t{=}1/R > 1$); the numbers, including Midpoint, are in Table 7. Large steps need a higher-order solver: at $R{=}4/9$ (4 steps), RK4 reaches 78.9% while Euler falls to 67.8%; Euler with $R{=}2/9$ ($\Delta t{=}4.5$) is unstable (5.9%). For $R \geq 7/9$, all three solvers sit within 0.3 points of the trained baseline.

Table 1. Plain Euler refinement with $\Delta t{=}1/R$ (T conserved). Top-1 (%). For weight-tied, R means $9R$ applications of the shared block (exact $9R$ when available; else nearest measured depth*). ODE limit: RK4 at the finest step in each sweep.

R (Δt)	CNX-T	Swin-T	R-50	R-101	Tied
1 (1)	80.95	81.08	80.34	81.67	80.34
2 (0.5)	80.79	80.90	80.06	81.58	80.27
4 (0.25)	80.53	80.65	79.84	81.38	80.22*
10 (0.1)	80.36	80.47	79.61	81.22	80.14*
32 (0.03)	80.30	80.38	79.50	81.12	80.14*
128 (0.008)	80.23	80.34	79.45	81.06	80.12*
ODE limit	80.23	80.32	79.43	81.05	80.12
Gap ($R{=}1 \to$ODE)	-0.72	-0.76	-0.91	-0.62	-0.22

*Nearest measured shared depth at $T{=}9$: 32, 96, 128, 1024 steps respectively (exact $9R$ would be 36, 90, 288, 1152).

Horizon, not resolution. Varying the number of unit steps at $\Delta t{=}1$ (so T grows) or varying Δt at fixed $R{=}1$ (9 steps; $T{=}9 \cdot \Delta t$) both peak at $T{=}9$ (Figure 4): the classification head expects the state reached after that integration time. Integrating too short or too long degrades smoothly near $T{=}9$ and collapses far from it. We conclude that the best Euler step is the one that preserves the trained horizon: $\Delta t{=}1/R$ for every model (non-tied and weight-tied).




Figure 3. Shared ConvNeXt-T at fixed T=9 for fractional $R \le 1$ (RK1 solid, RK4 dashed).




Figure 4. Shared ConvNeXt-T: top-1 vs. horizon T. Red: fixed Δt=1, more steps (T grows). Purple: fixed R=1 (9 steps), varying Δt (T=9 · Δt). Both peak at the trained horizon T=9.

Do refined blocks land on the same x? Near-baseline accuracy does *not* mean that R Euler steps of size $1/R$ reproduce the unit-step state. Figure 5 compares the refined ConvNeXt-T trajectory (R=100, Δt=0.01) with the native R=1 trajectory on the same images, in ℓ_2 distance (top, next to both state norms) and cosine similarity (bottom) (massive channel removed from the metrics, see Section 3.3.1; N=500 images). Three facts stand out.

- **Within each block** the refined trajectory moves *toward* the parallel R=1 checkpoint: the distance decays and the cosine rises until the block ends, so the refinement is not drifting away from the one-step endpoint of that block.
- **Across blocks** the gap grows: the block-end distance rises from ≈ 5.6 to ≈ 76 at t=9, against $\|x\| \approx 203$ at the stage exit, i.e. a relative gap $\|x^{(R)} - x_{R=1}\|/\|x\| \approx 0.36$.
- **The gap is a rotation.** The block-end cosine drops from 0.99 to 0.93 ($\sim 21°$), while $\|x\|$ differs by only $\approx 3\%$ (203 vs. 210); a pure rescaling of that size would account for a distance of ≈ 7, not 76.

Each block therefore implements a *different* map than its one-step counterpart once the input has already drifted; local refinement stays contractive toward the current block's R=1 target, but errors accumulate through the switched stack and the final x_T points in a different direction from the native one.

Finetuning stage 4 and the head after unrolling. As a complementary check, we freeze stem and stages 1–3 and finetune only stage 4 and the classification head on the unrolled transport (horizon T=9 conserved). On ConvNeXt-T with R=3 (Δt=1/3) this recovers 80.93% top-1—within 0.04 points of the untied baseline (80.97%).[1] The same protocol at the fine step used in Figure 5 yields XX% top-1 for ConvNeXt-T at R=100 (Δt=0.01) and XX% for the weight-tied model at R=100 (900 shared steps, Δt=0.01) after 10 epochs at learning rate 10^{-6} (`finetune_s4_r100_convnext.sh`, `finetune_s4_d900_shared_convnext.sh`). So even though the refined stage-3 endpoint differs substantially from the native x_T in representation space, a light adaptation of the decoder largely restores accuracy when T is kept: the transport changes; the head can re-read it.

Takeaway. Three facts summarise the looping probe. *(i) Discretisation.* Refining the Euler step at fixed T does *not* reproduce the native one-step state: at R=100, after removing the massive channel, the stage-3 endpoint has relative ℓ_2 gap ≈ 0.36 to the parallel R=1 path (Figure 5) and cosine ≈ 0.93 ($\sim 21°$), so the mismatch is mostly angular rather than a pure rescaling of $\|x\|$. The weight-tied stage does not accumulate this error: its cosine to the R=1 path settles at ≈ 0.98 (relative gap ≈ 0.20) instead of falling block after block (Section 3.3.4). *(ii) Continuous limit.* That gap is *not* solver noise: Euler and RK4 at the same fine step, and Euler R=100 vs. R=200, agree on x_T to relative distance $\ll 10^{-2}$ (Appendix B). A continuous limit of the piecewise residual field therefore exists, but it is not the trained R=1 discretisation. Neither fact is specific to training. A random-initialisation control (Appendix C) shows that the blocks of all five architectures, random or trained, converge to a single $\hat{x}_T$ under refinement. How far the one-step path lies from that limit is governed mainly by how far each

[1] Script: `scripts/finetune_s4_r_convnext.py`. For contrast, R=3 with Δt=1 (broken horizon T=27) collapses to 41% *without* finetuning (`convnext_r3_quick`).




Figure 5. ConvNeXt-T, R=100, Δt=0.01, against the native R=1 path. **Top:** $\|x^{(R)}(t) - x_{R=1}\|$ (solid), with the state norms of both paths for scale (dashed: R=100; squares: R=1). **Bottom:** $\cos(x^{(R)}, x_{R=1})$. Mean and P5–P95 over 500 images; massive channel ignored; dots mark block ends. The norms nearly coincide while the block-end gap grows with depth: the mismatch is mostly in angle.

block moves the state, $\|f_i(x_i)\|/\|x_i\|$: weights trained to be used once produce steps of 30–90% of $\|x\|$ and sit 10–21° from their limit, too far for one Euler step to track the flow. At the same relative step, training moves that distance in an architecture-dependent direction: trained Swin-T and ConvNeXt-T are closer to their limit than a random field (19.5° vs. 47.6°, 21.1° vs. 30.2°), the weight-tied model is level with it (10.9° vs. 11.9°), and the ResNets are farther. What distinguishes the trained networks is therefore not *whether* the refinement converges but *how* the trajectory is built: one shared block applied throughout the stage versus nine different blocks applied once each. Section 3.3 contrasts the two regimes. *(iii) Accuracy.* Top-1 nevertheless barely moves under refinement without training, because the head cares about class margins, not isometry of the full feature space. Finetuning stage 4 and the head recovers 80.93% at R=3 and XX% / XX% for ConvNeXt-T / weight-tied at R=100 —essentially the baseline once the decoder adapts. In short: residual blocks admit a well-defined fine-step flow, as any Lipschitz residual field does; their single unit step is too large to be a consistent solver of that flow; the flow nonetheless retains the network's function (the limit keeps $\approx$ 80% top-1, which a random field cannot show), accuracy survives because the head is tolerant, and a light S4+head adaptation closes almost all of the remaining gap.

Influenced by continuous-in-depth models (Queiruga et al., 2020; Chang et al., 2018), we also tried replacing the piecewise-constant schedule $\theta_t = \theta_{\lfloor t \rfloor}$ by a bilinear blend of consecutive block weights. It performs relatively badly on every architecture (e.g. -6.6 points on ConvNeXt-T at R=128 vs. plain); full numbers and the residual-norm trajectories are in Appendix E.

3.2.2. Piecewise vs. smooth residual fields

Figure 1 showed the two regimes on individual trajectories; Figure 2 (right) makes the same contrast on the residual-field norm over 500 images. In the non-tied ConvNeXt, $\|f_k(x)\|$ is approximately constant inside each block and jumps at integer depths: a *smooth function by parts*, i.e. an autonomous field on each unit interval $[i, i+1]$ with discontinuous switches of θ between blocks (Equation (3)). In the weight-tied model the same shared f is applied for the whole stage, so the residual norm evolves as one continuous curve that rises and then decays (Equation (9)). Markers at R=1 sit on those curves; refining to R=100 fills in the intra-block path without changing its global shape. This is the geometric counterpart of the accuracy tables: refining a switched stack converges to a slightly worse continuous limit, while refining a shared field stays near the trained accuracy as long as T is held fixed. Sections 3.3 and 3.4 analyse these trajectories in more detail—in particular, how untied blocks redirect the state between integer depths even though each intra-block piece remains integrable.

3.3. Geometrical analysis of feature trajectories

In this section we analyze the geometry of the trajectories regarding the weight-tied convnext vs the standard convnext. We also compare the standard convnext with resnet and swin, whose properties are very similar since they are non weight-tied and the network learned to make the blocks perform an unique functionality of one step, so there is no reason for the network to learn a more complex dynamic.

3.3.1. Massive activations excluded from analysis

After analyzing some trajectories on our first aproach, they seemed too homogeneos in convnext and swin cases, so we analyzed the features and founded the so called massive activations (Sun et al., 2024). In convnext shared and non-shared there is one channel that grows indifinetly. We did a similar analysis and concluded the same as (Sun et al., 2024)

3.3.2. Trajectories of weight-tied convnxt vs standard convnext

3.3.3. Trajectory analysis of weight-tied convnext

Inpired by some of the metrics of (Pandey et al., 2026) we perform an analysis of the trajectories ignoring the massive channels of Convnext and the massive tokens of swin. Resnet does not show signs of massive activations.

In weight-tied convnext we can see in Figure 2 (right) and Figure 1 (bottom left) the norm of the velocity, that is $f(x(t))$ that has a shape of a bell curve. This information only shows if the point is moving or not, but it doesn't tell if it rotates or move towards the same direction. That's why we plot several new metrics:

Acceleration

Here we decompose the acceleration vector into the sum of two components: The tangential and normal accelerations with respect to the velocity. Note, that in a high-dimentional space of 300,000 dimensions (the case of Stage 3 in convnext), there are 299.999 dimentions that are normal with the velocity, and only 1 that is tangent. The tangent component can be negative or positive with respect to the velocity that is, it reduces or increases the current velocity in this 1D line, but we cna only analyze the norm of the normal acceleration. Even in a such space, that tangential acceleration has a big representation.

We can see

Angular acceleration Trajectory curvature

The shape of the trajectory

With all this tools, we conclude that the trajectory at the start rotates at high speeds, giving the trajectory a high curvature, but with low velocity norm, that implies that it does small steps changing constantly of direction. The model is computing the direction where it has to accelerate the point to.

After that, the model starts to accelerate towards one direction, angular speed decreases, norm of angular acceleration increases due to the reduction of velocity the result is a major reduction on the curvature of the trajectory, while tangential acceleration hits its maximum. The model is expanding the most important features.

Finally, angular acceleration decreases, tangential acceleration rapidly decreases, becoming negative, the velocity decreases, the angular velocity increases again, and curvature raises again. We have the same scenario as in the first phase. The model is refining features again.

We observe that for the 500 images we analyzed, the trajectory is mostly of this form. But in the variance analysis, the velocity has its maximum variance on the second phase since the model is pushing the features of different classes apart from the origin in different directions.

3.3.4. Refinement error: accumulated vs. bounded

Figure 6 repeats the comparison of Figure 5 for the weight-tied network. Both models start the same way: after the first native step the cosine to the $R{=}1$ path is 0.99. They then diverge. In the standard ConvNeXt-T the block-end cosine keeps falling, to 0.93 at $t{=}9$: each block receives an input that has already drifted and adds its own discretisation error on top. In the weight-tied model it settles at ≈ 0.98 after two or three steps and stays there for the rest of the stage, so a single autonomous field keeps the refinement error bounded instead of accumulating it. The norms also behave differently: in ConvNeXt-T they nearly coincide (203 vs. 210), whereas the weight-tied refined path ends about 7% shorter (427 vs. 458), so part of its smaller gap is radial.

3.3.5. Integrating beyond the trained horizon

There is big difference between weight-tied convnext and standard convnext: First one reaches a velocity plateau where the input just grows indifinetly in the same direction.

In standard convnext, swin and resnet are different, we used R=100 with euler step 1, since the blocks use different parameters and the network was not trained to reuse params, it has a similar dynamics as the R=100 with Euler step of 0.01 but with more magnitude.

3.4. Are over-parametrized networks undoing what the previous layers have done?

Section 3.1 showed that one shared stage-3 block nearly matches nine independent ones (-0.61 top-1 points, 33% fewer parameters). A natural explanation is that the untied stack is over-parametrised along depth: consecutive blocks need not push the state in a coherent direction, and part of what block $k{+}1$ does can cancel what block k just did. We test that claim directly on feature trajectories, using the same 500 ImageNet validation images (one per class) as in Section 3.3, stage 3 only, with the massive channel removed (Section 3.3.1).

Setup. For each image we integrate the stage from $t{=}0$ to $t{=}9$ at native resolution ($R{=}1$) and under Euler refinement ($R{=}100$, $\Delta t{=}0.01$), and reduce every spatial feature coordinate whose net displacement $|\Delta_i| = |x_i(9) - x_i(0)|$ is above the per-image median. We partition the trajectory into the nine unit intervals $[k, k{+}1]$ (native blocks in ConvNeXt-T; the same time bins in the weight-tied model) and write $\mathrm{d}x_k$ for the displacement of a coordinate over interval k.




Figure 6. Refined vs. native (R=1) stage-3 path for the standard (left) and weight-tied (right) ConvNeXt-T. **Top:** $\|x^{(R)} - x_{R=1}\|$ (solid) with both state norms for scale (dashed: refined; squares: native). **Bottom:** $\cos(x^{(R)}, x_{R=1})$. Mean and P5–P95 over the same 500 images; massive channel ignored; dots mark the end of each native step. The switched stack accumulates angle at every block; the shared field saturates.

The scalars we report are means $\pm$ std over the 500 images (Table 2):

- *straightness*: $\|\sum_k \mathrm{d}x_k\| \,/\, \sum_k \|\mathrm{d}x_k\|$ in feature space (path length vs. net displacement);
- *wasted motion*: $1 - \sum_i |\mathrm{net}_i| / \sum_{k,i} |\mathrm{d}x_{k,i}|$, the fraction of per-coordinate travel that cancels before t=9;
- $\cos(\mathrm{d}x_k, \mathrm{d}x_{k+1})$: mean cosine between consecutive block displacements;
- *undo fraction*: when $\mathrm{sign}(\mathrm{d}x_k)$ flips at the next block, the cancelled mass $\min(|\mathrm{d}x_k|, |\mathrm{d}x_{k+1}|)$ normalised by $\sum |\mathrm{d}x_k|$;
- *zig-zag share*: mass-weighted share of coordinates that reverse at least twice across the nine blocks;
- *sign flips at* $t \in \mathbb{N}$: fraction of consecutive steps whose sign changes exactly at integer depths (block boundaries).

Results. Table 2 and Figure 7 give a consistent picture. Under refinement (R=100), the weight-tied model is nearly monotone along depth: straightness 0.78, wasted motion 0.19, consecutive-block cosine 0.92, undo fraction 0.02, and zig-zag share 0.14. Sign changes at integer times are essentially absent (0.00). ConvNeXt-T, with nine independent blocks, sits at the opposite extreme: straightness 0.50, wasted motion 0.48 (almost half of the travel cancels), cosine 0.17, undo fraction 0.25 ($\approx 12\times$ the shared value), and zig-zag share 0.90. Nearly half of the sign flips (0.45) fall exactly on block boundaries—the discontinuities of the switched field in Section 3.2.2, not an artefact of a coarse step. Native resolution (R=1) barely changes the ConvNeXt-T numbers; refining only makes the shared field look cleaner (undo 0.05 $\rightarrow$ 0.02), which matches the bounded refinement error of Section 3.3.4.

Reading. Untied stage 3 does not implement nine steps of one transport: consecutive blocks often point in weakly related or opposing directions and cancel a large fraction of each other's work. The weight-tied network cannot cancel itself in that way—a single autonomous field has no "next block" with different weights—and the geometry shows almost no undoing. That is why sharing the nine blocks costs less than one top-1 point (Section 3.1): much of the untied capacity along depth is spent rewriting features rather

Table 2. Pooled stage-3 trajectory statistics over 500 ImageNet images (massive channel ignored; coordinates with $|\Delta_i|$ above the per-image median). Weight-tied vs. standard ConvNeXt-T at native (R=1) and refined (R=100) resolution. Mean ± std across images.

Model	R	straightness	wasted motion	monotone share	$\cos(\Delta x_k, \Delta x_{k+1})$	reversal rate	undo fraction	zig-zag share	sign flips at $t \in \mathbb{N}$	median t_{50}
Weight-tied ConvNeXt	100	0.78±0.02	0.19±0.01	0.73±0.02	0.92±0.01	0.11±0.01	0.02±0.00	0.14±0.02	0.00±0.00	4.09±0.16
ConvNeXt-T	100	0.50±0.01	0.48±0.01	0.21±0.01	0.17±0.01	0.45±0.00	0.25±0.00	0.90±0.00	0.45±0.00	7.21±0.15
Weight-tied ConvNeXt	1	0.72±0.02	0.25±0.02	0.63±0.03	0.77±0.03	0.18±0.01	0.05±0.01	0.34±0.03	0.18±0.01	5.00±0.09
ConvNeXt-T	1	0.50±0.01	0.48±0.01	0.22±0.01	0.16±0.01	0.45±0.00	0.25±0.00	0.90±0.00	0.45±0.00	7.82±0.38




Figure 7. Stage-3 coordinates pooled over 500 images (R=100; massive channel removed; $|\Delta_i|$ above the per-image median). **Top:** weight-tied ConvNeXt; **bottom:** ConvNeXt-T. **Left:** progress $p_i(t) = (x_i(t) - x_i(0))/\Delta_i$ (median and P5–P95; thin lines: random coordinates). **Middle:** velocity toward the final value, coordinates sorted by peak time (red: toward the end state; blue: away). **Right:** phase density $(p_i,\ h_i/\Delta_i)$. The shared field advances mostly monotonically; the switched stack reverses and rewrites features between blocks.

than accumulating a coherent displacement toward x_T. The residual accuracy gap to the baseline is then more plausibly attributed to the small, non-cancellable specialization that independent θ_k still provide, not to a fundamentally different dynamical mechanism.

3.5. Shared field with per-block deltas

4. Results

5. Conclusion

References

Ainsworth, S. K., Hayase, J., and Srinivasa, S. Git re-basin: Merging models modulo permutation symmetries. In *International Conference on Learning Representations (ICLR)*, 2023.

Chang, B., Meng, L., Haber, E., Tung, F., and Begert, D. Multi-level residual networks from dynamical systems view. In *International Conference on Learning Representations (ICLR)*, 2018.

E, W. A proposal on machine learning via dynamical systems. *Communications in Mathematics and Statistics*, 5 (1):1–11, 2017.

Entezari, R., Sedghi, H., Saukh, O., and Neyshabur, B. The role of permutation invariance in linear mode connectivity of neural networks. In *International Conference on Learning Representations (ICLR)*, 2022.

Glorot, X. and Bengio, Y. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics (AISTATS)*, pp. 249–256, 2010.

Haber, E. and Ruthotto, L. Stable architectures for deep neural networks. *Inverse Problems*, 34(1):014004, 2017.

Hairer, E., Nørsett, S. P., and Wanner, G. *Solving Ordinary Differential Equations I: Nonstiff Problems*, volume 8 of *Springer Series in Computational Mathematics*. Springer, 2 edition, 1993.

He, K., Zhang, X., Ren, S., and Sun, J. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016.

Liu, Z., Mao, H., Wu, C.-Y., Feichtenhofer, C., Darrell, T., and Xie, S. A ConvNet for the 2020s. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.

Lu, Y., Zhong, A., Li, Q., and Dong, B. Beyond finite layer neural networks: Bridging deep architectures and numerical differential equations. In *International Conference on Machine Learning (ICML)*, 2018.

Pandey, V., Singh, G., and Mahdid, Y. Trajectory geometry of transformer representations across layers, 2026. URL https://arxiv.org/abs/2606.09287.

Queiruga, A. F., Erichson, N. B., Taylor, D., and Mahoney, M. W. Continuous-in-depth neural networks, 2020. URL https://arxiv.org/abs/2008.02389.

Sander, M. E., Ablin, P., and Peyré, G. Do residual neural networks discretize neural ordinary differential equations? In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 35, 2022.

Sun, M., Chen, X., Kolter, J. Z., and Liu, Z. Massive activations in large language models, 2024. URL https://arxiv.org/abs/2402.17762.

Sun, Q., Pickett, M., Nain, A. K., and Jones, L. Transformer layers as painters. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 25219–25227, 2025.

A. Full Midpoint and RK4 refinement tables

We use the same R (repetitions) as in the main text: $\Delta t{=}1/R$ so that $T{=}n$ is conserved ($n{=}9$ for ConvNeXt stage 3). Tables 3–6 report plain interpolation for Euler (RK1), Midpoint (RK2) and RK4 on each pretrained model. Table 7 gives the same solvers for the weight-tied ConvNeXt-T at fixed horizon $T{=}9$ ($9R$ applications of the shared block). In every case the three integrators converge to the same continuous limit once the step is fine enough; at $R{=}1$, Mid and RK4 already sit on that limit.

B. Solver agreement at the stage-3 endpoint

Section 3.2 asks whether a fine Euler step recovers the native $R{=}1$ state. A related question is whether two fine discretisations of the *same* residual field agree with each other—i.e. whether a continuous limit exists at all. Table 8 compares stage-3 endpoints x_T on the same $N{=}32$ ImageNet validation images (one per random class, seed 0), after zeroing the massive channel used in the main-text metrics. Relative distance is $\|x_a - x_b\|/\|x_b\|$; cosine is $\cos(x_a, x_b)$.

Euler and RK4 (and Euler $R{=}100$ vs. $R{=}200$) collapse onto the same x_T, while both remain far from the trained one-step path. RK4 reaches that limit already with the nine unit steps of the native schedule; the native Euler path does not. Midpoint at $R{=}1$ matches the limit in top-1 (80.23%, Table 3) while its state is still 12% away, a reminder that accuracy is a coarse probe of x_T.

C. Random-initialisation control for the continuous limit

Appendix B shows that the trained stage 3 has a continuous limit. That alone is weak evidence. Every residual field we study is a composition of Lipschitz maps (convolutions, linear layers, normalisation, GELU/ReLU, softmax attention), so the ODE $\dot{x} = f_i(x)$ has a unique solution on $[0, T]$ and Euler converges to it at first order, whatever the weights (Hairer et al., 1993). We check this empirically on all five architectures and use random fields of controlled strength as a reference scale for the trained ones.

Setup. Every convolution and linear layer is drawn with Xavier-normal initialisation (Glorot & Bengio, 2010) (gain 1, zero bias, seed 0); normalisation layers keep their default parameters, and ConvNeXt LayerScale is set to $\gamma{=}1$ (its default 10^{-6} makes $f \approx 0$). The stage-3 blocks are then re-drawn with Xavier gain $g \in \{0.25, 0.5, 1, 2, 4, 8\}$, so the stage-3 input is identical across gains and only the field strength changes. For ResNet the field is $f_i(x) = \mathrm{block}_i(x) - x$, which includes the ReLU applied after the addition; for Swin one block contains both residual sublayers (attention and MLP), as in the main text. For each

Table 3. ConvNeXt-T, plain, top-1 (%).

R	Euler	Mid	RK4
1	80.95	80.23	80.23
2	80.79	80.23	80.23
4	80.53	80.23	80.23
10	80.36	80.23	80.23
32	80.30	80.23	80.23
128	80.23	80.22	80.23

Table 4. Swin-T, plain, top-1 (%).

R	Euler	Mid	RK4
1	81.08	80.29	80.33
2	80.90	80.34	80.31
4	80.65	80.33	80.32
10	80.47	80.32	80.31
32	80.38	80.32	80.32
128	80.34	80.31	80.32

Table 5. ResNet-50, plain, top-1 (%).

R	Euler	Mid	RK4
1	80.34	78.94	79.42
2	80.06	79.41	79.43
4	79.84	79.44	79.43
10	79.61	79.44	79.43
32	79.50	79.43	79.44
128	79.45	79.43	79.43

Table 6. ResNet-101, plain, top-1 (%).

R	Euler	Mid	RK4
1	81.67	80.95	81.06
2	81.58	81.07	81.04
4	81.38	81.06	81.05
10	81.22	81.05	81.05
32	81.12	81.05	81.04
128	81.06	81.04	81.05

network we integrate stage 3 to $T{=}n$ and compare the endpoint x_T of Euler at $R \in \{1, 10, 100, 1000\}$ and of RK4 at $R{=}1$ against RK4 at $R{=}100$, on the $N{=}32$ images of Appendix B. The field strength is summarised by the mean relative step of the native path,

$$\rho \;=\; \frac{1}{n}\sum_{i=0}^{n-1}\frac{\|f_i(x_i)\|}{\|x_i\|}, \qquad x_{i+1} = x_i + f_i(x_i), \quad (10)$$

i.e. how far a single block moves the state relative to its size. Because ρ grows with g at a different rate in each architecture (about g^3 for ResNet, whose bottleneck has three unnormalised convolutions), we compare trained and random networks at matched ρ: for each architecture we add one gain $g^\star$ chosen so that ρ matches the trained network. Trained ConvNeXt rows zero the massive channel (Section 3.3.1); ResNet and Swin have no channel of comparable dominance at stage 3 (zeroing the largest one changes every entry by less than $0.6°$), so all rows except those use all channels.

Results. Table 9 supports two observations.

(i) The limit exists for every architecture. For every row, trained or random, the Euler error falls by roughly $10\times$ per decade of R, the first-order rate (trained Swin-T is slower between $R{=}10$ and $R{=}100$), and Euler at $R{=}1000$ is within $0.1°$ of the reference. The same holds at the larger gains not shown, with two numerical exceptions that confirm the mechanism rather than contradict it. ResNet at $g \geq 4$ overflows in float32: without a normalisation inside the block, $\|f_i(x)\|$ grows with $\|x\|$, so the state grows exponentially ($\rho \approx 18$ per block at $g{=}4$). Swin at $g{=}8$ is still $15.7°$ away at $R{=}1000$: the attention logits are so large that the softmax is nearly a hard selection, the field becomes very stiff, and a finer step is needed. Convergence of the refinement to a single $\hat{x}_T$ is therefore a property of the residual parameterisation, not something learned.

(ii) The native gap is of the order set by ρ, and training moves it in an architecture-dependent direction. Within each architecture the distance from the single-step path ($R{=}1$) to the limit grows monotonically with ρ, and with $\rho \approx 0.3$–0.9 every trained network lies 10–$21°$ away: one Euler step of size 1 is far from tracking the flow. At matched ρ, however, the trained and random networks differ, and not in a consistent direction. Trained Swin-T and ConvNeXt-T are *closer* to their limit than a random field of the same strength ($19.5°$ vs. $47.6°$ and $21.1°$ vs. $30.2°$), the weight-tied model is level with it ($10.9°$ vs. $11.9°$), and both ResNets are *farther* ($17.0°$ vs. $12.0°$ and $15.3°$ vs. $8.9°$). RK4 at $\Delta t{=}1$ follows the same split. Training thus changes how well a single step approximates the flow, but there is no universal tendency for single-use blocks to be better (or worse) one-step solvers than random ones. Script: `scripts/random_init_convergence.py`.

D. Block permutation, duplication and substitution

E. Bilinear weight interpolation

Continuous-in-depth work often assumes a smooth path in weight space between consecutive blocks (Queiruga et al.,

Table 7. Shared ConvNeXt-T, fixed $T{=}9$ ($\Delta t{=}1/R$; $9R$ shared steps), top-1 (%).

R	Steps	Δt	Euler	Mid	RK4
$1/9$	1	9	47.06	0.61	2.70
$2/9$	2	4.5	5.85	10.42	47.98
$3/9$	3	3	37.45	54.47	71.37
$4/9$	4	2.25	67.83	73.57	78.90
$5/9$	5	1.8	77.23	78.70	79.97
$6/9$	6	1.5	79.48	79.85	80.10
$7/9$	7	1.29	80.19	80.12	80.11
$8/9$	8	1.13	80.38	80.21	80.11
1	9	1	80.34	80.19	80.11
$4/3$	12	0.75	80.35	80.14	80.12
2	18	0.5	80.27	80.12	80.12
$32/9$	32	0.28	80.22	80.11	80.12
$128/9$	128	0.07	80.14	80.12	80.12
$1024/9$	1024	0.009	80.12	80.12	80.12
$10000/9$	10000	0.0009	80.12	—	—

Table 8. Pairwise stage-3 endpoint agreement (mean over $N{=}32$; ignore top-1 channel). Horizon $T{=}9$ in every row.

Pair (a vs. b)	rel. ℓ_2	cos	angle
ConvNeXt-T			
Euler $R{=}100$ vs. RK4 $R{=}100$	0.004	1.000	0.25°
Euler $R{=}100$ vs. Euler $R{=}200$	0.002	1.000	0.12°
Euler $R{=}100$ vs. Euler $R{=}1$	0.36	0.93	21°
Mid $R{=}1$ vs. Euler $R{=}100$	0.12	0.993	6.6°
RK4 $R{=}1$ vs. Euler $R{=}100$	0.010	0.9999	0.5°
Weight-tied ConvNeXt-T ($9R$ shared steps)			
Euler $R{=}100$ vs. RK4 $R{=}100$	0.002	1.000	0.1°
Euler $R{=}100$ vs. Euler $R{=}200$	0.001	1.000	0.05°
Euler $R{=}100$ vs. Euler $R{=}1$	0.20	0.98	11°
RK4 $R{=}1$ vs. RK4 $R{=}100$	0.003	1.000	0.16°

2020; Chang et al., 2018),

$$\theta(t) \;=\; (1-\alpha)\,\theta_i + \alpha\,\theta_{i+1}, \qquad \alpha = t - i. \tag{11}$$

Replacing the plain schedule $\theta_t = \theta_{\lfloor t \rfloor}$ by (11) hurts every model we tested: at $R{=}128$ the drop vs. plain is between 6.6 and 23.3 points (Table 10). Consecutive blocks are not neuron-aligned, so the midpoint of their weights is not a functional intermediate (Entezari et al., 2022; Ainsworth et al., 2023).

Figure 8 shows the ConvNeXt residual-field norm under plain vs. bilinear schedules at $R{=}100$. Plain keeps the piecewise-constant staircase of Figure 2 (right); bilinear adds high-frequency oscillation between block boundaries while preserving the same global growth of $\|f\|$. Bands are P5–P95 across 500 validation images (same suite as Figure 2).

Table 9. Angle between x_T and the RK4 $R{=}100$ reference ($T{=}n$, mean over $N{=}32$). g: Xavier gain of the stage-3 blocks; ρ: mean relative step (10); *: gain matched to the trained ρ. Rows sorted by ρ.

Init	ρ	Euler			RK4
		$R{=}1$	$R{=}10$	$R{=}100$	$R{=}1$
ConvNeXt-T (nine blocks)					
$g{=}0.5$	0.13	1.5°	0.15°	0.02°	0.00°
$g{=}1$	0.41	15.8°	1.6°	0.16°	0.07°
Trained	**0.54**	**21.1°**	**2.4°**	**0.25°**	**0.53°**
$g^\star{=}1.35$	0.56	30.2°	3.4°	0.34°	0.92°
$g{=}2$	0.77	47.0°	6.7°	0.69°	8.4°
Weight-tied ConvNeXt-T (one block)					
$g{=}0.5$	0.12	2.7°	0.27°	0.03°	0.00°
$g^\star{=}1$	0.30	11.9°	1.3°	0.13°	0.05°
Trained	**0.31**	**10.9°**	**1.0°**	**0.10°**	**0.16°**
$g{=}2$	0.63	27.1°	4.3°	0.46°	5.9°
ResNet-50 ($n{=}5$)					
$g{=}0.5$	0.04	0.4°	0.03°	0.00°	0.01°
$g{=}1$	0.34	7.0°	0.66°	0.07°	0.24°
$g^\star{=}1.15$	0.51	12.0°	1.2°	0.12°	0.48°
Trained	**0.52**	**17.0°**	**1.4°**	**0.15°**	**0.65°**
$g{=}2$	2.29	40.6°	7.8°	0.83°	6.6°
ResNet-101 ($n{=}22$)					
$g{=}0.5$	0.05	0.7°	0.05°	0.01°	0.02°
Trained	**0.30**	**15.3°**	**1.4°**	**0.15°**	**0.74°**
$g^\star{=}0.95$	0.30	8.9°	0.83°	0.08°	0.29°
$g{=}1$	0.35	10.3°	0.97°	0.10°	0.36°
$g{=}2$	2.33	39.6°	5.9°	0.63°	6.4°
Swin-T ($n{=}6$)					
$g{=}0.5$	0.15	1.7°	0.17°	0.02°	0.00°
$g{=}1$	0.48	17.2°	1.8°	0.18°	0.10°
Trained	**0.87**	**19.5°**	**4.3°**	**1.02°**	**2.7°**
$g^\star{=}1.8$	0.89	47.6°	7.1°	0.74°	6.6°
$g{=}2$	0.98	52.7°	8.7°	0.91°	10.5°

Table 10. Bilinear weight interpolation, Euler, top-1 (%).

R	CNX-T	CNX-T†	Swin-T	R-50	R-101
1	80.96	79.27	81.08	80.34	81.67
2	78.94	72.43	78.93	74.95	72.55
4	76.16	63.13	75.42	70.60	62.42
10	74.42	58.75	73.28	68.58	58.73
128	73.66	57.44	72.14	67.77	57.73
Δ vs plain @128	-6.6	-19.6	-8.2	-11.7	-23.3

†ConvNeXt-T trained without drop path.




Figure 8. ConvNeXt-T residual norm along stage 3 at R=100: plain vs. bilinear weight interpolation (mean and P5–P95 over 500 images).