

Write a program to implement BFS Using JAVA

Lab Assignment-9

CSE3002: Artificial Intelligence

Submitted by:

Jayakumar MHK (18BCE7031)


Under the Guidance of
Prof. Manomita Chakraborty
SCOPE
VIT-AP

Task:

Write a program to implement BFS (Breadth-first search)

Solution:

I have used OOPs, ArrayList, and Queue data structure to implement BFS using Java



This is the graph used as a testcase for BFS.

Below is the source code of the same.

```
import java.util.*;
import java.util.LinkedList;
class lab9{
static class Edge{
  int src;
  int nbr;
  public Edge(int s,int d){
    src=s;
    nbr=d;
  }
}

public static void main(String [] args){
    Scanner sc=new Scanner(System.in);
    System.out.println("Enter number of vertices");
    int v=sc.nextInt();
    ArrayList<Edge>[] graph=new ArrayList[v];
    for(int i=0;i<v;i++){
        graph[i]=new ArrayList<>();
    }
    System.out.println("Enter number of edges");
```

```
int e=sc.nextInt();
        System.out.println("Enter Each edge ");
            System.out.print("Edge "+(i+1)+" : ");
            int s=sc.nextInt()-1;
           int d=sc.nextInt()-1;
            graph[s].add(new Edge(s,d));
           graph[d].add(new Edge(d,s));
       boolean []vis=new boolean[v];
       System.out.println("Enter source and goal vertex");
       int src=sc.nextInt()-1;
       int goal=sc.nextInt()-1;
        DFS(src,goal,graph,vis);
       int src;
       public Bpair(int s,int i) {
            ins=i;
       public int compareTo(Bpair o){
           return this.ins-o.ins;
   public static void DFS(int src,int goal,ArrayList<Edge> []
graph,boolean [] vis){
        Queue<Integer> qu=new LinkedList<>();
       String asf="";
       qu.add(src);
       while(qu.size()>0){
            int node=qu.remove();
            if(vis[node] == true) {
            vis[node]=true;
            if(node==goal){
```

Output below:

