

ngspice-46 vs. Spectre — Feature Gap Analysis

Ngspice + OpenVAF Enhancements project

July 2026

Contents

ngspice-46 vs. a commercial simulator (Spectre) — feature gap analysis

1

ngspice-46 vs. a commercial simulator (Spectre) — feature gap analysis

A capability comparison of the ngspice-46 build in this repository against a Spectre-class commercial simulator, to show where the open-source tool already matches the commercial one and where the gaps are. Grounded in a direct read of the ngspice-46/src/ tree (analyses, solver, devices, RF, convergence, parallelism), not marketing feature lists.

Legend: ✓ present / on par · ⚠ partial, experimental, or via a workaround · ✗ absent. "Spectre" stands in for the commercial reference (Spectre / SpectreRF / Spectre X / RelXpert feature set).

The one column that matters is ngspice — Spectre has essentially everything, so its column is a baseline of ✓. The point of the table is where ngspice's mark is ⚠ or ✗.

Context: the Verilog-A / OSDI device side is not a gap — thanks to the OpenVAF-reloaded compiler in this repository it is on par with (often ahead of) commercial Verilog-A support. The gaps below are all on the simulator/analysis side.

Core numerics

Category	Feature	ngspice	Spectre
Core solver	Sparse LU (KLU) direct solver	✓ ¹	✓
Core solver	Legacy Sparse1.3 fallback	✓	✓
Core solver	Parallel / partitioned / GPU linear solve	✗	✓
Core solver	Matrix reordering + scaling beyond KLU defaults	⚠	✓
Integration	Trapezoidal + variable-order Gear	✓	✓
Integration	Advanced LTE-based step/order control	⚠	✓
Convergence	gmin stepping + source stepping homotopy	✓	✓
Convergence	Pseudo-transient / dynamic-gmin continuation	⚠	✓
Convergence	Damped / trust-region (globalized) Newton	⚠	✓
Convergence	Coordinated accuracy presets (errpreset)	✓	✓

The two convergence ⚠ rows: ngspice's DC path is not naked — it has per-device junction limiting (30 device families), an optional `nodedamping` step clamp, and a multi-stage homotopy cascade (`dynamic_gmin` → `new_gmin` → `spice3_gmin` → source stepping). What it lacks vs. commercial tools is a principled globalized Newton (residual-based trust-region / Armijo) and a classic pseudo-transient ($\dot{X}$ -embedded) continuation. [Enhancement-111](#) adds the former: `.option linesearch`, an Armijo backtracking line search on a new KCL-residual merit $\|F\|=\|G\cdot x-b\|$ (result-neutral, off by default) — see the [implementation write-up](#). [Enhancement-112](#) then extended it to the KLU solver — it originally ran only under Sparse 1.3 and segfaulted under `.option klu` — so the line search now works under both linear solvers, with a residual-merit sequence numerically identical between them.

¹ KLU is compiled in (SuiteSparse, statically linked) but is not the default in this build — the default direct solver is Sparse 1.3; KLU is selected with `.option klu`. The two agree on DC / AC / transient, and — since [Enhancement-113](#) — on noise and single-ended pole-zero as well (the KLU adjoint solve was doing a non-transposed solve, silently wrong

on asymmetric matrices; now fixed), and — since [Enhancement-114](#) — on DC/AC sensitivity (`.sens`), and — since [Enhancement-115](#) — on distortion (`.disto`) too. The only analysis still Sparse-only under KLU is balanced-output pole-zero; KLU is also less robust on stiff transient edges. Full behavior, defaults, and a solver-by-solver sweep of the example suite: [KLU vs. Sparse 1.3 solver notes](#).

Standard analyses (analog)

Category	Feature	ngspice	Spectre
Analyses	DC operating point / DC sweep	✓	✓
Analyses	Transient (<code>.tran</code>)	✓	✓
Analyses	AC small-signal (<code>.ac</code>)	✓	✓
Analyses	Noise, small-signal (<code>.noise</code> , <code>onoise/inoise</code> + integrated)	✓	✓
Analyses	Pole-zero (<code>.pz</code>)	✓	✓
Analyses	Transfer function (<code>.tf</code>)	✓	✓
Analyses	DC sensitivity (<code>.sens</code>)	✓	✓
Analyses	Distortion (<code>.disto</code>)	✓	✓
Analyses	Measurement / post-processing (<code>.meas</code>)	✓	✓

RF / periodic steady-state suite

Category	Feature	ngspice	Spectre
RF	S-parameter analysis + noise figure (<code>.sp</code>)	✓	✓
RF	Touchstone (<code>.sNp</code>) import / export	✓	✓
RF	Periodic steady state (PSS)	✓ ¹	✓
RF	Harmonic Balance (HB)	✗	✓
RF	Periodic / phase noise (Pnoise)	✗	✓
RF	Periodic AC (PAC, conversion gain)	⚠ ²	✓
RF	Periodic transfer function (PXF)	✗	✓
RF	Periodic S-parameters (PSP)	✗	✓
RF	Quasi-periodic / multi-tone (QPSS / QPAC)	✗	✓
RF	Envelope following	✗	✓

¹ PSS was ⚠(experimental `--enable-pss` flag, so `.pss` was unimplemented in shipped builds, and ~230 lines of shooting-loop trace per run). Since [Enhancement-117](#) it is built by default, quiet (trace behind `set ngdebug`), and verified against the analytic AC response; [Enhancement-118](#) then made it run under both linear solvers (KLU had hung on a timestep explosion from reused refactor pivots — now a full re-factor is forced each PSS step under KLU). It is still a brute-force shooting method and remains the foundation for the periodic small-signal analyses below. HB exists only as a `WITH_HB` stub that returns “unsupported”.

² PAC is ⚠(working command, first cut). The full periodic small-signal chain is now built and verified: [Enhancement-119](#) retains the periodic operating point, [Enhancement-120](#) extracts the periodic Jacobian harmonics G_k , C_k , [Enhancement-121](#) assembles and solves the $(2M+1)N$ harmonic conversion matrix $H_{\{nm\}} = G_{\{n-m\}} + j\omega_m \cdot C_{\{n-m\}}$, and [Enhancement-122](#) wraps it in a user-facing `.pac` command that runs PSS then sweeps the input frequency and writes the 0-th-sideband node responses as a complex plot (`print/plot/wrdata`). It is verified on the linear RC: the swept sideband-0 response reproduces the AC driving-point impedance across the whole band to $1.6e-7$. It stays ⚠ rather than ✓ because the first cut injects a unit current at the osc node (rather than a netlist-referenced small-signal source) and outputs only sideband 0 (rather than every conversion-gain sideband $f_{in} + k \cdot f_0$) — both reuse the same solve, as do `pnoise` and `PXF`.

Performance & scale

Category	Feature	ngspice	Spectre
Performance	Multithreaded device-model evaluation (OpenMP)	✓	✓
Performance	Element bypass / latency exploitation	⚠	✓
Performance	Fast-SPICE hierarchical / isomorphic engine	✗	✓

Category	Feature	ngspice	Spectre
Performance	Distributed (MPI) / cloud partitioning	×	✓
Performance	Handles 10^6 – 10^8 -node post-layout netlists	×	✓

Statistical / variability / yield

Category	Feature	ngspice	Spectre
Statistical	Monte Carlo	⚠	✓
Statistical	Native process/mismatch modeling + correlations	⚠	✓
Statistical	Low-discrepancy sampling (Sobol / Latin-hypercube)	×	✓
Statistical	High-sigma methods (importance sampling, worst-case distance)	×	✓
Statistical	Corner + MC + yield estimation flow	⚠	✓

Monte Carlo is ⚠ works, but script-driven (`alter + sgauss`, with the deterministic-seed RNG from Enhancement-10/66) rather than a native statistical block with sampling controls.

Reliability / aging

Category	Feature	ngspice	Spectre
Reliability	Device aging (HCI / NBTI / TDDB)	×	✓
Reliability	Stress → degrade → re-simulate (fresh/aged) flow	×	✓
Reliability	Electromigration + IR-drop (EMIR)	×	✓

Post-layout / parasitics

Category	Feature	ngspice	Spectre
Post-layout	Flat parasitic (RC) netlist simulation	✓	✓
Post-layout	RC reduction / model-order reduction	×	✓
Post-layout	n-port (S/Y/Z) extracted-block import	✓	✓

Behavioral / mixed-signal / AMS

Category	Feature	ngspice	Spectre
Modeling	Verilog-A (analog, LRM Annex C) via OSDI	✓	✓
Modeling	XSPICE code models + event-driven digital	✓	✓
Modeling	Verilog-AMS mixed-signal (connect modules)	×	✓
Modeling	Real-number modeling (wreal / RNM)	×	✓
Modeling	VHDL-AMS	×	✓

Interfaces & infrastructure

Category	Feature	ngspice	Spectre
Interface	Shared-library / programmatic API	✓	✓
Interface	Python bindings	✓	✓
Infrastructure	Built-in optimizer	×	✓
Infrastructure	Checkpoint / restart of long runs	⚠	✓

Where to invest (given the Verilog-A/OSDI side is done)

The realistic, winnable identity for this project is the open-source, OSDI/Verilog-A-native simulator with a real RF-noise and statistical story — not out-engineering 25 years of commercial fast-SPICE/parallel work. Ranked by leverage on the existing strength $\times$ differentiation $\times$ tractability:

1. RF periodic small-signal suite — PAC $\rightarrow$ Pnoise $\rightarrow$ PXF, on the hardened PSS. The PSS foundation is now shipped and verified under both linear solvers ([Enhancement-117](#), [Enhancement-118](#)), and [Enhancement-119](#) retains the periodic operating point (voltages + device states per sample) and [Enhancement-120](#) turns it into the periodic Jacobian harmonics G_k , C_k , and [Enhancement-121](#) assembles those into the $(2M+1)N$ harmonic conversion matrix and solves it, and [Enhancement-122](#) wraps that in a working `.pac` command (runs PSS, sweeps `f_in`, writes the sideband-0 node responses as a complex plot) — verified against the exact linear driving-point response to $1.6e-7$. The device/OSDI side already supplies the rest (noise-source topology, operating-point- and frequency-dependent `load_noise`); the remaining work is a source-referenced stimulus and multi-sideband conversion-gain output on `.pac`, then reusing the same solve for pnoise/PXF. Genuinely novel in open source.
2. Convergence robustness — coordinated accuracy presets (`errpreset`) landed in [Enhancement-110](#); the remaining piece is pseudo-transient / dynamic-gmin homotopy. Unglamorous but makes every analysis usable on real circuits; self-contained in the `ngspice` core.
3. High-sigma statistical sampling — high industrial value (yield / SRAM), moderate difficulty, leans on the deterministic-seed RNG already in place.

Explicitly lower priority: fast-SPICE parallelism and aging/EMIR — enormous efforts that don't leverage what makes this project distinctive.