

Producer-Consumer solution using threads in Java

In computing, the producer–consumer problem (also known as the bounded-buffer problem) is a classic example of a multi-process synchronization problem. The problem describes two processes, the producer and the consumer, which share a common, fixed-size buffer used as a queue.

- The producer's job is to generate data, put it into the buffer, and start again.
- At the same time, the consumer is consuming the data (i.e. removing it from the buffer), one piece at a time.

Problem

To make sure that the producer won't try to add data into the buffer if it's full and that the consumer won't try to remove data from an empty buffer.

Solution

The producer is to either go to sleep or discard data if the buffer is full. The next time the consumer removes an item from the buffer, it notifies the producer, who starts to fill the buffer again. In the same way, the consumer can go to sleep if it finds the buffer to be empty. The next time the producer puts data into the buffer, it wakes up the sleeping consumer.

An inadequate solution could result in a deadlock where both processes are waiting to be awakened.

Recommended Reading- Multithreading in JAVA, Synchronized in JAVA, Inter-thread Communication

Implementation of Producer Consumer Class

- A LinkedList list to store list of jobs in queue.
- A Variable Capacity to check for if the list is full or not



A mechanism to control the insertion and extraction from this list so that we do not insert into list if it is full or remove from it if it is empty.


Note: It is recommended to test the below program on a offline IDE as infinite loops and sleep method may lead to it time out on any online IDE

```
// Java program to implement solution of producer
// consumer problem.
import java.util.LinkedList;
public class Threadexample
    public static void main(String[] args)
                        throws InterruptedException
    {
        // Object of a class that has both produce()
        // and consume() methods
        final PC pc = new PC();
        // Create producer thread
        Thread t1 = new Thread(new Runnable()
            @Override
            public void run()
                try
                {
                    pc.produce();
                catch(InterruptedException e)
                    e.printStackTrace();
        });
        // Create consumer thread
        Thread t2 = new Thread(new Runnable()
        {
            @Override
            public void run()
                try
                {
                    pc.consume();
                catch(InterruptedException e)
                    e.printStackTrace();
            }
        });
        // Start both threads
        t1.start();
        t2.start();
        // t1 finishes before t2
        t1.join();
        t2.join();
    // This class has a list, producer (adds items to list
    // and consumber (removes items).
```

```
public static class PC
        // Create a list shared by producer and consumer
        // Size of list is 2.
        LinkedList<Integer> list = new LinkedList<>();
        int capacity = 2;
        // Function called by producer thread
        public void produce() throws InterruptedException
            int value = 0;
            while (true)
                synchronized (this)
                    // producer thread waits while list
                    // is full
                    while (list.size()==capacity)
                        wait();
                    System.out.println("Producer produced-"
                                                   + value);
                    // to insert the jobs in the list
                    list.add(value++);
                    // notifies the consumer thread that
                    // now it can start consuming
                    notify();
                    // makes the working of program easier
                    // to understand
                    Thread.sleep(1000);
                }
            }
        }
        // Function called by consumer thread
        public void consume() throws InterruptedException
            while (true)
            {
                synchronized (this)
                    // consumer thread waits while list
                    // is empty
                    while (list.size()==0)
                        wait();
                    //to retrive the ifrst job in the list
                    int val = list.removeFirst();
                    System.out.println("Consumer consumed-"
                                                     + val);
                    // Wake up producer thread
                    notify();
                    // and sleep
                    Thread.sleep(1000);
                }
           }
       }
    }
}
```



Output:



Important Points

- In **PC class** (A class that has both produce and consume methods), a linked list of jobs and a capacity of the list is added to check that producer does not produce if the list is full.
- In **Producer class**, the value is initialized as 0.
 - Also, we have an infinite outer loop to insert values in the list. Inside this loop, we have a synchronized block so that only a producer or a consumer thread runs at a time.
 - An inner loop is there before adding the jobs to list that checks if the job list is full, the producer thread gives up the intrinsic lock on PC and goes on the waiting state.
 - If the list is empty, the control passes to below the loop and it adds a value in the list.
- In the Consumer class, we again have an infinite loop to extract a value from the list.
 - Inside, we also have an inner loop which checks if the list is empty.
 - If it is empty then we make the consumer thread give up the lock on PC and passes the control to producer thread for producing more jobs.
 - If the list is not empty, we go round the loop and removes an item from the list.
- In both the methods, we use notify at the end of all statements. The reason is simple, once you have something in list, you can have the consumer thread consume it, or if you have consumed something, you can have the producer produce something.
- sleep() at the end of both methods just make the output of program run in step wise manner and not display everything all at once so that you can see what actually is happening in the program.

Exercise:

- Readers are advised to use if condition in place of inner loop for checking boundary conditions.
- Try to make your program produce one item and immediately after that the consumer consumes it before any other item is produced by the consumer.

Reference – https://en.wikipedia.org/wiki/Producer%E2%80%93consumer_problem

This article is contributed by **Rishabh Mahrsee**. If you like GeeksforGeeks and would like contribute, you can also write an article using contribute.geeksforgeeks.org or mail your article.

contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

GATE CS Corner Company Wise Coding Practice



Login to Improve this Article

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Recommended Posts:

Thread Pools in Java

CountDownLatch in Java

Inter-thread Communication in Java

Multithreading in Java

Semaphore in Java

BigDecimal Class in Java

Swap corner words and reverse middle characters

String Literal Vs String Object in Java

Download web page using Java

Memory leaks in Java

(Login to Rate)

Average Difficulty: 3.5/5.0 Based on 25 vote(s)

Basic Easy Medium Hard Expert

Add to TODO List

Mark as DONE

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments

Share this post!

@geeksforgeeks, Some rights reserved

Contact Us!

About Us!

Careers!

Privacy Policy









