# GIST 7128 ArcGIS 1: Introduction



## Lecture 7


**Database & Location Queries** 

#### **Module 7 Topics**

- Lecture
  - Database Concepts and Terminology
  - · Working with Databases in ArcGIS
  - Selecting Features by Attributes & Location
- Lab
  - Chapter 15. Querying Data
  - Chapter 16. Selecting Features by Location
  - · Chapter 17. Joining and Relating Data
- Project
  - EastCity Part 4: Query, Join, and Locate (4%)
  - EastCity Part 5: Spatial Analysis (4%)
  - EastCity Part 6: More Spatial Analysis (3%)


2

#### **Basic Relational Database Terminology**



- i.e. any "thing" you can think about
- this "thing" is important to the user and needs to be represented and tracked in the database
- e.g: Employee, City, Street, Graduation, WorkOrder
- Entity Class (a.k.a. Entity Type)
  - a set of entities of the same type
  - described by the structure of the entity
  - e.g. STREET entity class has Name, Lanes, Surface attributes
- Entity Instance (a.k.a. Entity Occurrence)
  - specific member of the Entity class (e.g. a particular Street)
  - described by the values of the attributes of an entity
  - identified by a primary key (e.g. StreetID = 51234)

**Basic Relational Database Terminology** 




- Table a collection of records that represent an Entity Class (e.g. STREET)
- **Record** (or Row) a set of field values that describe an Entity Instance (e.g. Main St, 2-lane, paved...)
- **Field** (or Column) an attribute or characteristic of an Entity Class (e.g. Surface)
- **Field Value** (or Cell) a single characteristic or attribute of an Entity Instance (e.g. "paved")

4

3

Lecture 7

Page 1




#### **Basic Relational Database Terminology**



- Relational Database
  - a collection of tables
  - a table is known as a "relation" in relational algebra
  - tables are related to one another based on one or more common fields
- Primary Key (PK)
  - a field that uniquely identifies a record in the table
  - field values must be unique, not null (& unchanging)
  - could be a collection of fields (Composite PK)
- Foreign Key (FK)
  - a field in one table that references the primary key of a second table to form a relationship

6





#### **Basic Relational Database Terminology**





- Relationships
  - Informal: The "glue" that holds the entities together
  - Formal: The association between the instances of one or more entity classes
  - Three major characteristics of relationships
    - Degree number of entity classes that participate
    - Cardinality number of instances of one entity class that can be associated with each instance of another entity class
    - Generalization some entity classes are sub-types of other, more general, entity classes
      - e.g. Students are Full-time, Part-time, or Distance Students

8









#### **ArcGIS Relationships**

- JOIN
  - Two tables displayed as one, 1:1 relationship only
    - More Precisely: only 1 FK record can match 1 PK record
  - Virtual Join
    - During map session only, files not changed
  - Permanent Join
    - Export joined tables or layer to a new dataset
- RELATE

8. Apply or OK


15

- Tables displayed separately, 1:N relationship
- Virtual Relate
  - During map session only, files not changed
- Permanent Relate
  - Defined in ArcCatalog (relationship class)
  - Stored in Geodatabase


13

Clear Verify Help Load... Save...

OK Apply Close



#### **Select Features by Attributes** Select features based on their attributes Requires the "WHERE Clause" Select By Attributes of an SQL Statement Neighborhood Parcels • User Inputs: "LANDUSE Add to current selection 1. Layer "ZONING" Rem 2. Method: New, Add, Remove, subset "OWNER NAME" 3. Field = <> Like 'ABARO, FELIBERTO S' > = And 'AGUIRRE, JOSE' 'ALBARRAN, ESTEVAN' 4. Relational (Comparison) Operator < <= Or 5. Value (enter or select from list) ls 6. Logical (Connection) Operator SELECT \* FROM neighborhood WHERE: and repeat 3, 4, 5 (optional step) 7. Verify



AB 2016 GIST-7128


#### **SQL "WHERE Clause" Examples**


- WHERE PID = 6412 OR PID = 6415
- WHERE PID IN (6412, 6415)
- WHERE PID IN (6412, 6413, 6414, 6415, 6416, 6417, 6418, 6419)
- WHERE PID >= 6412 AND PID <= 6419
- WHERE Address LIKE '% MAIN ST'
- WHERE Address LIKE ' MAIN ST'
- WHERE Address LIKE '% MAIN %'
- WHERE Name LIKE 'A%' OR Name LIKE 'B%'
- WHERE NOT (Name LIKE 'A%' OR Name LIKE 'B%')
- WHERE NOT (Name LIKE 'A%') AND NOT (Name LIKE 'B%')


**Attribute Query & Selection Set** 

- Query a question/request to the database
  - How many properties on this street?
  - Who are their owners?
  - What is their average value and annual taxes?
  - What other streets intersect this street?
  - Can guery data from one or more layers
- Selection Set results of a Query
  - Temporary until next query run
  - Can be modified →
  - Can be saved in a:
    - EXP (expression) file
    - Results to LYR file
    - MXD

✓ Create New Selection Add to Current Selection Remove From Current Selection Select From Current Selection







### Select by Attributes and Location



#### **Examples**

- 1. Select Cities with population greater than 100,000 and within 10 kms of a major fault line
- 2. Select Parcels that are zoned as residential and are in or touching the flood zone
- 3. Select Land Use features that are Public Schools and then select Parcels that are within 400m of them
- 4. Select Parcels based on cost and size and within 400m of a Public School

22

