Document title
Service Description (SD) Arrowhead Z-wave System Demonstrator – Switch Plug State service

Document type
Template

Date
2025-05-25

Version
0.4

Author
Salman Javed

Contact
Salman.javed@ltu.se

Status
For Approval

Page
1 (3)

Service Description (SD) Arrowhead Z-wave System Demonstrator – Switch Plug State service

Abstract

This document defines the template for the Service Description of Arrowhead compliant Services. A Service Description provides an abstract description of what is needed for systems/devices/units/software to provide and/or consume a specific service. SD's for Application Services are created (specified) by the Pilots WP's and by the common Arrowhead framework. The SD shall make it possible for an engineer with technical programming knowledge to achieve an Arrowhead compliant realization of a provider and/or consumer of description of how the service is implemented/realized by using the Communication Profile and the chosen technologies. A Service Description (SD) is the Service in a specific technology. All systems/devices/units/software implementing an Interface Design Description which complies with this SD will be able to exchange information with each other. All Arrowhead Service Description should be specified using this template and stored on a common repository (available on the SVN server), in order to document and formalize the pilot demonstrators and the common Arrowhead framework.

ARTEMIS Innovation Pilot Project: Arrowhead
THEME [SP1-JTI-ARTEMIS-2012-AIPP4 SP1-JTI-ARTEMIS-2012-AIPP6]
[Production and Energy System Automation Intelligent-Built environment and urban infrastructure for sustainable and friendly cities]
Grant agreement no: 332987. Project Coordinator: Professor Jerker Delsing | Luleå University of Technology

1. Service Description Overview

This service Switch the Binary Switch Plug ON or OFF and adds a record to the Plug device manager.

The encrypted JSON object contains the following fields:

Request:

```
  {
 "state" : 0,
 "serviceType" : "switch-plug-state",
 "deviceType" : "Plug"
  }
```

Response:
It indicates if the request is received or not.

2. Abstract Interfaces

This Service provides one functionality.

2.1. POST:

This is used to switch the Binary Switch Plug ON or OFF and create a record for the service invocation into Plug device manager using Post API.

3. Abstract Information Model

Table 1 Switch Plug State Service Request

Field	Description
state	Either 0 or 255 to switch the plug OFF or ON respectively
serviceType	switch-plug-state to switch ON or OFF the binary Plug
deviceType	Plug

Table 2 Switch Plug State Service Response

Field	Description
Output	It indicates if the request is received or not.

4. Non-functional Requirements

The service has none non-functional requirements.

5. Revision history

5.1. Amendments

No.	Date	Version	Subject of Amendments	Author
1	2021-01-6	0.1	First draft	Salman Javed

5.2. Quality Assurance

No.	Date	Version	Approved by
1			