

# **Getting Started with SAP Sybase IQ Column Store Analytics Server**

## **Lesson 2: Product Installation and Database Creation**



---

## Table of Contents

<b>1. Introduction.....</b>	<b>1</b>
<b>2. Where to Get SAP Sybase IQ Evaluation Software .....</b>	<b>3</b>
<b>3. Installation.....</b>	<b>4</b>
3.1 Running the Install Program .....	4
3.2 Validating the Install .....	6
3.3 Connecting to the SAP Sybase IQ Demo Database .....	9
<b>4. The TPC-H Schema .....</b>	<b>18</b>
<b>5. Creating the Database .....</b>	<b>19</b>
<b>6. Summary.....</b>	<b>26</b>

# 1. Introduction

This chapter discusses installing SAP Sybase IQ, verifying the installation, starting up the server and using client tools to connect to it. It will show you how to create a SAP Sybase IQ database. It will also describe the TPCCH schema that you will be creating in your SAP Sybase IQ database. This schema will be the basis for the work you will be doing in subsequent chapters of this book.

**Note:** This book has been written as though you will download, install and use the Linux AMD 64 evaluation edition version of the software.

**Note:** While the version of Linux should not matter, RHEL 6.4 was used to create this guide, the working steps and for the screenshots herein. The bash shell is used as the command interpreter for shell commands.

You will need the following amount of free disk space and memory resources on a Linux machine to do the basic lessons – install IQ, create a database and load the provided data into it:

Resource	Amount
Disk space for SAP Sybase IQ installed software	700MB
Disk space for Sybase Control Center installed software	550MB
Disk space for provided data files to load into SAP Sybase IQ	1GB
Disk space for SAP Sybase IQ database	4GB (1GB for system data; 2GB for user data; 1GB for temporary data)
TOTAL disk space required (sum of the above)	6.25GB
RAM	2GB



Getting ready to install SAP Sybase IQ.

---

There are two ways to try out SAP Sybase IQ for free:

- Evaluation Edition: 30 day free access to all capabilities of SAP Sybase IQ, without limit to functionality or data size.
- Express Edition: a free, non-expiring version of SAP Sybase IQ. All features are supported, but there is a limit of 5GB of data that you can store in the database. **Note:** No customer support is available with this edition.


The evaluation edition will be useful to those who want to quickly try out SAP Sybase IQ to evaluate the full range of its capabilities without limits, and to perform competitive analysis.

The express edition will be of use to ISVs and developers, who want to experiment with SAP Sybase IQ, and keep it around for awhile. They do not need to apply stress with large amounts of data. This edition will be also useful for creating demos of smart applications.

## 2. Where to Get SAP Sybase IQ Evaluation Software

Supporting materials and a link to both the express edition and trial evaluation of SAP Sybase IQ are available at this website:


[http://www.sap.com/campaign/ne/sybase/iq\\_16\\_free\\_trial\\_download/index.epx](http://www.sap.com/campaign/ne/sybase/iq_16_free_trial_download/index.epx)

 The Best-Run Businesses Run SAP


Contact SAP online or  
Call +1-800-8-SYBASE (792273)

### SAP Sybase IQ free downloads: Choose the right fit for you

Get actionable intelligence delivered at the speed of business – with SAP Sybase IQ analytics server. Transform the way you compete to win.




Choose the SAP Sybase IQ solution that best fits your business requirements – and download today.



#### SAP Sybase IQ Express Edition

Perform interactive analysis and ad-hoc queries extremely quickly, using off-the-shelf query tools. For data scientists and developers, this edition is for education and testing purposes only, with a data store of 5 GB.


[Register to download »](#)



#### SAP Sybase IQ 30-Day Trial Evaluation

Get a 30-day full-use evaluation of SAP Sybase IQ. Gain Big Data analytics support with a native MapReduce API, advanced and flexible Hadoop integration, PMML support, and new APIs for proprietary analytical libraries.

[Register to download »](#)



#### SAP Sybase IQ Quick Start Guide

Get started quickly with SAP Sybase IQ using this 'how-to' booklet that comes with a database schema and ready-to-load data. After completing the first three sections, you will have a running SAP Sybase IQ database.

[Download Now »](#)

[Privacy](#) [Terms of Use](#) [Legal Disclosure](#) [Copyright](#)

---

## 3. Installation

Read the “Installation and Configuration Guide” (a link is provided on the software download page as noted above), and follow all the pre-installation steps.

**Note:** No license key is required for the Evaluation Version (30 day trial). The Express Edition includes a new IQ\_XE SySAM license, which is installed as part of the Express Edition server package.

Unzip the installation file. You will see the file “setup.bin”, but before you execute this installation program, make sure you have read the installation guide and followed the pre-installation steps.


**Note:** Ensure 32-bit compatibility libraries are installed. If you start the SAP Sybase IQ installer in GUI mode without installing these libraries, the installer generates an exception and fails. RHEL 6.4, and earlier, requires 32-bit compatibility libraries to support Java-based applications in SAP Sybase IQ, including the SAP Sybase IQ installer. The following libraries are required to install SAP Sybase IQ on Red Hat Enterprise Linux 6:

- libXext-devel.i686
- libXtst-devel.i686


Other variants of 64 bit Linux will require 32-bit Wine installed to run the Windows Installer.

### 3.1 Running the Install Program

From a terminal window, change to the directory where you unzipped the installation image, and enter the command “./setup.bin”. The installer will launch, and you will see the following introduction screen:



Click on “Next” multiple times, accepting the defaults provided for installation path, and “Typical” install, until you reach the “Software License Type Selection” screen shown below:



Use the default, “Evaluate SAP Sybase IQ Server Suite 16.0 (64-bit)”. Click on "Next" to select a geographical location and accept the license agreement. Accept the defaults for a “Typical” installation by clicking on the “Install” button. When complete, the Configuration for Sybase Control Center will begin. Click “Next” multiple times, and accept the default ports. Then, you will see the security login modules screen:



Enter passwords for the SCC admin and SCC agent admin, ensuring to *remember the passwords*, which will be required to use SCC later. Then, you will be prompted to choose whether or not to run Sybase Control Center as a Windows service. Choosing yes allows Windows to automatically start and restart SCC, which is recommended. Continue, reviewing the information screen, and starting the Sybase Control Center Server (which will be used in this demo later).

When SAP Sybase IQ 16.0 installs successfully, you will see the following display:



Click on “Done”.

### 3.2 *Validating the Install*

The next step is to validate the install. SAP Sybase IQ comes with a demonstration database. If you can start up the demonstration database and connect to it with a client application, then you know that your installation has been successful.



---


First, add the following three lines that set required environment variables to the `.bashrc` file in your home directory (/opt/sybase is the default root directory for the SAP Sybase IQ install make sure to use the directory to which you installed SAP Sybase IQ), and re-invoke the `.bashrc` script:

```
export SYBASE=/opt/sybase
. $SYBASE/SYBASE.sh
. $SYBASE/IQ-16_0/IQ-16_0.sh
```

To start up the demonstration database, execute the following commands from a terminal window:

```
cd $IQDIR16/demo
sh ./mkiqdemo.sh
```

The first time you do this, IQ needs to create the demo database. You will see this:

A screenshot of a terminal window titled "sybase@evangengl-dbc-node001:~/IQ-15\_4/demo". The terminal shows the command prompt "[sybase@evangengl-dbc-node001 demo]\$ sh ./mkiqdemo.sh". Below the command, a message reads: "This script will create the iqdemo database in the current directory. An existing iqdemo database in this directory will need to be shutdown and over-written." followed by a prompt "Continue <Y/N>?" with a cursor. The terminal has a menu bar with "File", "Edit", "View", "Search", "Terminal", and "Help".

```
sybase@evangengl-dbc-node001:~/IQ-15_4/demo
File Edit View Search Terminal Help
[sybase@evangengl-dbc-node001 demo]$ sh ./mkiqdemo.sh

This script will create the iqdemo database in the current
directory. An existing iqdemo database in this directory
will need to be shutdown and over-written.

Continue <Y/N>? █
```

Enter “Y”, and SAP Sybase IQ will create the demo database. If the database is created successfully, you will see the following:

```
sybase@evangengl-dbc-node001:~/IQ-15_4/demo
File Edit View Search Terminal Help

Started.
Connecting to server via TCPIP ...
Using: uid=DBA;pwd=sql;eng=bld_demo_9502;dbn=utility_db;links=tcip{host=evangen
gl-dbc-node001;port=9502}

Creating database ...
Demo database created.

Shutting down server ...
SQL Anywhere Stop Server Utility Version 12.0.1.6567

-rw-rw-r-- 1 sybase sybase      550 Dec 14 14:21 iqdemo.cfg
-r--r--r-- 1 sybase sybase  3833856 Dec 14 14:21 iqdemo.db
-rw-r--r-- 1 sybase sybase 104857600 Dec 14 14:21 iqdemo.iq
-rw-r--r-- 1 sybase sybase   40689 Dec 14 14:21 iqdemo.iqmsg
-rw-r--r-- 1 sybase sybase 26214400 Dec 14 14:21 iqdemo.iqtmp
-rw-rw-r-- 1 sybase sybase    1150 Dec 14 14:20 iqdemo.lmp
-r----- 1 sybase sybase  327680 Dec 14 14:21 iqdemo.log
-rw-r--r-- 1 sybase sybase 104857600 Dec 14 14:21 iqdemo_main.iq

Demo database created successfully

[sybase@evangengl-dbc-node001 demo]$
```

The database was created, but the IQ server wasn't started to connect to it. To start the IQ server and connect to the demo database, enter the following command:

```
start_iq @iqdemo.cfg iqdemo.db
```

If the demo database started up correctly, you will see the following in your terminal window (the IQ server listens by default on port 2638):

```
sybase@evangengl-dbc-node001:~/IQ-15_4/demo
File Edit View Search Terminal Help

=====
I. 12/14 14:23:02. Starting database "iqdemo" (/opt/sybase/IQ-15_4/demo/iqdemo.d
b) at Wed Dec 14 2011 14:23
I. 12/14 14:23:03. Transaction log: iqdemo.log
I. 12/14 14:23:03. Starting checkpoint of "iqdemo" (iqdemo.db) at Wed Dec 14 201
1 14:23
I. 12/14 14:23:03. Finished checkpoint of "iqdemo" (iqdemo.db) at Wed Dec 14 201
1 14:23
I. 12/14 14:23:04. Database "iqdemo" (iqdemo.db) started at Wed Dec 14 2011 14:2
3
I. 12/14 14:23:04. IQ Server evangengl-dbc-node001_iqdemo.
I. 12/14 14:23:04. Database server started at Wed Dec 14 2011 14:23
I. 12/14 14:23:04. Trying to start SharedMemory link ...
I. 12/14 14:23:04. SharedMemory link started successfully
I. 12/14 14:23:04. Trying to start TCPIP link ...
I. 12/14 14:23:04. Starting on port 2638
I. 12/14 14:23:09. TCPIP link started successfully
I. 12/14 14:23:09. Now accepting requests
New process id is 6671


Server started successfully

[sybase@evangengl-dbc-node001 demo]$
```

At any time, you can see which IQ databases are running on your machine with the following command:

```
stop_iq
```

You will see the following:



```
sybase@evangengl-dbc-node001:~/IQ-15_4/demo
File Edit View Search Terminal Help
[sybase@evangengl-dbc-node001 demo]$ stop_iq

Checking system ...

The following 1 server(s) are owned by 'sybase'

## Owner          PID    Started  CPU Time  Additional Information
-----
1: sybase          6671    14:23    00:00:00  SVR:evangengl-dbc-node001_iqdemo DB:iqdemo
PORT:2638
/opt/sybase/IQ-15_4/bin64/iqsrv15 @iqdemo.cfg iqdemo.db -ti 4400 -
gn 25 -o /opt/sybase/IQ-15_4/logfiles/evangengl-dbc-node001_iqdemo.0001.srvlog -
hn
--

Please note that 'stop_iq' will shut down a server completely
without regard for users, connections, or load process status.
For more control, use the 'dbstop' utility, which has options
that control stopping servers based on active connections.

Do you want to stop the server displayed above <Y/N>? █
```

Type “N” to leave the IQ server up and running

### 3.3 Connecting to the SAP Sybase IQ Demo Database

You have started up the SAP Sybase IQ server and demo database, but you will want to connect to it with a client application in order to complete the validation of the install. A client application can connect to the SAP Sybase IQ server using ODBC, JDBC, or Sybase’s native interface called “Open Client”. There are also other database drivers for various programming environments: OLEDB, ADO.NET, Perl, PHP, Python, and Ruby.

Sybase Control Center is a web-based tool for monitoring and managing servers. It can be used to connect to a database and perform administrative tasks.

Before running SCC, ensure that write permissions are granted to the \$SYBASE folder and subfolders. To start SCC, enter the following in a terminal window:

```
$SYBASE/SCC-3_2/bin/scc.sh
```


Once started correctly, you should see the following screen:

```
user@localhost:~/Desktop
File Edit View Search Terminal Help
Free Physical Memory: 5290 MB
java.library.path: /iq/SCC-3_2/rtlib:/iq/SCC-3_2/bin/sa/bin_linux64
Java Home: /usr/java/default
Java Version: 1.7.0_25
Java VM Version: 23.25-b01
VM Process ID 2362@localhost.localdomain
VM Arguments: -Xms128m, -XX:MaxPermSize=128m, -XX:+HeapDumpOnOutOfMemoryError, -XX:HeapDumpPath="/iq/SCC-3_2/log", -Dcom.sybase.home=/iq, -Dcom.sybase.ua.toplevel=/iq/SCC-3_2, -Dcom.sybase.ua.home=/iq/SCC-3_2, -Dcom.sybase.platform=linux, -Djava.library.path=/iq/SCC-3_2/rtlib:/iq/SCC-3_2/bin/sa/bin_linux64, -Djava.security.policy=/iq/SCC-3_2/conf/java.policy, -Djava.util.logging.manager=com.sybase.ua.util.logging.bridge.JavaToLog4jLogManager, -Dcom.sybase.security.BootstrapConfigurationURL=file:///iq/SCC-3_2/conf/csbootstrap.properties
Message level: WARN
Message Server State: Server Started
Sybase Control Center successfully started
Agent RMI Connection URL:
    service:jmx:rmi:///jndi/rmi://localhost:9999/agent
Sybase Control Center successfully started
SCC Web Console:
    http://localhost:8282/scc
    https://localhost:8283/scc
Type help for more options
scc-console>
```


Either URL specified below SCC Web Console (circled in red) can be used to access the Sybase Control Center. Open up a web browser, and enter the following URL, from above:

`https://<scc_server_hostname>:8283/scc`

There is no security certificate for the HTTPS secure connection, but choose to proceed anyway. Depending on your browser, you will see a screen like this one:




Continue. You will then see the login screen:




Enter “sccadmin” for the user, with the password created during installation and click on “Log In”.

Once logged in, register the IQ resource by clicking resource in the top navigation bar and then clicking register in the drop down menu. Registering the server provides its identity and connection information to Sybase Control Center, which allows SCC be able to manage the server.




---

Name your resource, whatever you choose, setting the Resource Type to “IQ Server”.




The screenshot shows the 'Resource Registration' dialog box, specifically the 'Resource Type' step. The left sidebar has 'Resource Type' selected. The main area is titled 'Resource Type' and contains the instruction: 'Specify the name, type and description of the resource you want to register with Sybase Control Center.' There are three input fields: 'Resource name:' with the value 'iqdemo', 'Resource type:' with a dropdown menu set to 'IQ Server', and 'Description:' with the value 'Optional'. At the bottom are four buttons: 'Back', 'Next', 'Finish', and 'Cancel'.

Click next. Enter connection information, 2638 is a default port for IQ and the database name is optional.




The screenshot shows the 'Resource Registration' dialog box, specifically the 'Connection Information' step. The left sidebar has 'Connection Information' selected. The main area is titled 'Connection Information' and contains the instruction: 'Specify the connection information for your resource.' There is a tab labeled 'JDBC'. Below the tab are five input fields: 'IQ host name:' with the value 'localhost', 'IQ port number:' with the value '2638', 'Database:' with the value 'iqdemo.db', 'Character set:', and 'Language:'. At the bottom are four buttons: 'Back', 'Next', 'Finish', and 'Cancel'.

Enter DBA and “sql” for the password and click next.



The dialog box is titled "Resource Registration" and has a sidebar on the left with four items: "Resource Type", "Connection Information", "Authentication Information" (which is selected and highlighted in blue), and "Options". The main area is titled "Authentication Information" and contains the text "Enter credential information for this resource." Below this is a checkbox labeled "I do not want to supply authentication information" which is unchecked. There are two text input fields: "IQ Username" with a red asterisk and the value "DBA", and "IQ Password" with the value "+++". At the bottom are four buttons: "Back", "Next" (which is highlighted with a mouse cursor), "Finish", and "Cancel".

Check both boxes and click next again.




The dialog box is titled "Resource Registration" and has a sidebar on the left with four items: "Resource Type", "Connection Information", "Authentication Information", and "Options" (which is selected and highlighted in blue). The main area is titled "Options" and contains the text "Once the new resource is registered you have a few options." Below this are two checkboxes, both of which are checked: "Add this resource to the current perspective." and "Open the resource explorer to view this new resource." At the bottom are four buttons: "Back", "Next" (which is highlighted with a mouse cursor), "Finish", and "Cancel".


Click Finish.

Now the resource is added to the perspective. In Perspectives Resources, move your mouse over the server name textbox (in this example, iqdemo). A drop-down arrow appears, on the right. Click the drop-down beside the server name and choose “Authenticate”.






Authentication window opens. Enter information from resource set up.




Once authenticated, the Sybase Control Center agent must be registered and authenticated. The SCC agent was installed with the installer and allows management tasks to be performed.




On the Perspective Resources window, click the drop-down next to the server name and choose “Administration Console”.



On the Administration Console which opens, click “IQ Servers” under Browse. The server will appear on the list. Then, on the drop-down beside the server name, click “Register Agent...”




In the pop-up window, leave the defaults (<localhost> is the SCC agent host and 9999 is the default agent port) and click “OK”. Then, click the drop-down arrow beside the server name again and click “Authenticate Agent...”. Leave the agent user as “uafadmin” and provide the second password entered during installation. Click “OK”.




The agent is now registered and authenticated and can perform administrative tasks for the server.

Now click the arrow beside “IQ Servers”, under browse and then, expand the arrow beside “Schema Objects”, then “Tables”. Click on “Tables” under the Tables folder. You will see the tables that are part of the demo database in the right pane.



Click on the drop-down arrow beside “Customers” and click “Properties”. Then, you will see general properties of the table. Each item in the left pane provides different data on the table. Click on the “Data” item in the left pane. Now, all the customer data in the table is in the right pane.



The first screenshot shows the 'General' tab for the 'Customers' table. The left pane lists various table properties, and the right pane displays the following information:

- Name: Customers
- Owner: GROUP0
- Type: Table
- DbSPACE: iq\_main
- Comment: customers of the sporting goods company

The second screenshot shows the 'Data' tab for the same table. The left pane highlights the 'Data' option, and the right pane displays a table of customer data:


ID	Surname	GivenN...	Street	City	State	Country	Postal...	Phone	Compa...
101	Devlin	Michaels	114 Pion	Kingston	NJ	USA	07070	2015558	The Pow
102	Reiser	Beth	33 Whip	Rockwoo	NY	USA	10154	2125558	AMF Corp
103	Niedring	Erin	190 Winc	Tara	PA	USA	19301	2155556	Darling A
104	Mason	Meghan	5520 Du	Cheslea	TN	USA	37919	6155555	P.S.C.
105	McCarthy	Laura	110 High	Clinton	IN	USA	46032	3175558	Amo & S
106	Phillips	Paul	200 Che	Brandon	CT	USA	64579	2035553	Ralston I
107	Colburn	Kelly	1131 Val	Chandler	NC	USA	27695-7	9195555	The Hom
108	Goforth	Matthew	101 Way	Harriston	TN	USA	37421	6155558	Raleigh C
109	Gagliardi	Jessie	201 Park	Preston	PQ	Canada	K1A 0H3	8195559	Newton E
110	Aglioni	Michael	135 Nort	Oshawa	OH	USA	43216	6145552	The Pep
111	Ricci	Dylan	1470 Pro	Hastings	NY	USA	13202	3155554	Dynamici
112	McDonou	Shawn	1575 S M	Orillia	MN	USA	55428	6125555	McManus
113	Kaiser	Samuel	44 Bristo	Lake of t	MN	USA	55041	6125553	Lakes In
114	Chopp	Shane	95 Sumn	Newmark	MN	USA	55104	6125556	Howard C
115	Phillips	Shannon	2055 Coi	Newmark	MN	USA	55114	6125556	Sterling S
116	Gugliuzzi	Brian	391 Wyn	Stayner	NY	USA	10543	9145553	Sampson
117	Morgan	Meredith	9191 Gal	Unionvill	OH	USA	43081	6145558	Square S
118	Sanford	Kristina	22 96th	Chandler	NC	USA	27695-7	9195555	Raleigh /
119	Smith	Tomm	37 Post	Owen So	CA	USA	92677	7145554	Ocean Sp
120	Steinberg	Gertrude	14 Amon	Hockley	NY	USA	10523	9145553	Carney C

Now that you can connect to the demo database, you know that you have a solid installation of SAP Sybase IQ.

## 4. The TPC-H Schema

TPC-H is a decision support benchmark created by the Transaction Processing Performance Council. It consists of a schema, the data to populate that schema, and a set of business oriented queries. The schema models an industry database which manages, sells and distributes products worldwide. The tables in the schema consist of orders, line items, parts, suppliers, customers, and countries. The queries simulate various classes of business analysis: pricing, supply and demand, profit and revenue, and shipping

Here is a picture of the TPC-H schema as depicted in Sybase's PowerDesigner modeling tool:



The next task you are going to perform is to create a database which will be loaded with this schema.



**Create Databases Wizard**

**Database Definitions**

Specify information for databases to be created. Press the Add button to create a database definition. Alternatively, you can press the Import button to import a list of database definitions from a CSV file. If you do not know the CSV format, you can first create a definition via the Add button, and then press the Export button to export it to a CSV file. Then you can edit the file and import from it.

Validation	Server Name	Host	IQ Port	DB Path

Click “Add”. Then, you will be asked to specify agent and database information. Fill out the required information as specified below and in the diagram.

For “host” specify the machine name or localhost (if both SCC and the server are on the current machine). Leave the default port and logins but enter the password from the installation for SCC agent password.

Choose the name, port and login for the new database and enter it for IQ Server Name, IQ Server Port, IQ user and IQ password. Use the absolute path of where you want to save the database for Database path and IQ main dbspace path (the folder and files will be created, as necessary). If you check raw device, the files will be placed in raw storage. All other defaults can be kept.

### Add Database Definition

Specify Sybase Control Center agent and database information.

Host: \* localhost
  
SCC agent port: \* 9999
  
SCC agent user: \* uafadmin
  
SCC agent password: \* \*\*\*\*
  
Utility server user: \* DBA
  
Utility server password: \* \*\*\*
  


---

IQ Server Name: \* tpch
  
IQ Server Port: \* 1112
  
IQ user: \* DBA
  
IQ password: \* \*\*\*
  
Database path: \* /iq/TPCHDB/tpch.db
  


---

IQ page size: 128 Kilobytes
  
Catalog page size: 4 Kilobytes

IQ main dbspace path: \* /iq/TPCHDB/tpch.iq
  
IQ main dbspace size (MB): \* 1000
  
IQ main dbspace reserve (MB): 300
  
☐ Raw device
  


---

Local temporary dbspace path: /iq/TPCHDB/tpch.iqtemp
  
Local temporary dbspace size (MB): \* 1000
  
Local temporary dbspace reserve (MB): 300
  
☐ Raw device
  


---

Transaction log: /iq/TPCHDB/tpch.log
  
Transaction mirror log: /iq/TPCHDB/tpch.mlg
  


---

CHAR collation: ISO\_BINENG Sel...
  
NCHAR collation: UCA Sel...
  
Options: Settings

OK
Cancel

Click “OK”. If specified information is entered correctly, the server name will be added and there will be a green check mark under “Validation”.

### Create Databases Wizard

☒ Database Definitions
   
☒ Execution

#### Database Definitions

Specify information for databases to be created. Press the Add button to create a database definition. Alternatively, you can press the Import button to import a list of database definitions from a CSV file. If you do not know the CSV format, you can first create a definition via the Add button, and then press the Export button to export it to a CSV file. Then you can edit the file and import from it.


Add
Edit
Delete
Delete All
Import
Export

Database Definitions				
Validation	Server Name	Host	IQ Port	DB Path
✓	tpch	localhost	1112	/iq/TPCHDB/tpch.db


Back
Next
Close
Cancel

Click “Next”. Then, click “Execute” to create database. The progress bar will fill and log messages will appear.

When complete, you will see the following screen:



Click “Close”. Now, in the Perspective Resources, the new server will appear.






Note: Sybase Control Center for SAP Sybase IQ supports a maximum of one database per server. Due to this, adding the “tpch” database also added the “tpch” server.

Close Sybase Control Center, either in the browser or in the terminal by either of the following commands (The first one is run by clicking “Ctrl-C” in the terminal which SCC was started in):

```
scc-console> ^C
$SYBASE/SCC-3_2/bin/scc.sh -stop
```


We would like to now only look at the tpch server, but, first we need to edit the configuration settings. To do that, we will stop both servers.

At any time, a server can be shut down completely by issuing the command “stop\_iq” from a terminal window. If multiple servers are running, the option to pick a server to shut down is given:



```
user@localhost:/iq/IQ-16_0/demo
File Edit View Search Terminal Help
Checking system ...
The following 2 server(s) are owned by 'user'
## Owner      PID    Started CPU Time  Additional Information
--
1: user       10076   04:45   00:00:02  SVR:localhost_iqdemo DB:iqdemo PORT:2638
    /iq/IQ-16_0/bin64/iqsrv16 @iqdemo.cfg iqdemo.db -ti 4400 -gn 25 -o
    /iq/IQ-16_0/logfiles/localhost_iqdemo.0009.srvlog -hn 5
--
2: user       11188   05:03   00:00:01  SVR:tpch DB:tpch PORT:1111
    /iq/IQ-16_0/bin64/iqsrv16 @params.cfg -n tpch -x tcpip(port=1111)
    /iq/TPCHDB/tpch.db -gp 4096 -ti 4400 -gn 105 -o /iq/IQ-16_0/logfiles/tpch.0016.srvlog
--
Please note that 'stop_iq' will shut down a server completely
without regard for users, connections, or load process status.
For more control, use the 'dbstop' utility, which has options
that control stopping servers based on active connections.
Enter the server to shutdown ('1'...'2') or 'Q' to Quit: 1
```

The next server can also be shut down, by running “stop\_iq” again:



```
sybase@evangengl-dbc-node001:~/TPCHDB
File Edit View Search Terminal Help
[sybase@evangengl-dbc-node001 TPCHDB]$ stop_iq
Checking system ...
The following 1 server(s) are owned by 'sybase'
## Owner      PID    Started CPU Time  Additional Information
--
1: sybase      7162   10:20   00:00:15  SVR:evangengl-dbc-node001_iqdemo DB:iqdemo PORT:2638
    /opt/sybase/IQ-15_4/bin64/iqsrv15 @iqdemo.cfg iqdemo.db -ti 4400 -gn 25 -o
    /opt/sybase/IQ-15_4/logfiles/evangengl-dbc-node001_iqdemo.0002.srvlog -hn
--
Please note that 'stop_iq' will shut down a server completely
without regard for users, connections, or load process status.
For more control, use the 'dbstop' utility, which has options
that control stopping servers based on active connections.
Do you want to stop the server displayed above <Y/N>? y
```

---

Choose “y” to shut down the server.

Next, create a text file called “tpch.cfg” in the directory where you created your database (in this example: “/opt/sybase/TPCHDB”). The file should have the following contents:

```
# tpch.cfg
# -----
# This file contains the default ASIQ startup parameters. All servers
# started will default to these parameters, unless overridden by contents
# of parameter list.
# -----
# Must be in the format: One parameter per line
# -----

-n tpch

-c 32m
-gc 20
-gd all
-gl all
-gm 10
-gp 4096
-ti 4400

-iqmc 400
-iqtc 600

-o message.out

-zr sql
-zo iq.sql.out
```

This is the configuration file for starting up the SAP Sybase IQ database. The meaning of these parameters is as follows:

- -n tpch: specifies the name of the SAP Sybase IQ server
- -c 32m: sets initial memory reserved for caching catalog store pages
- -gc 20: sets the maximum interval between checkpoints
- -gd all: sets the permissions (anyone) required to start or stop a database
- -gl all: sets the permissions (anyone) required to load data using LOAD TABLE
- -gm 10: limits the number of concurrent connections to the server to 10
- -gp 4096: sets the maximum page size allowed, in bytes, for the catalog store
- -ti 4400: disconnect connections that haven't submitted a request for the specified number of minutes (default is 4400 – or 72 hours)
- -iqmc 400: specifies the main IQ store cache size in MB
- -iqtc 600: specifies the temp IQ store cache size in MB
- -o message.out: prints all server messages to the server message log file (database messages go the file “<dbname>.iqmsg”)

- -zr sql: enables SQL statement logging
- -zo iq.sql.out: redirects SQL statement logging information to a file separate from the regular log file


By default, the server listens on port 2638. You can, optionally, change this by adding a line to the tpch.cfg file similar to the following (server now listening on port 7878):

```
-x tcpip{port=7878}
```

You can start up the database from a terminal window by issuing the following command from the directory where you created the database file (in this example “/opt/sybase/TPCHDB”):

```
start_iq @tpch.cfg tpch.db
```

If the database starts up successfully, you will see messages similar to the following:



```

sybase@evangengl-dbc-node001:~/TPCHDB
File Edit View Search Terminal Help
Server Version      : 15.4.0.6567/GA
Open Client Version : N/A
User Parameters     : '@tpch.cfg' 'tpch.db'
Default Parameters  : -gn 25

=====
IQ server starting with:
  10 connections      (      -gm )
  26 cmd resources    ( -iqgovern )
  456 threads         (      -iqmt )
  512 Kb thread stack size ( -iqtss )
  233472 Kb thread memory size ( -iqmt * -iqtss )
  8 IQ number of cpus ( -iqnumbercpus )
  0 MB maximum size of IQMSG file ( -iqmsgsz )
  0 copies of IQMSG file archives ( -iqmsgnum )
=====

New process id is 12976

Server started successfully

[sybase@evangengl-dbc-node001 TPCHDB]$

```

Now, we want to open the tpch server with Sybase Control Center.

Run the SCC command as earlier:

```
scc.sh
```

Register the resource as earlier. Now we have a tpch resource, with the required configuration, which connects to our database.

Note: This tpch server will be on port 2638 (or 7878, if specified), not the one on 1112 as used to create the database.

---

## 6. Summary

During this lesson, you have installed SAP Sybase IQ, validated the installation, and created a database. You have learned how to start your database and connect to it. The next step is to create a schema and load data into your database

## Copyright

© Copyright 2011 SAP AG. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP AG. The information contained herein may be changed without prior notice.

Some software products marketed by SAP AG and its distributors contain proprietary software components of other software vendors.

Microsoft, Windows, Excel, Outlook, and PowerPoint are registered trademarks of Microsoft Corporation.

IBM, DB2, DB2 Universal Database, System i, System i5, System p, System p5, System x, System z, System z10, System z9, z10, z9, iSeries, pSeries, xSeries, zSeries, eServer, z/VM, z/OS, i5/OS, S/390, OS/390, OS/400, AS/400, S/390 Parallel Enterprise Server, PowerVM, Power Architecture, POWER6+, POWER6, POWER5+, POWER5, POWER, OpenPower, PowerPC, BatchPipes, BladeCenter, System Storage, GPFS, HACMP, RETAIN, DB2 Connect, RACF, Redbooks, OS/2, Parallel Sysplex, MVS/ESA, AIX, Intelligent Miner, WebSphere, Netfinity, Tivoli and Informix are trademarks or registered trademarks of IBM Corporation.

Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.

Adobe, the Adobe logo, Acrobat, PostScript, and Reader are either trademarks or registered trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Oracle is a registered trademark of Oracle Corporation.

UNIX, X/Open, OSF/1, and Motif are registered trademarks of the Open Group.

Citrix, ICA, Program Neighborhood, MetaFrame, WinFrame, VideoFrame, and MultiWin are trademarks or registered trademarks of Citrix Systems, Inc.

HTML, XML, XHTML and W3C are trademarks or registered trademarks of W3C®, World Wide Web Consortium, Massachusetts Institute of Technology.

Java is a registered trademark of Sun Microsystems, Inc.

JavaScript is a registered trademark of Sun Microsystems, Inc., used under license for technology invented and implemented by Netscape.

SAP, R/3, SAP NetWeaver, Duet, PartnerEdge, ByDesign, SAP Business ByDesign, and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and other countries.

Business Objects and the Business Objects logo, BusinessObjects, Crystal Reports, Crystal Decisions, Web Intelligence, Xcelsius, and other Business Objects products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of Business Objects S.A. in the United States and in other countries. Business Objects is an SAP company.

All other product and service names mentioned are the trademarks of their respective companies. Data contained in this document serves informational purposes only. National product specifications may vary.

These materials are subject to change without notice. These materials are provided by SAP AG and its affiliated companies ("SAP Group") for informational purposes only, without representation or warranty of any kind, and SAP Group shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP Group products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.