

# Intro to Instrumentation and Field Measurements in Remote Sensing

Javier Concha and Paul Romanczyk



Digital Imaging and Remote Sensing Lab  
Chester F. Carlson Center for Imaging Science  
Rochester Institute of Technology

January 9, 2015

Presented for 2015 Intersession Term

# Outline

- ① Introduction
- ② Background
- ③ Taking Measurements
- ④ DIRS Instruments
- ⑤ Data Processing
- ⑥ Conclusions

# Outline

## ① Introduction

## ② Background

## ③ Taking Measurements

## ④ DIRS Instruments

## ⑤ Data Processing

## ⑥ Conclusions

# Course Goals

- Learn the importance of field measurements
- Learn how to take field measurements
- Learn about DIRS instruments

# Course Description

- Friday: Introduction
- Monday: Introduction (con't) and DIRS instruments exhibition
- Tuesday: Lab: Reflectance measurements
- Wednesday: Lab: LIDAR measurements

# Definitions

- **Remote Sensing:**

“Remote sensing is the science of obtaining information about objects or areas from a distance, typically from aircraft or satellites.”

- **Field Measurements or Groundtruth or Ground-based data or reference data or ancillary data:**

“Observations or measurements made at or near the surface of the earth in support of remote sensing.”



# Motivation

## Why is it important?

- Validation: comparison to know how close a model is to the field measurements (accuracy)
- Calibration or Correction: adjust model or instrument to be more precise (data fitting)
- Data collection to get characteristics of target, materials, etc.

# Example: Field Data Collection Area of Study

R·I·T Rochester Institute of Technology



# Field Data Collection (con't)


## Area of Study

R·I·T

Rochester Institute of Technology




# Field Data Collection (con't)



Water Samples




Lab Analysis



Water Leaving  
Reflectance



Spectroradiometer



Backscattering


# Field Data Collection (con't)

## Lab Measurements

R·I·T

Rochester Institute of Technology

### Spectrophotometer



IOPs

Hydrolight



### Filtration and Spectrophotometric Analysis



Concentrations

# Field Data Collection (con't)

2013 and 2014 Seasons

R·I·T

Rochester Institute of Technology


		IOPs		Concentrations		Reflectances		Backscattering	
Date		Ponds	Lake	Ponds	Lake	Ponds	Lake	Ponds	Lake
2013	25-Aug	✓	✗	✓	✗	✗	✗	✗	✗
	19-Sep	✓	✓	✓	✓	✗	✓	✓	✓
	26-Sep	✓	✓	✓	✓	✗	✓	✗	✓
2014	17-May	✓	✗	✓	✗	✓	✗	✓	✗
	02-Jun	✗	✓	✗	✓	✗	✓	✗	✓
	11-Jul	✓	✓	✓	✓	✓	✓	✗	✓
	28-Aug	✗	✓	✗	✓	✗	✗	✗	✗
	29-Sep	✓	✓	✓	✓	✓	✓	✓	✓

# Retrieval Concentration Maps


R·I·T

Rochester Institute of Technology



RGB image



&lt;CHL&gt;, [µg/L]



&lt;TSS&gt;, [mg/L]

 $a_{CDOM}(440nm)$ , [1/m]

# Field Data Use

- Reflectance: Atmospheric Correction
- Chl-a concentration: comparison with model

# Outline

① Introduction

② Background

③ Taking Measurements

④ DIRS Instruments


⑤ Data Processing

⑥ Conclusions

# Examples of Kind of Measurements

- Reflectance: Radiometer
- Concentration: Spectrophotometer
- Location: GPS
- Structure: LIDAR
- Leaf Area Index (LAI): Ceptometer

# Radiometric Quantities: Radiance



$\Delta Q$ : radian energy incident

$\Delta t$ : time interval


$\Delta A$ : surface area at location  $(x,y,z)$

$\Delta\Omega$ : solid angle in direction  $(\theta,\varphi)$

$\Delta\lambda$ : photons wavelength interval

$$L(x, y, z, t, \theta, \varphi, \lambda) \equiv \frac{\Delta Q}{\Delta t \Delta A \Delta \Omega \Delta \lambda} \quad [Js^{-1} m^{-2} sr^{-1} nm^{-1}] \quad (1)$$

# Radiometric Quantities: Radiance



$\Delta Q$ : radian energy incident

$\Delta t$ : time interval


$\Delta A$ : surface area at location  $(x,y,z)$

$\Delta\Omega$ : solid angle in direction  $(\theta,\varphi)$

$\Delta\lambda$ : photons wavelength interval

$$L(x, y, z, t, \theta, \varphi, \lambda) \equiv \frac{\partial^4 Q}{\partial t \partial A \partial \Omega \partial \lambda} \quad [Js^{-1} m^{-2} sr^{-1} nm^{-1}] \quad (1)$$

# Radiance Sensor



(Source: [Mobley, 2010])

# Radiometric Quantities: Irradiance

**Spectral downwelling scalar irradiance** at depth  $z$ :

$$E_{od}(z, \lambda) = \int_{2\pi_d} L(z, \theta, \varphi, \lambda) d\Omega \quad [Wm^{-2}nm^{-1}] \quad (2)$$

**Spectral upwelling scalar irradiance** at depth  $z$ :


$$E_{ou}(z, \lambda) = \int_{2\pi_u} L(z, \theta, \varphi, \lambda) d\Omega \quad [Wm^{-2}nm^{-1}] \quad (3)$$

**Spectral scalar irradiance** at depth  $z$ :

$$E_o(z, \lambda) \equiv E_{od}(z, \lambda) + E_{ou}(z, \lambda) \quad (4)$$

$$= \int_{4\pi} L(z, \theta, \varphi, \lambda) d\Omega \quad (5)$$

# Scalar Irradiance Sensor



(Source: [Mobley, 2010])

# Radiometric Quantities: Irradiance


**Spectral downwelling plane irradiance** at depth  $z$ :

$$E_d(z, \lambda) = \int_{2\pi_d} L(z, \theta, \varphi, \lambda) |\cos\theta| d\Omega \quad [Wm^{-2}nm^{-1}] \quad (6)$$

Photosynthetic available radiation, **PAR**:

$$PAR(z) \equiv \int_{350nm}^{700nm} \frac{\lambda}{hc} E_o(z, \lambda) d\lambda \quad [photons s^{-1}m^{-2}] \quad (7)$$

# Planar Irradiance Sensor



(Source: [Mobley, 2010])

# Reflectance

- **Irradiance reflectance:**

$$R(z, \lambda) \equiv \frac{E_u(z, \lambda)}{E_d(z, \lambda)} \quad (8)$$

- **Remote sensing reflectance (water):**

$$R_{rs}(\theta, \varphi, \lambda) \equiv \frac{L_w(\theta, \varphi, \lambda)}{E_d(\lambda)} \quad [sr^{-1}] \quad (9)$$

where  $L_w$  is the **water-leaving radiance**

- **Bidirectional Reflectance Distribution Function (BRDF):**

$$r_{BRDF} = \frac{L(\theta_o, \phi_o)}{E(\theta_i, \phi_i)} \quad [sr^{-1}] \quad (10)$$

# Outline

- ① Introduction
- ② Background
- ③ Taking Measurements
- ④ DIRS Instruments
- ⑤ Data Processing
- ⑥ Conclusions

# Diffuse white reference panel (Spectralon)

R·I·T

Rochester Institute of Technology




- For a Lambertian surface:

$$L = \frac{E_d r}{\pi} \Rightarrow E_d = L\pi$$

- For spectralon  $r \approx 1$

( $\approx 100\%$ )

$$\Rightarrow E_d = L\pi$$



# Reflectance


- **Reflectance:**  $R(z, \lambda) \equiv \frac{L_u(z, \lambda)}{E_d(z, \lambda)}$
- Two measurements:
  - $E_d$ : Spectralon
  - $L_u$ : Target or sample


# Remote-Sensing Reflectance

- 3 measurements:
  - $L_g$  (spectralon)
  - $L_t = L_r + L_w$  (water)
  - $L_{sky}$
- Remote-sensing reflectance:
$$R_{rs} = L_w/E_d$$
$$= (L_t - L_r)/E_d$$

with  $L_r = 0.028 * L_{sky}$

  - $E_d = L_g * \pi$
  - $\phi$  : azimuthal angle
  - $\theta$  : zenith angle





# Things to consider for a field campaign

- Planning ahead: permits, what kind of measurements, how many people, what conditions, instruments availability, shipping, prioritization of data.
- Equipment check list
- Contact list: phone numbers, emergency numbers, emails
- Risk management form (RIT requirement)
- Direction how to get to the place

# Things to consider for a field campaign

- Have a good datasheet
- Download and look data from the instrument ASAP!!!
- Tools for in-field repairs and cleaning
- Water, food, field clothes, first aid kit
- Plan collection ahead of time
- Write down procedure
- Setting up plots/sites
- Take pictures

# Things to consider for a field campaign

- Read instrument manual
- Check and charge batteries in advance
- Check instrument in advance
- The data should be taken as close to the time of acquisition as possible (due to inevitable landscape changes)
- Weather conditions
- Take measurement in same illumination conditions

# Outline

- ① Introduction
- ② Background
- ③ Taking Measurements
- ④ DIRS Instruments
- ⑤ Data Processing
- ⑥ Conclusions

# DIRS Lab Instruments

- ASD (Spectroradiometer; reflectance, radiance)
- SVC (Spectroradiometer; reflectance, radiance)
- RIT LIDAR
- GRIT (Goniometer; BRDF)
- GPS (Location)
- HydroScat-2 (Backscattering)
- AccuPAR LP-80 (PAR energy)

# DIRS Lab Instruments (con't)

- WASP (Multispectral Instrument)
- WASP Lite (Multispectral Instrument)
- MISI (Multispectral Instrument)
- Thermistor (Temperature)
- Spectrophotometer (Absorbance)
- Camera

# Outline

- ① Introduction
- ② Background
- ③ Taking Measurements
- ④ DIRS Instruments
- ⑤ Data Processing
- ⑥ Conclusions

# Data Extraction

- Raw data in proprietary format (depending of the instrument). Ex: \*.dat, \*.SPC
- Translate or export to ASCII (\*.txt, \*.ASC)
- Text files manipulation (IDL, Matlab, Python, C++, bash).

# Data in ASCII format

## ASD

Text conversion of header file \Data\ASD\_2014\_toughbook\2014\_08\_28\_LANDSAT\water2b00004.asd.rad

-----  
water  
The instrument number was 6142/12  
New ASD spectrum file: Program version = 6.00 file version = 1.00  
Spectrum saved: 08/28/2014 at 12:21:57  
VNIR integration time : 34  
VNIR channel 1 wavelength = 350 wavelength step = 1  
There were 10 samples per data value  
xmin = 350 xmax= 2500  
ymin= 0 ymax= 1  
The instrument digitizes spectral values to 16 bits  
SWIR1 gain was 42 offset was 2064  
SWIR2 gain was 16 offset was 2076  
Join between VNIR and SWIR1 was 1000 nm  
Join between SWIR1 and SWIR2 was 1830 nm  
VNIR dark signal subtracted  
10 dark measurements taken Thu Aug 28 12:15:46 2014  
DCC value was 0  
Data is not compared to a white reference  
There was a 3-degree FOV foreoptic attached  
GPS-Latitude is 50  
GPS-Longitude is E0  
GPS-Altitude is 0  
GPS-UTC is Wed Dec 31 19:00:00 1969  
  
Smart Detector  
Serial# 0  
Signal (A) 0.000E00  
Dark (A) 0.000E00  
Ref (A) 0.000E00  
Status 0 - Uninitialized  
Gain E-4  
Averaging 0  
Temp (C) 0.0  
Humid (%) 0.0  
  
Wavelength water2b00004.asd.rad  
350 4.17592842131853E-03  
351 4.22246055677533E-03  
352 4.17632004246116E-03

# Data in ASCII format

SVC


R·I·T

Rochester Institute of Technology

```
/** Spectra Vista SIG Data ***/
name= gr092413_142.sig
instrument= HI: 9122002 (HR-1024i)
integration= 10.0, 30.0, 10.0, 1000.0, 40.0, 10.0
scan method= Time-based, Time-based
scan coadds= 200, 61, 156, 2, 46, 156
scan time= 2, 2
scan settings= AI, AI
external data set1= 0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0
external data set2= 0,0,0,0,0,0,0,0,0,0,0,0,0,0,0,0
external data dark= 0,0,0,0,0,0,0,0
external data mask= 0
optic= LENS 4(1), LENS 4(1)
temp= 36.1, -4.6, -10.2, 36.1, -4.6, -10.1
battery= 7.78, 7.74
error= 3, 1
units= Radiance, Radiance
time= 9/19/2013 12:08:32 PM, 9/19/2013 12:08:53 PM
longitude= 07732.3414W , 07732.3417W
latitude= 4316.3654N , 4316.3657N
gpstime= 151249.000 , 151309.000
comm=
memory slot= 152, 153
factors= 1.053, 1.013, 1.000 [Overlap: Remove @ 980,1903, Matching Type: Radiance @ 961 - 1000
data=
334.0 7105.27 101.36 1.43
335.5 7798.39 129.59 1.66
337.0 8765.39 127.53 1.45
338.5 9767.27 162.84 1.67
340.0 10394.63 151.98 1.46
341.5 11282.51 197.12 1.75
```

# Text files manipulation

## SVC



# Outline

- ① Introduction
- ② Background
- ③ Taking Measurements
- ④ DIRS Instruments
- ⑤ Data Processing
- ⑥ Conclusions

# Field Campaigns

- Negative

- Weather dependent
- Extreme environmental conditions (too cold or too hot)
- Instrumentation failure
- Long days

- Positive

- Brings theory to practice
- Appreciate nature (nice to be outside your office)
- Get to know more about your colleagues
- Know new places
- It is FUN!

# Field Campaigns in Pictures

R·I·T

Rochester Institute of Technology



# Field Campaigns in Pictures

R·I·T Rochester Institute of Technology



# Field Campaigns in Pictures



Introduction  
oooooooooooo

Background  
oooooooo

Taking Measurements  
ooooooo

DIRS Instruments  
oo

Data Processing  
oooo

Conclusions  
oooo●oooooooooooo

# Field Campaigns in Pictures

R·I·T Rochester Institute of Technology



Introduction  
oooooooooooo

Background  
oooooooo

Taking Measurements  
ooooooo

DIRS Instruments  
oo

Data Processing  
oooo

Conclusions  
ooooo●oooooooooooo

# Field Campaigns in Pictures

R·I·T Rochester Institute of Technology



# Field Campaigns in Pictures



# Field Campaigns in Pictures



# Field Campaigns in Pictures



# Field Campaigns in Pictures



# Field Campaigns in Pictures



# Field Campaigns in Pictures



Introduction



Background



Taking Measurements



DIRS Instruments



Data Processing



Conclusions



# Field Campaigns in Pictures

R·I·T

Rochester Institute of Technology



Introduction  
oooooooooooo

Background  
oooooooo

Taking Measurements  
ooooooo

DIRS Instruments  
oo

Data Processing  
oooo

Conclusions  
oooooooooooooooo●oooooo

# Field Campaigns in Pictures

R·I·T Rochester Institute of Technology



Introduction  
oooooooooooo

Background  
oooooooo

Taking Measurements  
ooooooo


DIRS Instruments  
oo

Data Processing  
oooo


Conclusions  
oooooooooooooooooooo

# Field Campaigns in Pictures

R·I·T Rochester Institute of Technology



# Field Campaigns in Pictures



# Field Campaigns in Pictures



# Field Campaigns in Pictures



# Field Campaigns in Pictures

R·I·T Rochester Institute of Technology



Thanks for your attention!

QUESTIONS?



Thanks for your attention!

# QUESTIONS?



# References



[[Mobley, 2010]

Ocean optics web book.

<http://www.oceanopticsbook.info/>.

]Mobley, C. D. (2010).