

QUOTATION REQUEST — FINAL PRODUCT SPECIFICATION

Ekio Light — Core Recovery and Core Beauty

v2.0 · 2026-08-20

This is a request for quotation, based on the specification below — not a purchase order. Please do not begin production, tooling, or component procurement based on this document. We need your formal budget (unit pricing, packaging/manual production cost, lead time, and payment terms) before we place an order. This specification consolidates the technical brief we sent on 2026-07-27, your confirmed answers to it, and your confirmed answers on LED quality and irradiance data.

1. WHAT WE WANT TO ORDER

Two new variants of the **Ekio Light Core** device you currently produce for us, on the same chassis:

Product	LEDs	Package	Wavelengths	Status
Core (current, reference only — not part of this quote)	13	Dual-die chip	660 · 850 nm	In production
Core Recovery	13	Tri-die chip	660 · 810 · 940 nm	New — please quote
Core Beauty	13	Tri-die chip	590 · 630 · 670 nm	New — please quote

2. CONFIRMED SPECIFICATION

The following is now final. Please quote against this specification as written.

2.1 Shared with the current Core (unchanged)

- Chassis and mold: 162 × 90 × 45 mm — same mold, no modifications.
- 13 LED emitters, same physical layout on the PCB.
- Rechargeable battery, USB-C charging.
- Lifespan >20,000 hours.
- Zero visible flicker, low electromagnetic field emission.
- Base certifications: RoHS, CE, WEEE.

2.2 Confirmed by you

- Both tri-die packages exist: **660/810/940 nm** and **590/630/670 nm**.
- PCB supports **3 independent driver channels**.
- The 3 dies cannot run at full current simultaneously; **product maximum power is 10 W**, shared across dies in combined mode.
- No new CE testing required for the electrical/EMC baseline.
- **LED chip quality (brand, batch consistency, lifespan) and irradiance data (mW/cm² per band and combined) — confirmed as satisfactory.** Thank you.

2.3 Core Recovery — specification

- Wavelengths: **660 · 810 · 940 nm**, tri-die chip, all 13 positions.
- **Single mode only**: all three bands fire together — no independent per-band selection.
- CW and 10 Hz pulsed as mode options (applied to the combined output).
- Hardware thermal cutoff via NTC sensor + comparator (exact threshold to be confirmed with you).
- No substitutions accepted without prior consultation: 810 nm ≠ 800/830 nm; 940 nm ≠ 850/880 nm; no "905 nm" LEDs (does not exist as a precision LED).
- **Chassis color: black**. Suggestions welcome if you have a finish or shade that looks better on this chassis.

2.4 Core Beauty — specification

- Wavelengths: **590 · 630 · 670 nm**, tri-die chip, all 13 positions.
- **Single mode only**: all three bands fire together — no independent per-band selection, no user-selectable intensity levels.
- No infrared (no 810, 850, or any band above 700 nm).
- No blue or violet (405, 450, 485 nm).
- Auto shut-off timer enabled by default, not trivial for the user to disable (exact timing to be confirmed with you).
- CW mandatory; 10 Hz pulsed optional.
- **Chassis color: gold**. Suggestions welcome if you have a finish or shade that looks better on this chassis.

2.5 Packaging and manuals

- We are designing **custom packaging and a custom instruction manual for each model** (Core Recovery and Core Beauty). We will provide artwork and specifications separately — this is not a reuse of the current Core box.

2.6 Marketing/regulatory note

- Both products are marketed as **wellness devices**, not medical devices. Product documentation must not contain therapeutic or clinical claims.

3. WHAT WE NEED IN YOUR QUOTATION

Please provide:

1. **Unit price per variant**.
2. **Packaging and manual production cost per variant**, based on our own custom design (artwork/specs to follow).
3. **Production lead time** from confirmed PO to delivery, for each variant.
4. **Payment terms** (deposit %, balance on shipment, etc.).

4. TARGET DATE

For planning purposes: our target is to have **both Core Recovery and Core Beauty in stock by early November 2026**, ahead of Black Friday. Please tell us in your quotation whether your lead time makes this realistic, and if not, what the earliest realistic date is.

Please reply with your quotation referencing the section numbers above.