

OPERATION CARBON FOOTPRINT

535.03 ± 0.66 kgCO_{2e}

Audited to ISO 14083 / GLEC v3.1 · Omega (Ω) Engine mass allocation

Issued · audited measurement

Carbon intensity

ECI

ECI not applicable — empty haul

EcoTrace Index — not a regulatory standard

Veracity

VCI

97.2 %

Certified

050 · reject floor100

Confidence in the figure — signal, physics & parameters.
Not a measure of emissions level.

OPERATION DETAILS

Operator	Northbridge Logistics	Vehicle	Medium_Duty
Depot	Manchester	Operation type	long_haul
Segments	loaded 3 · empty 1	Empty-mileage	18.3%
Loaded tkm	-811.4		

PER-SKU ALLOCATION

SKU 1	93.94 kgCO _{2e}
SKU 2	105.71 kgCO _{2e}
SKU 3	335.37 kgCO _{2e}
Allocated	535.03 kgCO _{2e}

TRUST & VERIFICATION

Certificate SHA-256
ccfb5127399742a79c3cbd83579432fc1c8c2196074c02fb added7cf0a2f9927de

Timestamp
Timestamped — RFC 3161 (DigiCert) · 2026-07-02T18:28:38+00:00



Scan to verify at
verify.ecotracedgreen.com

How to read this certificate

The audited figure is the CO₂e computed to the ISO 14083 / GLEC standard. Everything else is an EcoTrace reading aid that helps you interpret it.

1

The audited figure — CO₂e (ISO 14083)

The carbon footprint is computed to the ISO 14083 / GLEC standard — an audited methodology. This is the only regulatory figure on the certificate; the indices below are interpretive aids.

2

ECI — the energy label of a transport operation

Like an EU appliance's A–G label, the Carbon Intensity (ECI) grades an operation by grams of CO₂e per tonne·kilometre — its carrying efficiency — using the cargo mass identified by the Omega (Ω) Engine, not the declared mass. The grade compares the operation against a GLEC benchmark.

GRADE	INTENSITY VS BENCHMARK
 A	$\leq 0.60\times$ benchmark
 B	$\leq 0.75\times$ benchmark
 C	$\leq 0.90\times$ benchmark
 D	$\leq 1.10\times$ benchmark
 E	$\leq 1.30\times$ benchmark
 F	$\leq 1.60\times$ benchmark
 G	$> 1.60\times$ benchmark

3

VCI — reliability of the measurement, not the amount of CO₂e

The Veracity (VCI) score is the confidence in the figure, expressed 0–100%. A high VCI does not mean low emissions — it means high confidence in the figure. It combines three drivers: **signal** (sufficient fuel and GPS data), **physics** (the model satisfied the conservation laws) and **parameters** (drivetrain values within admissible bands). Below 50% the measurement is rejected — not trustworthy enough to certify.



Transparency. CO₂e is computed to ISO 14083 / GLEC (an audited standard). ECI and VCI are proprietary EcoTrace indices, provided as reading aids — they are not regulatory standards.