

OPERATION CARBON FOOTPRINT

470.29 ± 0.39 kgCO_{2e}



Audited to ISO 14083 / GLEC v3.1 · Omega (Ω) Engine mass allocation

Issued · audited measurement

Carbon intensity

ECI

262.7

gCO_{2e}/tkm

G

A

B

C

D

E

F

G

4.24× the GLEC benchmark (62) — indicative, pending certified values.

Veracity

VCI

97.0

%

Certified

0

50 · reject floor

100

Confidence in the figure — signal, physics & parameters.
Not a measure of emissions level.

OPERATION DETAILS

Operator	Meridian Haulage Ltd	Vehicle	Standard_HGV
Depot	Hull	Operation type	long_haul
Segments	loaded 1 · empty 1	Empty-mileage	50.0%
Loaded tkm	1790.4		

PER-SKU ALLOCATION

SKU 1	470.29 kgCO _{2e}
Allocated	470.29 kgCO _{2e}

TRUST & VERIFICATION

Certificate SHA-256
67a3846ed0e9a0e1880d2cd41bb8674eb078e904ca4ba6fd62627a63f0b9a8d2

Timestamp
Timestamped — RFC 3161 (DigiCert) · 2026-07-02T18:28:17+00:00

Scan to verify at
verify.ecotracegreen.com

How to read this certificate

The audited figure is the CO₂e computed to the ISO 14083 / GLEC standard. Everything else is an EcoTrace reading aid that helps you interpret it.

1 The audited figure — CO₂e (ISO 14083)

The carbon footprint is computed to the ISO 14083 / GLEC standard — an audited methodology. This is the only regulatory figure on the certificate; the indices below are interpretive aids.

2 ECI — the energy label of a transport operation

Like an EU appliance's A–G label, the Carbon Intensity (ECI) grades an operation by grams of CO₂e per tonne·kilometre — its carrying efficiency — using the cargo mass identified by the Omega (Ω) Engine, not the declared mass. The grade compares the operation against a GLEC benchmark.

GRADE	INTENSITY VS BENCHMARK
 A	≤ 0.60× benchmark
 B	≤ 0.75× benchmark
 C	≤ 0.90× benchmark
 D	≤ 1.10× benchmark
 E	≤ 1.30× benchmark
 F	≤ 1.60× benchmark
 G	> 1.60× benchmark · this operation

3 VCI — reliability of the measurement, not the amount of CO₂e

The Veracity (VCI) score is the confidence in the figure, expressed 0–100%. A high VCI does not mean low emissions — it means high confidence in the figure. It combines three drivers: **signal** (sufficient fuel and GPS data), **physics** (the model satisfied the conservation laws) and **parameters** (drivetrain values within admissible bands). Below 50% the measurement is rejected — not trustworthy enough to certify.

-  **Transparency.** CO₂e is computed to ISO 14083 / GLEC (an audited standard). ECI and VCI are proprietary EcoTrace indices, provided as reading aids — they are not regulatory standards.