

THOUGHTS ON JAVA

BLOG ▼

VIDEOS

BOOK

TRAINING

WORK WITH ME

TOJ SUPPORTER

ABOUT ▼

MEMBER LIBRARY

Special thanks to all [Thoughts on Java Supporters](#) for supporting this article:

How to generate UUIDs as primary keys with Hibernate

By [Thorben Janssen](#) — 7 Comments

tweet

share

share

share

share

share

e-mail



Most developers prefer numerical primary keys because they are efficient to use and [easy to generate](#). But that doesn't mean that a primary key has to be a number.

UUIDs, for example, have gained some popularity over the recent years. The main advantage of a UUID is its (practical) global uniqueness which provides a huge advantage for distributed systems.

If you use the typical, numerical ID that gets incremented for each new record, you need to generate all IDs by the same component of your system or the components need to communicate with each other. With a globally unique UUID, you don't need all of this. Each component can generate a UUID and there will not be any conflicts.

THOUGHTS ON JAVA

[BLOG ▼](#)[VIDEOS](#)[BOOK](#)[TRAINING](#)[WORK WITH ME](#)[TOJ SUPPORTER](#)[ABOUT ▼](#)[MEMBER LIBRARY](#)

[Follow me on YouTube](#) to not miss any new videos.

On the other hand, the UUID also has some disadvantages. The most obvious one is its size. It's 4 times larger than a numerical ID and can't be handled as efficiently. You should, therefore, decide carefully if you want to use UUIDs or numeric IDs and discuss it with your database administrator.

If you decide to use UUIDs, you can, of course, also persist them with Hibernate. With just a few additional annotations, you can even let Hibernate generate the UUIDs for you.

Generate UUIDs with Hibernate

The [IETF RFC 4122](#) defines 4 different strategies to generate UUIDs. Hibernate's UUIDGenerator supports 2 of them:

1. The default strategy generates the UUID based on random numbers (IETF RFC 4122 Version 4).
2. You can also configure a generator that uses the IP address of the machine and a timestamp (IETF RFC 4122 Version 1).

Let's have a look at the default strategy first.

Join the [Thoughts on Java Library](#)

THOUGHTS ON JAVA

[BLOG ▼](#)[VIDEOS](#)[BOOK](#)[TRAINING](#)[WORK WITH ME](#)[TOJ SUPPORTER](#)[ABOUT ▼](#)

MEMBER LIBRARY

- ✔ More than 60 printable Hibernate Tips
- ✔ A 3-Part Video Course about Finding and Fixing N+1 Select Issues

Signup For Free:

JOIN NOW!

Already a member? [Login here.](#)

Random number based UUID (IETF RFC 4122 version 4)

By default, Hibernate uses a random number based generation strategy. As always, you don't have to do much to get the default behaviour. You just need to add a `@GeneratedValue` annotation that references the ID generator to your primary key attribute and define the generator with one of Hibernate's `@GenericGenerator` annotations. The `@GenericGenerator` annotation requires 2 parameters, the name of the generator and the name of the class that implements the generator. In this case, it's the `org.hibernate.id.UUIDGenerator`.

That's all you have to do to let Hibernate generate UUIDs as primary key values. You can see an example of it in the following code snippet.

THOUGHTS ON JAVA

[BLOG ▼](#)[VIDEOS](#)[BOOK](#)[TRAINING](#)[WORK WITH ME](#)[TOJ SUPPORTER](#)[ABOUT ▼](#)

MEMBER LIBRARY

```
7      /
10     @Column(name = "id", updatable = false, nullable = false)
11     private UUID id;
12
13     ...
14 }
```

UUIDVersion4.java hosted with ❤ by GitHub

[view raw](#)

When you now persist a new *Book* entity, Hibernate generates a UUID before writing the new record to the database.

```
1 Book b = new Book();
2 b.setTitle("The Hound of the Baskervilles");
3 b.setPublishingDate(LocalDate.of(1902, 4, 30));
4 em.persist(b);
```

PersistBookEntity.java hosted with ❤ by GitHub

[view raw](#)

```
1 12:23:19,356 DEBUG AbstractSaveEventListener:118 - Generated identifier: d7cd23b8-991c-470f-ac63-d8fb106f391e, using
2 12:23:19,388 DEBUG SQL:92 - insert into Book (publishingDate, title, version, id) values (?, ?, ?, ?)
3 12:23:19,392 TRACE BasicBinder:65 - binding parameter [1] as [DATE] - [1902-04-30]
4 12:23:19,393 TRACE BasicBinder:65 - binding parameter [2] as [VARCHAR] - [The Hound of the Baskervilles]
5 12:23:19,393 TRACE BasicBinder:65 - binding parameter [3] as [INTEGER] - [0]
6 12:23:19,394 TRACE BasicBinder:65 - binding parameter [4] as [OTHER] - [d7cd23b8-991c-470f-ac63-d8fb106f391e]
```

UUIDVersion4.log hosted with ❤ by GitHub

[view raw](#)

IP and timestamp based UUID (IETF RFC 4122 version 1)

Hibernate can also generate a UUID based on IETF RFC 4122 version 1. If you follow the specification, you should generate the UUID with the MAC address instead of the IP address. As long as nobody is messing around with it, the MAC address of each device should be unique and due to this help to create a unique UUID.

Hibernate uses the IP address instead of the MAC address. In general, this is not an issue. But if the servers of your distributed system are running in different networks you should make sure that none of them share the same IP address.

THOUGHTS ON JAVA

BLOG ▼

VIDEOS

BOOK

TRAINING

WORK WITH ME

TOJ SUPPORTER

ABOUT ▼

MEMBER LIBRARY

```
2 public class Book {
3
4     @Id
5     @GeneratedValue(generator = "UUID")
6     @GenericGenerator(
7         name = "UUID",
8         strategy = "org.hibernate.id.UUIDGenerator",
9         parameters = {
10             @Parameter(
11                 name = "uuid_gen_strategy_class",
12                 value = "org.hibernate.id.uuid.CustomVersionOneStrategy"
13             )
14         }
15     )
16     @Column(name = "id", updatable = false, nullable = false)
17     private UUID id;
18
19     ...
20 }
```

UUIDVersion1.java hosted with ❤ by GitHub

[view raw](#)

When you now persist the new *Book* entity, Hibernate will use the *CustomVersionOneStrategy* class to generate the UUID based on IETF RFC 4122 version 1.

```
1 Book b = new Book();
2 b.setTitle("The Hound of the Baskervilles");
3 b.setPublishingDate(LocalDate.of(1902, 4, 30));
4 em.persist(b);
```

PersistBookEntity.java hosted with ❤ by GitHub

[view raw](#)

```
1 12:35:22,760 DEBUG AbstractSaveEventListener:118 - Generated identifier: c0a8b214-578f-131a-8157-8f431d060000, using
2 12:35:22,792 DEBUG SQL:92 - insert into Book (publishingDate, title, version, id) values (?, ?, ?, ?)
3 12:35:22,795 TRACE BasicBinder:65 - binding parameter [1] as [DATE] - [1902-04-30]
4 12:35:22,795 TRACE BasicBinder:65 - binding parameter [2] as [VARCHAR] - [The Hound of the Baskervilles]
5 12:35:22,796 TRACE BasicBinder:65 - binding parameter [3] as [INTEGER] - [0]
6 12:35:22,797 TRACE BasicBinder:65 - binding parameter [4] as [OTHER] - [c0a8b214-578f-131a-8157-8f431d060000]
```

UUIDVersion1.log hosted with ❤ by GitHub

[view raw](#)

THOUGHTS ON JAVA

[BLOG ▼](#)[VIDEOS](#)[BOOK](#)[TRAINING](#)[WORK WITH ME](#)[TOJ SUPPORTER](#)[ABOUT ▼](#)

MEMBER LIBRARY

▼ 2 EBOOKS ABOUT JPA AND HIBERNATE

✓ More than 50 Cheat Sheets

✓ More than 60 printable Hibernate Tips

✓ A 3-Part Video Course about Finding and Fixing N+1 Select Issues

Signup For Free:

JOIN NOW!

Already a member? [Login here.](#)

Summary

As you've seen, you can also use UUIDs as primary keys and let Hibernate handle the value generation. Hibernate's UUIDGenerator supports the creation of version 1 and version 4 UUIDs as defined by IETF RFC 4122. By default, it generates version 4 UUIDs which is a good fit for most use cases.

Unfortunately, this is not part of the JPA specification and will require some adaptations, if you need to switch your JPA implementation.

THOUGHTS ON JAVA

BLOG ▼

VIDEOS

BOOK

TRAINING

WORK WITH ME

TOJ SUPPORTER

ABOUT ▼

MEMBER LIBRARY

Implement Your Persistence Layer with Ease

[Learn More About Hibernate](#)

Need Some Help with Your Project?

THOUGHTS ON JAVA

[BLOG ▼](#)[VIDEOS](#)[BOOK](#)[TRAINING](#)[WORK WITH ME](#)[TOJ SUPPORTER](#)[ABOUT ▼](#)[MEMBER LIBRARY](#)

Comments

Daniel Pozzi says

October 6, 2016 at 1:25 pm

Does hibernate automatically know the best way to store the UUID? I've seen this suggestion on stackoverflow:

```
@Column(name = "id", columnDefinition = "BINARY(16)")
```

[Reply](#)

Thorben Janssen says

October 6, 2016 at 1:46 pm

That depends on the database specific dialect. If you're using PostgreSQL (as I do in this example), Hibernate PostgreSQL dialect will map it to the PostgreSQL-specific UUID datatype.

[Reply](#)

Steve Ebersole says

October 14, 2016 at 2:08 am

THOUGHTS ON JAVA

[BLOG ▼](#)[VIDEOS](#)[BOOK](#)[TRAINING](#)[WORK WITH ME](#)[TOJ SUPPORTER](#)[ABOUT ▼](#)

MEMBER LIBRARY

donald.coffin@reminetworks.com says

November 5, 2017 at 5:06 pm

Is it possible to generate a Version 5 UUID using Hibernate?

[Reply](#)

Thorben Janssen says

November 21, 2017 at 7:48 pm

No, unfortunately not.

[Reply](#)

Menai Ala Eddine says

March 21, 2018 at 4:21 pm

Hi Thorben Janssen ,You have greal tuto ,this post helped me to understand UUID ,i will read all posts about Hibernate ,you give a great descriptions .

Best regards

[Reply](#)

Thorben Janssen says

April 21, 2018 at 2:58 pm

Thanks 😊

[Reply](#)

THOUGHTS ON JAVA

[BLOG ▼](#)[VIDEOS](#)[BOOK](#)[TRAINING](#)[WORK WITH ME](#)[TOJ SUPPORTER](#)[ABOUT ▼](#)

MEMBER LIBRARY

Name *


Email *

Website

POST COMMENT

This site uses Akismet to reduce spam. [Learn how your comment data is processed.](#)

Join over 7.000 developers
in the
Thoughts on Java Library



THOUGHTS ON JAVA

BLOG ▼

VIDEOS

BOOK

TRAINING

WORK WITH ME

TOJ SUPPORTER

ABOUT ▼

MEMBER LIBRARY

Don't like ads?

Become a Thoughts on Java Supporter.

Build your persistence layer
with ease



Get it Now!

LET'S CONNECT



Thorben Janssen

Independent consultant, trainer
and author

THOUGHTS ON JAVA

[BLOG ▼](#)[VIDEOS](#)[BOOK](#)[TRAINING](#)[WORK WITH ME](#)[TOJ SUPPORTER](#)[ABOUT ▼](#)[MEMBER LIBRARY](#)

[Hibernate für Fortgeschrittene
\(1-day Workshop - German\)](#)

12th September 2018

Workshop-Tage 2018

(Switzerland):

[Hibernate + jOOQ + Flyway = Die
besten relationalen
Persistenzframeworks in einem
Stack \(1-day Workshop -
German\)](#)

13th September 2018

Workshop-Tage 2018

(Switzerland):

[Spring Data JDBC – Der neue
Stern am Persistenzhimmel? \(1-
day Workshop - German\)](#)

9th-10th October 2018

Geecon (Poland):

[Performance Tuning with JPA 2.2
and Hibernate Workshop \(2-day
Workshop - English\)](#)

5th-9th November 2018

W-JAX 2018 (Germany):

[Hibernate-Workshop –
Performance-Tuning für
Enterprise-Anwendungen \(1-day
Workshop - German\)](#)

5th-9th November 2018

W-JAX 2018 (Germany):

[Das Hibernate-Universum –
Fernab bekannter CRUD-
Galaxien \(Talk - German\)](#)

Looking for an [on-site training?](#)


THOUGHTS ON JAVA

[BLOG ▼](#)[VIDEOS](#)[BOOK](#)[TRAINING](#)[WORK WITH ME](#)[TOJ SUPPORTER](#)[ABOUT ▼](#)[MEMBER LIBRARY](#)

Getting Started With Hibernate



12 Java YouTube Channels You Should Follow In 2018



Ultimate Guide – Association Mappings with JPA and Hibernate



Ultimate Guide to JPQL Queries with JPA and Hibernate



Hibernate Best Practices

RECENT POSTS

THOUGHTS ON JAVA

[BLOG ▼](#)[VIDEOS](#)[BOOK](#)[TRAINING](#)[WORK WITH ME](#)[TOJ SUPPORTER](#)[ABOUT ▼](#)[MEMBER LIBRARY](#)

[Hibernate Tips: Permanently remove records when using soft delete](#)

[How to lazily load non-relational attributes in a portable way](#)

[Hibernate Tips: Map an Unidirectional One-to-Many Association Without a Junction Table](#)

[Hibernate Tips: Get the SQL Connection used by your Hibernate Session](#)

[5 Reasons and 101 Bugfixes – Why You Should Use Hibernate 5.3](#)

[Update your Database Schema Without Downtime](#)

[Hibernate Tips: How to Call a Function that returns a SYS_REFCURSOR](#)

THOUGHTS ON JAVA

BLOG ▼

VIDEOS

BOOK

TRAINING

WORK WITH ME

TOJ SUPPORTER

ABOUT ▼

MEMBER LIBRARY



Don't like ads?
Become a Thoughts on Java
Supporter.

Copyright © 2018 [Thoughts on Java](#)

[Impressum](#) [Disclaimer](#) [Privacy Policy](#)