


[LINUX](#)
[MAC OS](#)
[BSD](#)
[UNIX](#)
[SHELL SCRIPTING](#)
[WEB SERVERS](#)
[WINDOWS](#)
[VIRTUALIZATION](#)
[DATABASES](#)
[MONITORING](#)
[IOT](#)
[MORE](#)
[META SCG](#)
[Home](#) » [Linux](#) » Adjusting Linux Kernel Parameters with Docker Compose

ABOUT BEN CANE



Benjamin Cane is a systems architect in the financial services industry. He writes about Linux systems administration on his blog and has recently published his first book, Red Hat Enterprise Linux Troubleshooting Guide.

Adjusting Linux Kernel Parameters with Docker Compose

Posted by: Ben Cane in Linux December 20th, 2017

Docker Compose is a great utility for anyone developing Dockerized applications. It's a tool that I personally use daily. Recently I came across yet another powerful feature of Docker Compose: the ability to change Linux Kernel Parameters.

In today's article, we will explore how to use this often overlooked but "useful when you need it" feature of Docker Compose.

To get started however, let's first create a Redis service using Docker Compose.

Starting with a Simple Redis Service

Docker Compose is a tool that allows users to create Dockerized services with a simple YAML file. To get a better understanding of how this works, let's go ahead and create

an example

```
docker-compose.yml
```

```
1 version: '3'
2 services:
3   redis:
4     image: redis:latest
```

In the above example, we have a single "service" named

```
redis
```

. This service definition is how Docker Compose allows users to define different services. Docker Compose will take these services and run them within Docker containers.

In the example above, the

```
redis
```

service is provided by a container using the

```
redis:latest
```

image. To start this service, we can simply execute the

```
docker-compose
```

command followed by the



The VirtualBox Essentials

- Get started with the open source virtualization platform
- Perform basic configuration, clone, export, import, and remove VMachines
- Get your own Virtual Machines up and running in minimum time

[Download for Free](#)

NEWSLETTER

13,218 insiders are already receiving weekly updates and complimentary whitepapers!

Join them now to gain **access** to the latest news in the Linux and OS developers world, as well as about IoT, embedded programming, scripting languages and technologies.

Email address:

[Sign up](#)

JOIN US



With **1,500** unique and placed articles on resource sites across the web

```

04 Creating rediscomposeexample_redis_1 ... done
05 Attaching to rediscomposeexample_redis_1
06 redis_1 | 1:C 12 Oct 03:57:02.915 # Warning: no config file specified, using the default config. In order
to specify a config file use redis-server /path/to/redis.conf
07 redis_1 | 1:M 12 Oct 03:57:02.937 # WARNING: The TCP backlog setting of 511 cannot be enforced because
/proc/sys/net/core/somaxconn is set to the lower value of 128.
08 redis_1 | 1:M 12 Oct 03:57:02.937 # Server started, Redis version 3.2.6
09 redis_1 | 1:M 12 Oct 03:57:02.939 # WARNING you have Transparent Huge Pages (THP) support enabled in your
kernel. This will create latency and memory usage issues with Redis. To fix this issue run the command
'echo never > /sys/kernel/mm/transparent_hugepage/enabled' as root, and add it to your /etc/rc.local in
order to retain the setting after a reboot. Redis must be restarted after THP is disabled.
10 redis_1 | 1:M 12 Oct 03:57:02.940 * The server is now ready to accept connections on port 6379

```

In the above output, we can see that the

```
docker-compose up
```

command created a single container, named

```
rediscomposeexample_redis_1
```

As far as creating a single Redis container with Docker Compose, that is it. With only a few lines within a

```
docker-compose.yml
```

file and a single command, we have a running Redis container. However, this example doesn't show the power of Docker Compose.

To get a better idea of how Docker Compose is useful, let's add another container into the mix.

Multi-service Docker Compose

Since our first example used a Redis service, let's make our next container a bit more interesting. We will go ahead and add a Redis Commander service to our

```
docker-compose.yml
```

file.

Redis Commander is an application that allows users to explore a Redis instance through a browser. What this means is not only do we have to have an instance of Redis Commander, we also need to be able to connect it to our

```
redis
```

service.

```

1 version: '3'
2 services:
3   redis:
4     image: redis:latest
5   redis-commander:
6     image: tenstartups/redis-commander
7     command: --redis-host redis
8     ports:
9       - 8081:8081

```

In the above example, we added another service named

```
redis-commander
```

. This service will launch a container using the

```
tenstartups/redis-commander
```

image.

At this point, the

```
redis-commander
```

service would not be able to connect to the

```
redis
```

service. For these services to communicate, we need to define the dependency within the

```
docker-compose.yml
```

file.

We can do this by adding the

```
depends_on
```

key shown below.



The VirtualBox Essentials

- Get started with the open source virtualization platform
- Perform basic configuration, clone, export, import, and remove VMachines
- Get your own Virtual Machines up and running in minimum time

Download for Free

```
10 ports:
11 - 8081:8081
```

With our two services linked, let's go ahead and execute another

```
docker-compose up
```

```
01 $ docker-compose up
02 Creating network "rediscomposeexample_default" with the default driver
03 Creating rediscomposeexample_redis_1 ...
04 Creating rediscomposeexample_redis_1 ... done
05 Creating rediscomposeexample_redis-commander_1 ...
06 Creating rediscomposeexample_redis-commander_1 ... done
07 Attaching to rediscomposeexample_redis_1, rediscomposeexample_redis-commander_1
08 redis_1 | 1:C 16 Oct 20:56:51.613 # Warning: no config file specified, using the default
09 redis_1 | 1:M 16 Oct 20:56:51.618 # WARNING: The TCP backlog setting of 511 cannot be enforced
10 redis_1 | 1:M 16 Oct 20:56:51.618 # Server started, Redis version 3.2.6
11 redis_1 | 1:M 16 Oct 20:56:51.619 # WARNING you have Transparent Huge Pages (THP) support
12 redis_1 | 1:M 16 Oct 20:56:51.619 * The server is now ready to accept connections on port 6379
13 redis-commander_1 | No Save: true
14 redis-commander_1 | listening on 0.0.0.0 : 8081
15 redis-commander_1 | Redis Connection redis:6379 Using Redis DB #0
```

In the above example, we can see there are two Docker containers running: a

```
redis
```

container as well as a

```
redis-commander
```

container.

This is a much better example of why Docker Compose is a powerful tool. In this example, we quickly specified multiple services within a single YAML file. We then turn those services into linked Docker containers with a single command.

We can also copy this

```
docker-compose.yml
```

file to any server and start up these same services. So not only is Docker Compose useful for local development, it can also be useful for deployment.

!Sign up for a free Codeship Account

Modifying Kernel Parameters with Docker Compose

Now that we have a better idea of what Docker Composes is and how it works, let's get to an uncommon feature: using Docker Compose to change Linux Kernel Parameters of our services.

If we look back at the output from our above example when we started the

```
redis
```

service, we can see a couple of warnings. One of those warnings is in regards to the

```
somaxconn
```

setting.

```
1 redis_1 | 1:M 16 Oct 20:56:51.618 # WARNING: The TCP backlog setting of 511 cannot be enforced
because /proc/sys/net/core/somaxconn is set to the lower value of 128.
```

The

```
somaxconn
```

parameter is a Linux Kernel Parameter that specifies the maximum backlogged TCP/IP sockets. This parameter is a setting in Linux that by default is set to

```
128
```

. This means that the kernel will only allow

```
128
```

connections to be "backlogged" at a time.

For highly accessed services like Redis, this may not be enough. The error above shows that Redis was attempting to use a value of



The VirtualBox Essentials

- Get started with the open source virtualization platform
- Perform basic configuration, clone, export, import, and remove VMachines
- Get your own Virtual Machines up and running in minimum time

Download for Free

value is the default of

128

, Redis was not able to use a value of

511

In a non-containerized world, changing this kernel parameter would be as simple as placing the following into the

/etc/sysctl.conf

file.

```
1 net.core.somaxconn=1024
```

After adding the above, you would simply execute

```
sysctl -p
```

. However, in the container world this is a bit different.

We could perform the same tasks via a

Dockerfile

. However in our example, we are using public images from DockerHub. A simpler approach would be to specify this setting within the

docker-compose.yml

file itself.

To do this, we simply need to add the

```
sysctl
```

key as shown below.

```
01 version: '3'
02 services:
03   redis:
04     image: redis:latest
05     sysctls:
06       net.core.somaxconn: 1024
07   redis-commander:
08     image: tenstartups/redis-commander
09     command: --redis-host redis
10     depends_on:
11       - redis
12     ports:
13       - 8081:8081
```

In the above, we added two simple lines. These two lines will set the

```
net.core.somaxconn
```

parameter to

```
1024
```

. This is well above the

```
511
```

value Redis was trying to use.

Let's see what happens if we once again execute a

```
docker-compose up
```

command.

```
1 $ docker-compose up redis
2 Recreating rediscomposeexample_redis_1 ...
3 Recreating rediscomposeexample_redis_1 ... done
4 Attaching to rediscomposeexample_redis_1
5 redis_1 | 1:C 16 Oct 21:27:24.423 # Warning: no config file specified, using the default
6 redis_1 | 1:M 16 Oct 21:27:24.426 # Server started, Redis version 3.2.6
7 redis_1 | 1:M 16 Oct 21:27:24.427 # WARNING you have Transparent Huge Pages (THP) support
8 redis_1 | 1:M 16 Oct 21:27:24.427 * DB loaded from disk: 0.000 seconds
9 redis_1 | 1:M 16 Oct 21:27:24.427 * The server is now ready to accept connections on port 6379
```



The VirtualBox Essentials

- Get started with the open source virtualization platform
- Perform basic configuration, clone, export, import, and remove VMachines
- Get your own Virtual Machines up and running in minimum time

Download for Free

to the command. This is a way of telling Docker Compose to only bring up the

```
redis
```

service.

If we look at the above, we can see that the warning around the

```
somaxconn
```

value is gone. This means with two simple lines, we were successful in changing the Redis container's

```
somaxconn
```

kernel parameter.


Summary

In today's article, we went through a little refresher on Docker Compose. We explored how it is useful for launching multiple connected containers. Finally, we also learned an often overlooked feature, one we can use to easily change the Linux Kernel Parameters within our containers.

Published on System Code Geeks with permission by Ben Cane, partner at our SCG program. See the original article here: [Adjusting Linux Kernel Parameters with Docker Compose](#)

Opinions expressed by System Code Geeks contributors are their own.

Do you want to know how to develop your skillset to become a sysadmin Rockstar?



Subscribe to our newsletter to start Rocking right now!
To get you started we give you our best selling eBooks for **FREE!**

1. Introduction to NGINX
2. Apache HTTP Server Cookbook
3. VirtualBox Essentials
4. Nagios Monitoring Cookbook
5. Linux BASH Programming Cookbook
6. PostgreSQL Database Tutorial

and many more

Email address:

Tagged with: DOCKER

Leave a Reply

1 Comment on "Adjusting Linux Kernel Parameters with Docker Compose"

Notifv of ☐ new follow-up comments

Email ☐

>



The VirtualBox Essentials

- Get started with the open source virtualization platform
- Perform basic configuration, clone, export, import, and remove VMachines
- Get your own Virtual Machines up and running in minimum time

Sort by: newest

Fred

Excellent, thanks. I was just about to containerized Redis!

Guest

3 days 17 hours ago

KNOWLEDGE BASE

[Courses](#)

[Minibooks](#)

THE CODE GEEKS NETWORK

[.NET Code Geeks](#)

[Java Code Geeks](#)

[System Code Geeks](#)

[Web Code Geeks](#)

HALL OF FAME

[Apache Configuration Tutorial \(CentOS / Ubuntu Linux\)](#)

[Apache enable SSL / TLS tutorial](#)

[Apache mod_rewrite example: Redirecting and rewriting URLs](#)

[Apache name-based Virtual Host Configuration Example \(and setting bandwidth usage limits\)](#)

[Apache URL rewrite example: Rewriting and redirecting URLs with mod_rewrite](#)

[How to install the Apache web server \(CentOS / Ubuntu Linux Installation\)](#)

[Linux sed Examples](#)

[Nginx Configuration Guide \(Ubuntu 12.04 LTS\)](#)

[Nginx SSL configuration guide \(Ubuntu 12.04 LTS\)](#)

[Nginx Websockets proxying guide \(Ubuntu 12.04 LTS\)](#)

ABOUT SYSTEM CODE GEEKS

SCGs (System Code Geeks) is an independent online community focused on ultimate Operating System developers resource center; targeted at the architect, technical team lead (senior developer), project manager and alike. SCGs serve the OS developer, OS engineer and DevOps community with written by domain experts, articles, tutorials, reviews, announcements and open source projects.

DISCLAIMER

All trademarks and registered trademarks appearing on System Code Geeks are the property of their respective owners.

System Code Geeks and all content copyright © 2010-2017, Exelisis Media P.C. | [Terms of Use](#) | [Privacy Policy](#) | [Contact](#)

The VirtualBox Essentials

- Get started with the open source virtualization platform
- Perform basic configuration, clone, export, import, and remove VMachines
- Get your own Virtual Machines up and running in minimum time

[Download for Free](#)

<https://www.systemcodegeeks.com/linux/adjusting-linux-kernel-parameters-docker-compose/>

6/6