

(/)

Access a File from the Classpath in a Spring Application

Last modified: June 18, 2018

| by baeldung (/author/baeldung/)

Spring (/category/spring/) +

I just announced the new *Spring 5* modules in REST With Spring:

>> CHECK OUT THE COURSE (/rest-with-spring-course#new-modules)

1. Introduction

In this tutorial, we'll see various ways to access and load the contents of a file that's on the classpath using Spring.

2. Using *Resource*

The *Resource* interface helps in abstracting access to low-level resources. In fact, it supports handling of all kinds of file resources in a uniform manner. Let's start by looking at various methods to obtain a *Resource* instance.

2.1. Manually

For accessing a resource from the classpath, we can simply use *ClassPathResource*:

```
1 public Resource loadEmployees() {  
2     return new ClassPathResource("data/employees.dat");  
3 }
```

By default, *ClassPathResource* removes some boilerplate for selecting between the thread's context classloader and the default system classloader.

However, we can also indicate the classloader to use either directly:

```
1 return new ClassPathResource("data/employees.dat", this.getClass().get
```

Or indirectly through a specified class:

```
1 return new ClassPathResource(  
2     "data/employees.dat",  
3     Employee.class.getClassLoader());
```

Note that from *Resource*, we can easily jump to Java standard representations like *InputStream* or *File*.

2.2. Using @Value

We can also inject a *Resource* with *@Value*:

```
1 @Value("classpath:data/resource-data.txt")  
2 Resource resourceFile;
```

And *@Value* supports other prefixes, too, like *file:* and *url:*.

2.3. Using ResourceLoader

Or, if we want to lazily load our resource, we can use *ResourceLoader*:

```
1 | @Autowired
2 | ResourceLoader resourceLoader;
```

And then we retrieve our resource with *getResource*:

```
1 | public Resource loadEmployees() {
2 |     return resourceLoader.getResource(
3 |         "classpath:data/employees.dat");
4 | }
```

Note, too that *ResourceLoader* is implemented by all concrete *ApplicationContexts*, which means that we can also simply depend on *ApplicationContext* if that suits our situation better:

```
1 | ApplicationContext context;
2 |
3 | public Resource loadEmployees() {
4 |     return context.getResource("classpath:data/employees.dat");
5 | }
```

3. Using ResourceUtils

As a caveat, there is another way to retrieve resources in Spring, but the *ResourceUtils* Javadoc

(<https://docs.spring.io/spring/docs/current/javadoc-api/org/springframework/util/ResourceUtils.html>) is clear that the class is mainly for internal use.

If we see usages of *ResourceUtils* in our code:

```
1 | public File loadEmployeesWithSpringInternalClass()
2 |     throws FileNotFoundException {
3 |     return ResourceUtils.getFile(
4 |         "classpath:data/employees.dat");
5 | }
```

We should carefully consider the rationale as **it's probably better to use one of the standard approaches above.**

4. Reading Resource Data

Once we have a *Resource*, it's easy for us to read the contents. As we have already discussed, we can easily obtain a *File* or an *InputStream* reference from the *Resource*.

Let's imagine we have the following file, *data/employees.dat*, on the classpath:

```
1 | Joe Employee,Jan Employee,James T. Employee
```

4.1. Reading as a *File*

Now, we can read its contents by calling *getFile*:

```
1 | @Test
2 | public void whenResourceAsFile_thenReadSuccessful()
3 |     throws IOException {
4 |
5 |     File resource = new ClassPathResource(
6 |         "data/employees.dat").getFile();
7 |     String employees = new String(
8 |         Files.readAllBytes(resource.toPath()));
9 |     assertEquals(
10 |         "Joe Employee,Jan Employee,James T. Employee",
11 |         employees);
12 | }
```

Although, note that this approach **expects the resource to be present in the filesystem and not within a jar file**.

4.2. Reading as an *InputStream*

Let's say, though, that our resource *is* inside a jar.

Then, we can instead read a *Resource* as an *InputStream*:



```
1  @Test
2  public void whenResourceAsStream_thenReadSuccessful()
3      throws IOException {
4      InputStream resource = new ClassPathResource(
5          "data/employees.dat").getInputStream();
6      try (BufferedReader reader = new BufferedReader(
7          new InputStreamReader(resource))) {
8          String employees = reader.lines()
9              .collect(Collectors.joining("\n"));
10
11          assertEquals("Joe Employee,Jan Employee,James T. Employee", employees);
12      }
13  }
```

5. Conclusion

In this quick article, we've seen a few ways to access and read a resource from the classpath using Spring including eager and lazy loading and on the filesystem or in a jar.

And, as always, I've posted all these examples over on GitHub (<https://github.com/eugenp/tutorials/tree/master/spring-core>).

I just announced the new Spring 5 modules in REST With Spring:

>> CHECK OUT THE LESSONS (</rest-with-spring-course#new-modules>)

Leave a Reply



Start the discussion...

[✉ Subscribe ▼](#)

CATEGORIES

[SPRING \(/CATEGORY/SPRING/\)](/CATEGORY/SPRING/)[REST \(/CATEGORY/REST/\)](/CATEGORY/REST/)[JAVA \(/CATEGORY/JAVA/\)](/CATEGORY/JAVA/)[SECURITY \(/CATEGORY/SECURITY-2/\)](/CATEGORY/SECURITY-2/)[PERSISTENCE \(/CATEGORY/PERSISTENCE/\)](/CATEGORY/PERSISTENCE/)[JACKSON \(/CATEGORY/JACKSON/\)](/CATEGORY/JACKSON/)[HTTPCLIENT \(/CATEGORY/HTTP/\)](/CATEGORY/HTTP/)[KOTLIN \(/CATEGORY/KOTLIN/\)](/CATEGORY/KOTLIN/)

SERIES

[JAVA "BACK TO BASICS" TUTORIAL \(/JAVA-TUTORIAL\)](/JAVA-TUTORIAL)[JACKSON JSON TUTORIAL \(/JACKSON\)](/JACKSON)[HTTPCLIENT 4 TUTORIAL \(/HTTPCLIENT-GUIDE\)](/HTTPCLIENT-GUIDE)[REST WITH SPRING TUTORIAL \(/REST-WITH-SPRING-SERIES/\)](/REST-WITH-SPRING-SERIES/)[SPRING PERSISTENCE TUTORIAL \(/PERSISTENCE-WITH-SPRING-SERIES/\)](/PERSISTENCE-WITH-SPRING-SERIES/)[SECURITY WITH SPRING \(/SECURITY-SPRING\)](/SECURITY-SPRING)

ABOUT

[ABOUT BAELDUNG \(/ABOUT/\)](/ABOUT/)[THE COURSES \(HTTP://COURSES.BAELDUNG.COM\)](http://COURSES.BAELDUNG.COM)[CONSULTING WORK \(/CONSULTING\)](/CONSULTING)[META BAELDUNG \(HTTP://META.BAELDUNG.COM/\)](http://META.BAELDUNG.COM/)[THE FULL ARCHIVE \(/FULL_ARCHIVE\)](/FULL_ARCHIVE)[WRITE FOR BAELDUNG \(/CONTRIBUTION-GUIDELINES\)](/CONTRIBUTION-GUIDELINES)[CONTACT \(/CONTACT\)](/CONTACT)[EDITORS \(/EDITORS\)](/EDITORS)[MEDIA KIT \(PDF\) \(HTTPS://S3.AMAZONAWS.COM/BAELDUNG.COM/BAELDUNG+-+MEDIA+KIT.PDF\)](https://S3.AMAZONAWS.COM/BAELDUNG.COM/BAELDUNG+-+MEDIA+KIT.PDF)

[TERMS OF SERVICE \(/TERMS-OF-SERVICE\)](#)

[PRIVACY POLICY \(/PRIVACY-POLICY\)](#)

[COMPANY INFO \(/BAELDUNG-COMPANY-INFO\)](#)

