

[dustwell.com](#)[About Me](#)  
[Past Academic Work](#)

## Blog Posts

[How to hash passwords](#)  
[Snapshotting with Rsync](#)  
["An hour" vs. "A hour"](#)  
[Yes/No proposition bets](#)  
[div, span, and CSS "display:"](#)  
[Pair programming + screen](#)  
[SSH keys in 2 easy steps](#)  
[Fixing Your Flaky Internet](#)  
[How X-over-SSH works](#)  
[Drinking Distilled Water](#)  
[djb-dns installation](#)  
[Vim Cheat Sheet](#)  
[Oil ETFs leak money](#)

## SSH keys in 2 easy steps February 13, 2010

These are simple instructions that will let you ssh from one Linux machine to another without needing to type your password.

## Step 1) Generate your public signature

On your local machine (where you are ssh-ing *from*) type:

```
ssh-keygen
```

(Then hit ENTER to accept the default output file of `~/.ssh/id_rsa.pub` and ENTER again twice if you're lazy and want to use a blank passphrase.) Note that you only have to generate a key **once** per client machine - the same public key will be used to access all servers.

## Step 2) Copy your public signature to the server

Again, from your local machine, type:

```
cat ~/.ssh/id_rsa.pub | ssh remote_user@remote.example.com "cat >> ~/.ssh/authorized_keys"
```

(but replace `remote_user@remote.example.com` with your actual user and server.)

This fancy shell command **appends** the contents of your public signature to the end of the `~/.ssh/authorized_keys` file on the server. (If you did a simple `scp` it would overwrite any previous authorized keys you've stored.)

## You're done!

Next time you ssh into the server

```
ssh remote_user@remote.example.com
```

It should do this without prompting for any passwords.

0 Comments

Dustin Boswell's Blog




 Javier Martin Alon... ▾ Recommend Tweet Share

Sort by Oldest ▾



Be the first to comment.

---

 Subscribe  Add Disqus to your siteAdd DisqusAdd  Disqus' Privacy PolicyPrivacy PolicyPrivacy