

GRUMO

GRÚAS Y MONTAJES S. A. S.

EQUIM
EQUIPOS Y MONTAJES

SWEEP CHAIN CONVEYOR

**Save time and
money replace
your old sweeper
today!!!**

Factory & Offices
Calle 16 N° 10 - 42 Barrio Gaitán
+57 3045397024
info@equimsas.com
Bucaramanga – Colombia
www.equimsas.com

SWEEP CHAIN CONVEYOR

The chain sweeper is a piece of equipment designed for discharging residual grain stored in flat silos. Its main function is to move and transport the product toward the extraction systems using paddles that slide along the floor. This prevents accumulation inside the silo, ensuring a fast and efficient grain discharge without causing damage, while providing a uniform sweep.



REFERENCE	SILO DIAMETER	CAPACITY Ton/ hr
BC-25.60	Up to 60 ft	70
BC-25.78	Up to 78 ft	100
BC-25.90	Up to 90 ft	120

The data shown in the refers to corn.
Lengths according to silos diameter.

▪ Technical Advantages

- **Safety and reliability:** prevents the use of electrical extensions directly on the motor, which could cause a short circuit due to twisting and potentially trigger an explosion in the dusty environment inside the silo. Prevents personnel from entering the silo to manually advance the sweeper, as is required with screw-type sweepers.
- **Cleaning:** Provides greater floor cleanliness inside the silo due to the direct contact of the paddles with the floor, compared to screw-type sweepers.
- **Durability:** Less wear on moving parts thanks to the linear movement instead of a helical one, resulting in greater durability and lower maintenance costs.

The flow is adjusted according to the chain speed and the number of paddles, reaching capacities of 70 to 120 ton/hr, depending on the density and type of product stored in the silo.



Features

The sweeper is equipped with a slip ring system, which allows:

- Uninterrupted power supply during the sweeper's circular movement.
- Integration of safety sensors and control signals.