Data Access Guide

Analytical databases `wansoft` and `zenput` | Fonda Argentina | Version 1.8 (2026-10-22)

Contents

1. What is where 2
2. Golden rules (read before writing any query) 3
3. Branch crosswalk 4
4. Which table answers which question 6
   - 4.1 Available history 7
5. Domains 9
   - 5.1 Sales (Wansoft, all branches) 9
   - 5.2 Costs (Wansoft or Odoo, by branch) 9
   - 5.3 Purchases (Wansoft history + Odoo, merged) 11
   - 5.4 Inventory 13
   - 5.5 Zenput (zenput database) 15
   - 5.6 Governance tables 16
   - 5.7 Expenses: supplier invoices (Wansoft + Odoo) 16
6. Do not use 17
7. Freshness and schedule 17
8. Access 18
9. Still missing (under construction) 18
10. Version history 19

Appendix A. Table schemas 21
   - A.1 Sales 21
   - A.2 Costs 25
   - A.3 Purchases and invoices 28
   - A.4 Inventory 35
   - A.5 Governance and dimensions 43
   - A.6 Zenput (database zenput) 48

Audience: external teams building their own ETL on top of these databases (for example, a question-and-answer / chatbot layer). It tells you **which table to use for each business question, which fields matter, how tables join, and the traps to avoid**. Every rule here was checked against the live schema and data on 2026-09-28; the guide is current as of **2026-10-27**. Every table and column it names was confirmed to exist in production on 2026-10-07, and the full schema of every table (Appendix A) was taken from production on 2026-10-13. PDF version: data-access-guide.en.pdf.

Version 1.9 (2026-10-27). Every change to this guide raises its version number and is recorded in Section 10.

What is new in version 1.9 (compared with 1.8 of 2026-10-22):

- **New daily stock table, Wansoft + Odoo:** `analytics_inventory_stock_daily`, one row per branch × product × day, with the full history and every day (zero-stock days included). **It replaces the note "How to compute inventory (for now)" of 1.8** and the entries – exits formula (Sections 4, 4.1 and 5.4).
- **Supplier-invoice history corrected:** `analytics_expense_invoices` and `getexpenses_factura` are complete from **2023-01-01**; before that there are only scattered invoices (back to 2019-02-18). Version 1.8 said "since 2019-02-18" (Sections 4.1 and 5.7).
- **How to query the large inventory tables** without reading them whole, and the start date per branch (Sections 4.1 and 8).
- **Access:** 30 `wansoft` tables (`analytics_inventory_stock_daily` added).

1. What is where

Two MySQL (MariaDB 10.4) databases on the same server:

Database	Content
`wansoft`	Sales, costs, purchases, inventory and the unified analytical layer
`zenput`	Operational checklists (forms, answers) and tasks from Zenput

Source systems behind them:

Source	What it provides	How it arrives
Wansoft (POS/ERP)	Sales and cash closing for all branches; costs, purchases and inventory for branches not yet on Odoo, and the others' history	Daily download via its SOAP API
Odoo	Purchases, inventory and costs of the branches operating on Odoo, from their start date	Daily read-only extraction
Zenput	Checklists and tasks	Daily API download

Layers inside `wansoft`:

Layer	Tables	Use it for
Operational tables	`get*`, `costeomensual*`	Sales, cash closing and Wansoft-side detail (Wansoft copies); costs of every branch, computed from Wansoft or Odoo per branch (Section 5.2)
Canonical	`canonical_purchase_*`	Internal: Odoo and Wansoft purchases merged into one shape. Prefer the analytics layer

Analytics (business-ready)	`analytics_*`	Purchases and inventory for all branches, both sources merged
Dimensions	`dim_company_analytical`, `dim_product`, `dim_vendor`, `dim_time`	Descriptions and attributes for the analytics layer

2. Golden rules (read before writing any query)

1. **A branch is identified three different ways** depending on the table. Use the crosswalk in Section 3; never join tables on branch names blindly.
2. Short key (`Acoxpa`, `Oceanía`): sales tables (`Sucursal`) and the analytics layer (`company_source_key`).
3. **Numeric Wansoft id** (`5320`): costs (`subsidiary_id`) and the inventory tables — where the id is stored in a column confusingly named `subsidiary_name`.
4. Long Wansoft name (`Fonda Argentina - Acoxpa`): costs (`subsidiary_name`) and invoices (`getexpenses_factura.Sucursal`).
5. **`getexpenses_factura.Sucursal` contains the same branch spelled two ways** because of historical encoding damage (`Cancún` and `Canc??n`, `Oceanía` and `Ocean??a`). Map it to the crosswalk before grouping.
6. **Sales tables store amounts and dates as text** (`varchar`). Cast them: `CAST(Total AS DECIMAL(14,2))`, `DATE(Fecha)` (format `2026-09-01T00:00:00`).
7. **Analytics tables carry `include_in_business_views`.** Filter `include_in_business_views = 1` for business numbers; the other rows are kept for audit (internal providers, unmapped products, review cases) and carry an `exclude_reason`.
8. **Purchases and inventory come from two systems; the analytics layer already merges them without overlap** (Section 5.3). Do not rebuild the merge from raw tables.
9. **Data is loaded once a day, at about 01:30, through the previous day.** Each run also re-checks recent days (sales 10 days, costs and butchery 10, Wansoft invoices/inventory/cash closing 5, purchases 35), so the last few days can still change.
10. Costs tables are **cumulative snapshots**, not daily amounts (Section 5.2).

3. Branch crosswalk

Wansoft id	Short key (`sucursal`, `company_source_key`)	Wansoft long name (costs)	Odoo company	Purchases & inventory source	Odoo start date
5320	Acoxpa	Fonda Argentina - Acoxpa	FONDA COSTA NERA	Wansoft → **Odoo from 2026-10-01**	2026-10-01
4959	Aeropuerto	Fonda Argentina - Aeropuerto	FONDA ARGENTINA AEROPUERTO	Wansoft	—
4960	Antenas	Fonda Argentina - Antenas	FONDA ARGENTINA LAS ANTENAS	Wansoft → **Odoo from 2026-10-01**	2026-10-01
6175	Cancun	Fonda Argentina - Cancún	—	Wansoft	—
12802	CentroMyJ	Fonda Argentina - Centro Mario y July	MARIO Y JULY	Odoo (born on Odoo)	2026-06-01
4958	Isabel La Católica	Fonda Argentina - Isabel La Católica	FONDA ARGENTINA	Wansoft → **Odoo from 2026-10-01**	2026-10-01
12057	La Esquina Coyoacán	Fonda Argentina - Coyoacan	FONDA ARGENTINA COYOACAN	Wansoft → **Odoo from 2026-10-01**	2026-10-01
4752	Metepec	Fonda Argentina - Tollocan	FONDA ARGENTINA TOLLOCAN	Wansoft	—
4433	Napoles	Fonda Argentina - Nápoles	FONDA ARGENTINA POLYFORUM	Wansoft	—
5943	Oceanía	Fonda Argentina - Oceanía	FONDA ARGENTINA ENCUENTRO OCEANIA	Wansoft → **Odoo from 2026-10-01**	2026-10-01
6174	Playa del Carmen	Fonda Argentina - Playa del Carmen	—	Wansoft	—
12806	Puebla	Fonda Argentina - Puebla	FONDA ARGENTINA PUEBLA	Odoo (born on Odoo)	2026-06-10
5319	San Jeronimo	Fonda Argentina – San Jerónimo	FONDA ARGENTINA SAN JERONIMO	Wansoft → **Odoo from 2026-10-01**	2026-10-01
5321	Taquería parroquia	Fonda Argentina – Taquería Parroquía	—	Wansoft	—
4962	Taquería Viaducto	Fonda Argentina - Taqueria Viaducto	—	Wansoft	—
6560	Tepeyac	Fonda Argentina - Tepeyac	FONDA ARGENTINA MAQ	Wansoft → **Odoo from 2026-10-01**	2026-10-01
5396	Versalles	Fonda Argentina - Taquería Exhibimex	—	Wansoft	—
5318	Vía Vallejo	Fonda Argentina – Vía Vallejo	FONDA ARGENTINA VALLEJO	Wansoft → **Odoo from 2026-10-01**	2026-10-01
4961	Viaducto	Fonda Argentina - Viaducto	FONDA ARGENTINA VIADUCTO	Wansoft	—

Notes:

- Names differ between systems for the same branch: Metepec = "Tollocan", Napoles = "Polyforum", Versalles = "Taquería Exhibimex", Acoxpa = "Costa Nera" in Odoo. Long names use either a hyphen (`-`) or an en dash (`–`).
- `7697` "Taqueria San Fernando" belonged to the group **until 2025-02-28** and is not one of the 19 current branches. Everything its Wansoft account recorded afterwards (cash closings until July 2025, invoices of March and April 2025, zero cost rows until 2026) **does not belong to the group and must not be summed**. Its name changes per table: `Taq San Fernando` in sales, `Fonda Argentina - Taqueria San Fernando` in costs and cash closing, `Taqueria San Fernando` in invoices. Its sales tickets only reach 2024-12-31 (January and February 2025 are only in the cash closing). In `analytics_expense_invoices` its key is `Taqueria San Fernando` and its later invoices carry `exclude_reason = 'branch_left_group'`.
- **Sales always come from Wansoft for every branch**, whatever the purchases source.
- **New branches** (today Puebla and CentroMyJ, and every branch opened from now on) are born on Odoo: purchases, inventory and costs come from Odoo; in Wansoft they only record sales and daily closings.
- **Costs:** every branch operating on Odoo, migrated or new, takes its cost from Odoo **from its start date on**, and from Wansoft before that date. **Temporary exception: Antenas** keeps Wansoft costs while its Odoo database is repaired (it was the prototype). **Isabel La Católica, San Jeronimo and Vía Vallejo** keep Wansoft costs until Odoo has **a complete month invoiced**; then each switches to Odoo by itself from the first day of the next month. See Section 5.2.
- Internal providers **El Bodegón de Fito** and **Las Empanadas de María Eva** (central kitchens) are excluded as buying companies from business views.
- The same information, as data: `dim_company_analytical` and `analytics_company_domain_coverage` (Section 5.6). They use the short key and do not carry the Wansoft id; use this table for that link.

4. Which table answers which question

Question	Table	Filter / note
Sales, tickets, covers per day/branch	`getallordenesbyday_new_venta`	one row per ticket
What was sold (dishes, groups)	`getallordenesbyday_new_detalleventa`	one row per line
Payment methods, tips	`getallordenesbyday_new_pago`	one row per payment
Official daily close (Z report), cancellations, courtesies, discounts	`getglobalcashclosing`	one row per branch per closing
Monthly cost of sales, waste, margin	`costeomensual`	month-to-date snapshot; take the last day
Weekly cost	`costeomensual_semanapyq`	week-to-date snapshot
Daily cost of sales	`gettotalcostbydate`	one row per branch per day
Butchery yields	`gettablajeriareport`	history of Wansoft branches only; being phased out (see 5.2)
Purchases (goods) for any branch, any period	`analytics_purchase_order_lines` / `analytics_purchase_orders` / `analytics_purchase_daily_company_product`	`include_in_business_views = 1`
Spend by accounting account (Costo operativo, Gastos directos, ...)	`analytics_expense_invoices`	every branch, Wansoft + Odoo (5.7); `getexpenses_factura` is Wansoft only
Inventory entries/exits detail (Wansoft)	`getinputinventory_entrada`, `getoutgoinginventory_salida`	Wansoft branches
What the Odoo branches keep capturing in Wansoft (comparison only)	`wansoft_parallel_inputinventory_entrada`, `wansoft_parallel_outgoinginventory_salida`	from 2026-10-01; never in totals (see 5.4)
Current stock, all 19 branches	`analytics_inventory_balance` (and `analytics_inventory_current_product_location` for Odoo by location)	`include_in_business_views = 1`; today's snapshot only
Stock on any date, all 19 branches, Wansoft + Odoo	`analytics_inventory_stock_daily`	one row per branch × product × day; always filter by branch and dates (5.4)
Odoo stock by location (warehouse, kitchen), day by day	`odoo_inventory_quant_daily`	Odoo's raw snapshot, from 2026-10-08 (see 5.4)
Checklist results	`zenput.submissions` + `zenput.submission_answers`	—
Tasks	`zenput.zenput_tasks`	—
Which source feeds each branch	`analytics_company_domain_coverage`	—
From which day each branch's cost comes from Odoo	`costs_source_by_company`	`odoo_cost_start_date` NULL = Wansoft
Every inventory movement (purchases, sales, waste, consumption, production, adjustments, transfers), Wansoft + Odoo, full history	`analytics_inventory_movements`	`include_in_business_views = 1`; always filter by branch and dates (5.4)
Wansoft code of an Odoo product	`analytics_odoo_product_code`	one row per Odoo product (5.4)

4.1 Available history

Start dates measured in production on 2026-09-28 (and on 2026-10-27 for the new tables); the go-live of October 1 did not change them (it only removed duplicate copies of rows). Tables keep filling daily through the previous day. **They are the table's oldest date: each branch starts when it opened or started capturing** (for example Cancún and Playa del Carmen in August 2022, Tepeyac in November 2022, Coyoacán in January 2026, CentroMyJ and Puebla in 2026). For the start per branch and table, group by branch as shown in Section 8.

Data	Table	Source	Since	Notes
Sales: tickets, lines, modifiers	`getallordenesbyday_new_venta`, `_new_detalleventa`, `_new_modificador`	Wansoft	2021-09-01	2021-12-14 to 2021-12-31 has almost no tickets (a gap in the source history, accepted)
Sales: payments per ticket	`getallordenesbyday_new_pago`	Wansoft	2025-01-01	No payments per ticket before 2025; use the cash closing
Daily cash closing	`getglobalcashclosing`	Wansoft	2022-01-01	—
Daily cost of sales	`gettotalcostbydate`	Wansoft or Odoo (5.2)	2021-07-31	—
Month-to-date cost	`costeomensual`	Wansoft or Odoo (5.2)	2022-01-01	Puebla and CentroMyJ have costs from July 2026 (5.2)
Week-to-date cost	`costeomensual_semanapyq`	Wansoft or Odoo (5.2)	2024-01-02	—
Butchery yields	`gettablajeriareport`	Wansoft	2022-01-01	Being phased out (Section 5.2)
Supplier invoices by accounting account	`getexpenses_factura`	Wansoft	**2023-01-01**	Before that only scattered invoices (back to 2019-02-18, about 300 in 2022); only while a branch enters purchases in Wansoft
Unified supplier invoices	`analytics_expense_invoices`	**Wansoft + Odoo**	**2023-01-01**	Before that only scattered invoices (back to 2019-02-18). Wansoft until each branch's Odoo start and Odoo from then on; Puebla and CentroMyJ with their whole Odoo history, opening investment included (5.7)
Inventory entries	`getinputinventory_entrada`	Wansoft	2021-09-01	—
Inventory exits	`getoutgoinginventory_salida`	Wansoft	2020-11-30	About 1.1 million rows have an empty `Fecha` (`0000-00-00`): adjustments and waste whose business date is in `FechaReal`. **Do not exclude them**: use `COALESCE(NULLIF(Fecha, '0000-00-00'), FechaReal)` (5.4)
Unified purchases	`analytics_purchase_order_lines`, `analytics_purchase_orders`, `analytics_purchase_daily_company_product`	**Wansoft + Odoo**	**2021-09-01**	Wansoft until each branch's Odoo start date, Odoo from then on (2026-10-01 for the migrated branches; Puebla and CentroMyJ since they opened in June). Checked year by year: same rows and amounts as production's Wansoft invoices

Unified stock	`analytics_inventory_current_product_location`, `analytics_inventory_balance`	**Wansoft + Odoo**	Current snapshot	No history by design (for history use `analytics_inventory_stock_daily`); the Wansoft balance is recomputed nightly from every movement since 2020-11-30
Parallel Wansoft inventory (8 migrated branches)	`wansoft_parallel_inputinventory_entrada`, `wansoft_parallel_outgoinginventory_salida`	Wansoft	2026-10-01	Comparison with Odoo only; rows before 2026-10-01 are September movements, read them from the main tables (5.4)
Odoo stock day by day	`odoo_inventory_quant_daily`	Odoo	2026-10-08	One raw capture per night (product × location); no Odoo stock history before that date
Checklists	`zenput.submissions`, `zenput.submission_answers`	Zenput	2025-06-11	—
Tasks	`zenput.zenput_tasks`	Zenput	2025-06-03	—
Unified inventory movements	`analytics_inventory_movements`	**Wansoft + Odoo**	2020-09-29	Wansoft until each branch's Odoo start and Odoo from then on (CentroMyJ from 2026-06-09, Puebla from 2026-07-20); what was captured in parallel is kept with `include_in_business_views = 0`
Unified daily stock	`analytics_inventory_stock_daily`	**Wansoft + Odoo**	2020-09-29	Each product from its first movement in the branch; all 19 branches complete from October 2021. Wansoft until each branch's Odoo start and Odoo from then on (CentroMyJ from 2026-06-17, Puebla from 2026-07-20)
Calendar	`dim_time`	—	2020-01-01	Until 2035-12-31

5. Domains

5.1 Sales (Wansoft, all branches)

`getallordenesbyday_new_venta` — ticket header.

Field	Meaning
`Sucursal`	Branch short key
`Movimento`	Ticket id within the branch (sic, no "i"); join key
`Fecha`	Business date, text `YYYY-MM-DDT00:00:00`
`Total`, `Subtotal`, `IVA`, `IEPS`, `Descuento`	Amounts, text
`Personas`	Covers
`Mesa`, `Mesero`, `Orden`, `Terminal`	Table, waiter, order number, terminal
`TipoOrden`	`Restaurant`, `Para llevar`, `eCommerce`
`HoraApertura`, `HoraCierre`	Open / close time
`Estatus`	Always `0` in current data

Joins (both columns needed, the ticket id repeats across branches): `venta.Sucursal = detalle.Sucursal AND venta.Movimento = detalle.Movimiento_Id`; same for `getallordenesbyday_new_pago` and `getallordenesbyday_new_modificador`.

`getallordenesbyday_new_detalleventa` — lines: `Platillo`, `CodigoPlatillo`, `Grupo`, `TipoGrupo` (e.g. food / drinks), `Cantidad`, `PrecioUnitario`, `Total`, `Costo`, `Cortesia`, `Hora`.

`getallordenesbyday_new_pago` — `MetodoDePago`, `Total`, `Propina`, `Terminal`.

Waiters: delivery and app orders are attributed to a **placeholder waiter** whose name varies by branch (`APLICACIONES`, `Apps Llevar`). Exclude it when ranking real waiters.

```
SELECT Sucursal, DATE(Fecha) AS dia,
      COUNT(*) AS tickets,
      SUM(CAST(Personas AS UNSIGNED)) AS comensales,
      SUM(CAST(Total AS DECIMAL(14,2))) AS venta
FROM getallordenesbyday_new_venta
WHERE Fecha >= '2026-09-01' AND Fecha < '2026-10-01'
GROUP BY Sucursal, DATE(Fecha);
```

`getglobalcashclosing` — the official close per branch (`subsidiary_id`, `fecha_corte`): `total_ventas`, `no_ordenes`, `total_personas`, averages, and counts/amounts of courtesies, cancellations, discounts, voids, promotions. Amounts here are **sale value**. Use it to reconcile daily totals.

5.2 Costs (Wansoft or Odoo, by branch)

Where each branch's cost comes from:

Branch type	Cost source today
Wansoft only	Wansoft cost report

Migrated to Odoo (Acoxpa, Tepeyac, Oceanía, La Esquina Coyoacán)	Wansoft through 2026-09-30; Odoo from 2026-10-01
October wave (Isabel La Católica, San Jeronimo, Vía Vallejo)	Wansoft until Odoo has a complete month invoiced (every day with sales has Odoo cost and the month total is plausible against Wansoft); Odoo from the first day of the next month. A month never mixes both systems. Until then their Wansoft rows carry merma and consumo as 0, since these are no longer captured there
New, born on Odoo (Puebla, CentroMyJ and any branch opened later)	Odoo since it opened. Odoo has no cost of sales for CentroMyJ before July 2026 nor for Puebla before 2026-07-27: those days are 0
Antenas (temporary exception)	Wansoft, while its Odoo database is repaired

Odoo cost is computed from Odoo accounting (direct-cost accounts) and stored in the same tables. It fills `CostoTotal`, `CostoDeProductosVendidos` and `CostoDeMerma`; `CostoDeCortesías` and `CostoDeCancelaciones` come from the cash closing; the other columns stay empty (no Odoo equivalent). **In Odoo rows the columns with no equivalent are NULL**: use `COALESCE(column, 0)` when adding or subtracting, or the result is NULL (e.g. `CostoTotal - CostoDeConsumo` is NULL for Puebla). The switch is per day: days before the start date keep Wansoft's cost. When the switch falls in the middle of a month or week, the accumulated tables (`costeomensual`, `costeomensual_semanapyq`) stay whole: they add Wansoft's part up to the day before the switch to Odoo's from that day, with no day counted twice. On Odoo rows `CostoTotal` no longer includes consumo.

Which source each branch uses, as data: the table `costs_source_by_company` (rewritten every night with the pipeline's own rule) has, per branch, `company_source_key`, `wansoft_subsidiary_id`, `odoo_company_id`, `odoo_cost_start_date` (first day on Odoo cost; NULL = always Wansoft) and `reason` (`wansoft`, `policy`, `exception`, `auto_switch_pending`, `switched`, `no_policy`). Use it instead of copying the rules of this section.

Costs of recent days are not complete yet, and each source shows it differently:

- **Wansoft:** its cost grows while it processes the inventory deduction of what was sold. `CostoIdealDeProductosPendientesDeRebaja` (in `costeomensual` and `costeomensual_semanapyq`) is the cost not yet deducted; when it is 0 the period is complete. All of September 2026 is already at 0; in early October 1% to 24% was pending depending on the branch, more on weekends.
- **Odoo:** its cost comes from each day's customer invoices (the Wansoft sales passed to Odoo), which are created with a lag: in September 2026, 40% to 70% of a day's sales was invoiced the next day, 70% to 100% after 7 days, and everything by the month-end closing. To know whether a day is complete, compare Odoo's invoiced amount with Wansoft's net sales for that day. The pipeline re-reads Odoo for the current month (and the previous one until the 10th), so after the closing the tables are complete.
- **How sales reach Odoo:** a sale is always recorded in Wansoft. An automation in Odoo turns it into a sales order and a customer invoice, which carries the cost of sales. **It only processes a ticket when every ingredient of its recipe is in stock**; if one is missing, the sale waits until there is stock. This keeps the cost real and makes branches record their production, receive their purchases and manage their inventory. As a result, days with pending sales have no cost in Odoo yet: this is not a load error.

If you need a cost for recent days, mark it as an estimate or wait until the period is complete.

Keyed by `subsidiary_id` (Wansoft id). All three are **snapshots**:

Table	One row =	How to read it
`costeomensual`	Month-to-date cumulative, from the 1st through `created_date`	Month total = the row with the latest `created_date` of that month
`costeomensual_semanapyq`	Week-to-date cumulative, Monday through the day **before** `created_date`	Week total = latest row of the week

`gettotalcostbydate`	Cost of sales of the single day `created_date`	Sum over days

`mes_ano` is text `MM-YYYY`. Unique per (`subsidiary_id`, `created_date`).

Fields in `costeomensual` and how the owner's reports use them:

Report figure	Formula
Costo Total	`CostoTotal - COALESCE(CostoDeConsumo, 0)`
Costo Teórico	`CostoDeProductosVendidos`
Gasto de Venta	`CostoDeConsumo`
Costo de Mermas	`CostoDeMerma`
Cortesías / Cancelaciones	`CostoDeCortesías`, `CostoDeCancelaciones` (sale value, from the cash closing)

```
-- Month cost per branch: last snapshot of the month
SELECT c.subsidiary_id, c.subsidiary_name, c.created_date,
      c.CostoTotal - COALESCE(c.CostoDeConsumo, 0) AS costo_total,
      c.CostoDeProductosVendidos AS costo_teorico
FROM costeomensual c
JOIN (SELECT subsidiary_id, MAX(created_date) AS d
     FROM costeomensual
     WHERE created_date >= '2026-08-01' AND created_date < '2026-09-01'
     GROUP BY subsidiary_id) last ON last.subsidiary_id = c.subsidiary_id AND last.d = c.created_date;
```

Butchery yields (`gettablajeriareport`) are being phased out. They only exist for branches that enter purchases and inventory in Wansoft: new branches (Puebla, CentroMyJ) have none, and migrated branches will stop having them once they stop entering purchases in Wansoft. Odoo does not record butchery this way: it applies calculated yields, and at month end the real inventory is checked against the calculated one. Use this table only as history for Wansoft branches.

5.3 Purchases (Wansoft history + Odoo, merged)

Use the analytics layer. It already merges both sources with this rule per branch:

- Branch purchasing in Wansoft: Wansoft invoices-type entries (`getinputinventory_entrada` with `TipoEntrada = 'Factura'`).
- Branch migrated to Odoo: Wansoft history **before** its Odoo start date (Section 3), then confirmed Odoo purchase orders (`state` purchase/done) from that date on. No overlap, no gap.
- Internal providers as buying company are excluded; a branch buying *from* an internal provider is kept.

`source_system` (`wansoft`/`odoo`) tells where each row came from; `final_purchase_source_status` explains why it was kept (for example `wansoft_history_before_odoo`).

When a purchase appears (important when reading recent days):

- **Odoo:** an order counts once it is **confirmed**; drafts and requests for quotation never count. It enters with the load of the night after it is confirmed, **under its order date**: an order dated day 5 and confirmed on day 7 appears in the table on day 8, but on day 5. So purchases of recent days can keep growing.
- **Wansoft:** a purchase counts when its **invoice is captured**, usually when the goods arrive.

- For the same goods the two moments can differ. The main case is **El Bodegón de Fito** (central kitchen), which invoices late: Odoo counts its orders when confirmed, Wansoft only when the invoice arrives.

Unclassified purchases (from the load of the night of 2026-10-07 to 10-08): a real purchase counts in the business views even if its vendor or product is not yet classified in the catalogs. `catalog_status` says which state it is in: `catalogado`, `producto_por_clasificar` (the product exists but its classification still has to be confirmed), `producto_sin_catalogo`, `proveedor_sin_catalogo` or `proveedor_y_producto_sin_catalogo`. Use it to show those purchases apart in a breakdown by category; the totals already include them. Only deliberately excluded products and purchases made by the internal providers stay out (`include_in_business_views = 0`). The catalogs are rebuilt every night. Since October 8, a Wansoft purchase carrying its Wansoft code and department is `catalogado` even when its link to the equivalent Odoo product is still pending approval: `producto_por_clasificar` is left for products that really lack a classification.

Table	Grain	Key fields
`analytics_purchase_order_lines`	purchase line	`company_source_key`, `order_date`, `vendor_name`, `product_name`, `wansoft_code`, `wansoft_department`, `product_qty`, `price_unit`, `price_subtotal` (before tax), `price_total` (with tax), `source_system`
`analytics_purchase_orders`	purchase order / invoice	same header fields plus totals
`analytics_purchase_daily_company_product`	branch × day × product	`business_price_subtotal_total`, `business_product_qty_total` (already business-filtered)

Join to dimensions with `product_analytical_key` → `dim_product`, `vendor_analytical_key` → `dim_vendor`, `company_analytical_key` → `dim_company_analytical`, `order_date_key` → `dim_time.date_key`.

```
SELECT company_source_key, DATE_FORMAT(order_date, '%Y-%m') AS mes,
      source_system, SUM(price_subtotal) AS compras_sin_iva
FROM analytics_purchase_order_lines
WHERE include_in_business_views = 1
 AND order_date >= '2026-01-01'
GROUP BY company_source_key, mes, source_system;
```

Example: the migrated branches (Acoxpa, Antenas, Tepeyac, Oceanía, Coyoacán) come back with `source_system = 'wansoft'` through September 2026 and with `'odoo'` from October, with no month repeated or missing; Puebla and CentroMyJ, born on Odoo, come back with `'odoo'` since they opened in June 2026.

`getexpenses_factura` is a different thing: every Wansoft supplier invoice classified by accounting account (`Cuenta`: Costo operativo, Gastos de venta, Gastos directos, Sueldos y salarios, Fletes, ...), including services, software and payroll that are not goods. Odoo purchase orders only cover goods. So:

- For goods purchases across both systems, use the analytics layer.
- To compare with Wansoft's "Compras" reports, use only `Cuenta = 'Costo operativo'`.
- **Odoo and Wansoft do not match each other for the same branch and month.** During the parallel capture, Odoo purchases came out 7% to 19% above Wansoft's `Costo operativo` (September 2026: Acoxpa +7.2%, Coyoacán +11.1%, Oceanía +18.5%). It is a difference between the two source systems, not a loading error, and it is mostly explained by when each system counts a purchase (see "When a purchase appears"): in one week of Acoxpa reviewed, most orders matched their invoice exactly and almost all of the difference was El Bodegón de Fito orders not yet invoiced; the rest, small differences between the order amount and the invoice amount. The analytics layer does not double it because it never mixes both systems for the same branch and day; do not compare Odoo against Wansoft expecting

them to match.

- **Non-goods spend** (rent, services, software, payroll, freight...) of branches already operating on Odoo is in `analytics_expense_invoices` (Section 5.7), with Odoo's vendor bills. In `getexpenses_factura` those branches only have invoices up to their Odoo start date.

Some Wansoft invoices have an empty `Cuenta`. Amounts and dates in this table are text. **`Estatus = 'Por pagar'` does not mean unpaid:** invoices are rarely marked paid in Wansoft (payment is recorded elsewhere), so do not use that field for accounts payable.

How to identify an invoice: use `IdDocumento`, the document's id in Wansoft, unique across the table. The `id` column is useless (it is 0 on every row), `Factura_Id` and `Egresos_Id` are empty and `UUID` is missing on more than half of the invoices. Until 2026-10-20, 90 Coyoacán invoices of 2026-01-28 to 2026-02-09 were stored twice: under the branch's old name (`La Esquina Coyoacán`) and under the current one (`Fonda Argentina - Coyoacan`). The old-name copies, which had outdated statuses and folios, were removed, and since then the table has a unique key on `IdDocumento`.

5.4 Inventory

- **Today's stock, all 19 branches:** `analytics_inventory_balance`, one row per branch × Wansoft product code; `source_system` says where it comes from: `wansoft` (the 9 Wansoft branches: entries – exits since the first movement) or `odoo` (the 10 Odoo branches: Odoo's stock). `analytics_inventory_current_product_location` gives the Odoo side by location (warehouse, kitchen). Filter `include_in_business_views = 1`. **It is today's snapshot: rewritten every night, no history kept.**
- **Stock per day, all 19 branches (since version 1.9):** `analytics_inventory_stock_daily`, one row per branch × product × day, from Wansoft and Odoo, with the full history (about 18 million rows). Every product appears **on every day** from its first movement in the branch to yesterday, zero-stock days included: if a product has no row on a date, it had not had any movement in that branch yet. Always filter by branch and dates.

Field	Meaning
`stock_date`	Day; the stock is at the close of that day
`company_source_key`	Branch (short key)
`product_code`	Common product code, the same as in `analytics_inventory_movements` (Wansoft code or temporary `ODOO-<id>`)
`source_system`	`wansoft` or `odoo`: which system that day comes from
`product_name`	Product name
`stock_qty`	Stock at the close of the day, in the product's unit (can be negative if the source system's is)
`stock_value`	Stock value: in Odoo, its valuation; in Wansoft, approximate, from the movements' cost
`moved_qty`	Net movement of that day (+ in, – out); 0 when nothing moved
`final_source_status`	`wansoft_final` (Wansoft branch), `wansoft_history_before_odoo` (migrated branch, before its Odoo start), `odoo_final` (Odoo)
`include_in_business_views`	Always 1 in this table
`built_at`	When the row was computed

Rules: - **Migrated branches:** Wansoft until the day before their Odoo start and Odoo from that day (2026-10-01 for the 8 October branches). Each system with its own count: there can be a jump on the start day, because Odoo starts from its opening inventory. - **Wansoft:** stock = sum of the movements since the first one; the last day equals

analytics_inventory_balance. - **Odoo:** computed **backwards from Odoo's latest snapshot** (odoo_inventory_quant_daily, internal locations), so the last day is exactly what Odoo shows. Odoo sometimes registers moves days later with an earlier date: when they arrive, past days are recomputed by themselves. The Odoo series is recomputed in full every night. - Every night the Wansoft days touched by movements captured in the last 10 days are recomputed, so recent days can still change.

```
-- Stock of a branch at the close of 2026-09-30 (products with stock only)
SELECT product_code, product_name, stock_qty, stock_value
FROM analytics_inventory_stock_daily
WHERE company_source_key = 'Viaducto' AND stock_date = '2026-09-30'
 AND stock_qty <> 0;
-- Coca Cola Mini (1000-105-203-005): 2,939, the same as the entries – exits formula below.
```

Checked in production on 2026-10-26 and 2026-10-27: no missing day for any branch × product; the last day equals Odoo's stock in the 10 Odoo branches and analytics_inventory_balance in the Wansoft branches. Only difference: 8 products at Aeropuerto, because 16 entries of November 2021 are twice in getinputinventory_entrada and analytics_inventory_balance adds them twice; analytics_inventory_stock_daily counts them once. - **Wansoft movements:** getinputinventory_entrada (entries; TipoEntrada: Factura, Transferencia, Entrada con canal, Producto procesado, Ajuste de inventario) and getoutgoinginventory_salida (exits, tens of millions of rows: always filter by date and subsidiary_name). Branch = Wansoft id in subsidiary_name; product = CodigoProducto; quantity Cantidad, cost CostoUnitario. Wansoft branches only; the 8 branches migrated to Odoo end on 2026-09-30. - **Parallel Wansoft inventory (since the night of 12 to 13 October 2026):** the 8 branches migrated to Odoo (Acoxpa, Antenas, Tepeyac, Oceanía, La Esquina Coyoacán, Isabel La Católica, San Jerónimo, Vía Vallejo) keep capturing entries and exits in Wansoft. That capture is loaded into wansoft_parallel_inputinventory_entrada and wansoft_parallel_outgoinginventory_salida, with the same columns as the main tables. **It is for comparing Wansoft with Odoo only: never add it to stock or totals**; for these branches the official source from 2026-10-01 is Odoo. Use only dates from 2026-10-01 on: earlier rows are September movements, read them from the main tables. - **Stock on a past date from Wansoft's raw tables** (for auditing; normally use analytics_inventory_stock_daily): entries – exits up to that date, with the same rules as today's balance (no transfers, no purchase orders, no capture errors or rejected invoices). Exits with an empty Fecha are adjustments and waste dated in FechaReal: do not exclude them.

```
-- Stock of Coca Cola Mini (1000-105-203-005) at Viaducto (4961) at the close of 2026-09-30
SELECT
 (SELECT COALESCE(SUM(Cantidad), 0) FROM getinputinventory_entrada
   WHERE subsidiary_name = '4961' AND CodigoProducto = '1000-105-203-005'
     AND TipoEntrada NOT IN ('Orden de compra a proveedor', 'Transferencia')
     AND DATE(FechaEntrada) <= '2026-09-30')
 -
 (SELECT COALESCE(SUM(Cantidad), 0) FROM getoutgoinginventory_salida
   WHERE subsidiary_name = '4961' AND CodigoProducto = '1000-105-203-005'
     AND TipoSalida NOT IN ('Error de captura', 'Factura de egresos rechazada', 'Transferencia')
     AND COALESCE(NULLIF(Fecha, '0000-00-00'), FechaReal) <= '2026-09-30') AS stock;
-- 2,939. With '2026-10-07' it gives 3,170, equal to analytics_inventory_balance that night.
```

- **Odoo stock day by day:** odoo_inventory_quant_daily, from stock date 2026-10-08. One row per stock_date, location and Odoo product (odoo_product_id, product_name, location_name, location_usage internal or transit, quantity, company_source_key), without mappings. To read it in Wansoft codes, join odoo_product_id to analytics_odoo_product_code (below). **There is no Odoo stock history before 2026-10-08**; for Odoo's history use analytics_inventory_stock_daily.
- **Unified inventory movements (since version 1.4):** analytics_inventory_movements, one row per movement of one product in one branch, Wansoft and Odoo, with full history (about 40 million rows). Use it for flows: how much of each

product was bought, sold, wasted or consumed, per branch and day, whatever the system.

Field	Meaning
`movement_date`	Business date of the movement
`company_source_key`	Branch (short key)
`source_system`	`wansoft` or `odoo`
`direction`	`in` (into the branch) or `out`
`movement_type`	Normalized type: `purchase_receipt`, `sale_consumption`, `sale_cancellation`, `waste`, `theft`, `consumption`, `production_in`, `production_out`, `transfer_in`, `transfer_out`, `adjustment`, `initial_inventory`, `other`
`source_movement_type`	The original type (Wansoft `TipoEntrada`/`TipoSalida`; Odoo source → destination)
`product_code`, `product_code_status`	Common product code: the Wansoft code (`wansoft`) or a temporary `ODOO-<id>` (`temporal_odoo`) while the Odoo product has no equivalence; once it does, the code changes across its whole history
`wansoft_code`, `odoo_product_id`, `product_name`, `unit_name`	Product and unit
`quantity`	Signed quantity (+ in, – out), in the product's unit
`unit_cost`, `total_cost`	Cost (Wansoft: unit cost; Odoo: valuation); `total_cost` signed
`counts_in_stock`	Whether the movement changes stock (Wansoft internal transfers and purchase orders do not)
`final_source_status`, `include_in_business_views`	As in purchases: filter `include_in_business_views = 1` for business figures. Migrated branches take Wansoft before their Odoo start and Odoo from then on; what was captured in parallel in the other system has `include_in_business_views = 0` (`wansoft_parallel_after_odoo`, `odoo_parallel_before_start`)

```
-- Waste and consumption per month of one branch, both systems
SELECT DATE_FORMAT(movement_date, '%Y-%m') AS month, movement_type,
      SUM(-quantity) AS quantity, SUM(-total_cost) AS cost
FROM analytics_inventory_movements
WHERE company_source_key = 'Acoxpa' AND include_in_business_views = 1
 AND movement_type IN ('waste', 'consumption')
 AND movement_date >= '2026-01-01'
GROUP BY month, movement_type;
```

Every night the Wansoft movements captured in the last 10 days and the whole Odoo side are reloaded, so recent days can still change. For stock use `analytics_inventory_stock_daily` (per day) or `analytics_inventory_balance` (today). - **Wansoft code of an Odoo product:** `analytics_odoo_product_code` (`odoo_product_id`, `odoo_product_name`, `wansoft_code`, `wansoft_product_name`), one row per Odoo product with a current, reviewed equivalence; rewritten every night, the same one `analytics_inventory_movements` uses. Use it to read `odoo_inventory_quant_daily` in Wansoft codes. **Do not use `dim_product` for this**: it includes equivalences still under review. - Detailed coverage per branch: `docs/inventory-coverage-by-branch.md` in the repository.

5.5 Zenput (`zenput` database)

Table	Grain	Key fields
`form_templates`	checklist template	`form_id`, `title`, `category_name`

`submissions`	one filled checklist	`submission_id`, `form_template_id` → `form_templates.form_id`, `location_name`, `user_display_name`, `date_submitted`
`submission_answers`	one answer	`submission_id`, `title` (question), `field_type`, `value_as_string`
`zenput_tasks`	task	`task_id`, `title`, `account_name` (location), `status_name`, `assignee_display_name`, `date_due`, `is_closed`, `is_completed_late`

`location_name` / `account_name` are Zenput's own location names, not the short key; some Zenput locations have no POS branch.

5.6 Governance tables

- `dim_company_analytical`: one row per company, flags (`is_active_branch`, `is_internal_provider`, `is_final_operating_branch`), source per domain, `operational_start_date`.
- `analytics_company_domain_coverage`: which source feeds each domain per branch, with counts and a `coverage_status`.
- `costs_source_by_company`: from which day each branch's cost comes from Odoo (`odoo_cost_start_date`, NULL = Wansoft) and why (`reason`); rewritten every night (Section 5.2).
- `dim_time`: calendar (`date_key` = `YYYYMMDD`), weeks, months, ISO weeks.

5.7 Expenses: supplier invoices (Wansoft + Odoo)

`analytics_expense_invoices` gathers **every supplier invoice of every branch**, from Wansoft and from Odoo, with the full history (complete from 2023-01-01; before that only scattered invoices, back to 2019-02-18), classified with Wansoft's own Cuentas and Subcuentas. It is rebuilt in full every night. Use it for expenses instead of `getexpenses_factura`, which remains as Wansoft's raw table.

- **What it holds:** from Wansoft, every invoice of `getexpenses_factura`; from Odoo, every vendor bill and vendor credit note. Same rule as purchases: Wansoft until each branch's Odoo start and Odoo from then on; Puebla and CentroMyJ, born on Odoo, with their whole Odoo history, opening investment included.
- **Ids:** `expense_document_id` identifies the invoice (`wansoft:<IdDocumento>` or `odoo:<id>`); `expense_row_key` identifies the row. An Odoo bill with lines on several Cuentas takes one row per Cuenta: for an invoice total, sum its rows.
- **Classification:** `tipo_de_egreso`, `cuenta`, `subcuenta`. Wansoft as captured. Odoo through the equivalence of its accounts to Wansoft's, decided by Fonda Argentina (`classification_status` says how each row was classified). New Cuenta **`Inversión inicial`** (`tipo_de_egreso = 'Inversión'`): equipment, works and installation of openings.
- **Amounts** are numbers, in pesos: `subtotal`, `discount`, `iva`, `ieps`, `retentions` (withheld, positive) and `total` = subtotal + iva + ieps – discount – retentions, as in Wansoft. Credit notes (`document_type = 'credit_note'`) are negative.
- **Status:** for Wansoft, `status` is refreshed every night with Wansoft's current status (Pagada / Por pagar / Rechazada); "Por pagar" in Wansoft still does not mean unpaid. For Odoo: Pagada, En pago, Pago parcial, Por pagar, Revertida, Cancelada; `payment_date` when Odoo records a payment.
- **Business figures: filter `include_in_business_views = 1`.** The rest is kept with its `exclude_reason`: `rejected`, `cancelled`, `advance` (advance payments, so the final bill counts once), `internal_provider_or_holding`, `before_odoo_start` (what the migrated branches captured in Odoo before their start) and `branch_left_group` (San Fernando after 2025-02-28).

- `uuid_document_count`: how many included invoices share the same UUID (empty when unique); Wansoft has some invoices captured twice or with a mistyped UUID.
- **Moving from Wansoft to Odoo changes what is recorded:** Odoo carries expenses a branch did not enter in Wansoft (for example Acoxpa's rent appears from October 2026). It is not a rise in spend.

Equivalence with `getexpenses_factura`: `IdDocumento` → `source_document_id`; `Sucursal` → `company_source_key`; `FechaDeExpedicion` → `invoice_date`; `Folio`, `UUID` → `folio`, `uuid`; `NombreProveedor`, `RFCProveedor`, `ClaveProveedor` → `vendor_name`, `vendor_rfc`, `vendor_key`; `TipoDeEgreso`, `Cuenta`, `Subcuenta` → `tipo_de_egreso`, `cuenta`, `subcuenta`; `Subtotal`, `IVA`, `IEPS`, `Discount`, `Retentions`, `Total` → the same amounts, as numbers; `Estatus` → `status` (refreshed).

Checked on 2026-10-21 against the source systems' own reports: Aeropuerto, September 2026 (Wansoft's purchases report, 302 invoices) and Acoxpa, October, and Puebla, September (Odoo's bills and journal items): equal invoice by invoice and by account.

Example, monthly spend by Cuenta of one branch:

```
SELECT DATE_FORMAT(invoice_date, '%Y-%m') AS mes, cuenta, SUM(subtotal) AS subtotal
FROM analytics_expense_invoices
WHERE include_in_business_views = 1 AND company_source_key = 'Acoxpa'
 AND invoice_date >= '2026-07-01'
GROUP BY 1, 2
ORDER BY 1, 3 DESC;
```

Restricted access: see Section 8.

6. Do not use

Tables	Why
`canonical_purchase_*`, `odoo_purchase_*`, `odoo_stock_move_snapshot` and the `odoo_inventory_*` **except `odoo_inventory_quant_daily`**	Intermediate layers; the analytics tables are the business-ready result
`inventory_*`, `product_catalog_mapping`, `backup_product_catalog_mapping`, `product_replacement_candidates`, `stg_*`	Mapping and review workbench; for the product equivalence use `analytics_odoo_product_code`
`odoo_company_migration_policy`, `odoo_cutover_validation_log`	Pipeline control
`getinventorybydepartment`, `getstockinventory_inventario`, `getinventorybyday_*`	Old snapshots, not refreshed daily
`vw_inventory_*`	Diagnostic views
`tmp_*`	Temporary

7. Freshness and schedule

- Daily pipeline at **01:30** (Mexico City time), about one hour; data through the previous day. In production since 2026-10-01.
- Rolling re-checks: sales 10 days (reconciled against all of Wansoft's cash closings of the day; the latest day is validated the next night), costs and butchery 10 days (Odoo cost: the current month and, until the 10th, the previous one), Wansoft invoices/inventory/cash closing 5 days, Wansoft purchases 35 days. Odoo purchases are fully reloaded every night; an

order appears the night after it is confirmed (section 5.3).

- Costs in Wansoft can be recalculated by Wansoft after the fact; the latest snapshot wins.
- Some branches (Antenas, Vía Vallejo, Coyoacán, Metepec, Taquería Parroquia, Versalles, Tepeyac) upload their cash closing to Wansoft only the next morning, even when they close at night: their `getglobalcashclosing` row arrives **one day late** (sales are on time in the tickets). Until it arrives, that day has no cancellations, courtesies or discounts; take sales from the tickets.
- Weekly backup Thursdays 18:00. Avoid heavy queries at 01:30–03:00.

8. Access

Access is through a dedicated **read-only** database user limited to the tables in Sections 4–5, provided separately (credentials are never written in this document). Query `getoutgoinginventory_salida` and the sales detail tables with date filters: they hold tens of millions of rows. Each user is limited to 4 simultaneous connections and 30 minutes per query.

Large inventory tables: always filter `analytics_inventory_movements` (about 40 million rows) by `company_source_key` and a `movement_date` range, and `analytics_inventory_stock_daily` (about 18 million) by `company_source_key` and a `stock_date` range: that way they use their indexes and answer in seconds. A count or a group over the whole movements table (for example by `source_system`, or with `include_in_business_views` and no branch filter) reads all of it and takes more than 10 minutes (measured on 2026-10-27). For the first and last date per branch, `MIN(movement_date)` / `MAX(movement_date)` with `GROUP BY company_source_key` and no other filter answers instantly.

The tables the user can read are exactly those of Appendix A, with all their columns. When a new table is added (Section 9), it is granted to the user and this guide and the appendix are updated.

Requirement for tukanmx: restricted access to expenses. `analytics_expense_invoices` and `getexpenses_factura` hold sensitive information (rent, salaries, professional fees, administrative expenses, with the vendor of each). On its platform, tukanmx must restrict **both** to the users Fonda Argentina authorises, with each user's expense level:

Level	What it sees
None	No supplier invoices
Operational	Only the Cuentas `Costo operativo`, `Gastos de venta` and `Gastos Directos`
Full	Every Cuenta, including rent, salaries, fees and opening investment

Fonda Argentina hands over the initial user list with each user's level.

9. Still missing (under construction)

State on 2026-10-27. Nothing is under construction any more: the unified daily stock (`analytics_inventory_stock_daily`) is live since 2026-10-26 (5.4). When a new table arrives, it will be granted to the user and documented here.

Other upcoming changes:

- **Aeropuerto and Taquería Viaducto move to Odoo on 2026-11-01** (as branches of the company FONDA ARGENTINA AEROPUERTO). From that day their purchases, inventory and costs come from Odoo, with the same rule as Section 3; sales stay in Wansoft.
- **Isabel La Católica, San Jerónimo and Vía Vallejo** keep Wansoft costs until Odoo has a complete month invoiced; `costs_source_by_company` shows the switch day (5.2).

- **Antenas** keeps Wansoft costs while its Odoo database is repaired.
- **Access security:** the user's access will be limited to a fixed IP and the connection will be encrypted (TLS); we will announce the date and what is needed to connect.

10. Version history

The most recent version comes first.

Version 1.9 (2026-10-27)

- **New daily stock table, Wansoft + Odoo:** `analytics_inventory_stock_daily`, one row per branch × product × day, with the full history and every day (zero-stock days included); replaces 1.8's interim inventory note and the entries – exits formula (Sections 4, 4.1 and 5.4).
- **Supplier-invoice history corrected:** `analytics_expense_invoices` and `getexpenses_factura` complete from 2023-01-01; before that only scattered invoices (4.1 and 5.7).
- **How to query the large inventory tables** without reading them whole, and the start date per branch (Sections 4.1 and 8); San Fernando's name per table (Section 3).
- **Section 9:** nothing under construction any more.
- **Access:** 30 `wansoft` tables, all in Appendix A.

Version 1.8 (2026-10-22)

- **New supplier invoices table, Wansoft + Odoo:** `analytics_expense_invoices`, every branch with its full history, classified by Wansoft's Cuenta / Subcuenta; replaces `getexpenses_factura` for expenses (Section 5.7).
- **How to compute inventory for now** (note at the top of the guide); daily stock arrives in 1.9.
- **Taquería San Fernando (7697)** belonged to the group until 2025-02-28; anything later must not be summed (Section 3).
- **Restricted access to expenses:** `analytics_expense_invoices` and `getexpenses_factura`, by level None / Operational / Full (Section 8). Access: 29 `wansoft` tables.

Version 1.7 (2026-10-20)

- **How to identify a Wansoft invoice:** use `getexpenses_factura.IdDocumento`, which is unique; the `id` column is useless. 90 duplicated Coyoacán invoices were removed (5.3).

Version 1.6 (2026-10-20)

- **Restricted access to the expenses table:** when `analytics_expense_invoices` arrives, tukanmx must restrict it to the users Fonda Argentina authorises and, preferably, segment visibility by expense type (Sections 8 and 9).

Version 1.5 (2026-10-19)

- **How sales reach Odoo and why its cost can lag:** Odoo's automation only processes a ticket when every ingredient of its recipe is in stock; while one is missing, that day has no cost in Odoo (5.2).
- **Rule for switching costs to Odoo:** the October-wave branches switch to Odoo costs only once Odoo has a complete month invoiced, from the first day of the next month; a month never mixes both systems (Sections 3, 5.2 and 9).

Version 1.4 (2026-10-16)

- **Unified inventory movements:** new table `analytics_inventory_movements`, one row per movement (purchase, sale, waste, consumption, production, adjustment, transfer) of Wansoft and Odoo, with full history, a normalized type, cost and a common product code (5.4).
- **Wansoft code of an Odoo product:** new table `analytics_odoo_product_code`, refreshed every night (5.4). Corrects version 1.3, which pointed at `inventory_mapping_dictionary`, a table that is not granted.
- **Section 6 corrected:** `odoo_inventory_quant_daily` is to be used; the list of tables not to use no longer includes it.
- **Access:** the 4 tables that were missing are now granted (`costs_source_by_company`, `odoo_inventory_quant_daily` and the two `wansoft_parallel_*`) plus the 2 new ones; 28 `wansoft` tables in total, all in Appendix A.
- **Section 9 updated:** the unified movements are live; next steps: access limited to a fixed IP and an encrypted connection (TLS).

Version 1.3 (2026-10-13)

- **Odoo stock day by day:** new table `odoo_inventory_quant_daily`, from 2026-10-08 (Sections 4 and 5.4).
- **Wansoft stock on a past date:** rule and verified example; exits without `Fecha` are dated by `FechaReal` (5.4).
- **Parallel Wansoft inventory** of the 8 branches migrated to Odoo: new tables `wansoft_parallel_inputinventory_entrada` and `wansoft_parallel_outgoinginventory_salida`, for comparison only (5.4).
- **Cash closings that arrive one day late** in 7 branches (Section 7).
- **New Section 9:** what is under construction (unified inventory movements, daily stock, supplier invoices) and Aeropuerto and Taquería Viaducto moving to Odoo on 2026-11-01.
- **New Appendix A:** every column (type, nulls, keys) of the 30 tables the user can read.
- **Access:** 3 more tables granted (`odoo_inventory_quant_daily` and the two `wansoft_parallel_*`); 26 `wansoft` tables in total.

Version 1.2 (2026-10-07)

- Costs: each branch's cost source as data (new table `costs_source_by_company`), the automatic per-branch switch from Wansoft to Odoo, and how to tell whether recent costs are complete (5.2).
- Purchases: unclassified purchases count in the business views, with the new column `catalog_status`; when a purchase appears (Odoo when confirmed, Wansoft when the invoice arrives) (5.3).
- Freshness and schedule with the facts of the first production week (Section 7).

Version 1.1 (2026-10-01)

- Production start on 2026-10-01: the migrated branches take purchases and inventory from Odoo from that date (Section 3).
- Costs: each branch on Odoo takes its cost from Odoo from its start date; cost history of Puebla and CentroMyJ (5.2).
- Warning: Odoo and Wansoft purchases do not match each other for the same branch and month (5.3).

Version 1.0 (2026-09-28)

- First edition, Spanish and English with PDF: table per question, golden rules, branch crosswalk, available history, domains, tables not to use, freshness and access.

Appendix A. Table schemas

Columns of every table the read-only user can query, taken from the production schema on 2026-10-27. **Null**: whether the column accepts NULL. **Key**: `PRI` primary key, `UNI` part of a unique key, `MUL` part of an index. The meaning of the important fields is in the section shown in brackets.

A.1 Sales

`getallordenesbyday_new_venta`: ticket header (5.1). 24 columns.

Column	Type	Null	Key
`id`	int(11)	no	PRI
`Sucursal`	varchar(255)	yes	—
`Venta_Id`	varchar(255)	yes	—
`Movimento`	varchar(255)	yes	MUL
`Orden`	varchar(255)	yes	—
`Mesa`	varchar(255)	yes	—
`Fecha`	varchar(255)	yes	—
`Mesero`	varchar(255)	yes	—
`Subtotal`	varchar(255)	yes	—
`IVA`	varchar(255)	yes	—
`IEPS`	varchar(255)	yes	—
`Total`	varchar(255)	yes	—
`Terminal`	varchar(255)	yes	—
`Personas`	varchar(255)	yes	—
`Descuento`	varchar(255)	yes	—
`Impuesto`	varchar(255)	yes	—
`MontoDescontado`	varchar(255)	yes	—
`TipoOrden`	varchar(255)	yes	—
`HoraApertura`	varchar(255)	yes	—
`HoraCierre`	varchar(255)	yes	—
`Moneda`	varchar(255)	yes	—
`CodigoCliente`	varchar(255)	yes	—
`Estatus`	varchar(255)	yes	—
`Ventas_Id`	varchar(255)	yes	—

`getallordenesbyday_new_detalleventa`: ticket lines (5.1). 30 columns.

Column	Type	Null	Key
id	int(11)	no	PRI
Sucursal	varchar(255)	yes	—
Movimiento_Id	varchar(255)	yes	MUL
DetalleVenta_Id	varchar(255)	yes	—
Descripcion	varchar(255)	yes	—
Cantidad	varchar(255)	yes	—
PrecioUnitario	varchar(255)	yes	—
Descuento	varchar(255)	yes	—
Subtotal	varchar(255)	yes	—
IVA	varchar(255)	yes	—
IEPS	varchar(255)	yes	—
Total	varchar(255)	yes	—
Modificador	varchar(255)	yes	—
Hora	varchar(255)	yes	—
Costo	varchar(255)	yes	—
TipoGrupo	varchar(255)	yes	—
CodigoTipoGrupo	varchar(255)	yes	—
CuentaContableTipoGrupo	varchar(255)	yes	—
Grupo	varchar(255)	yes	—
CodigoGrupo	varchar(255)	yes	—
CuentaContableGrupo	varchar(255)	yes	—
CodigoPlatillo	varchar(255)	yes	—
CuentaContablePlatillo	varchar(255)	yes	—
Platillo	varchar(255)	yes	—
ConIVA	varchar(255)	yes	—
ComandaId	varchar(255)	yes	—
TipoPlatilloId	varchar(255)	yes	—
TipoPromocionId	varchar(255)	yes	—
Cortesia	varchar(255)	yes	—
DetallesVenta_Id	varchar(255)	yes	—

`getallordenesbyday_new_pago`: ticket payments (5.1). 17 columns.

Column	Type	Null	Key

id	int(11)	no	PRI
Sucursal	varchar(255)	yes	—
Movimiento_Id	varchar(255)	yes	—
Fecha	varchar(255)	yes	—
IdMetodoDePago	varchar(255)	yes	—
MetodoDePago	varchar(255)	yes	—
CodigoMetodoDePago	varchar(255)	yes	—
ClaveSATMetodoDePago	varchar(255)	yes	—
CuentaContableMetodoDePago	varchar(255)	yes	—
Terminal	varchar(255)	yes	—
Total	varchar(255)	yes	—
Propina	varchar(255)	yes	—
Equivalencia	varchar(255)	yes	—
Moneda	varchar(255)	yes	—
MontoRecibidoEnMoneda	varchar(255)	yes	—
PagoAnticipadoId	varchar(255)	yes	—
Pagos_Id	varchar(255)	yes	MUL

`getallordenesbyday_new_modificador`: line modifiers (5.1). 28 columns.

Column	Type	Null	Key
id	int(11)	no	PRI
Sucursal	varchar(255)	yes	—
Movimiento_Id	varchar(255)	yes	MUL
Descripcion	varchar(255)	yes	—
Cantidad	varchar(255)	yes	—
PrecioUnitario	varchar(255)	yes	—
Descuento	varchar(255)	yes	—
Subtotal	varchar(255)	yes	—
IVA	varchar(255)	yes	—
IEPS	varchar(255)	yes	—
Total	varchar(255)	yes	—
Modificador	varchar(255)	yes	—
Hora	varchar(255)	yes	—
Costo	varchar(255)	yes	—

`TipoGrupo`	varchar(255)	yes	—
`CodigoTipoGrupo`	varchar(255)	yes	—
`CuentaContableTipoGrupo`	varchar(255)	yes	—
`Grupo`	varchar(255)	yes	—
`CodigoGrupo`	varchar(255)	yes	—
`CuentaContableGrupo`	varchar(255)	yes	—
`CodigoPlatillo`	varchar(255)	yes	—
`CuentaContablePlatillo`	varchar(255)	yes	—
`Platillo`	varchar(255)	yes	—
`ConIVA`	varchar(255)	yes	—
`ComandaId`	varchar(255)	yes	—
`TipoPlatilloId`	varchar(255)	yes	—
`TipoPromocionId`	varchar(255)	yes	—
`Modificadores_Id`	varchar(255)	yes	—

`getglobalcashclosing`: cash closing (Z report) per branch and day (5.1). 49 columns.

Column	Type	Null	Key
`id`	int(11)	no	PRI
`subsidiary_id`	int(11)	yes	MUL
`subsidiary_name`	varchar(255)	yes	—
`fecha_corte`	datetime	yes	—
`usuario`	varchar(255)	yes	—
`subtotal`	decimal(10,2)	yes	—
`iva`	decimal(10,2)	yes	—
`ieps`	decimal(10,2)	yes	—
`total_ventas`	decimal(10,2)	yes	—
`efectivo_por_ventas`	decimal(10,2)	yes	—
`efectivo_por_propina`	decimal(10,2)	yes	—
`fondo_de_caja`	decimal(10,2)	yes	—
`efectivo_real`	decimal(10,2)	yes	—
`no_ordenes`	int(11)	yes	—
`no_platillos`	int(11)	yes	—
`total_personas`	int(11)	yes	—
`promedio_platillos_orden`	decimal(10,2)	yes	—

promedio_por_orden	decimal(10,2)	yes	—
promedio_por_persona	decimal(10,2)	yes	—
total_ordenes_para_llevar	int(11)	yes	—
total_mesas_atendidas	int(11)	yes	—
total_ordenes_a_domicilio	int(11)	yes	—
total_ordenes_recoger	int(11)	yes	—
no_cortesias_en_cuentas	int(11)	yes	—
cortesias_en_cuentas	decimal(10,2)	yes	—
no_cortesias_en_platillos	int(11)	yes	—
cortesias_en_platillos	decimal(10,2)	yes	—
no_cancelaciones_en_cuentas	int(11)	yes	—
cancelaciones_en_cuentas	decimal(10,2)	yes	—
no_cancelaciones_en_platillos	int(11)	yes	—
cancelaciones_en_platillos	decimal(10,2)	yes	—
no_descuentos_en_cuentas	int(11)	yes	—
descuentos_en_cuentas	decimal(10,2)	yes	—
no_descuentos_en_platillos	int(11)	yes	—
descuentos_en_platillos	decimal(10,2)	yes	—
no_anulaciones_en_cuentas	int(11)	yes	—
anulaciones_en_cuentas	decimal(10,2)	yes	—
no_anulaciones_en_platillos	int(11)	yes	—
anulaciones_en_platillos	decimal(10,2)	yes	—
no_dxu_platillos	int(11)	yes	—
dxu_platillos	decimal(10,2)	yes	—
no_descuentos_megapuntos	int(11)	yes	—
descuentos_megapuntos	decimal(10,2)	yes	—
no_promociones	int(11)	yes	—
promociones	decimal(10,2)	yes	—
no_cupones	int(11)	yes	—
cupones	decimal(10,2)	yes	—
mes_ano	varchar(7)	yes	—
created_at	timestamp	no	—

A.2 Costs

`costeomensual`: month-to-date cost, daily snapshot (5.2). 17 columns.

Column	Type	Null	Key
`id`	int(11)	no	PRI
`subsidiary_id`	int(11)	yes	MUL
`subsidiary_name`	varchar(255)	yes	—
`CostoTotal`	decimal(10,2)	yes	—
`CostoDeProductosVendidos`	decimal(10,2)	yes	—
`CostoIdealDeProductosPendientesDeRebaja`	decimal(10,2)	yes	—
`CostoDeCortesías`	decimal(10,2)	yes	—
`CostoDeCancelaciones`	decimal(10,2)	yes	—
`CostoDeMerma`	decimal(10,2)	yes	—
`CostoDeDesperdicio`	decimal(10,2)	yes	—
`CostoDeRobo`	decimal(10,2)	yes	—
`CostoDeConsumo`	decimal(10,2)	yes	—
`AjustePorSobrantes`	decimal(10,2)	yes	—
`UtilidadMarginal`	decimal(10,2)	yes	—
`mes_ano`	varchar(7)	yes	—
`created_at`	timestamp	no	—
`created_date`	date	yes	—

`costeomensual_semanapyq`: week-to-date cost (5.2). 17 columns.

Column	Type	Null	Key
`id`	int(11)	no	PRI
`subsidiary_id`	int(11)	yes	MUL
`subsidiary_name`	varchar(255)	yes	—
`CostoTotal`	decimal(10,2)	yes	—
`CostoDeProductosVendidos`	decimal(10,2)	yes	—
`CostoIdealDeProductosPendientesDeRebaja`	decimal(10,2)	yes	—
`CostoDeCortesías`	decimal(10,2)	yes	—
`CostoDeCancelaciones`	decimal(10,2)	yes	—
`CostoDeMerma`	decimal(10,2)	yes	—
`CostoDeDesperdicio`	decimal(10,2)	yes	—
`CostoDeRobo`	decimal(10,2)	yes	—

`CostoDeConsumo`	decimal(10,2)	yes	—
`AjustePorSobrantes`	decimal(10,2)	yes	—
`UtilidadMarginal`	decimal(10,2)	yes	—
`mes_ano`	varchar(7)	yes	—
`created_at`	timestamp	no	—
`created_date`	date	yes	—

`gettotalcostbydate`: cost of sales of the day (5.2). 7 columns.

Column	Type	Null	Key
`id`	int(11)	no	PRI
`subsidiary_id`	int(11)	yes	MUL
`subsidiary_name`	varchar(255)	yes	—
`CostoTotalVenta`	decimal(10,2)	yes	—
`mes_ano`	varchar(7)	yes	—
`created_at`	timestamp	no	—
`created_date`	date	yes	—

`gettablajeriareport`: butchery yields, Wansoft history only (5.2). 17 columns.

Column	Type	Null	Key
`id`	int(11)	no	PRI
`subsidiary_id`	int(11)	yes	—
`subsidiary_name`	varchar(255)	yes	—
`InputDate`	date	yes	—
`UserName`	varchar(255)	yes	—
`QuantityOfBaseProduct`	decimal(15,10)	yes	—
`ProductBase`	varchar(255)	yes	—
`ProductBaseCost`	decimal(15,4)	yes	—
`UnitOfMeasureOfBaseProduct`	varchar(50)	yes	—
`QuantityDecrease`	decimal(15,10)	yes	—
`Warehouse`	varchar(255)	yes	—
`QuantityOfGeneratedProduct`	decimal(15,10)	yes	—
`GeneratedProduct`	varchar(255)	yes	—
`UnitCostOfGeneratedProduct`	decimal(15,10)	yes	—
`totalCostOfGeneratedProduct`	decimal(15,10)	yes	—

`RegistrationDate`	date	yes	—
`created_at`	timestamp	no	—

`costs_source_by_company`: cost source per branch (5.2). 6 columns.

Column	Type	Null	Key
`company_source_key`	varchar(100)	no	PRI
`wansoft_subsidiary_id`	int(11)	yes	—
`odoo_company_id`	int(11)	yes	—
`odoo_cost_start_date`	date	yes	—
`reason`	varchar(30)	no	—
`updated_at`	datetime	no	—

A.3 Purchases and invoices

`analytics_purchase_order_lines`: purchase lines, Wansoft + Odoo (5.3). 58 columns.

Column	Type	Null	Key
`purchase_order_line_analytical_key`	bigint(20)	no	PRI
`canonical_purchase_order_line_id`	bigint(20)	no	UNI
`source_system`	varchar(50)	no	MUL
`source_domain`	varchar(100)	yes	—
`source_order_line_id`	varchar(100)	yes	—
`source_order_id`	varchar(100)	yes	—
`purchase_order_name`	varchar(255)	yes	—
`company_source_key`	varchar(255)	yes	MUL
`company_analytical_key`	bigint(20)	yes	—
`company_id`	varchar(100)	yes	—
`company_name`	varchar(255)	yes	—
`final_purchase_source_status`	varchar(100)	yes	—
`company_migration_type`	varchar(100)	yes	—
`history_source`	varchar(100)	yes	—
`include_odoo_history`	tinyint(1)	yes	—
`operational_start_date`	date	yes	—
`migration_policy_source`	varchar(100)	yes	—
`order_date`	datetime	yes	—
`order_date_key`	int(11)	yes	—

vendor_analytical_key	bigint(20)	yes	MUL
vendor_id	varchar(100)	yes	—
vendor_name	varchar(255)	yes	—
normalized_vendor_name	varchar(255)	yes	—
is_internal_vendor	tinyint(1)	no	—
include_vendor_in_business_views	tinyint(1)	no	—
product_analytical_key	bigint(20)	yes	MUL
product_id	varchar(100)	yes	—
product_name	varchar(255)	yes	—
wansoft_code	varchar(100)	yes	—
wansoft_product_name	varchar(255)	yes	—
wansoft_department	varchar(255)	yes	—
product_mapping_found	tinyint(1)	yes	—
product_mapping_status	varchar(100)	yes	—
product_mapping_source	varchar(100)	yes	—
purchase_line_type	varchar(100)	yes	—
purchase_product_scope	varchar(100)	yes	—
purchase_mapping_bucket	varchar(100)	yes	—
purchase_classification_source	varchar(100)	yes	—
extracted_product_code	varchar(100)	yes	—
product_identity_status	varchar(100)	yes	—
dim_product_mapping_status	varchar(100)	yes	—
is_product_mapped	tinyint(1)	no	—
is_product_review_required	tinyint(1)	no	—
include_product_in_business_views	tinyint(1)	no	—
product_qty	decimal(18,4)	yes	—
qty_received	decimal(18,4)	yes	—
qty_invoiced	decimal(18,4)	yes	—
price_unit	decimal(18,4)	yes	—
price_subtotal	decimal(18,4)	yes	—
price_total	decimal(18,4)	yes	—
state	varchar(100)	yes	—
canonical_loaded_at	timestamp	yes	—

include_in_business_views	tinyint(1)	no	MUL
exclude_reason	varchar(500)	yes	—
line_review_status	varchar(100)	yes	—
catalog_status	varchar(50)	yes	—
created_at	datetime	no	—
updated_at	datetime	no	—

analytics_purchase_orders: purchase orders / invoices, Wansoft + Odoo (5.3). 43 columns.

Column	Type	Null	Key
purchase_order_analytical_key	bigint(20)	no	PRI
source_system	varchar(50)	no	MUL
source_domain	varchar(100)	yes	—
source_order_id	varchar(100)	no	—
purchase_order_name	varchar(255)	yes	—
company_source_key	varchar(255)	yes	MUL
company_analytical_key	bigint(20)	yes	—
company_id	varchar(100)	yes	—
company_name	varchar(255)	yes	—
final_purchase_source_status	varchar(100)	yes	—
company_migration_type	varchar(100)	yes	—
history_source	varchar(100)	yes	—
include_odoo_history	tinyint(1)	yes	—
operational_start_date	date	yes	—
migration_policy_source	varchar(100)	yes	—
order_date	datetime	yes	—
order_date_key	int(11)	yes	—
vendor_analytical_key	bigint(20)	yes	MUL
vendor_id	varchar(100)	yes	—
vendor_name	varchar(255)	yes	—
normalized_vendor_name	varchar(255)	yes	—
is_internal_vendor	tinyint(1)	no	—
include_vendor_in_business_views	tinyint(1)	no	—
line_count	bigint(20)	no	—
business_line_count	bigint(20)	no	—

excluded_line_count	bigint(20)	no	—
review_required_line_count	bigint(20)	no	—
internal_vendor_line_count	bigint(20)	no	—
review_required_product_line_count	bigint(20)	no	—
orphan_product_line_count	bigint(20)	no	—
product_qty_total	decimal(18,4)	yes	—
qty_received_total	decimal(18,4)	yes	—
qty_invoiced_total	decimal(18,4)	yes	—
price_subtotal_total	decimal(18,4)	yes	—
price_total_total	decimal(18,4)	yes	—
state_values	text	yes	—
canonical_loaded_at_min	timestamp	yes	—
canonical_loaded_at_max	timestamp	yes	—
include_in_business_views	tinyint(1)	no	MUL
exclude_reason	varchar(500)	yes	—
order_review_status	varchar(100)	yes	—
created_at	datetime	no	—
updated_at	datetime	no	—

analytics_purchase_daily_company_product: purchases per branch × day × product (5.3). 42 columns.

Column	Type	Null	Key
daily_company_product_key	bigint(20)	no	PRI
company_source_key	varchar(255)	no	MUL
company_analytical_key	bigint(20)	yes	—
order_date	date	yes	—
order_date_key	int(11)	no	—
product_analytical_key	bigint(20)	yes	MUL
product_analytical_group_key	bigint(20)	no	MUL
source_system	varchar(50)	no	MUL
product_identity_status	varchar(100)	yes	—
dim_product_mapping_status	varchar(100)	yes	—
is_product_mapped	tinyint(1)	no	—
is_product_review_required	tinyint(1)	no	—
include_product_in_business_views	tinyint(1)	no	—

`line_count`	bigint(20)	no	—
`business_line_count`	bigint(20)	no	—
`excluded_line_count`	bigint(20)	no	—
`review_required_line_count`	bigint(20)	no	—
`internal_vendor_line_count`	bigint(20)	no	—
`review_required_product_line_count`	bigint(20)	no	—
`orphan_product_line_count`	bigint(20)	no	—
`purchase_order_count`	bigint(20)	no	—
`vendor_count`	bigint(20)	no	—
`product_qty_total`	decimal(18,4)	yes	—
`qty_received_total`	decimal(18,4)	yes	—
`qty_invoiced_total`	decimal(18,4)	yes	—
`business_product_qty_total`	decimal(18,4)	yes	—
`business_qty_received_total`	decimal(18,4)	yes	—
`business_qty_invoiced_total`	decimal(18,4)	yes	—
`excluded_product_qty_total`	decimal(18,4)	yes	—
`excluded_qty_received_total`	decimal(18,4)	yes	—
`excluded_qty_invoiced_total`	decimal(18,4)	yes	—
`price_subtotal_total`	decimal(18,4)	yes	—
`price_total_total`	decimal(18,4)	yes	—
`business_price_subtotal_total`	decimal(18,4)	yes	—
`business_price_total_total`	decimal(18,4)	yes	—
`excluded_price_subtotal_total`	decimal(18,4)	yes	—
`excluded_price_total_total`	decimal(18,4)	yes	—
`include_in_business_views`	tinyint(1)	no	MUL
`exclude_reason`	varchar(500)	yes	—
`aggregate_review_status`	varchar(100)	yes	MUL
`created_at`	datetime	no	—
`updated_at`	datetime	no	—

`getexpenses_factura`: Wansoft supplier invoices by account (5.3). 37 columns.

Column	Type	Null	Key
`id`	int(11)	no	—
`Sucursal`	varchar(255)	yes	—

`Factura_Id`	varchar(255)	yes	—
`IdDocumento`	varchar(255)	yes	UNI
`Folio`	varchar(255)	yes	—
`RFCProveedor`	varchar(255)	yes	—
`NombreProveedor`	varchar(255)	yes	—
`ClaveProveedor`	varchar(255)	yes	—
`CuentaContableProveedor`	varchar(255)	yes	—
`Subtotal`	varchar(255)	yes	—
`IVA`	varchar(255)	yes	—
`IEPS`	varchar(255)	yes	—
`Total`	varchar(255)	yes	—
`FechaDeExpedicion`	varchar(255)	yes	—
`FechaDeExpiracion`	varchar(255)	yes	—
`TerminosDePago`	varchar(255)	yes	—
`Cuenta`	varchar(255)	yes	—
`Subcuenta`	varchar(255)	yes	—
`Estatus`	varchar(255)	yes	—
`TotalDeudor`	varchar(255)	yes	—
`TipoDeEgreso`	varchar(255)	yes	—
`UUID`	varchar(255)	yes	—
`IdOrdenCompra`	varchar(255)	yes	—
`FolioOrdenCompra`	varchar(255)	yes	—
`FechaDeRegistro`	varchar(255)	yes	—
`DiasCredito`	varchar(255)	yes	—
`ColoniaProveedor`	varchar(255)	yes	—
`CiudadProveedor`	varchar(255)	yes	—
`CPProveedor`	varchar(255)	yes	—
`TelefonoProveedor`	varchar(255)	yes	—
`CorreoProveedor`	varchar(255)	yes	—
`CalleProveedor`	varchar(255)	yes	—
`NumeroIntProveedor`	varchar(255)	yes	—
`NumeroExtProveedor`	varchar(255)	yes	—
`Discount`	varchar(255)	yes	—

`Retentions`	varchar(255)	yes	—
`Egresos_Id`	varchar(255)	yes	—

`analytics_expense_invoices`: supplier invoices of every branch, Wansoft + Odoo, by account (5.7). 36 columns.

Column	Type	Null	Key
`expense_row_key`	char(32)	no	PRI
`expense_document_id`	varchar(40)	no	MUL
`source_system`	varchar(10)	no	—
`source_document_id`	varchar(32)	no	—
`document_type`	varchar(20)	no	—
`company_source_key`	varchar(100)	yes	MUL
`source_company_name`	varchar(255)	yes	—
`invoice_date`	date	yes	—
`due_date`	date	yes	—
`folio`	varchar(255)	yes	—
`uuid`	varchar(64)	yes	—
`uuid_document_count`	int(11)	yes	—
`vendor_name`	varchar(255)	yes	—
`vendor_rfc`	varchar(20)	yes	—
`vendor_key`	varchar(50)	yes	—
`tipo_de_egreso`	varchar(100)	yes	—
`cuenta`	varchar(255)	yes	MUL
`subcuenta`	varchar(255)	yes	—
`is_costo_operativo`	tinyint(1)	no	—
`classification_status`	varchar(30)	no	—
`source_account_name`	varchar(500)	yes	—
`subtotal`	decimal(18,2)	no	—
`discount`	decimal(18,2)	no	—
`iva`	decimal(18,2)	no	—
`ieps`	decimal(18,2)	yes	—
`retentions`	decimal(18,2)	no	—
`total`	decimal(18,2)	no	—
`status`	varchar(30)	yes	—
`source_status`	varchar(50)	yes	—

status_from_live	tinyint(1)	no	—
payment_date	date	yes	—
payment_terms	varchar(255)	yes	—
purchase_order_ref	varchar(500)	yes	—
include_in_business_views	tinyint(1)	no	MUL
exclude_reason	varchar(50)	yes	—
built_at	datetime	no	—

A.4 Inventory

analytics_inventory_balance: today's stock, all 19 branches (5.4). 15 columns.

Column	Type	Null	Key
inventory_balance_key	bigint(20)	no	PRI
company_source_key	varchar(255)	no	MUL
source_system	varchar(20)	no	—
wansoft_code	varchar(255)	no	MUL
product_name	varchar(500)	yes	—
current_balance_qty	decimal(18,4)	no	—
source_row_count	bigint(20)	no	—
entrada_qty	decimal(18,4)	yes	—
salida_qty	decimal(18,4)	yes	—
final_inventory_source_status	varchar(100)	no	—
include_in_business_views	tinyint(1)	no	MUL
exclude_reason	varchar(500)	yes	—
refreshed_at	datetime	no	—
created_at	datetime	no	—
updated_at	datetime	no	—

analytics_inventory_current_product_location: today's Odoo stock by location (5.4). 37 columns.

Column	Type	Null	Key
inventory_current_product_location_key	bigint(20)	no	PRI
current_snapshot_loaded_at	datetime	no	MUL
snapshot_date	date	yes	—
snapshot_date_key	int(11)	no	MUL
product_analytical_key	bigint(20)	no	MUL

odoo_product_id	varchar(100)	yes	—
odoo_product_name	varchar(500)	yes	—
product_code	varchar(255)	yes	—
wansoft_code	varchar(255)	yes	—
wansoft_product_name	varchar(500)	yes	—
wansoft_department	varchar(255)	yes	—
product_identity_status	varchar(100)	yes	—
dim_product_mapping_status	varchar(100)	yes	—
is_product_mapped	tinyint(1)	no	—
is_product_review_required	tinyint(1)	no	—
include_product_in_business_views	tinyint(1)	no	—
source_location_id	varchar(100)	no	MUL
location_name	varchar(500)	yes	—
normalized_location_name	varchar(500)	yes	—
location_usage_type	varchar(100)	yes	—
is_virtual_location	tinyint(1)	no	—
is_partner_location	tinyint(1)	no	—
is_internal_location	tinyint(1)	no	—
location_mapping_status	varchar(100)	yes	—
company_source_key	varchar(255)	yes	—
company_mapping_status	varchar(100)	yes	—
source_row_count	bigint(20)	no	—
current_stock_qty	decimal(18,4)	no	—
positive_stock_qty	decimal(18,4)	no	—
zero_stock_row_count	bigint(20)	no	—
negative_stock_qty	decimal(18,4)	no	—
negative_row_count	bigint(20)	no	—
include_in_business_views	tinyint(1)	no	MUL
exclude_reason	varchar(500)	yes	—
aggregate_review_status	varchar(100)	no	MUL
created_at	datetime	no	—
updated_at	datetime	no	—

`getinputinventory_entrada`: Wansoft inventory entries (5.4). 38 columns.

Column	Type	Null	Key
id	int(11)	no	PRI
subsidiary_name	varchar(255)	yes	—
IdEntrada	varchar(50)	yes	MUL
ClaveAlmacen	varchar(50)	yes	—
Almacen	varchar(255)	yes	—
IdAlmacen	int(11)	yes	—
CuentaContableAlmacen	varchar(255)	yes	—
CodigoDepartamento	varchar(255)	yes	—
Departamento	varchar(255)	yes	—
CuentaContableDepartamento	varchar(255)	yes	—
IdProducto	int(11)	yes	—
CodigoProducto	varchar(50)	yes	—
NombreProducto	varchar(255)	yes	—
CodigoUnidadDeMedida	varchar(50)	yes	—
IdUnidadDeMedida	int(11)	yes	—
UnidadDeMedida	varchar(50)	yes	—
TipoEntrada	varchar(50)	yes	—
Cantidad	decimal(15,10)	yes	—
CostoUnitario	decimal(15,4)	yes	—
ProductoConIVA	tinyint(1)	yes	—
Caducidad	date	yes	—
FechaEntrada	datetime	yes	MUL
Factura	varchar(50)	yes	—
FechaFactura	date	yes	—
RFCProveedor	varchar(50)	yes	—
ClaveProveedor	varchar(50)	yes	—
NombreProveedor	varchar(255)	yes	—
IdTransferencia	int(11)	yes	—
FolioTransferencia	varchar(50)	yes	—
IdOrdenCompra	int(11)	yes	—
FolioOrdenCompra	varchar(50)	yes	—
RFCProveedorOrdenCompra	varchar(50)	yes	—

`ProveedorOrdenCompra`	varchar(255)	yes	—
`IdDocumento`	int(11)	yes	—
`IdUsuario`	int(11)	yes	—
`NombreUsuario`	varchar(255)	yes	—
`FechaReal`	date	yes	—
`created_at`	timestamp	no	—

`getoutgoinginventory_salida`: Wansoft inventory exits (5.4). 29 columns.

Column	Type	Null	Key
`id`	int(11)	no	PRI
`subsidiary_name`	varchar(255)	yes	MUL
`IdSalida`	varchar(50)	yes	—
`IdEntrada`	varchar(50)	yes	—
`IdAlmacen`	int(11)	yes	—
`Almacen`	varchar(255)	yes	—
`CuentaContableAlmacen`	varchar(255)	yes	—
`CuentaContableDepartamento`	varchar(255)	yes	—
`Departamento`	varchar(255)	yes	—
`IdProducto`	int(11)	yes	—
`CodigoProducto`	varchar(50)	yes	—
`NombreProducto`	varchar(255)	yes	—
`CodigoUnidadDeMedida`	varchar(50)	yes	—
`IdUnidadDeMedida`	int(11)	yes	—
`UnidadDeMedida`	varchar(50)	yes	—
`TipoSalida`	varchar(50)	yes	—
`Cantidad`	decimal(15,10)	yes	—
`CostoUnitario`	decimal(15,4)	yes	—
`Caducidad`	date	yes	—
`FechaSalida`	datetime	yes	MUL
`IdTransferencia`	varchar(50)	yes	—
`FolioTransferencia`	varchar(50)	yes	—
`Orden`	varchar(50)	yes	—
`Fecha`	date	yes	—
`IdDetalleVenta`	varchar(50)	yes	—

`IdUsuario`	varchar(50)	yes	—
`NombreUsuario`	varchar(255)	yes	—
`FechaReal`	date	yes	—
`created_at`	timestamp	no	—

`wansoft_parallel_inputinventory_entrada`: entries the Odoo branches keep capturing in Wansoft, comparison only (5.4). 38 columns.

Column	Type	Null	Key
`id`	int(11)	no	PRI
`subsidiary_name`	varchar(255)	yes	—
`IdEntrada`	varchar(50)	yes	MUL
`ClaveAlmacen`	varchar(50)	yes	—
`Almacen`	varchar(255)	yes	—
`IdAlmacen`	int(11)	yes	—
`CuentaContableAlmacen`	varchar(255)	yes	—
`CodigoDepartamento`	varchar(255)	yes	—
`Departamento`	varchar(255)	yes	—
`CuentaContableDepartamento`	varchar(255)	yes	—
`IdProducto`	int(11)	yes	—
`CodigoProducto`	varchar(50)	yes	—
`NombreProducto`	varchar(255)	yes	—
`CodigoUnidadDeMedida`	varchar(50)	yes	—
`IdUnidadDeMedida`	int(11)	yes	—
`UnidadDeMedida`	varchar(50)	yes	—
`TipoEntrada`	varchar(50)	yes	—
`Cantidad`	decimal(15,10)	yes	—
`CostoUnitario`	decimal(15,4)	yes	—
`ProductoConIVA`	tinyint(1)	yes	—
`Caducidad`	date	yes	—
`FechaEntrada`	datetime	yes	MUL
`Factura`	varchar(50)	yes	—
`FechaFactura`	date	yes	—
`RFCProveedor`	varchar(50)	yes	—
`ClaveProveedor`	varchar(50)	yes	—

NombreProveedor	varchar(255)	yes	—
IdTransferencia	int(11)	yes	—
FolioTransferencia	varchar(50)	yes	—
IdOrdenCompra	int(11)	yes	—
FolioOrdenCompra	varchar(50)	yes	—
RFCProveedorOrdenCompra	varchar(50)	yes	—
ProveedorOrdenCompra	varchar(255)	yes	—
IdDocumento	int(11)	yes	—
IdUsuario	int(11)	yes	—
NombreUsuario	varchar(255)	yes	—
FechaReal	date	yes	—
created_at	timestamp	no	—

wansoft_parallel_outgoinginventory_salida: exits the Odoo branches keep capturing in Wansoft, comparison only (5.4). 29 columns.

Column	Type	Null	Key
id	int(11)	no	PRI
subsidiary_name	varchar(255)	yes	MUL
IdSalida	varchar(50)	yes	—
IdEntrada	varchar(50)	yes	—
IdAlmacen	int(11)	yes	—
Almacen	varchar(255)	yes	—
CuentaContableAlmacen	varchar(255)	yes	—
CuentaContableDepartamento	varchar(255)	yes	—
Departamento	varchar(255)	yes	—
IdProducto	int(11)	yes	—
CodigoProducto	varchar(50)	yes	—
NombreProducto	varchar(255)	yes	—
CodigoUnidadDeMedida	varchar(50)	yes	—
IdUnidadDeMedida	int(11)	yes	—
UnidadDeMedida	varchar(50)	yes	—
TipoSalida	varchar(50)	yes	—
Cantidad	decimal(15,10)	yes	—
CostoUnitario	decimal(15,4)	yes	—

`Caducidad`	date	yes	—
`FechaSalida`	datetime	yes	MUL
`IdTransferencia`	varchar(50)	yes	—
`FolioTransferencia`	varchar(50)	yes	—
`Orden`	varchar(50)	yes	—
`Fecha`	date	yes	—
`IdDetalleVenta`	varchar(50)	yes	—
`IdUsuario`	varchar(50)	yes	—
`NombreUsuario`	varchar(255)	yes	—
`FechaReal`	date	yes	—
`created_at`	timestamp	no	—

`odoo_inventory_quant_daily`: Odoo stock day by day, since 2026-10-08 (5.4). 14 columns.

Column	Type	Null	Key
`stock_date`	date	no	PRI
`odoo_location_id`	int(11)	no	PRI
`odoo_product_id`	int(11)	no	PRI
`captured_at`	datetime	no	—
`odoo_company_id`	int(11)	yes	—
`odoo_company_name`	varchar(255)	yes	—
`company_source_key`	varchar(100)	yes	MUL
`location_name`	varchar(500)	yes	—
`location_usage`	varchar(30)	no	—
`product_code`	varchar(100)	yes	—
`product_name`	varchar(500)	yes	—
`quantity`	decimal(18,4)	no	—
`reserved_quantity`	decimal(18,4)	no	—
`quant_count`	int(11)	no	—

`analytics_inventory_movements`: unified inventory movements, Wansoft + Odoo (5.4). 24 columns.

Column	Type	Null	Key
`movement_key`	bigint(20)	no	PRI
`movement_date`	date	no	—
`company_source_key`	varchar(100)	no	MUL

source_system	varchar(10)	no	MUL
source_record	varchar(20)	no	MUL
source_movement_id	varchar(80)	no	—
captured_date	date	yes	—
direction	char(3)	no	—
movement_type	varchar(20)	no	—
source_movement_type	varchar(100)	yes	—
wansoft_code	varchar(50)	yes	—
odoo_product_id	int(11)	yes	—
product_name	varchar(255)	yes	—
unit_name	varchar(50)	yes	—
quantity	decimal(18,6)	no	—
unit_cost	decimal(18,6)	yes	—
total_cost	decimal(18,4)	yes	—
location_name	varchar(255)	yes	—
counts_in_stock	tinyint(1)	no	—
final_source_status	varchar(40)	no	—
include_in_business_views	tinyint(1)	no	—
loaded_at	datetime	no	—
product_code	varchar(60)	yes	MUL
product_code_status	varchar(15)	yes	—

analytics_inventory_stock_daily: stock per branch × product × day, Wansoft + Odoo (5.4). 11 columns.

Column	Type	Null	Key
stock_date	date	no	PRI
company_source_key	varchar(100)	no	PRI
product_code	varchar(60)	no	PRI
source_system	varchar(10)	no	—
product_name	varchar(255)	yes	—
stock_qty	decimal(18,6)	no	—
stock_value	decimal(18,4)	yes	—
moved_qty	decimal(18,6)	no	—
final_source_status	varchar(40)	no	—
include_in_business_views	tinyint(1)	no	—

built_at	datetime	no	—

analytics_odoo_product_code: Wansoft code of each Odoo product (5.4). 6 columns.

Column	Type	Null	Key
odoo_product_id	int(11)	no	PRI
odoo_product_name	varchar(255)	yes	—
wansoft_code	varchar(50)	no	MUL
wansoft_product_name	varchar(255)	yes	—
mapping_source	varchar(50)	yes	—
updated_at	datetime	no	—

A.5 Governance and dimensions

analytics_company_domain_coverage: source of each domain per branch (5.6). 31 columns.

Column	Type	Null	Key
company_source_key	varchar(255)	no	PRI
display_name	varchar(255)	no	—
is_active_branch	tinyint(1)	no	—
is_internal_provider	tinyint(1)	no	—
is_final_operating_branch	tinyint(1)	no	—
is_future_rollout	tinyint(1)	no	—
is_zenput_location	tinyint(1)	no	—
is_zenput_only	tinyint(1)	no	—
purchases_source_system	varchar(100)	no	—
inventory_source_system	varchar(100)	no	—
sales_source_system	varchar(100)	no	—
zenput_source_status	varchar(100)	no	—
rollout_type	varchar(100)	yes	MUL
rollout_status	varchar(100)	yes	—
operational_start_date	date	yes	—
has_purchases	tinyint(1)	no	MUL
has_purchase_orders	tinyint(1)	no	—
has_purchase_lines	tinyint(1)	no	—
has_inventory	tinyint(1)	no	—
has_zenput_submissions	tinyint(1)	no	—

has_zenput_tasks	tinyint(1)	no	—
has_sales_future_placeholder	tinyint(1)	no	—
purchase_order_count	bigint(20)	no	—
purchase_line_count	bigint(20)	no	—
inventory_snapshot_count	bigint(20)	no	—
zenput_submission_count	bigint(20)	no	—
zenput_task_count	bigint(20)	no	—
coverage_status	varchar(100)	no	MUL
coverage_notes	text	yes	—
created_at	datetime	no	—
updated_at	datetime	no	—

dim_company_analytical: branches and companies (5.6). 25 columns.

Column	Type	Null	Key
company_analytical_key	bigint(20)	no	PRI
company_source_key	varchar(255)	no	UNI
display_name	varchar(255)	no	MUL
normalized_name	varchar(255)	yes	—
brand_group	varchar(255)	yes	—
is_active_branch	tinyint(1)	no	—
is_internal_provider	tinyint(1)	no	—
is_final_operating_branch	tinyint(1)	no	—
is_future_rollout	tinyint(1)	no	—
is_wansoft_company	tinyint(1)	no	—
is_odoo_company	tinyint(1)	no	—
is_zenput_location	tinyint(1)	no	—
is_zenput_only	tinyint(1)	no	—
purchases_source_system	varchar(100)	no	MUL
inventory_source_system	varchar(100)	no	—
sales_source_system	varchar(100)	no	—
zenput_source_status	varchar(100)	no	—
rollout_type	varchar(100)	yes	MUL
rollout_status	varchar(100)	yes	—
operational_start_date	date	yes	—

include_in_business_views	tinyint(1)	no	—
exclude_reason	varchar(255)	yes	—
notes	text	yes	—
created_at	datetime	no	—
updated_at	datetime	no	—

dim_product: products (5.3). 38 columns.

Column	Type	Null	Key
product_analytical_key	bigint(20)	no	PRI
product_display_name	varchar(500)	no	—
normalized_product_name	varchar(500)	no	MUL
product_canonical_name	varchar(500)	yes	—
product_identity_status	varchar(100)	no	MUL
wansoft_code	varchar(255)	yes	MUL
wansoft_product_name	varchar(500)	yes	—
wansoft_department	varchar(255)	yes	—
wansoft_family	varchar(255)	yes	—
wansoft_group	varchar(255)	yes	—
odoo_product_id	varchar(255)	yes	MUL
odoo_product_name	varchar(500)	yes	—
odoo_default_code	varchar(255)	yes	—
odoo_category	varchar(255)	yes	—
odoo_uom	varchar(100)	yes	—
mapping_status	varchar(100)	no	MUL
mapping_source	varchar(255)	yes	—
mapping_confidence	varchar(100)	yes	—
is_mapped	tinyint(1)	no	—
is_unmapped	tinyint(1)	no	—
is_review_required	tinyint(1)	no	—
is_excluded	tinyint(1)	no	—
exclude_reason	varchar(255)	yes	—
company_scope	varchar(255)	yes	—
scope_bucket	varchar(255)	yes	MUL
product_business_domain	varchar(255)	yes	—

is_restaurant_product	tinyint(1)	no	—
is_bodegon_product	tinyint(1)	no	—
is_empanadas_product	tinyint(1)	no	—
is_shared_cross_company	tinyint(1)	no	—
source_system	varchar(100)	no	MUL
source_table	varchar(255)	yes	—
source_product_key	varchar(255)	no	—
source_product_name	varchar(500)	yes	—
include_in_business_views	tinyint(1)	no	MUL
notes	text	yes	—
created_at	datetime	no	—
updated_at	datetime	no	—

dim_vendor: vendors (5.3). 18 columns.

Column	Type	Null	Key
vendor_analytical_key	bigint(20)	no	PRI
vendor_display_name	varchar(255)	no	MUL
normalized_vendor_name	varchar(255)	no	UNI
vendor_canonical_name	varchar(255)	yes	—
vendor_source_system	varchar(100)	no	MUL
wansoft_vendor_id	varchar(255)	yes	—
odoo_vendor_id	varchar(255)	yes	—
source_vendor_name	text	yes	—
source_vendor_key	text	yes	—
is_internal_vendor	tinyint(1)	no	MUL
is_external_vendor	tinyint(1)	no	—
is_active	tinyint(1)	no	—
is_review_required	tinyint(1)	no	—
include_in_business_views	tinyint(1)	no	MUL
exclude_reason	varchar(255)	yes	—
notes	text	yes	—
created_at	datetime	no	—
updated_at	datetime	no	—

`dim_time`: calendar (5.6). 37 columns.

Column	Type	Null	Key
`date_key`	int(11)	no	PRI
`calendar_date`	date	no	UNI
`year`	smallint(6)	no	MUL
`year_start_date`	date	no	—
`year_end_date`	date	no	—
`is_year_start`	tinyint(1)	no	—
`is_year_end`	tinyint(1)	no	—
`quarter_number`	tinyint(4)	no	—
`quarter_name`	varchar(10)	no	—
`year_quarter`	varchar(20)	no	MUL
`quarter_start_date`	date	no	—
`quarter_end_date`	date	no	—
`is_quarter_start`	tinyint(1)	no	—
`is_quarter_end`	tinyint(1)	no	—
`month_number`	tinyint(4)	no	—
`month_name`	varchar(20)	no	—
`month_short_name`	varchar(10)	no	—
`year_month_label`	varchar(10)	no	MUL
`month_start_date`	date	no	—
`month_end_date`	date	no	—
`is_month_start`	tinyint(1)	no	—
`is_month_end`	tinyint(1)	no	—
`week_of_year`	tinyint(4)	no	—
`iso_week_of_year`	tinyint(4)	no	—
`iso_year`	smallint(6)	no	MUL
`week_start_date`	date	no	—
`week_end_date`	date	no	—
`is_week_start`	tinyint(1)	no	—
`is_week_end`	tinyint(1)	no	—
`day_of_month`	tinyint(4)	no	—
`day_of_year`	smallint(6)	no	—

day_of_week_number	tinyint(4)	no	—
day_of_week_name	varchar(20)	no	—
day_of_week_short_name	varchar(10)	no	—
is_weekend	tinyint(1)	no	MUL
created_at	datetime	no	—
updated_at	datetime	no	—

A.6 Zenput (database zenput)

form_templates: checklist templates (5.5). 8 columns.

Column	Type	Null	Key
form_id	int(11)	no	PRI
title	varchar(255)	yes	—
num_submissions	int(11)	yes	—
date_created	datetime	yes	—
date_last_submitted	datetime	yes	—
creator_full_name	varchar(255)	yes	—
category_name	varchar(255)	yes	—
last_updated	timestamp	no	—

submissions: submitted checklists (5.5). 6 columns.

Column	Type	Null	Key
submission_id	varchar(255)	no	PRI
form_template_id	int(11)	yes	MUL
location_name	varchar(255)	yes	—
user_display_name	varchar(255)	yes	—
date_submitted	datetime	yes	—
time_to_complete	int(11)	yes	—

submission_answers: answers (5.5). 6 columns.

Column	Type	Null	Key
answer_id	int(11)	no	PRI
submission_id	varchar(255)	yes	MUL
field_id	int(11)	yes	—
title	text	yes	—

`field_type`	varchar(50)	yes	—
`value_as_string`	text	yes	—

`zenput_tasks`: tasks (5.5). 42 columns.

Column	Type	Null	Key
`task_id`	int(11)	no	PRI
`title`	text	yes	—
`description`	text	yes	—
`company_id`	int(11)	yes	—
`account_id`	int(11)	yes	—
`account_name`	varchar(255)	yes	—
`account_address`	text	yes	—
`account_city`	varchar(100)	yes	—
`account_state`	varchar(100)	yes	—
`account_zipcode`	varchar(20)	yes	—
`account_country`	varchar(10)	yes	—
`account_lat`	decimal(10,8)	yes	—
`account_lon`	decimal(11,8)	yes	—
`status_id`	int(11)	yes	—
`status_type`	varchar(50)	yes	—
`status_name`	varchar(50)	yes	—
`reply_type`	varchar(50)	yes	—
`reporter_id`	int(11)	yes	—
`reporter_display_name`	varchar(255)	yes	—
`assignee_id`	int(11)	yes	—
`assignee_display_name`	varchar(255)	yes	—
`date_created`	datetime	yes	—
`date_modified`	datetime	yes	—
`date_start`	datetime	yes	—
`date_due`	datetime	yes	—
`time_zone`	varchar(100)	yes	—
`is_active`	tinyint(1)	yes	—
`is_closed`	tinyint(1)	yes	—
`project_id`	int(11)	yes	—

`fulfillment_type`	varchar(50)	yes	—
`fulfillment_date_completed`	datetime	yes	—
`fulfillment_date_submitted`	datetime	yes	—
`fulfillment_user_id`	int(11)	yes	—
`fulfillment_user_display_name`	varchar(255)	yes	—
`fulfillment_fields`	longtext	yes	—
`date_submitted`	datetime	yes	—
`deleted`	tinyint(1)	yes	—
`num_comments`	int(11)	yes	—
`is_completed_late`	tinyint(1)	yes	—
`current_state`	varchar(50)	yes	—
`subscribers`	longtext	yes	—
`last_updated`	timestamp	no	—