
Photovoltaics in Germany

Figures on capacity, density, electricity mix and redispatch

Data sources

- Energy-Charts.info: electricity mix, installed capacity and district/state PV history.
- Marktstammdatenregister: operating-unit records, commissioning cohorts and EEG-exit inputs.
- SMARD: monthly redispatch observations and state aggregates.
- BKG VG250: administrative boundaries and identifiers.
- Destatis: official state land-area totals.
- Netzentwicklungsplan: 2025 scenario tables and map pages.
- BNetzA: congestion-management and curtailment reports.

Electricity mix by source



Electricity mix by source, Germany, 2025
Visualization: EIFER
Data: Energy-Charts.info (retrieved 16.10.2026)


Key messages

1. Renewables supplied about 60% of Germany's electricity generation in 2025.
2. Wind and solar were the dominant renewable contributors in the mix.

Methodology
Adapted from the Energy-Charts annual electricity-mix figure for Germany in 2025; the displayed categories and values are retained from the provider figure.

Sources
Energy-Charts.info: annual electricity mix, Germany 2025.

Installed electricity capacity by technology



Installed electricity capacity by technology, Germany, 2026

Visualization: EIFER

Data: Energy-Charts.info (retrieved 16.10.2026)

Key messages

1. PV has become one of Germany's leading installed electricity-capacity technologies.


Methodology

The Energy-Charts installed-power view is adapted for Germany 2026. Technology values are taken from the provider view in its capacity units; no forecast or generation conversion is applied.

Sources

Energy-Charts.info: installed-power view.

National PV density by district



Key messages

1. High-capacity districts are not always the most intense once area is considered.
2. The map shows where installed PV is concentrated spatially.


Methodology

The district density values are taken from the Energy-Charts solar-per-area map and matched to BKG district geometries for the map and labels.

Sources

Energy-Charts installed-power map; BKG VG250.

National PV density: 2000–2026



Key messages

1. PV expansion moves from a few concentrated areas toward broad national coverage.
2. Southern and western districts remain prominent high-density areas as deployment spreads elsewhere.
3. Growth in the total is accompanied by persistent spatial concentration.


Methodology

One PNG frame is generated for each year from 2000–2026. District capacities are divided by district area, coloured with a fixed 0–780 kWp/km^2 scale, and embedded with `animateinline` and `multiframe`; year and total labels come from the workbook totals. The same yearly frames are also exported as a GIF for PowerPoint.

Sources

Energy-Charts installed-power map; BKG VG250.

East and West: observed comparison



Key messages

1. East and West show a large difference in installed capacity, but a much smaller difference in capacity density.
2. Normalising by area changes the regional comparison substantially.


Methodology

Published district/state observations are assigned to fixed East and West groups, summed by year, and divided by summed group area. No interpolation or model adjustment is applied.

Sources

Energy-Charts installed-power map; BKG VG250; Destatis areas.

North and South: observed comparison





Key messages

1. The north–south difference in installed PV is less pronounced than the geographic impression suggests.
2. Similar installed capacity does not imply similar generation: southern irradiance can raise output without changing the capacity comparison.


Methodology

Published district/state observations are filtered into fixed North and South groups. Capacity is aggregated directly and density is calculated from total capacity divided by total group area; irradiance and generation are not modelled.

Sources

Energy-Charts installed-power map; BKG VG250; Destatis areas.

East and West: capacity forecast





Key messages

1. The East–West gap is much larger in total capacity than in capacity density.
2. NEP means Network Development Plan: its A–C pathways are planning scenarios for future capacity, not a fitted prediction.


Methodology

State observations are aggregated into fixed East and West groups, then divided by summed Destatis areas. Historical values come from Energy-Charts; the A–C band and B line are transcribed from NEP scenario tables.

Sources

Energy-Charts installed-power map; NEP 2037–2045, 2025 second draft; Destatis state areas.

North and South: capacity forecast





Key messages

1. Observed North–South differences in installed PV are modest relative to the regional map impression.
2. The NEP pathways imply different future expansion scales, not a measured current gap.


Methodology

State observations are filtered into fixed North and South groups. Capacity is summed by year and density is recalculated from group capacity and area; future paths are copied from NEP scenario tables.

Sources

Energy-Charts installed-power map; NEP 2037–2045, 2025 second draft; Destatis state areas.

NEP B: ground-mounted and rooftop density



Key messages

1. Rooftop and ground-mounted PV have different spatial signatures.
2. The common scale makes the technologies comparable.


Methodology

Six panels are reconstructed from NEP scenario-B map pages using one shared colour scale. District values are colour-read estimates rather than a published district table; BKG geometries provide the common map frame.

Sources

NEP 2037–2045, 2025 first draft, scenario B; BKG VG250.

Baden-Württemberg versus Bavaria



Key messages

1. Bavaria leads in both total capacity and capacity density; the density gap is smaller than the capacity gap.
2. Both series show strong post-2010 expansion.


Methodology

The two state records are selected from the Energy-Charts workbook. Capacity remains the published state total; density is calculated using each state's Destatis area, with no capacity normalisation.

Sources

Energy-Charts installed-power map; BKG VG250; Destatis state areas.

Saxony-Anhalt versus Thuringia



Key messages

1. Saxony-Anhalt leads Thuringia in both total installed capacity and capacity density.
2. The gap widens markedly after 2010, with Saxony-Anhalt reaching roughly twice Thuringia's 2026 capacity.


Methodology

The two state identifiers are matched to the historical workbook and plotted with identical units, year coverage and density calculation. State capacity is retained; density is calculated from capacity and Destatis area.

Sources

Energy-Charts installed-power map; BKG VG250; Destatis state areas.

Burgenland versus Saale-Holzland



Installed photovoltaic capacity — Saale-Holzland-Kreis vs Burgenlandkreis historical capacity and latest-year map density

Data: Energy-Charts info (retrieved 16.10.2026)

Key messages

1. The two districts diverge in both capacity and density.
2. Local comparisons can reveal patterns hidden at state scale.
3. District and state results should not be ranked as one population.


Methodology

The district identifiers are matched to the Energy-Charts historical capacity and density records; BKG geometries provide the district map frame.

Sources

Energy-Charts installed-power map; BKG VG250.

Capacity versus density: all federal states




Key messages

1. Total capacity and density identify different leaders.
2. Small-area states can be intense without being large in total.
3. The scatter is descriptive; no regression is implied.

Methodology
Each state's latest capacity record is joined with its official area and density is calculated as capacity divided by area. Points are labelled by state abbreviation; no regression line or causal estimate is added.

Sources
Energy-Charts installed-power map; Destatis state areas.

Capacity versus density: city states



Key messages

1. Small denominators amplify capacity density.
2. High density does not mean high total capacity.
3. City-state values need a different spatial interpretation.


Methodology

The state capacity–density table is filtered to Berlin, Bremen and Hamburg after density is calculated from capacity and area. The subset is isolated to make the denominator effect visible.

Sources

Energy-Charts installed-power map; Destatis state areas.

Capacity versus density: non-city states



Key messages

1. Removing city states reveals the larger-area pattern.
2. The logarithmic axis prevents large states from dominating visibility.
3. Density itself is not transformed.

Methodology

The state table is filtered to non-city states. Capacity is displayed on a logarithmic axis for legibility, while density remains the linear capacity-per-area calculation.

Sources

Energy-Charts installed-power map; Destatis state areas.

Capacity versus density: all states



Key messages

1. The axis scaling makes small and large states visible together.
2. Relative differences are easier to inspect than absolute gaps.
3. The underlying capacity and density values are unchanged.


Methodology

State capacity and area pairs are plotted with a logarithmic capacity coordinate. Only the coordinate transform changes; capacity, density and labels remain source-derived values.

Sources

Energy-Charts installed-power map; Destatis state areas.

Historical curtailment by state: grid congestion management (EinsMan)



Key messages

1. Curtailment was strongly concentrated in the north: Schleswig-Holstein accounted for 72.3% of the mapped total in 2016, while Lower Saxony accounted for 45.6% in 2021.
2. The concentration shifted within the north: Schleswig-Holstein's share fell to 32.0% by 2021 as Lower Saxony became the largest contributor.
3. The historical measure combines renewable plants with combined heat and power (CHP), so it is not a PV-only measure.


Methodology

Here, EinsMan means grid congestion management: the temporary reduction of generation when network constraints require it. The figure transcribes BNetzA annual state values for renewable and CHP plants; map labels show each state's share of the national total. Published dashes remain missing, and no values are estimated from colour, neighbouring states or interpolation.

Sources

BNetzA annual congestion-management reports, 2016–2021.

Recent all-technology redispatch by state



Key messages

1. The national technology mix is changing: wind accounted for about 51% of the recorded total in 2023, versus 37% in 2025; PV rose from about 4% to 15%.
2. The geographic pattern is consistent with a hypothesis of more wind-related reductions in the north and more solar-related reductions in the south.
3. This remains a hypothesis: the source does not cross technology and state.


Methodology

The SMARD CSV is filtered to complete calendar years 2023–2025, grouped by state, and summed in GWh. This recent series covers all technologies. The national technology percentages are calculated separately from SMARD's technology table; the state table is not crossed with technology, so the north–south technology interpretation is not tested by this figure.

Sources

SMARD monthly data CSV; SMARD technology breakdown; SMARD state redispatch information.

Household price and PV selling tariff (ongoing)



Key messages

1. Household electricity prices and PV selling tariffs move on different paths.
2. The long-run tariff decline contrasts with the higher household-price series.


Methodology

A BDEW household-price series is combined with selected EEG/PV tariff anchors on a common year axis. The post-2026 selling-tariff segment is scenario-based; self-consumption, taxes, financing and operating costs are excluded.

Sources

BNetzA/EEG tariff archive; BDEW household-price series.

PV capacity by MaStR unit-size band (ongoing)



Key messages

1. Growth is visible across both small and large unit bands.
2. Cohort size reflects commissioning records, not annual generation.
3. Register completeness and snapshot date matter for interpretation.


Methodology

The dated MaStR full export is filtered to operating PV units, grouped by commissioning year, and assigned to unit-size bands. Capacity is summed within each cohort; this is a register-based reconstruction.

Sources

Marktstammdatenregister full export, revision 26.2, snapshot 13 October 2026.

EEG-exit cohorts (ongoing)



Key messages

1. The figure tracks both the number of affected units and their installed capacity, so large systems matter even when they are few in number.
2. The main exit wave arrives around 2030–2033, when early-2010s cohorts reach the end of support.
3. Support expiry does not imply closure or repowering.

Methodology

MaStR operating units are linked to commissioning records, grouped by commissioning year, and assigned an illustrative exit year equal to commissioning year plus 21. The two panels report cumulative units and capacity by cohort; the visual style is adapted from the PwC chart.

Sources

Marktstammdatenregister operating-unit data; EEG commissioning records; exit rule: commissioning year + 21; PwC, *Alte Photovoltaik-Anlagen: Ende der Förderung in Sicht*.