



Merchant

[Use Case](#)

[Models](#)

[Merchant Setting](#)

[Repository](#)

[MerchantRepository](#)

[Services](#)

[MerchantService](#)

Use Case

- Create merchant setting using entity id
- Update merchant setting
- Get merchant setting by entity id

Models

Merchant Setting

```
type MerchantSetting struct {  
    EntityID string `json:"entity_id" gorm:"primaryKey"`  
    CashboxID string `json:"cashbox_id"`  
    Enabled bool `json:"enabled"`  
    CreatedAt time.Time `json:"created_at"`  
    UpdatedAt time.Time `json:"updated_at"`  
}
```

Repository

MerchantRepository

```
type MerchantRepository interface {  
    SaveMerchantSetting(ctx context.Context, setting *models.MerchantSetting) error  
    UpdateMerchantSetting(ctx context.Context, setting *models.MerchantSetting) error  
    GetMerchantSetting(ctx context.Context, entityID string) (*models.MerchantSetting, error)  
}
```

Services

MerchantService

```
type MerchantSetting interface {  
    CreateMerchantSetting(ctx context.Context, entityID string) (*models.MerchantSetting, error)  
    UpdateMerchantSetting(ctx context.Context, setting *models.MerchantSetting) error  
    GetMerchantSetting(ctx context.Context, entityID string) (*models.MerchantSetting, error)  
}
```