



# Payment

Use Case

Models

Receipt

Transaction

Services

PaymentService

Repositories

ReceiptRepository

TransactionRepository

## Use Case

- **Handle integration with Payme API**
  - Subscribe API
  - Merchant API
- Create receipt for order using order id, card id and amount
- Pay receipt
- Get receipt by order
- Save transaction
- Update transaction
- Get transaction by id

## Models

### Receipt

```

type Receipt struct {
    ID          string    `json:"id" gorm:"primaryKey"`
    OrderID     string    `json:"order_id" gorm:"index:idx_order_receipt"`
    CardID      string    `json:"card_id"`
    Amount      int       `json:"amount"`
    CreatedAt   time.Time `json:"created_at"`
}

```

## Transaction

```

type Transaction struct {
    ID          string    `json:"id" gorm:"primaryKey"`
    RestaurantID string    `json:"restaurant_id" gorm:"index:idx_restaurant_tx"`
    Currency    string    `json:"currency"`
    Status      string    `json:"status"`
    CreateTime  int       `json:"create_time"`
    PayTime     int       `json:"pay_time"`
    CancelTime  int       `json:"cancel_time"`
    CardID      string    `json:"card_id"`
    Amount      int       `json:"amount"`
    Account     map[string]string `json:"account" gorm:"serializer:json"`
    CreatedAt   time.Time `json:"created_at"`
    UpdatedAt   time.Time `json:"updated_at"`
}

```

## Services

### PaymentService

```

type PaymentService interface {
    CreateReceipt(ctx context.Context, orderID, cardID string, amount int) (*models.Receipt, error)
    PayReceipt(ctx context.Context, receiptID string) error
    GetReceiptByOrder(ctx context.Context, orderID string) (*models.Receipt, error)
    SaveTransaction(ctx context.Context, tx *models.Transaction) error
    UpdateTransaction(ctx context.Context, tx *models.Transaction) error
    GetTransaction(ctx context.Context, txID string) (*models.Transaction, error)
}

```

# Repositories

## ReceiptRepository

```
type ReceiptRepository interface {  
    SaveReceipt(ctx context.Context, receipt *models.Receipt) error  
    GetReceipt(ctx context.Context, receiptID string) (*models.Receipt, error)  
    GetReceiptByOrder(ctx context.Context, orderID string) (*models.Receipt, error)  
}
```

## TransactionRepository

```
type TransactionRepository interface {  
    SaveTx(ctx context.Context, tx *models.Transaction) error  
    UpdateTx(ctx context.Context, tx *models.Transaction) error  
    GetTx(ctx context.Context, txID string) (*models.Transaction, error)  
}
```