les30n-5 managen Vairn package · npm i yarn -- global - install yarn globally · yarn add package Name - install package · yarn remove packageName-uninstall package APP. 3 « Browser Router > a Toast Container > c Routess c route path= '1' element = { < login Page 15},5 < route path = '1 debts - element = { < Debts. «Route path= /transaction element = {cTransaction. Page 1>31> C/Routes C/BZOWSEZR ONE Utez > Login Page jsx Delets Page ij sk Transaction, isk degan pagelan oclib olami? Function componentala, rafce V san

Login Page jax const Loginpage = () => { const (user, set llser ] = use State (? user namos const navigate = use NavigateG; const submit = () => { Saytimin you gilanmay e brevent Defoult (); if (usez, usezname=== abdulazia & & usez. password = == '12345') } 3 else { debts') toast. e2202 ('E2202'); con-80 Randlellser = (e) => { set Usez ({... usez, [e. tazget. id]: e. tazget. value 3); < Form on Bulmit = { su Bmit }> Form. Control on change = { handle User }

De 6 / s. Plage, jsx const (debts, set Debts) = use state (C ? id: 'o', name; 'Mamuri, dest: 120 fid: 1 hame: Kurshid, debt: 1000, phone: 388730737 ? dels s.map ((delt) =) { ¿ Debts Card Reyz Edebt, id 3 E. debil Debts Card . S & x const Debtscard= ({id, name, debt, plone})= (h3) In eme 3 (1h3) cp> Sdebt 3 < 1p> (p) Sphone 3 (1p) · Proptypes npm i prop-types impat propTypes from prop-types;

Debts Card. prop Types = 1 name: Proptypes, strings phone: Prop Types. string, debt: Prop Types. number Prop. Types. String id.