AQ-00 · attestqa

Sign-off Sheet

Version 1.6 · 2026-10-10 · Author: Vijay Javvadi

1. What is being signed

This sheet covers the design document set for attestqa, prepared before any development begins. Signing it means: the product, its design, and the plan in these documents are agreed as the starting point; development may begin with the v1.0.0 month of AQ-05; and any later change to a decision below is recorded as a decision record in `research/decisions/` rather than made silently.

Each document is identified by the SHA-256 hash of its PDF, so the version signed can always be proven later.

2. Changes since version 1.0

1.6. The frozen corpus was entered as the first 18 findings and the first lines of the Paper I manuscript were drafted from them. In doing so, an error in these documents was found and corrected: they said the corpus showed six weakening routes and that none reached the suite. The corpus shows five routes, and three weakenings did reach disk before being caught by reading the ledger (AQ-01 §2, AQ-08 H2 and H5).

1.5. Paper I is written as the work happens: a living manuscript in the Paper I folder, every result line tied to a finding and its ledger events, lines added the day the finding is logged and joined into paragraphs each month, with a checker for unsupported or unused findings (AQ-08 §6). Decision D27 is new.

1.4. Version numbers now follow three levels: a new major number for each product stage (v1.0.0 web testing, v2.0.0 API, v3.0.0 web version, v4.0.0 security, v5.0.0 ETL), the middle number for the monthly releases within a stage, and the last number for minor fixes. The schedule is unchanged; the twelve monthly releases are renumbered v1.0.0 to v5.0.0, and the ETL database adapter now ships with v5.0.0. Decision D22 is reworded; D14 follows it.

1.3. The plan is now a monthly release schedule sized to 4–5 hours a day, seven days a week (about 31 hours a week): v1.0.0 on 15 November 2026, then one release on the 15th of every month to v5.0.0 in October 2027, each shipping something usable (AQ-05). Release numbers across all documents follow it. AQ-07 gains a folder-by-folder account of what happens to the existing agentic-qa code. A new document, AQ-09, covers open-source publishing: public repository from the first day, npm with provenance, signed installers, and a Zenodo DOI for every release. Decisions D22 to D26 are new; D14 and D9 use the new release numbers.

1.2. attestqa now builds on six packages already published under `@vijaypjavvadi`: bdd2pw and pw-emit for code generation, synthdata for test data, pw-self-heal for locator suggestions (suggest-only, never silent run-time healing), sel2pw for importing Selenium suites, and usagecontract as a second API oracle. They stay in their own repositories and are used as dependencies. pw-triage is kept in step with core triage. The first-run screen gains an "import a Selenium suite" entry. Decision D21 is new; D16 now names pw-emit.

1.1. Version 1.1 adds the four test types and requirements from trackers, following the discussion on 9 October 2026. Test type became a second setting beside the mode (web, API, security, ETL), each with its own adapter, oracle source and refusal rules. Jira and Azure DevOps are now explicit requirement sources, behind one read-only tracker interface, and there is a new Requirements screen with a coverage grid. The release order is now web testing, API testing, the web version of attestqa, security testing and ETL testing (agreed: API before the web version). The Attest prototype now shows web and API results together. Hypothesis H5 (cross-type weakening) and study S4 were added. Decisions D14 to D20 are new or changed.

3. Documents

ID	Document	Ver.	File	Pages	SHA-256	Review
AQ-01	Product Document	1.5	`01_Product.pdf`	8	`227fc8f041827b6d0ee4a21f8809a61617358692cfcd4c2ac58697846a8682da`	☐ Approved ☐ Changes
AQ-02	Design Document and UI Prototype	1.4	`02_Design_UI_Prototype.pdf`	8	`d4a5a8a4932ae93c38b96904e206a36756cab426a76ed4e5009b4e4ad23d9c3f`	☐ Approved ☐ Changes
AQ-03	High-Level Design	1.4	`03_HLD.pdf`	10	`83c24c246b5e3ff79eca3894d6ce103675519290571cb32c2421bc0866edc681`	☐ Approved ☐ Changes
AQ-04	Low-Level Design	1.4	`04_LLD.pdf`	10	`798fe1a96a9739c20359903174f7f15b4e362dec0878acae03a27fe16ba6fca8`	☐ Approved ☐ Changes
AQ-05	Implementation Plan and Release Schedule	1.4	`05_Implementation_Plan.pdf`	6	`ccb45f40dce7e50463de8bf1e992a8d7af910ca17cf38e5fc12b9b972f0b9c3b`	☐ Approved ☐ Changes
AQ-06	Local Test Strategy and Target Applications	1.4	`06_Local_Test_Strategy.pdf`	5	`061f4a7f17bdbe67472ed6c2579bd7fa4ba8182eda30f45ed6f1617f5da6e9db`	☐ Approved ☐ Changes
AQ-07	Code Migration and Open-Source Packaging	1.4	`07_Migration_and_Packaging.pdf`	7	`d4373d7795ca182d16f0ca6f33096b6b0240932b57baaa1445f957d819593365`	☐ Approved ☐ Changes
AQ-08	Research Logging Plan	1.6	`08_Research_Logging_Plan.pdf`	4	`5a59556cd9ae2a4caa1ebdf4df3fa170c61292361fa4a32358213bd9e7eb80a3`	☐ Approved ☐ Changes
AQ-09	Open-Source Release and Publishing	1.1	`09_Open_Source_Publishing.pdf`	3	`f7fe9552b4a1ea6c7e6e7efeddaccf5e198b014f40e485eaa142e534158781e9`	☐ Approved ☐ Changes

4. Decisions needing explicit agreement

#	Decision	Where	Answer
D1	Working directory `E:\EB1A_Research\Application\attestqa` with `Docs`, `Winapp`, `WebApplication`, `TestRunApplication` as named.	AQ-03 §3	☐ Agree ☐ Change
D2	Add two folders: `packages/` (shared code published to npm) and `research/` (findings, decisions, hypotheses, manifests).	AQ-03 §3	☐ Agree ☐ Change
D3	Rename the existing GitHub repository in place to `attestqa` (keeps redirects and the Zenodo DOI), rather than creating a new one.	AQ-07 §4	☐ Agree ☐ Change
D4	Create the `@attestqa` npm organisation for the scoped packages.	AQ-07 §5	☐ Agree ☐ Change
D5	Store desktop secrets with Electron `safeStorage` (Windows DPAPI) rather than Windows Credential Manager by name.	AQ-04 §4.4	☐ Agree ☐ Change

#	Decision	Where	Answer
D6	Sign the installer with Azure Trusted Signing (fallback: OV certificate). Signing is release-blocking.	AQ-03 §7	☐ Agree ☐ Change
D7	Core goes to 2.0.0 at the start of desktop work: ledger `tool` becomes `attestqa`, three event kinds added, 1.x ledgers stay readable.	AQ-04 §2.2	☐ Agree ☐ Change
D8	Second provider for the cross-model study: Azure OpenAI (alternative: OpenAI).	AQ-06 §3	☐ Agree ☐ Change
D9	Park the VS Code extension 0.1.0 until the web version (v3.0–v3.1); no extension work before then.	AQ-07 §1	☐ Agree ☐ Change
D10	Use the target list and rules of engagement in AQ-06; active security scanning only on local Juice Shop.	AQ-06 §4–5	☐ Agree ☐ Change
D11	Freeze hypotheses H1–H5 as written and hash them before any study data is collected.	AQ-08 §3.3	☐ Agree ☐ Change
D12	Explore mode has no oracle and writes drafts only, for every test type; it can never file a bug or report a pass.	AQ-01 §4–5, AQ-04 §2.4, §2.6	☐ Agree ☐ Change
D13	The UI offers no chat with the model; the only text box is answered from the ledger.	AQ-01 §10, AQ-02 §2	☐ Agree ☐ Change
D14	Release order: web testing (v1), API testing (v2), the web version of attestqa with MCP (v3), security testing (v4), ETL testing (v5).	AQ-05 §2–3	☐ Agree ☐ Change
D15	Test type is a second setting beside the mode; all types share the gate, ledger, triage and report, and each adds only an adapter, an oracle source and its own refusal rules.	AQ-01 §5, AQ-03 §5	☐ Agree ☐ Change
D16	All test types are written as `@playwright/test` files, generated through `pw-emit` and run by the same runner; ZAP findings are converted into test results.	AQ-03 §5, §10	☐ Agree ☐ Change
D17	Requirements come from Azure DevOps and Jira through one tracker interface, read-only except bug creation after confirmation; Jira adapter built for v1.0.0.	AQ-01 §6, AQ-04 §2.7	☐ Agree ☐ Change
D18	Coverage is computed from test tags, approvals and results, never by the model; shown on a new Requirements screen.	AQ-02 §4.2, AQ-04 §2.8	☐ Agree ☐ Change
D19	Active security scanning is a destructive action offered only when written authorisation is recorded for the target.	AQ-04 §2.6	☐ Agree ☐ Change
D20	ETL database access is read-only, enforced by a statement parser and read-only connections; ETL targets built from the local synthetic databases.	AQ-04 §2.6, AQ-06 §4.5	☐ Agree ☐ Change
D21	Build on our published packages as dependencies (bdd2pw, pw-emit, synthdata, pw-self-heal, sel2pw, usagecontract), not copies; each stays in its own repository; pw-self-heal is suggest-only in governed runs.	AQ-01 §13, AQ-03 §13, AQ-07 §6	☐ Agree ☐ Change
D22	Versioning: a new major number for each stage (v1.0.0 web, v2.0.0 API, v3.0.0 web version, v4.0.0 security, v5.0.0 ETL); the middle number for significant changes within a stage (the monthly releases); the last number for minor fixes. npm packages keep their own versions, listed in every release note.	AQ-05 §1	☐ Agree ☐ Change
D23	At least one release a month, on the 15th, starting v1.0.0 on 15 Nov 2026; planned at about 115 of ~135 monthly hours (4–5 h/day, 7 days); a late feature moves to next month, the date does not.	AQ-05 §1–3, §6	☐ Agree ☐ Change
D24	The repository is public from the first commit; secrets, private-system ledgers and non-consenting targets are never published.	AQ-09 §1	☐ Agree ☐ Change
D25	Releases are built, signed and published by GitHub Actions on a tag Vijay pushes: npm trusted publishing with provenance, signed installer with checksums and SBOM.	AQ-09 §2–4	☐ Agree ☐ Change
D26	Every release is archived on Zenodo with its own DOI; study datasets get separate DOIs, with hypotheses committed publicly before data collection.	AQ-09 §2, §6	☐ Agree ☐ Change
D27	Paper I is written line by line from findings during development, not at the end; every result line cites a finding id; Paper I2 keeps its own experiment and draws results only from it.	AQ-08 §6	☐ Agree ☐ Change

5. Already agreed in discussion (recorded, no action needed)

The tracker is optional. The ledger stays on disk and is never sent to any attestqa service. The product is open source under MIT, desktop first on Windows. Users bring their own model (Anthropic, OpenAI, Azure OpenAI, AWS Bedrock, an OpenAI-compatible gateway, or local) with their company's sign-in. Generated tests are plain Playwright code in a folder the user owns. The UI is React and TypeScript, shared by desktop and web. Generated test projects live in `TestRunApplication`. Editable Markdown sources are kept beside the PDFs in `Docs/src`. API testing comes before the web version of attestqa.

6. Comments and requested changes

7. Signature

Role	Name	Signature	Date
Product owner and author	Vijay Javvadi		
Outcome	☐ Approved as is ☐ Approved with the changes in §6 ☐ Not approved — revise and resubmit		