#### A Gentle Introduction to R

Jonathan Whiteley

2023-08-04

## Pop Quiz

We will review these at the end, so you can see how much you have learned.

- What does 'CRAN' stand for?
- Why is it called 'R'?
- How can you use R interactively?
- How do you find out what a function does & how to use it?
- How do you store values to re-use later?
- True or False: Warnings can be ignored, but an Error means I made a mistake.
- True or False: Error messages will tell me how to fix the problem.

### Learning Objectives

- Get familiar with the R interface
- Enter commands
  - ▶ input & output: using R interactively
  - use some common functions
- Understand Errors & Warnings
- Use technical terms for R concepts
- How to get Help

# Why is it named $\mathbf{R}$ ?

- R started as an open-source implementation of the S statistical computing language (S-PLUS)
  - S was created at Bell Laboratories in 1976
  - R was based on the S syntax (mostly v3), but works very differently "under the hood".
- R was created by Ross Ihaka and Robert Gentleman at the University of Aukland in the early 1990s.



- R has a slightly different interface for each **O**perating **S**ystem (OS)
  - ► GUI = Graphical User Interface
- In every case, you interact with R primarily using a command line
  - aka "Question-and-Answer Model"
  - You ask R to do something (a command), and R tells you the answer (result).
  - ▶ Instructions are given to R using the R language.

## The R command-line

- The command prompt normally looks like this:
  - >

(the colour varies, depending on the interface)

- ▶ This is R's way of saying "I am ready to accept new commands".
- ▶ Type a new command on the line after this prompt (i.e., input).
- Press return/enter to execute the current command
- If the prompt looks like this:
  - +

it means the last command was incomplete and R is waiting for more input.

R will not do anything until the command is completed or cancelled.

- ► This usually means you forgot a closing quote ", parenthesis (, bracket [, or brace {
- You can cancel the current command at any time by pressing escape (esc)



In this presentation,

• commands that can be entered in the command-line look like this:

```
Input (commands)
```

Expected output (results) look like this:

```
## Output (results)
```



• some plots and graphs that can be made with R

demo(graphics)

demo(image)

• image-like graphics and maps that can be made a liWehop monospace text.

demo()
Text with
print("inline code").

bullet point

```
demo(graphics) #
demo(image) #
demo(lm.glm) #
demo() #
```

- some plots and graphs that can be made with R
- image-like graphics and maps that can be made with R
- a demonstration of linear modelling & GLMs

## R is a calculator

1 + 1	10 - 1
## [1] 2	## [1] 9
2 * 2	8 / 2
## [1] 4	## [1] 4
2^3	sqrt(9)
## [1] 8	## [1] 3

- These are expressions
- Expressions are evaluated, and the value (result) is returned (sometimes invisibly)



- With the cursor next to the empty prompt (>), use the up & down arrow keys (↑↓) to re-produce previous commands
- This lets you "scroll through your command history"
- Press up (↑) once, and you get the last command you entered without having to copy & paste

10 / 12

### Symbolic variables

• You can store values (*objects*) in symbolic variables (*names*) using an assignment operator

```
<- assign the value on the right to the name on the left</pre>
```

Names can include:

```
letters a-z A-Z numbers 0-9 periods . underscores _
```

```
A <- 10
B <- 10 * 10
A_log <- log(A)
B.seq <- 1:B
```

 Names should begin with a letter

#### References & More Information

#### help.start()

- An Introduction to R
- The R Language Definition
- R Manuals (https://cran.r-project.org/manuals.html)
- R Contributed Documentation
  - e.g., http://cran.r-project.org/doc/contrib/usingR.pdf
- Internet search
  - Stack Overflow
  - Cookbook for R