Get Token

API to acquire an access token via an authorization_code exchange and concurrently includes the user's profile in the response.

The `access_token` obtained through this API has a specific validity period that lasts until `3:30 AM` the following day, regardless of the time it was generated. For instance, if you generate a token at 8 PM on Tuesday, it will expire at 3:30 AM on Wednesday. This also means that a token created at 2:30 AM on Wednesday will still expire at 3:30 AM on the same Wednesday. Therefore, users are advised to plan their activities accordingly, ensuring they accommodate the token's expiration schedule in their usage. The `code` sent as part of this request is valid for a single use, regardless of whether the access token generation succeeds or encounters an issue.

Request

```
curl -X 'POST' 'https://api.upstox.com/v2/login/authorization/token' \
-H 'accept: application/json' \
-H 'Content-Type: application/x-www-form-urlencoded' \
-d 'code={your_code}&client_id={your_client_id}&client_secret=
{your_client_secret}&redirect_uri=
{your_redirect_url}&grant_type=authorization_code'
```

For additional samples in various languages, please refer to the Sample code section on this page.

Request Body

Name	Required	Type	Description
code	true	string	The `code` is a unique parameter included in the URL upon a successful Authorize API authentication.
client_id	true	string	The API key obtained during the app generation process.

Name	Required	Type	Description
client_secret	true	string	The API secret obtained during the app generation process. This private key remains confidential, known only to the application and the authorization server.
redirect_uri	true	string	The URL provided during app generation.
grant_type	true	string	This value must always be `authorization_code`.

Responses 200 4XX

Response Body

```
{
  "email": "******",
  "exchanges": ["NSE", "NFO", "BSE", "CDS", "BFO", "BCD"],
  "products": ["D", "CO", "I"],
  "broker": "UPSTOX",
  "user_id": "******",
  "user_name": "******",
  "order_types": ["MARKET", "LIMIT", "SL", "SL-M"],
  "user_type": "individual",
  "poa": false,
  "is_active": true,
  "access_token": "******************"
  "extended_token": "******************"
}
```

Name	Type	Description
email	string	E-mail address of the user
exchanges	string[]	List of exchanges enabled for the user. Valid exchanges can be found in the Exchange Appendix

Name	Type	Description
products	string[]	Lists the types of products enabled for the user. Possible values: `I`, `D`, `CO`, `MTF`
broker	string	The broker ID
user_id	string	Uniquely identifies the user (commonly referred as UCC)
user_name	string	Name of the user
order_types	string[]	Order types enabled for the user. Possible values: `MARKET`, `LIMIT`, `SL`, `SL-M`
user_type	string	Identifies the user's registered role with the broker. This will be individual for all retail users
poa	boolean	Indicates whether the user has authorized power of attorney for transactions.
is_active	boolean	Indicates if the account status is active.
access_token	string	The authentication token to be used with every subsequent API request.
extended_token	string	This token is designed for prolonged usage, primarily for read-only access to various API endpoints. For more detailed information on the extended token, including its benefits and how to opt for it, please refer to the Extended Token Documentation.

Sample Code

Get access token using auth code

Python | Node.js | Java | PHP | Python SDK | Node.js SDK | Java SDK

```
import requests
```

```python
url = 'https://api.upstox.com/v2/login/authorization/token'
headers = {
    'accept': 'application/json',
    'Content-Type': 'application/x-www-form-urlencoded',
}

data = {
    'code': '{your_code}',
    'client_id': '{your_client_id}',
    'client_secret': '{your_client_secret}',
    'redirect_uri': '{your_redirect_url}',
    'grant_type': 'authorization_code',
}

response = requests.post(url, headers=headers, data=data)

print(response.status_code)
print(response.json())
```

POST /login/authorization/token

Request

LIVE URL
https://api.upstox.com/v2

Body

`code` **required**

code

`client_id` **required**

OAuth API key that is a public identifier for app

`client_secret` **required**

OAuth client secret that is a private secret known only to app and authoriza

`redirect_uri` **required**

Authorization server will redirect the user back to the application via redirec

`grant_type` **required**

Type of grant used to get an access token

NOTE

- If a user attempting to log in has no active segments, the error `No segments for these users are active. Manual reactivation is recommended from Upstox app/web.` will occur, preventing the Token API from generating the access_token. To resolve this, users must manually reactivate their segment through the Upstox web or mobile application before attempting to log in again.