Intraday Candle Data V3

This API is an extended version of standard Intraday Candle Data API, which allows you to retrieve Open, High, Low, and Close (OHLC) values for the current trading day. It supports customizable time intervals across various units such as `minutes`, `hours`, `days`.

This API is particularly useful for traders and analysts who require detailed intraday data for technical analysis, backtesting, or algorithmic trading strategies. This V3 API provides additional custom interval options that are not available in the standard Intraday Candle Data API.

This API provides the following unit and interval options for intraday data:

Unit	Interval Options
minutes	1, 2, 3, ... 300
hours	1, 2, ... 5
days	1

Request

```
curl --location 'https://api.upstox.com/v3/historical-
candle/intraday/NSE_EQ%7CINE848E01016/minutes/1' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {your_access_token}'
```

Additional samples in various languages are available in the Sample Code section on this page.

Path Parameters

Name	Required	Type	Description
instrument_key	true	string	The unique identifier for the financial instrument for which historical data is being

Name	Required	Type	Description
			queried. For the regex pattern applicable to this field, see the Field Pattern Appendix.
unit	true	string	Specifies the unit for the candles. Possible values: `minutes`, `hours`, `days`.
interval	true	string	Specifies the interval for the candles. Possible values: `1`, `2`, `3`, ..., `300` for minutes. `1`, `2`, ..., `5` for hours. `1` for days.

Responses 200 4XX

Response Body


```
{
  "status": "success",
  "data": {
    "candles": [
      [
        "2025-01-12T15:15:00+05:30",
        2305.3,
        2307.05,
        2301,
        2304.65,
        559982,
        0
      ],
      [
        "2025-01-12T14:45:00+05:30",
        2309.1,
        2310.75,
        2305.25,
        2305.3,
        740124,
        0
      ]
    ]
```

```
  }
}
```

Name	Type	Description
status	string	A string indicating the outcome of the request. Typically `success` for successful operations.
data	object	Contains OHLC values for all instruments across various timeframes.
data.candles	array[]	Array of candle data, each presented as an array with sequential elements representing trading activity.
data.candle[0]	number	`Timestamp`: Indicating the start time of the candle's timeframe.
data.candle[1]	number	`Open`: The opening price of the asset for the given timeframe.
data.candle[2]	number	`High`: The highest price at which the asset traded during the timeframe.
data.candle[3]	number	`Low`: The lowest price at which the asset traded during the timeframe.
data.candle[4]	number	`Close`: The closing price of the asset for the given timeframe.
data.candle[5]	number	`Volume`: The total amount of the asset that was traded during the timeframe.
data.candle[6]	number	`Open Interest`: The total number of outstanding derivative contracts, such as options or futures.

Sample Code

Get data with a 1-minute interval

Curl Python Node.js Java PHP Python SDK Node.js SDK Java SDK

```
curl --location 'https://api.upstox.com/v3/historical-candle/intraday/NSE_EQ%7CINE848E01016/minutes/1' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {your_access_token}'
```

Get data with a 3-minute interval

Curl Python Node.js Java PHP Python SDK Node.js SDK Java SDK

```
curl --location 'https://api.upstox.com/v3/historical-candle/intraday/NSE_EQ%7CINE848E01016/minutes/3' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {your_access_token}'
```

Get data with a 5-minute interval

Curl Python Node.js Java PHP Python SDK Node.js SDK Java SDK

```
curl --location 'https://api.upstox.com/v3/historical-candle/intraday/NSE_EQ%7CINE848E01016/minutes/5' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {your_access_token}'
```

Get data with a 15-minute interval

Curl Python Node.js Java PHP Python SDK Node.js SDK Java SDK

```
curl --location 'https://api.upstox.com/v3/historical-candle/intraday/NSE_EQ%7CINE848E01016/minutes/15' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {your_access_token}'
```

Get data with a 30-minute interval

Curl | Python | Node.js | Java | PHP | Python SDK | Node.js SDK | Java SDK

```
curl --location 'https://api.upstox.com/v3/historical-candle/intraday/NSE_EQ%7CINE848E01016/minutes/30' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {your_access_token}'
```

Get data with a 1-hour interval

Curl | Python | Node.js | Java | PHP | Python SDK | Node.js SDK | Java SDK

```
curl --location 'https://api.upstox.com/v3/historical-candle/intraday/NSE_EQ%7CINE848E01016/hours/1' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {your_access_token}'
```

Get data with a 2-hour interval

Curl | Python | Node.js | Java | PHP | Python SDK | Node.js SDK | Java SDK

```
curl --location 'https://api.upstox.com/v3/historical-candle/intraday/NSE_EQ%7CINE848E01016/hours/2' \
--header 'Content-Type: application/json' \
--header 'Accept: application/json' \
--header 'Authorization: Bearer {your_access_token}'
```

Get current day data

Curl | Python | Node.js | Java | PHP | Python SDK | Node.js SDK | Java SDK

```
curl --location 'https://api.upstox.com/v3/historical-candle/intraday/NSE_EQ%7CINE848E01016/days/1' \
--header 'Content-Type: application/json' \
```

```
--header 'Accept: application/json' \
--header 'Authorization: Bearer {your_access_token}'
```

GET /historical-candle/intraday/:instrument_key/:unit/:interval

Request

LIVE URL
https://api.upstox.com/v3

`instrument_key` — path **required**

instrument_key

`unit` — path **required**

unit

`interval` — path **required**

interval