Response Structure

Success response

Single Object Response Structure

Used for endpoints that return a single object, like `/order/place` and `/user/profile`.

```
{
    "status": "success",
    "data": {
      "key1": "value1",
      "key2": "value2",
      ...
    }
}
```

Multiple Object Response Structure

Used for endpoints that return a multiple object, like `/user/get-funds-and-margin`

```
{
    "status": "success",
    "data": [
      {
        "key1": "value1",
        "key2": "value2",
        ...
      },
      {
        "key1": "value1",
        "key2": "value2",
        ...
      }
    ]
}
```

Properties:

Property	Description
status	A string indicating the outcome of the request. Typically `success` for successful operations.
data	`Single` An object holding the response content with various key-value pairs. `Multiple` An array containing the main content of the response. Each element of the array is an object with various key-value pairs.

Error response

```
{
  "status": "error",
  "errors": [
    {
      "error_code": "string",
      "message": "string",
      "property_path": null,
      "invalid_value": null
    }
  ]
}
```

Properties:

Property	Description
status	A string indicating the outcome of the request. In this context, the term `error` represents a failure in the operation.
errors	An array containing the main content of the error response.
error_code	A specific error. Refer to the "Error Code" section for explanations.
message	Descriptive error message.
property_path	Indicates which part of the request triggered the error. It can be null.

Property	Description
invalid_value	Shows the value causing the error. It can be null.

NOTICE OF DEPRECATION

The camelCase fields (`errorCode`, `propertyPath`, and `invalidValue`) are deprecated and will be removed in future versions. Use the snake_case versions for consistency.