

EXP NO:

DATE:

**DEVELOP A C PROGRAM TO ANALYZE A GIVEN C CODE SNIPPET AND
RECOGNIZE DIFFERENT TOKENS, INCLUDING KEYWORD, IDENTIFIERS,
OPERATOR AND SPECIAL SYMBOLS**

AIM:

To develop a C program that analyzes a given C code snippet and recognizes different tokens, including keywords, identifiers, operators, and special symbols.

ALGORITHM:

- ☐ **Start**
- ☐ Take a C code snippet as input from the user or a file.
- ☐ Initialize necessary arrays and variables for keywords, identifiers, operators, and special symbols.
- ☐ Tokenize the input string using spaces, newlines, and other delimiters.
- ☐ For each token:
 - Check if it is a **keyword** (compare with a predefined list of C keywords).
 - Check if it is an **identifier** (valid variable/function name that doesn't match a keyword).
 - Check if it is an **operator** (e.g., +, -, *, /, ==, &&).
 - Check if it is a **special symbol** (e.g., {, }, (,), :, ,).
- ☐ Print the categorized tokens.
- ☐ **End**

PROGRAM:

```
#include <stdio.h>
#include <string.h>
#include <ctype.h>
// List of C keywords
const char *keywords[] = {
    "int", "float", "char", "double", "if", "else", "for", "while",
    "do", "return", "void", "switch", "case", "break", "continue",
    "default", "struct", "typedef", "enum", "union", "static",
    "extern", "const", "sizeof", "goto", "volatile", "register"
};
const int num_keywords = sizeof(keywords) / sizeof(keywords[0]);
```

```

// List of C operators
const char *operators[] = {"+", "-", "*", "/", "=", "==", "!=", "<", ">", "<=", ">=", "&&", "||",
"++", "--"};

const int num_operators = sizeof(operators) / sizeof(operators[0]);

// List of special symbols
const char special_symbols[] = {';', '(', ')', '{', '}', '[', ']', ',', '#', '&', '|', ':', '"', '\\'};

// Function to check if a word is a keyword
int isKeyword(char *word) {
    for (int i = 0; i < num_keywords; i++) {
        if (strcmp(word, keywords[i]) == 0)
            return 1;
    }
    return 0;
}

// Function to check if a character is an operator
int isOperator(char *word) {
    for (int i = 0; i < num_operators; i++) {
        if (strcmp(word, operators[i]) == 0)
            return 1;
    }
    return 0;
}

// Function to check if a character is a special symbol
int isSpecialSymbol(char ch) {
    for (int i = 0; i < sizeof(special_symbols); i++) {
        if (ch == special_symbols[i])
            return 1;
    }
    return 0;
}

// Function to classify tokens

```

```

void analyzeTokens(char *code) {
    char *token = strtok(code, " \t\n"); // Tokenizing by spaces, tabs, and newlines
    printf("\nRecognized Tokens:\n");
    while (token != NULL) {
        if (isKeyword(token))
            printf("Keyword: %s\n", token);
        else if (isOperator(token))
            printf("Operator: %s\n", token);
        else if (isalpha(token[0]) || token[0] == '_') // Identifiers start with a letter or underscore
            printf("Identifier: %s\n", token);
        else if (isSpecialSymbol(token[0]))
            printf("Special Symbol: %s\n", token);
        else
            printf("Unknown Token: %s\n", token);
        token = strtok(NULL, " \t\n");
    }
}

// Main function
int main() {
    char code[500];
    printf("Enter a C code snippet:\n");
    fgets(code, sizeof(code), stdin);
    analyzeTokens(code);
    return 0;
}

```

OUTPUT:

Enter a C code snippet:

```
int main() {  
    int a = 5, b = 10;  
    float c = a + b;  
    if (c > 10) {  
        printf("Result: %f", c);  
    }  
    return 0;  
}
```

Recognized Tokens:

Keyword: int

Identifier: main()

Special Symbol: {

Implementation	
Output/Signature	

RESULT :

Thus the above program reads a C code snippet, tokenizes it using space, tab, and newline as delimiters, classifies each token as a keyword, identifier, operator, or special symbol based on predefined lists, and prints the recognized tokens along with their types.