

Custom Search

COURSES

Login

HIRE WITH US



Array in Python | Set 1 (Introduction and Functions)

Other than some generic containers like `list`, Python in its definition can also handle containers with specified data types. Array can be handled in python by module named "**array**". They can be useful when we have to manipulate only a specific data type values.

Operations on Array :

1. array(data type, value list) :- This function is used to **create** an array with data type and value list specified in its arguments. Some of the data types are mentioned in the table below.

TYPE CODE	C TYPE	PYTHON TYPE	MINIMUM SIZE IN BYTES
'b'	signed char	int	1
'B'	unsigned char	int	1
'u'	Py_UNICODE	unicode character	2
'h'	signed short	int	2
'H'	unsigned short	int	2
'i'	signed int	int	2
'I'	unsigned int	int	2
'l'	signed long	int	4
'L'	unsigned long	int	4
'q'	signed long long	int	8
'Q'	unsigned long long	int	8
'f'	float	float	4

TYPE CODE	C TYPE	PYTHON TYPE	MINIMUM SIZE IN BYTES
'd'	double	float	8

2. append() :- This function is used to **add the value** mentioned in its arguments at the **end** of the array.

3. insert(i,x) :- This function is used to **add the value at the position** specified in its argument.

```
# Python code to demonstrate the working of
# array(), append(), insert()

# importing "array" for array operations
import array

# initializing array with array values
# initializes array with signed integers
arr = array.array('i', [1, 2, 3])

# printing original array
print ("The new created array is : ",end=" ")
for i in range (0, 3):
    print (arr[i], end=" ")

print("\r")

# using append() to insert new value at end
arr.append(4);

# printing appended array
print("The appended array is : ", end="")
for i in range (0, 4):
    print (arr[i], end=" ")

# using insert() to insert value at specific position
# inserts 5 at 2nd position
arr.insert(2, 5)

print("\r")

# printing array after insertion
print ("The array after insertion is : ", end="")
for i in range (0, 5):
    print (arr[i], end=" ")
```

Output:

```
The new created array is : 1 2 3
The appended array is : 1 2 3 4
The array after insertion is : 1 2 5 3 4
```

4. pop() :- This function **removes the element at the position** mentioned in its argument, and returns it.

5. remove() :- This function is used to **remove the first occurrence** of the value mentioned in its arguments.

```
# Python code to demonstrate the working of
# pop() and remove()

# importing "array" for array operations
import array

# initializing array with array values
# initializes array with signed integers
arr= array.array('i',[1, 2, 3, 1, 5])

# printing original array
print ("The new created array is : ",end="")
for i in range (0,5):
    print (arr[i],end=" ")

print ("\r")

# using pop() to remove element at 2nd position
print ("The popped element is : ",end="")
print (arr.pop(2));

# printing array after popping
print ("The array after popping is : ",end="")
for i in range (0,4):
    print (arr[i],end=" ")

print("\r")

# using remove() to remove 1st occurrence of 1
arr.remove(1)

# printing array after removing
print ("The array after removing is : ",end="")
for i in range (0,3):
    print (arr[i],end=" ")
```

Output:

```
The new created array is : 1 2 3 1 5
The popped element is : 3
The array after popping is : 1 2 1 5
The array after removing is : 2 1 5
```

6. index() :- This function returns the **index of the first occurrence** of value mentioned in arguments.

7. reverse() :- This function **reverses** the array.

```
# Python code to demonstrate the working of
# index() and reverse()

# importing "array" for array operations
```

```
import array

# initializing array with array values
# initializes array with signed integers
arr= array.array('i',[1, 2, 3, 1, 2, 5])

# printing original array
print ("The new created array is : ",end="")
for i in range (0,6):
    print (arr[i],end=" ")

print ("\r")

# using index() to print index of 1st occurrence of 2
print ("The index of 1st occurrence of 2 is : ",end="")
print (arr.index(2))

#using reverse() to reverse the array
arr.reverse()

# printing array after reversing
print ("The array after reversing is : ",end="")
for i in range (0,6):
    print (arr[i],end=" ")
```

Output:

```
The new created array is : 1 2 3 1 2 5
The index of 1st occurrence of 2 is : 1
The array after reversing is : 5 2 1 3 2 1
```

Reference :

<https://docs.python.org/3/library/array.html#module-array>

This article is contributed by **Manjeet Singh**. If you like GeeksforGeeks and would like to contribute, you can also write an article using [contribute.geeksforgeeks.org](https://www.geeksforgeeks.org/contribute) or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Recommended Posts:

[Array in Python | Set 2 \(Important Functions\)](#)

[Mathematical Functions in Python | Set 3 \(Trigonometric and Angular Functions\)](#)

[Mathematical Functions in Python | Set 4 \(Special Functions and Constants\)](#)

[Mathematical Functions in Python | Set 2 \(Logarithmic and Power Functions\)](#)

[Mathematical Functions in Python | Set 1 \(Numeric Functions\)](#)

[Virtual Functions and Runtime Polymorphism in C++ | Set 1 \(Introduction\)](#)

Log functions in Python

Functions in Python

Operator Functions in Python | Set 1

Decimal Functions in Python | Set 1

First Class functions in Python

Iterator Functions in Python | Set 1

Partial Functions in Python

Operator Functions in Python | Set 2

Prime functions in Python SymPy

Article Tags :

Python

School Programming



20

☐

To-do

☐

Done

1.6

Based on **44** vote(s)

Feedback/ Suggest Improvement

Add Notes

Improve Article

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

6 Comments

GeeksforGeeks

 Login Recommend 4 Tweet Share

Sort by Newest



Join the discussion...

LOG IN WITH

OR SIGN UP WITH DISQUS **Dushyant Pathak** • 8 months ago

inserts 5 at 2nd position



This should instead be inserts 5 at Index 2. The original one is a little confusing.

  • Reply • Share ›**rahul chawla** • a year ago

due to end="" we get error in ide can anyone explain why??

  • Reply • Share ›**mayank bansal** → rahul chawla • a year ago

Try the above program in Python3 because end="" does not support in earlier Python versions.

1   • Reply • Share ›**i hate animes, i love cartoon** • a year ago

is there any function that return the array size?

  • Reply • Share ›**Raj Panday** → i hate animes, i love cartoon • 21 hours ago

You can also call for for loop range instead of typing random number we can write:

for i in range(0,len(arr)):

print(arr[i],end=" ")

  • Reply • Share ›**mayank bansal** → i hate animes, i love cartoon • a year ago

print len(arr)

1   • Reply • Share › Subscribe Add Disqus to your siteAdd DisqusAdd Disqus' Privacy PolicyPrivacy PolicyPrivacy

A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

[About Us](#)
[Careers](#)
[Privacy Policy](#)
[Contact Us](#)

PRACTICE

[Courses](#)
[Company-wise](#)
[Topic-wise](#)
[How to begin?](#)

LEARN

[Algorithms](#)
[Data Structures](#)
[Languages](#)
[CS Subjects](#)
[Video Tutorials](#)

CONTRIBUTE

[Write an Article](#)
[Write Interview Experience](#)
[Internships](#)
[Videos](#)

@geeksforgeeks, Some rights reserved