RAJALAKSHMI ENGINEERING COLLEGE

Jaya Raghul A 251801110-2025-AIDS

Started on	Thursday, 6 August 2026, 10:27 AM
State	Finished
Completed on	Thursday, 6 August 2026, 11:23 AM
Time taken	56 mins 2 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;
```

```
    int s =1;
```

```
    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main()
{
    int n;
    int i= 1;
    int s =1;
    int count = 2;
    scanf("%d",&n);
    while(s <= n)
    {
        count++;
         i++;
         count++;
         s += i;
         count++;
     }
     count++;
     printf("%d", count);
     return 0;
}
```

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Jaya Raghul A 251801110-2025-AIDS

Started on	Thursday, 6 August 2026, 10:37 AM
State	Finished
Completed on	Thursday, 6 August 2026, 11:22 AM
Time taken	44 mins 56 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int main()
{
    int n, count;
    scanf("%d", &n);



    if(n == 1)
    count = 1;
    else
    count =5*n +2;


    printf("%d" , count);

    return 0;
}
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔

	Input	Expected	Got	
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Jaya Raghul A 251801110-2025-AIDS

J2

Started on	Wednesday, 26 August 2026, 12:35 PM
State	Finished
Completed on	Thursday, 17 September 2026, 10:45 AM
Time taken	21 days 22 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```
#include<stdio.h>
int main(){
    int n;
    int count=0;
    scanf("%d",&n);
    for(int i=1;i<=n;++i){
        count++;
        if(n%i==0){
            count++;

        }
        count++;
    }
    count++;
    printf("%d",count);
    return 0;
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Jaya Raghul A 251801110-2025-AIDS

Started on	Wednesday, 26 August 2026, 12:49 PM
State	Finished
Completed on	Thursday, 17 September 2026, 10:46 AM
Time taken	21 days 21 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time

complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

int main()
{
    int n, c = 0;
    long long count = 0;

    scanf("%d", &n);


    count++;

    for (int i = n / 2; ; i++)
    {

        count++;

        if (i >= n)
            break;

        for (int j = 1; ; j = 2 * j)
        {

            count++;

            if (j >= n)
                break;

            for (int k = 1; ; k = k * 2)
            {

                count++;

                if (k >= n)
                    break;


                c++;
                count++;
            }
        }
    }

    printf("%lld", count);
```

```
46      return 0;
47  }
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Jaya Raghul A 251801110-2025-AIDS

J2

Started on	Wednesday, 26 August 2026, 12:55 PM
State	Finished
Completed on	Thursday, 17 September 2026, 10:46 AM
Time taken	21 days 21 hours
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>
void reverse(int n)
{
    int rev = 0, remainder;
    int count = 3;

    while (n != 0)
    {
        count++;

        remainder = n % 10;
        count++;

        rev = rev * 10 + remainder;
        count++;

        n /= 10;
        count++;
    }

    printf("%d", count);
}

int main()
{
    int n;
    scanf("%d", &n);

    reverse(n);

    return 0;
}
```

	Input	Expected	Got	
✔	12	11	11	✔

	Input	Expected	Got	
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course